



Shenzhen BANTEK Testing Co., Ltd.

Report No.: BTEK251110005A02E0202

RF Test Report

For BTEK251110005A02E02

Project No.:	BTEK251110005A02E0202
Product Description:	22.3℃, 49%, 102.9kPa
Test Engineer:	Zora
Test Date:	2025-12-10



Shenzhen BANTEK Testing Co., Ltd.

Report No.: BTEK251110005A02E0202

Test Summary

Item	Result
Duty Cycle	Pass
Bandwidth	Pass
Maximum Conducted Output Power	Pass
Maximum Power Spectral Density	Pass
Frequency Stability	Pass
Band Edge	Pass
Additional Spurious Emission	Pass



1. Duty Cycle

1.1 Test Result


1.1.1 Ant1


Ant1							
Mode	Tx Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	0.181	0.287	63.07	2.00	0.06
		5200	0.181	0.287	63.07	2.00	0.04
		5240	0.182	0.287	63.41	1.98	0.06
802.11n (HT20)	SISO	5180	0.168	0.275	61.09	2.14	0.08
		5200	0.169	0.276	61.23	2.13	0.08
		5240	0.169	0.275	61.45	2.11	0.09
802.11ac (VHT20)	SISO	5180	0.153	0.260	58.85	2.30	0.11
		5200	0.154	0.260	59.23	2.27	0.08
		5240	0.156	0.259	60.23	2.20	0.14



1.2 Test Graph


1.2.1 Ant1









802.11a_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5180MHz_Ant1_NTNV



802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV







802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV



802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV



802.11ac(VHT20) HCH 5240MHz Ant1_NTNV



2025-12-10 11:16:48



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11a	SISO	5180	1	17.156	/	Pass
		5200	1	17.085	/	Pass
		5240	1	17.150	/	Pass
802.11n (HT20)	SISO	5180	1	18.455	/	Pass
		5200	1	18.367	/	Pass
		5240	1	18.303	/	Pass
802.11ac (VHT20)	SISO	5180	1	18.354	/	Pass
		5200	1	18.336	/	Pass
		5240	1	18.378	/	Pass


2.1.2 26dB BW

Mode	TX Type	Frequency (MHz)	ANT	26dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11a	SISO	5180	1	21.629	/	Pass
		5200	1	21.446	/	Pass
		5240	1	21.375	/	Pass
802.11n (HT20)	SISO	5180	1	21.828	/	Pass
		5200	1	21.469	/	Pass
		5240	1	21.695	/	Pass
802.11ac (VHT20)	SISO	5180	1	21.480	/	Pass
		5200	1	21.551	/	Pass
		5240	1	21.682	/	Pass

2.2 Test Graph


2.2.1 OBW








802.11a_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5180MHz_Ant1_NTNV







802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV




802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV









2.2.2 26dB BW







802.11a_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5180MHz_Ant1_NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV



802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV



802.11ac(VHT20) HCH_5240MHz_Ant1_NTNV





3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power


Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11a	SISO	5180	13.05	<=23.98	Pass
		5200	12.99	<=23.98	Pass
		5240	13.00	<=23.98	Pass
802.11n (HT20)	SISO	5180	12.43	<=23.98	Pass
		5200	12.50	<=23.98	Pass
		5240	12.71	<=23.98	Pass
802.11ac (VHT20)	SISO	5180	12.19	<=23.98	Pass
		5200	11.90	<=23.98	Pass
		5240	11.86	<=23.98	Pass


Note1: Antenna Gain: Ant1: 2.03dBi;




3.2 Test Graph

3.2.1 Power







802.11a_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5180MHz_Ant1_NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV



802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV



802.11ac(VHT20) HCH_5240MHz_Ant1_NTNV





4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/MHz)		Verdict
			ANT1	Limit	
802.11a	SISO	5180	2.09	<=11	Pass
		5200	2.13	<=11	Pass
		5240	2.46	<=11	Pass
802.11n (HT20)	SISO	5180	1.18	<=11	Pass
		5200	1.27	<=11	Pass
		5240	1.38	<=11	Pass
802.11ac (VHT20)	SISO	5180	0.99	<=11	Pass
		5200	0.88	<=11	Pass
		5240	0.96	<=11	Pass


Note1: Antenna Gain: Ant1: 2.03dBi;




4.2 Test Graph

4.2.1 PSD







802.11a_HCH_5240MHz_Ant1_NTNV




802.11n(HT20)_LCH_5180MHz_Ant1_NTNV




802.11n(HT20)_MCH_5200MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV




802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV



802.11ac(VHT20)_MCH_5200MHz_Ant1_NTNV



802.11ac(VHT20) HCH 5240MHz Ant1_NTNV





5. Frequency Stability

5.1 Test Result

5.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Temperature (°C)	Voltage (VAC)	Measured Frequency (MHz)	Limit (MHz)	Verdict
802.11a	SISO	5180	20	102	5180.040	5150 to 5250	Pass
				120	5180.020	5150 to 5250	Pass
				138	5180.040	5150 to 5250	Pass
			-30	120	5180.020	5150 to 5250	Pass
			-20	120	5180.060	5150 to 5250	Pass
			-10	120	5180.040	5150 to 5250	Pass
			0	120	5180.080	5150 to 5250	Pass
			10	120	5180.040	5150 to 5250	Pass
			30	120	5180.060	5150 to 5250	Pass
			40	120	5180.040	5150 to 5250	Pass
			50	120	5180.060	5150 to 5250	Pass
		5200	20	102	5200.040	5150 to 5250	Pass
				120	5200.080	5150 to 5250	Pass
				138	5200.040	5150 to 5250	Pass
			-30	120	5200.020	5150 to 5250	Pass
			-20	120	5200.040	5150 to 5250	Pass
			-10	120	5200.060	5150 to 5250	Pass
			0	120	5200.040	5150 to 5250	Pass
			10	120	5200.080	5150 to 5250	Pass
			30	120	5200.060	5150 to 5250	Pass
			40	120	5200.060	5150 to 5250	Pass
			50	120	5200.060	5150 to 5250	Pass
		5240	20	102	5240.100	5150 to 5250	Pass
				120	5240.020	5150 to 5250	Pass
				138	5240.040	5150 to 5250	Pass
			-30	120	5240.080	5150 to 5250	Pass
			-20	120	5240.060	5150 to 5250	Pass
			-10	120	5240.080	5150 to 5250	Pass
			0	120	5240.020	5150 to 5250	Pass
			10	120	5240.040	5150 to 5250	Pass
			30	120	5240.040	5150 to 5250	Pass
			40	120	5240.080	5150 to 5250	Pass
			50	120	5240.060	5150 to 5250	Pass
802.11n (HT20)	SISO	5180	20	102	5180.080	5150 to 5250	Pass
				120	5179.980	5150 to 5250	Pass
				138	5180.080	5150 to 5250	Pass
			-30	120	5180.060	5150 to 5250	Pass
			-20	120	5180.000	5150 to 5250	Pass
			-10	120	5180.040	5150 to 5250	Pass
			0	120	5180.000	5150 to 5250	Pass
			10	120	5180.040	5150 to 5250	Pass



			30	120	5180.040	5150 to 5250	Pass
			40	120	5180.020	5150 to 5250	Pass
			50	120	5180.080	5150 to 5250	Pass
		5200	20	102	5200.040	5150 to 5250	Pass
				120	5200.060	5150 to 5250	Pass
				138	5200.040	5150 to 5250	Pass
			-30	120	5200.060	5150 to 5250	Pass
			-20	120	5200.040	5150 to 5250	Pass
			-10	120	5200.060	5150 to 5250	Pass
			0	120	5200.100	5150 to 5250	Pass
			10	120	5199.960	5150 to 5250	Pass
			30	120	5199.980	5150 to 5250	Pass
			40	120	5200.040	5150 to 5250	Pass
			50	120	5200.040	5150 to 5250	Pass
		5240	20	102	5240.040	5150 to 5250	Pass
				120	5240.020	5150 to 5250	Pass
				138	5240.020	5150 to 5250	Pass
			-30	120	5240.020	5150 to 5250	Pass
			-20	120	5240.080	5150 to 5250	Pass
			-10	120	5240.060	5150 to 5250	Pass
			0	120	5240.020	5150 to 5250	Pass
			10	120	5240.040	5150 to 5250	Pass
			30	120	5240.060	5150 to 5250	Pass
			40	120	5240.020	5150 to 5250	Pass
			50	120	5240.020	5150 to 5250	Pass
802.11ac (VHT20)	SISO	5180	20	102	5180.020	5150 to 5250	Pass
				120	5179.980	5150 to 5250	Pass
				138	5180.060	5150 to 5250	Pass
			-30	120	5180.020	5150 to 5250	Pass
			-20	120	5180.000	5150 to 5250	Pass
			-10	120	5180.080	5150 to 5250	Pass
			0	120	5180.000	5150 to 5250	Pass
			10	120	5180.020	5150 to 5250	Pass
			30	120	5180.060	5150 to 5250	Pass
			40	120	5180.040	5150 to 5250	Pass
			50	120	5180.080	5150 to 5250	Pass
		5200	20	102	5200.080	5150 to 5250	Pass
				120	5200.060	5150 to 5250	Pass
				138	5200.060	5150 to 5250	Pass
			-30	120	5200.040	5150 to 5250	Pass
			-20	120	5200.000	5150 to 5250	Pass
			-10	120	5200.020	5150 to 5250	Pass
			0	120	5200.040	5150 to 5250	Pass
			10	120	5200.040	5150 to 5250	Pass
			30	120	5200.060	5150 to 5250	Pass
			40	120	5200.000	5150 to 5250	Pass
			50	120	5200.080	5150 to 5250	Pass
		5240	20	102	5240.080	5150 to 5250	Pass
				120	5240.060	5150 to 5250	Pass
				138	5240.060	5150 to 5250	Pass
			-30	120	5239.980	5150 to 5250	Pass
			-20	120	5240.000	5150 to 5250	Pass
			-10	120	5240.140	5150 to 5250	Pass
			0	120	5240.040	5150 to 5250	Pass



			10	120	5240.060	5150 to 5250	Pass
			30	120	5240.020	5150 to 5250	Pass
			40	120	5240.040	5150 to 5250	Pass
			50	120	5240.080	5150 to 5250	Pass

6. Band Edge


6.1 Test Result


6.1.1 BandEdge

Mode	TX Type	Frequency (MHz)	ANT	Level of Unwanted Emissions (dBm)		Verdict
				Result	Limit	
802.11a	SISO	5180	1	Refer To Test Graph		Pass
		5240	1	Refer To Test Graph		Pass
802.11n (HT20)	SISO	5180	1	Refer To Test Graph		Pass
		5240	1	Refer To Test Graph		Pass
802.11ac (VHT20)	SISO	5180	1	Refer To Test Graph		Pass
		5240	1	Refer To Test Graph		Pass

6.2 Test Graph


6.2.1 BandEdge






No	Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Status	Remark	No	Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Status	Remark
1	5358.480	-50.09	-21.20	28.89	Pass	Peak	7	5358.480	-54.95	-41.20	13.75	Pass	AVG
2	5401.680	-49.30	-21.20	28.10	Pass	Peak	8	5401.680	-54.83	-41.20	13.63	Pass	AVG
3	5427.360	-49.63	-21.20	28.43	Pass	Peak	9	5427.360	-54.77	-41.20	13.57	Pass	AVG
4	5438.400	-48.35	-21.20	27.15	Pass	Peak	10	5438.400	-54.87	-41.20	13.67	Pass	AVG
5	5445.840	-49.42	-21.20	28.22	Pass	Peak	11	5445.840	-54.94	-41.20	13.74	Pass	AVG
6	5453.520	-49.50	-21.20	28.30	Pass	Peak	12	5453.520	-54.77	-41.20	13.57	Pass	AVG

802.11n(HT20)_LCH_5180MHz_Ant1_NTNV




802.11n(HT20)_HCH_5240MHz_Ant1_NTNV






802.11ac(VHT20)_LCH_5180MHz_Ant1_NTNV



No	Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Status	Remark	No	Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Status	Remark
1	5004.000	-48.92	-21.20	27.72	Pass	Peak	7	5004.000	-53.47	-41.20	12.27	Pass	AVG
2	5030.500	-49.05	-21.20	27.85	Pass	Peak	8	5030.500	-53.26	-41.20	12.06	Pass	AVG
3	5068.000	-47.35	-21.20	26.15	Pass	Peak	9	5068.000	-53.27	-41.20	12.07	Pass	AVG
4	5095.500	-48.27	-21.20	27.07	Pass	Peak	10	5095.500	-53.71	-41.20	12.51	Pass	AVG
5	5125.500	-47.74	-21.20	26.54	Pass	Peak	11	5125.500	-53.28	-41.20	12.08	Pass	AVG
6	5148.500	-41.70	-21.20	20.50	Pass	Peak	12	5148.500	-50.67	-41.20	9.47	Pass	AVG

802.11ac(VHT20)_HCH_5240MHz_Ant1_NTNV



No	Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Status	Remark	No	Frequency (MHz)	Level (dBm)	Limit (dBm)	Margin (dB)	Status	Remark
1	5380.560	-49.63	-21.20	28.43	Pass	Peak	7	5380.560	-54.78	-41.20	13.58	Pass	AVG
2	5397.120	-50.20	-21.20	29.00	Pass	Peak	8	5397.120	-54.56	-41.20	13.36	Pass	AVG
3	5420.880	-50.20	-21.20	29.00	Pass	Peak	9	5420.880	-54.82	-41.20	13.62	Pass	AVG
4	5434.320	-49.76	-21.20	28.56	Pass	Peak	10	5434.320	-54.71	-41.20	13.51	Pass	AVG
5	5445.120	-48.92	-21.20	27.72	Pass	Peak	11	5445.120	-54.59	-41.20	13.39	Pass	AVG
6	5454.000	-49.29	-21.20	28.09	Pass	Peak	12	5454.000	-54.73	-41.20	13.53	Pass	AVG