

Radiofrequency radiation exposure evaluation: mobile devices

RESULT :

Pass

Test Specification

Test item	:	SMART CONTROLLER
Identification / Type No.	:	WSDKZQ-014
FCC ID	:	2BU2WH20260306GHF3E
Test standard	:	CFR47 FCC Part 2: Section 2.1091
		CFR47 FCC Part 1: Section 1.1310
		FCC KDB Publication 447498 D04

➤ **FCC requirements**

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤60
3.0-30	1842/f	4.89/f	*(900/f ²)	<60
30-300	61.4	0.163	1.0	<60
300-1,500			f/300	<60
1,500-100,000			5	<60
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG/(4 \pi R^2)$$

S = Power Density (mW/m²)

P = RF output Power (mW)

G = EUT Antenna gain (numeric)

R = Separation distance between radiator and human body (cm)

From the minimum separation distance, R=20cm

Test mode	Max. RF Output Power (dBm)	Antenna Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2.4G WLAN	14.70	2.54	17.24	52.966	0.0105	1	Pass
BLE	-3.35	2.54	-0.81	0.829	0.00016	1	Pass

The product does not support simultaneous transmitting.

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”