

WPT RF EXPOSURE TEST REPORT

Applicant : SHUN FO TECHNOLOGY CO., LIMITED
Address : FLAT A598, 6/F, HOWARD FACTORY BUILDING, 66 TSUNVIP STREET, KWUN TONG 999077, HONG KONG HK, China
Manufacturer : SHUN FO TECHNOLOGY CO., LIMITED

Address : FLAT A598, 6/F, HOWARD FACTORY BUILDING, 66 TSUNVIP STREET, KWUN TONG 999077, HONG KONG HK, China

Product Name : Magnetic wireless charger

Model Number : C20

Trademark : N/A

FCC ID : 2BU5T-C20

Test Date : Feb. 28, 2026 - Mar. 06, 2026

Date of Report : Mar. 06, 2026

Test Result : This device described above has been tested by BKC, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.

Test Procedure Used:

Standards : FCC part 2.1091
KDB 680106 D01 Wireless Power Transfer v04

Prepared by(Test Engineer):
Carey Zheng



Reviewer(Supervisor):
Casey Wang



Approved(Manager):
Jerry Liao



TABLE OF CONTENT

1. General Information	4
1.1. Customer basic information	4
1.2. Description of Device (EUT)	4
1.3. Channel List	4
1.4. Special Accessories and Auxiliary Equipment	4
1.5. Test mode	4
1.6. Sensor Specifications	5
1.7. Measurement Uncertainty (95% confidence levels, k=2)	6
1.8. Test Facility	6
1.9. Test Equipment	6
2. RF Exposure	7
2.1. Limit	7
2.2. Test Setup	7
2.3. Test Procedure	7
2.4. Test Result	8
3. Test Photographs	9
4. Appendix I: Photos of the EUT	9





1. General Information

1.1. Customer basic information

Contacts : zhenyu Shi
E-Mail : sunshoujun@info.wycy.com
Telephone : 18588457171

1.2. Description of Device (EUT)

Product Name : Magnetic wireless charger
Product Model No : C20
Test Auxiliary1 : Adapter
Test Auxiliary2 : Cellphone
Test Auxiliary Model No. 1 : HW088
Test Auxiliary Model No. 2 : Apple 14
Transmitting mode : Keep the EUT in continuously wireless charging mode
Power supply : Input voltage/current: DC 5V===2A/ 9V===2A
Wireless Output: 15W/10W/7.5W/5W

1.3. Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
/	/	/	/	/	/

1.4. Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Hardware Version	Software Version
/	/	/	/	/

1.5. Test mode

The special RF test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode.

Pretest Test Mode	Description of Mode
1	EUT Wireless charging(5W)
2	EUT Wireless charging(7.5W)
3	EUT Wireless charging(10W)
4	EUT Wireless charging(15W)

Note: All test modes were pre-tested, but we only recorded the worst case in this report.


1.6.Sensor Specifications

Specifications

Accuracy at 23°C±5°C, 80% RH or less (no condensation)

Sensor cross-sectional area	100 cm ²
Rated magnetic flux density	2 mT at a single axis (There is a derating characteristics dependent on frequency)
Frequency characteristics	10 Hz to 400 kHz
Measured axes	X, Y, Z
Place of use	Indoors, up to an altitude of 2000 m
Storage temperature and humidity	-10°C to 50°C, 80% RH or less (no condensation)
Operating temperature and humidity	0°C to 40°C, 80% RH or less (no condensation)
Period of guaranteed accuracy	1 year
External dimensions	Approx. $\phi 122 \times 295$ (L) mm
Weight	Approx. 210 g (7.4 oz)
Application Standard	Safety EN61010 Pollution degree 2 EMC EN61326

Frequency-dependent derating characteristics



1.7.Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
RF frequency	2×10^{-5}	
E-field	+ 1.06 dB	
H-field	± 0.7 dB	
Temperature	+1 degree	
Humidity	$\pm 5 \%$	
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%		

1.8.Test Facility

Site Description		
Name of Firm	:	Shenzhen BKC Testing Co., Ltd.
Site Location	:	Room 103, 1/F, Huaya Building, Huaya Industrial Park, Longhua Community, Longhua District, Shenzhen, Guangdong, China.
ISED CAB identifier	:	CN0188
ISED Company Number	:	34333
FCC Designation Number	:	CN1416
FCC Test Firm Registration Number	:	701543

1.9.Test Equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Exposure Level Tester	HIOKI	HIOKI-3470-01	071016320	Dec. 31 2025	Dec. 30 2026
2	100 cm2 Magnetic Field Sensor	HIOKI	100cm ² sensor	0376-B1	Dec. 31 2025	Dec. 30 2026

2. RF Exposure

2.1.Limit


The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

2.2.Test Setup



2.3.Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (20 cm from all sides) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 v04.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

2.4. Test Result

E-Filed Strength at 20 cm from the edges surrounding the EUT (V/m)

Frequency Range (kHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limits (V/m)
110-205	0.76	0.75	0.73	0.75	0.76	614

H-Filed Strength at 20 cm from the edges surrounding the EUT (A/m)

Frequency Range (kHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Limits (A/m)
110-205	0.16	0.13	0.15	0.17	0.15	1.63

Note: The EUT of 1%, 50%, 99% have test, the worst case recorded in this report.



3. Test Photographs

Please see Attachment BKC26020730BE-3.

4. Appendix I: Photos of the EUT

Please see Attachment BKC26020730BE-4 and -5.

