

TEST REPORT

Applicant: MYAVRO LIMITED

Address: 50a London Street Reading Berkshire RG1 4SQ United Kingdom

Product Name: 5G digital mobile smartphone

FCC ID: 2BU6A-A1

IC: 35309-A1

HVIN: M829_V1

47 CFR Part 15, Subpart E(15.407)
RSS-247 Issue 4, July 24, 2025
RSS-Gen, Issue 5, February 2021 Amendment 2
Standard(s): ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 +
Errata to C63.10a-2024
KDB 789033 D02 General U-NII Test Procedures New Rules
v02r01

Report Number: 2602P41234E-RF-00G

Report Date: 2026/4/20

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Reviewed By: Alice Tan

Title: RF Engineer

Pedro Yun

Approved By: Pedro Yun

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL ▲	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	9
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	11
3.4 SUPPORT CABLE LIST AND DETAILS	11
3.5 BLOCK DIAGRAM OF TEST SETUP	12
3.6 TEST FACILITY	14
3.7 MEASUREMENT UNCERTAINTY	14
4. REQUIREMENTS AND TEST PROCEDURES	15
4.1 AC LINE CONDUCTED EMISSIONS	15
4.1.1 Applicable Standard	15
4.1.2 EUT Setup	17
4.1.3 EMI Test Receiver Setup	17
4.1.4 Test Procedure	18
4.1.5 Corrected Amplitude & Margin Calculation	18
4.1.6 Test Result	18
4.2 RADIATION SPURIOUS EMISSIONS	19
4.2.1 Applicable Standard	19
4.2.2 EUT Setup	21
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	23
4.2.4 Test Procedure	23
4.2.5 Corrected Result & Margin Calculation	24
4.2.6 Test Result	24
4.3 26DB ATTENUATED BELOW THE CHANNEL POWER	25
4.3.1 Applicable Standard	25
4.3.2 EUT Setup	25
4.3.3 Test Procedure	25
4.3.4 Test Result	25
4.4 EMISSION BANDWIDTH	26
4.4.1 Applicable Standard	26
4.4.2 EUT Setup	26
4.4.3 Test Procedure	26
4.4.4 Test Result	27
4.5 MAXIMUM CONDUCTED OUTPUT POWER	28

4.5.1 Applicable Standard	28
4.5.2 EUT Setup	30
4.5.3 Test Procedure	30
4.5.4 Test Result	30
4.6 MAXIMUM POWER SPECTRAL DENSITY	31
4.6.1 Applicable Standard	31
4.6.2 EUT Setup	33
4.6.3 Test Procedure	33
4.6.4 Test Result	33
4.7 DUTY CYCLE	34
4.7.1 EUT Setup	34
4.7.2 Test Procedure	34
4.7.3 Judgment	34
4.8 ANTENNA REQUIREMENT	35
4.8.1 Applicable Standard	35
4.8.2 Judgment	35
4.9 ADDITIONAL REQUIREMENT	36
4.9.1 Applicable Standard	36
4.9.2 Judgment	37
5. TEST DATA AND RESULTS	38
5.1 AC LINE CONDUCTED EMISSIONS	38
5.2 RADIATION SPURIOUS EMISSIONS	41
5.3 26DB ATTENUATED BELOW THE CHANNEL POWER	165
5.4 EMISSION BANDWIDTH	171
5.5 99% OCCUPIED BANDWIDTH	201
5.6 MAXIMUM CONDUCTED OUTPUT POWER	218
5.7 MAXIMUM POWER SPECTRAL DENSITY	224
5.8 DUTY CYCLE	254
EXHIBIT A - EUT PHOTOGRAPHS	257
EXHIBIT B - TEST SETUP PHOTOGRAPHS	258

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2602P41234E-RF-00G	Original Report	2026/4/20

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	5G digital mobile smartphone
EUT Model:	myAvro A1
Operation Frequency:	5150-5250MHz: 5180-5240 MHz (802.11a/n ht20/ac vht20/ax he20) 5190-5230 MHz (802.11n ht40/ac vht40/ax he40) 5210 MHz (802.11ac vht80/ax he80) 5250-5350MHz: 5260-5320 MHz (802.11a/n ht20/ac vht20/ax he20) 5270-5310 MHz (802.11n ht40/ac vht40/ax he40) 5290 MHz (802.11ac vht80/ax he80) 5470-5725MHz: 5500-5720 MHz (802.11a/n ht20/ac vht20/ax he20) 5510-5710 MHz (802.11n ht40/ac vht40/ax he40) 5530-5690MHz (802.11ac vht80/ax he80) 5725-5850MHz: 5745-5825 MHz (802.11a/n ht20/ac vht20/ax he20) 5755-5795 MHz (802.11n ht40/ac vht40/ax he40) 5775 MHz (802.11ac vht80/ax he80)
Maximum Average Output Power (Conducted):	10.72 dBm in 5150-5250 MHz Band 11.98 dBm in 5250-5350 MHz Band 14.23 dBm in 5470-5725 MHz Band 14.99 dBm in 5725-5850 MHz Band
Maximum Average Output Power (EIRP):	12.01 dBm in 5150-5250 MHz Band 13.04 dBm in 5250-5350 MHz Band 16.94 dBm in 5470-5725 MHz Band
Modulation Type:	802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM 802.11ax: OFDMA-BPSK, QPSK, 16QAM, 64QAM,256QAM,1024QAM
Rated Input Voltage:	3.88Vdc from battery or 5/9Vdc from adapter
Serial Number:	For AC line conducted emissions and Radiated Spurious Emissions: 3FXP-9 For RF Conducted test:3FXP-2
EUT Received Date:	2026/1/10
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter	Jiangsu Chenyang Electron Co.,Ltd.	CK20W01US	Input: 100-240Vac 50/60Hz 0.7A Output: 5.0Vdc 3A /9Vdc 2.22A /12Vdc 1.67A /5-11Vdc 1.81A

1.3 Antenna Information Detail▲

Antenna	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Chain 0 (ANT8)	PIFA	50	5150-5250MHz	1.29dBi
			5250-5350MHz	1.06 dBi
			5470-5725MHz	2.71 dBi
			5725-5850MHz	2.55 dBi
Chain 1 (ANT9)	PIFA	50	5150-5250MHz	0.19 dBi
			5250-5350MHz	0.19 dBi
			5470-5725MHz	1.54 dBi
			5725-5850MHz	0.49 dBi

Note:

The system supports 2T2R CDD modes at 802.11n/ac/ax modes.
Per KDB 662911 D01 Multiple Transmitter Output v02r01:

For power measurements:

CDD Mode:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

directional gain=1.29dBi for 5150-5250MHz

directional gain=1.06dBi for 5250-5350MHz

directional gain=2.71dBi for 5470-5725MHz

directional gain=2.55dBi for 5725-5850MHz

For power spectral density (PSD) measurements:

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

directional gain=1.29dBi+3.01dB =4.30dBi for 5150-5250MHz

directional gain=1.06dBi+3.01dB =4.07dBi for 5250-5350MHz

directional gain=2.71dBi+3.01dB =5.72dBi for 5470-5725MHz

directional gain=2.55dBi+3.01dB =5.56dBi for 5725-5850MHz

The design of compliance with §15.203:



Unit uses a permanently attached antenna.



Unit uses a unique coupling to the intentional radiator.



Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC line conducted emissions	Compliant
FCC§15.205 & §15.209 & §15.407(b); RSS-247 Clause 7.3	Undesirable Emission& Restricted Bands	Compliant
RSS-247 Clause 7.3.1.3	26dB attenuated below the channel power	Compliant
FCC§15.407(a) (e) RSS-247 Clause 7.3 RSS-Gen Clause 6.7	Emission Bandwidth	Compliant
FCC§15.407(a) RSS-247 Clause 7.3	Maximum Conducted Output Power	Compliant
FCC§15.407 (a) RSS-247 Clause 7.3	Power Spectral Density	Compliant
§15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant
RSS-247 Clause 7.3.7	Additional requirements	Compliant

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11a/n ht20/ac vht20/ax he20:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
/	/	/	/	116	5580	165	5825
/	/	/	/	120	5600	/	/
/	/	/	/	124	5620	/	/
/	/	/	/	128	5640	/	/
/	/	/	/	132	5660	/	/
/	/	/	/	136	5680	/	/
/	/	/	/	140	5700	/	/
/	/	/	/	144*	5720	/	/

For 802.11n ht40/ac vht40/ax he40:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
/	/	/	/	118	5590	/	/
/	/	/	/	126	5630	/	/
/	/	/	/	134	5670	/	/
/	/	/	/	142*	5710	/	/

For 802.11ac vht80/ax he80:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
/	/	/	/	122	5610	/	/
/	/	/	/	138*	5690	/	/

Note 1:

*:Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

Note 2: The above frequencies in bold were performed the test.

Note 3: For AC line conducted emissions, the maximum output power channel was tested.

Note 4: For Radiated Spurious Emissions 9kHz~1GHz and 18~40GHz, the maximum output power channel was tested.

3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

The EUT configuration is below:

EUT Exercise Software:		engineering mode			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:					
5150-5250 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5180	6Mbps	18	11
	Middle	5200	6Mbps	18	11
	Highest	5240	6Mbps	18	11
802.11ac vht20	Lowest	5180	MCS0	18	11
	Middle	5200	MCS0	18	11
	Highest	5240	MCS0	18	11
802.11ac vht40	Lowest	5190	MCS0	18	11
	Highest	5230	MCS0	18	11
802.11ac vht80	Middle	5210	MCS0	18	11
802.11ax he20	Lowest	5180	MCS0	18	11
	Middle	5200	MCS0	18	11
	Highest	5240	MCS0	18	11
802.11ax he40	Lowest	5190	MCS0	18	11
	Highest	5230	MCS0	18	11
802.11ax he80	Middle	5210	MCS0	18	11
5250-5350 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5260	6Mbps	20	12
	Middle	5280	6Mbps	20	12
	Highest	5320	6Mbps	20	12
802.11ac vht20	Lowest	5260	MCS0	20	12
	Middle	5280	MCS0	20	12
	Highest	5320	MCS0	20	12
802.11ac vht40	Lowest	5270	MCS0	20	12
	Highest	5310	MCS0	20	12
802.11ac vht80	Middle	5290	MCS0	20	12
802.11ax he20	Lowest	5260	MCS0	20	12
	Middle	5280	MCS0	20	12
	Highest	5320	MCS0	20	12
802.11ax he40	Lowest	5270	MCS0	20	12
	Highest	5310	MCS0	20	12
802.11ax he80	Middle	5290	MCS0	20	12

5470-5725 MHz Band:

Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5500	6Mbps	17	13
	Middle	5600	6Mbps	17	13
	Highest	5700	6Mbps	17	13
	Cross	5720	6Mbps	17	13
802.11ac vht20	Lowest	5500	MCS0	17	13
	Middle	5600	MCS0	17	13
	Highest	5700	MCS0	17	13
	Cross	5720	MCS0	17	13
802.11ac vht40	Lowest	5510	MCS0	17	13
	Middle	5590	MCS0	17	13
	Highest	5670	MCS0	17	13
	Cross	5710	MCS0	17	13
802.11ac vht80	Lowest	5530	MCS0	17	13
	Highest	5610	MCS0	17	13
	Cross	5690	MCS0	17	13
802.11ax he20	Lowest	5500	MCS0	17	13
	Middle	5600	MCS0	17	13
	Highest	5700	MCS0	17	13
	Cross	5720	MCS0	17	13
802.11ax he40	Lowest	5510	MCS0	17	13
	Middle	5590	MCS0	17	13
	Highest	5670	MCS0	17	13
	Cross	5710	MCS0	17	13
802.11ax he80	Lowest	5530	MCS0	17	13
	Highest	5610	MCS0	17	13
	Cross	5690	MCS0	17	13

5725-5850 MHz Band:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
802.11a	Lowest	5745	6Mbps	17	13
	Middle	5785	6Mbps	17	13
	Highest	5825	6Mbps	17	13
802.11ac vht20	Lowest	5745	MCS0	17	13
	Middle	5785	MCS0	17	13
	Highest	5825	MCS0	17	13
802.11ac vht40	Lowest	5755	MCS0	17	13
	Highest	5795	MCS0	17	13
802.11ac vht80	Middle	5775	MCS0	17	13
802.11ax he20	Lowest	5745	MCS0	17	13
	Middle	5785	MCS0	17	13
	Highest	5825	MCS0	17	13
802.11ax he40	Lowest	5755	MCS0	17	13
	Highest	5795	MCS0	17	13
802.11ax he80	Middle	5775	MCS0	17	13

Note:

1. The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80/ax he20/ax he40/ax he80, the 802.11n ht20/n ht40 were reduced since the identical parameters with 802.11 ac vht20/ac vht40.
2. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.
3. The device supports SISO in all modes, and MIMO 2T2R in 802.11n/ac/ax modes, per pretest, 2T2R mode was the worst mode and reported for 802.11n/ac/ax modes.
4. For 802.11 ax mode, the device only supports full-RU.

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	SIM Card	/	180722

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	no	no	1.5	Adapter	EUT

3.5 Block Diagram of Test Setup


AC line conducted emissions:



Spurious Emissions:
Below 1GHz:



Above 1GHz:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.55 dB
Power Spectral Density, conducted	±0.55 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.06dB, 30MHz~1GHz: 6.13 dB, 1GHz~6GHz: 4.79 dB, 6GHz~18GHz: 4.63 dB, 18GHz~26.5GHz: 4.79 dB, 26.5GHz~40GHz: 4.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.83 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

- (1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.
- (2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.
- (3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50


Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard

FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of - 27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

Frequency band 5150-5250 MHz:

RSS-247 Clause 7.3.1.3

For transmitters with operating frequencies in the band 5150-5250 MHz:

- a. all emissions outside the 5150-5350 MHz band shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density;
- b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.
- c. if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing DFS (see section 7.3.6) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency band 5250-5350 MHz:

RSS-247 Clause 7.3.2.3

Devices shall comply with the following:

- a. all emissions outside the band 5150-5350 MHz shall not exceed -27dBm/MHz peak e.i.r.p spectral density.
- b. all emissions inside the band 5150-5250 MHz shall either:
 - i. not exceed -27 dBm/MHz peak e.i.r.p spectral density, or
 - ii. comply with the power spectral density for operation in section 7.3.1.2.

Frequency bands 5470-5725 MHz:

RSS-247 Clause 7.3.3.3

Equipment operating in the bands 5470-5725 MHz shall comply with the following unwanted emission limits:

- a. for devices with fundamental emissions fully contained within the 5470-5725 MHz band, all unwanted emissions outside the band 5470-5725MHz shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density.
- b. for devices with bandwidth overlapping the band edge of 5725 MHz, all unwanted emissions shall not exceed -27 dBm/MHz peak e.i.r.p. spectral density at 5850 MHz instead of 5725 MHz.

Frequency band 5725-5850 MHz


RSS-247 Clause 7.3.4.3

Equipment operating in the band 5725-5850 MHz shall comply with the following peak e.i.r.p. spectral density limits:


- a. 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b. 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c. 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d. -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

4.2.2 EUT Setup


9kHz~30MHz:




30MHz~1GHz:



1-18GHz:



18-40GHz:



The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2020. The specification used was FCC 15.209, FCC 15.407, RSS-247, RSS-Gen limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	120 kHz	500 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 40GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	≥1/T

Note: T is minimum transmission duration

4.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

For Radiated 18-40GHz test, which was performed at 1.0 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.0m
Distance extrapolation Factor = $20 \log (\text{specific distance } [3m]/\text{test distance } [1.0m])$ dB = 9.54 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Result & Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in $\mu\text{V/m}$

E_{Log} is the field strength of the emission, in $\text{dB}\mu\text{V/m}$

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10} (d_{\text{standard}}/d_{\text{measure}})$$

The basic equation except 18-40GHz test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For Radiated 18-40GHz test:

Factor = Antenna Factor + Cable Loss- Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

For the spurious emission below 30MHz, the limit was converted from $\text{dB}\mu\text{A/m}$ to $\text{dB}\mu\text{V/m}$ by adding 51.5 dB.

4.2.6 Test Result

Please refer to section 5.2.


4.3 26dB Attenuated Below the Channel Power

4.3.1 Applicable Standard

RSS-247 Clause 7.3.1.3

b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.

4.3.2 EUT Setup



4.3.3 Test Procedure

- Set $RBW = 1\% \sim 5\%$ of the emission bandwidth.
- Set the $VBW > RBW$.
- Detector = RMS.
- Trace mode = max hold
- Measure the emission attenuated below the channel power

4.3.4 Test Result

Please refer to section 5.3.

4.4 Emission Bandwidth

4.4.1 Applicable Standard

FCC §15.407 (a), (h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

RSS-247 Clause 7.3.1.3


b. any unwanted emissions that falls between the upper edge of the 26 dB bandwidth and 5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth.

c. if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing DFS (see section 7.3.6) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

RSS-247 Clause 7.3.4.2

For equipment operating in the band 5725-5850 MHz, the 6 dB bandwidth shall be at least 500 kHz.

4.4.2 EUT Setup



4.4.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2020 Section 12.5.2

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) ≥ 3 RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2020 Section 12.5.3&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.4 Test Result

Please refer to section 5.4 and section 5.5.

4.5 Maximum Conducted Output Power

4.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 7.3.1.2

Frequency band 5150-5250 MHz:

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed the lesser of:

a. 30 mW; or

b. $1.76 + 10 \log_{10} B$, dBm.

OEM devices installed in vehicles with a maximum e.i.r.p. greater than 15 mW shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For all other devices the maximum e.i.r.p. spectral density shall not exceed 10dBm/MHz. The maximum e.i.r.p. shall not exceed the lesser of:

a. 200 mW; or

b. $10 + 10 \log_{10} B$, dBm.

RSS-247 Clause 7.3.2.2**Frequency band 5250-5350 MHz:**

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed the lesser of:

- a. 30 mW; or
- b. $1.76 + 10 \log_{10} B$, dBm.

OEM devices installed in vehicles with a maximum e.i.r.p. greater than 15 mW shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

All other devices shall comply with the following:

a. the maximum power spectral density shall not exceed 11 dBm/MHz and the maximum conducted output power shall not exceed the lesser of:

- i. 250 mW; or
- ii. $11 + 10 \log_{10} B$, dBm.

b. the maximum e.i.r.p. shall not exceed the lesser of:

- i. 1.0 W; or
- ii. $17 + 10 \log_{10} B$, dBm.

c. Devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 7.3.3.2**Frequency band 5470-5725 MHz:**

Equipment operating in the band 5470-5725 MHz band shall comply with the following power limits:

a. the maximum conducted output power shall not exceed the lesser of:

- i. 250 mW; or
- ii. $11 + 10 \log_{10} B$, dBm.

b. the maximum power spectral density shall not exceed 11 dBm/MHz.

c. the maximum e.i.r.p. shall not exceed the lesser of:

- i. 1.0 W; or
- ii. $17 + 10 \log_{10} B$, dBm.

d. equipment with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 7.3.4.3**Frequency band 5725-5850 MHz:**

Equipment operating in the band 5725-5850 shall comply with the following power limits:

a. the maximum conducted output power shall not exceed 1 W; and


b. the maximum output power spectral density shall not exceed 30dBm/500 kHz.

When using transmitting antennas with a directional gain exceeding 6 dBi, the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

However, FFTP devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter maximum conducted output power and the power spectral density. FFTP operations exclude the use of PTMP systems, omnidirectional applications and multiple collocated transmitters transmitting the same information. However, remote stations of PTMP systems shall be permitted to operate at e.i.r.p. greater than 4 W under the same conditions as for FFTP systems.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.5.3 Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.5.4 Test Result

Please refer to section 5.6.

4.6 Maximum Power Spectral Density

4.6.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 7.3.1.2

Frequency band 5150-5250 MHz:

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed the lesser of:

a. 30 mW; or

b. $1.76 + 10 \log_{10} B$, dBm.

OEM devices installed in vehicles with a maximum e.i.r.p. greater than 15 mW shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For all other devices the maximum e.i.r.p. spectral density shall not exceed 10 dBm/MHz. The maximum e.i.r.p. shall not exceed the lesser of:

a. 200 mW; or

b. $10 + 10 \log_{10} B$, dBm.

RSS-247 Clause 7.3.2.2**Frequency band 5250-5350 MHz:**

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed the lesser of:

- a. 30 mW; or
- b. $1.76 + 10 \log_{10} B$, dBm.

OEM devices installed in vehicles with a maximum e.i.r.p. greater than 15 mW shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

All other devices shall comply with the following:

a. the maximum power spectral density shall not exceed 11 dBm/MHz and the maximum conducted output power shall not exceed the lesser of:

- i. 250 mW; or
- ii. $11 + 10 \log_{10} B$, dBm.

b. the maximum e.i.r.p. shall not exceed the lesser of:

- i. 1.0 W; or
- ii. $17 + 10 \log_{10} B$, dBm.

c. Devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 7.3.3.2**Frequency band 5470-5725 MHz:**

Equipment operating in the band 5470-5725 MHz band shall comply with the following power limits:

a. the maximum conducted output power shall not exceed the lesser of:

- i. 250 mW; or
- ii. $11 + 10 \log_{10} B$, dBm.

b. the maximum power spectral density shall not exceed 11 dBm/MHz.

c. the maximum e.i.r.p. shall not exceed the lesser of:

- i. 1.0 W; or
- ii. $17 + 10 \log_{10} B$, dBm.

d. equipment with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 7.3.4.3**Frequency band 5725-5850 MHz:**

Equipment operating in the band 5725-5850 shall comply with the following power limits:

a. the maximum conducted output power shall not exceed 1 W; and


b. the maximum output power spectral density shall not exceed 30dBm/500 kHz.

When using transmitting antennas with a directional gain exceeding 6 dBi, the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

However, FFTP devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter maximum conducted output power and the power spectral density. FFTP operations exclude the use of PTMP systems, omnidirectional applications and multiple collocated transmitters transmitting the same information. However, remote stations of PTMP systems shall be permitted to operate at e.i.r.p. greater than 4 W under the same conditions as for FFTP systems.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.6.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

4.6.4 Test Result

Please refer to section 5.7.

4.7 Duty Cycle

4.7.1 EUT Setup



4.7.2 Test Procedure

According to ANSI C63.10-2020 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver is used if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.7.3 Judgment

Report Only. Please refer to section 5.8.

4.8 Antenna Requirement

4.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

4.9 Additional requirement

4.9.1 Applicable Standard

According to RSS-247 Clause 7.3.7 Additional Requirements

The following requirements shall apply:

- a** the device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. A description on how this is done shall accompany the application for equipment certification. Note that this is not intended to prohibit transmission of control or signalling information or the use of repetitive codes where required by the technology.
- b** all LE-LAN devices must contain security features to protect against modification of software by unauthorized parties.

Manufacturers must implement security features in any digitally modulated devices capable of operating in any of the frequency ranges within the 5 GHz band, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software must prevent the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers may use various means, including the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment certification.

Manufacturers must take steps to ensure that DFS functionality cannot be disabled by the operator of the LE-LAN device.

- c** the user manual for LE-LAN devices shall contain instructions related to the restrictions mentioned in the above sections, namely that:
 - i.** any devices capable of operating in the band 5150–5250 MHz shall only be used indoors to reduce the potential for harmful interference to co-channel mobile satellite systems (this requirement does not apply to OEM devices installed in vehicles by vehicle manufacturers);
 - ii.** for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the bands 5250-5350 MHz and 5470-5725 MHz shall be such that the equipment still complies with the e.i.r.p. limit;
 - iii.** for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the band 5725-5850 MHz shall be such that the equipment still complies with the e.i.r.p. limits as appropriate; and
 - iv.** where applicable, antenna type(s), antenna models(s), and worst-case tilt angle(s) necessary to remain compliant with the e.i.r.p. elevation mask requirement set forth in section 7.3.2.4 or 7.3.5.3 shall be clearly indicated.

4.9.2 Judgment

RSS-247 Clause 7.3.7 a:

The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. Please refer to the declaration

RSS-247 Clause 7.3.7 b:

The devices must contain security features to protect against modification of software by unauthorized parties. Please refer to the declaration

RSS-247 Clause 7.3.7 c:

- i. The device operates on 5150-5250MHz is only for indoor use.
- ii. This device is equipped with a built-in integrated antenna, and operates on 5250-5350MHz/5470-5725MHz/5725-5850 MHz meet the EIRP limit, please refer to the power test result.
- iii. This device is equipped with a built-in integrated antenna, and all the EIPR compliance with RSS-247 requirement. Please refer to the conducted output power test result.
- iv. The device EIRP less than 200mW (23 dBm) for 5250-5350MHz.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	3FXP-9	Test Date:	2026/01/20
Test Site:	CE	Test Mode:	Transmitting
Tester:	Leesin Xiang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.9	Relative Humidity: (%)	51	ATM Pressure: (kPa)	101.1
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2025/6/25	2026/6/24
Unknown	Coaxial Cable	RG 142	C-0200-05	2025/5/6	2026/5/5
R&S	EMI Test Receiver	ESCI	100224	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A


** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Note: 802.11ax80 5775MHz was tested.

Project No.: 2602P41234E-RF
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 3FXP-9
Tester: Leesin Xiang
Note:




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.407	31.98	10.67	42.65	57.71	15.06	QP
2	0.407	21.45	10.67	32.12	47.71	15.59	Average
3	0.447	33.27	10.65	43.92	56.92	13.00	QP
4	0.447	22.97	10.65	33.62	46.92	13.30	Average
5	0.504	35.42	10.61	46.03	56.00	9.97	QP
6	0.504	23.58	10.61	34.19	46.00	11.81	Average
7	8.042	32.92	11.07	43.99	60.00	16.01	QP
8	8.042	24.54	11.07	35.61	50.00	14.39	Average
9	9.121	34.50	10.78	45.28	60.00	14.72	QP
10	9.121	26.08	10.78	36.86	50.00	13.14	Average
11	15.379	37.07	11.12	48.19	60.00	11.81	QP
12	15.379	28.72	11.12	39.84	50.00	10.16	Average

Project No.: 2602P41234E-RF
 Port: neutral
 Test Mode: Transmitting
 IF B/W 9kHz PK/AV

Serial No.: 3FXP-9
 Tester: Leesin Xiang
 Note:

Date: 2026-01-20



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.461	28.12	10.56	38.68	56.68	18.00	QP
2	0.461	12.10	10.56	22.66	46.68	24.02	Average
3	0.505	27.35	10.51	37.86	56.00	18.14	QP
4	0.505	13.67	10.51	24.18	46.00	21.82	Average
5	8.262	31.72	10.91	42.63	60.00	17.37	QP
6	8.262	20.32	10.91	31.23	50.00	18.77	Average
7	8.995	28.88	10.88	39.76	60.00	20.24	QP
8	8.995	20.08	10.88	30.96	50.00	19.04	Average
9	14.121	30.79	10.97	41.76	60.00	18.24	QP
10	14.121	20.29	10.97	31.26	50.00	18.74	Average
11	15.111	35.47	11.00	46.47	60.00	13.53	QP
12	15.111	22.43	11.00	33.43	50.00	16.57	Average

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	3FXP-9	Test Date:	2026/4/16
Test Site:	Chamber A	Test Mode:	Transmitting
Tester:	Jayce Wang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.5	Relative Humidity: (%)	42	ATM Pressure: (kPa)	100.4

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-2	2024/4/16	2027/4/15
Narda	Coaxial Attenuator	757C-6dB	34010	2024/4/16	2027/4/15
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	372193	2025/7/30	2026/7/29
R&S	EMI Test Receiver	ESCI	100035	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Please refer to the below plots.
After pre-scan in the X, Y and Z axes of orientation, the worst case(Y axes was the worst) is refer to plots.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

5150-5250MHz:(802.11ax20 5240MHz was tested)

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9


Polarization: Parallel

Tester: Lancer Zhang

Test Mode: Transmitting

Note: 5.2G WIFI


RBW:200Hz,VBW:1kHz



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.037	-2.55	45.38	42.83	116.19	73.36	Peak
2	0.047	-1.63	43.80	42.17	114.12	71.95	Peak
3	0.075	2.77	39.19	41.96	110.09	68.13	Peak
4	0.102	4.73	34.88	39.61	107.44	67.83	Peak
5	0.108	7.67	34.51	42.18	106.91	64.73	Peak
6	0.132	4.86	33.11	37.97	105.19	67.22	Peak

Project No.: 2602P41234E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 5.2G WIFI
RBW:9kHz,VBW:30kHz


Serial No.: 3FXP-9
Tester: Lancer Zhang



5250-5350MHz: (802.11ax80 5290MHz was tested)


Project No.: 2602P41234E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 5.3G WIFI
RBW:200Hz,VBW:1kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



Project No.: 2602P41234E-RF
 Polarization: Parallel
 Test Mode: Transmitting
 Note: 5.3G WIFI
 RBW:9kHz,VBW:30kHz

Serial No.: 3FXP-9
 Tester: Lancer Zhang



5470-5725MHz: (802.11ax40 5590MHz was tested)

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Parallel


Tester: Lancer Zhang

Test Mode: Transmitting

Note: 5.6G WIFI

RBW:200Hz,VBW:1kHz


Date: 2026-04-16



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.030	-2.81	46.71	43.90	118.10	74.20	Peak
2	0.055	0.86	42.63	43.49	112.85	69.36	Peak
3	0.076	2.49	39.12	41.61	110.04	68.43	Peak
4	0.081	2.43	38.08	40.51	109.41	68.90	Peak
5	0.112	6.67	34.26	40.93	106.58	65.65	Peak
6	0.132	4.86	33.11	37.97	105.19	67.22	Peak

Project No.: 2602P41234E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 5.6G WIFI
RBW:9kHz,VBW:30kHz


Serial No.: 3FXP-9
Tester: Lancer Zhang



5725-5850MHz: (802.11ax40 5795MHz was tested)


Project No.: 2602P41234E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 5.8G WIFI
RBW:200Hz,VBW:1kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



Project No.: 2602P41234E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 5.8G WIFI
RBW:9kHz,VBW:30kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



30MHz-1GHz

5150-5250MHz: (802.11ax20 5240MHz was tested)

Project No.: 2602P41234E-RF

Polarization: Horizontal


Test Mode: Transmitting

Note: 5.2G WIFI

RBW:120kHz,VBW:500kHz


Serial No.: 3FXP-9

Tester: Lancer Zhang



Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 5.2G WIFI
RBW:120kHz,VBW:500kHz


Serial No.: 3FXP-9
Tester: Lancer Zhang



5250-5350MHz: (802.11ax80 5290MHz was tested)


Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 5.3G WIFI
RBW:120kHz,VBW:500kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 5.3G WIFI
RBW:120kHz,VBW:500kHz


Serial No.: 3FXP-9
Tester: Lancer Zhang



5470-5725MHz: (802.11ax40 5590MHz was tested)

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 5.6G WIFI
RBW:120kHz,VBW:500kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical


Tester: Lancer Zhang

Test Mode: Transmitting

Note: 5.6G WIFI

RBW: 120kHz, VBW: 500kHz

Date: 2026-04-16




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	41.64	44.15	-12.26	31.89	40.00	8.11	QP
2	69.77	43.69	-16.55	27.14	40.00	12.86	Peak
3	129.91	34.80	-9.64	25.16	43.50	18.34	Peak
4	210.42	40.71	-12.50	28.21	43.50	15.29	Peak
5	270.56	34.28	-9.00	25.28	46.00	20.72	Peak
6	362.71	31.24	-7.22	24.02	46.00	21.98	Peak

5725-5850MHz: (802.11ax40 5795MHz was tested)


Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 5.8G WIFI
RBW:120kHz,VBW:500kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 5.8G WIFI
RBW:120kHz,VBW:500kHz

Serial No.: 3FXP-9
Tester: Lancer Zhang



2) 1-40GHz:

Serial Number:	3FXP-9	Test Date:	2026/1/23~2026/1/30
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Alan Xie, Leo Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	18.4-22.9	Relative Humidity: (%)	29-59	ATM Pressure: (kPa)	101.4-102.1
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2025/11/17	2026/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2025/11/14	2026/11/13
AH	Preamplifier	PAM-0118P	469	2025/4/11	2026/4/10
AH	Preamplifier	PAM-1840VH	191	2025/9/4	2026/9/3
R&S	Spectrum Analyzer	FSV40	101944	2025/8/8	2026/8/7
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2025/8/25	2026/8/24



* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



Test Data:

Please refer to the below plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.

1-18GHz:
5150-5250MHz:
Chain 0

802.11a, Low Channel, Horizontal								802.11a, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6350.40	50.60	0.28	50.88	68.20	17.32	Peak	1	6342.70	50.48	0.26	50.74	68.20	17.46	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz								Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							
Serial No.: 3FXP-9 Tester: Alan Xie								Serial No.: 3FXP-9 Tester: Alan Xie							
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10360.00	47.41	2.29	49.70	68.20	18.50	Peak	1	10360.00	48.22	2.29	50.51	68.20	17.69	Peak
2	15540.00	47.90	3.87	51.77	74.00	22.23	Peak	2	15540.00	47.66	3.87	51.53	74.00	22.47	Peak
3	17979.30	48.21	11.14	59.35	74.00	14.65	Peak	3	17979.30	48.37	11.14	59.51	74.00	14.49	Peak
4	17979.30	36.27	11.14	47.41	54.00	6.59	Average	4	17979.30	36.35	11.14	47.49	54.00	6.51	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11a_U-NII-1 middle channel 5200MHz Chain0

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6160.10	50.34	0.15	50.49	68.20	17.71	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11a_U-NII-1 middle channel 5200MHz Chain0

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6324.00	50.91	0.20	51.11	68.20	17.09	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11a_U-NII-1 middle channel 5200MHz Chain0

Peak:RBW:1MHz,VBW:3MHz

Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

3

2

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10400.00	46.03	2.30	48.33	68.20	19.87	Peak
2	15600.00	47.63	3.82	51.45	74.00	22.55	Peak
3	17983.90	48.41	11.18	59.59	74.00	14.41	Peak
4	17983.90	36.37	11.18	47.55	54.00	6.45	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11a_U-NII-1 middle channel 5200MHz Chain0

Peak:RBW:1MHz,VBW:3MHz

Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

3

2


1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10400.00	47.57	2.30	49.87	68.20	18.33	Peak
2	15600.00	47.65	3.82	51.47	74.00	22.53	Peak
3	17983.90	48.13	11.18	59.31	74.00	14.69	Peak
4	17983.90	36.29	11.18	47.47	54.00	6.53	Average

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain0
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6129.30	50.41	0.09	50.50	68.20	17.70	Peak

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain0
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 3FXP-9
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6331.70	50.64	0.24	50.88	68.20	17.32	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3FXP-9
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.84	2.33	49.17	68.20	19.03	Peak
2	15720.00	47.61	3.59	51.20	74.00	22.80	Peak
3	17981.60	47.86	11.17	59.03	74.00	14.97	Peak
4	17981.60	36.27	11.17	47.44	54.00	6.56	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.40	2.33	48.73	68.20	19.47	Peak
2	15720.00	47.38	3.59	50.97	74.00	23.03	Peak
3	17910.30	49.06	10.67	59.73	74.00	14.27	Peak
4	17910.30	36.53	10.67	47.20	54.00	6.80	Average

Chain 1

802.11a, Low Channel, Horizontal	802.11a, Low Channel, Vertical																																																																																
Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Level (dBuV/m) Frequency (MHz) Fundamental test with Filter Switch Unit PK AV <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>5946.70</td><td>50.12</td><td>0.43</td><td>50.55</td><td>68.20</td><td>17.65</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	5946.70	50.12	0.43	50.55	68.20	17.65	Peak	Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Level (dBuV/m) Frequency (MHz) Fundamental test with Filter Switch Unit PK AV <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6353.70</td><td>51.06</td><td>0.29</td><td>51.35</td><td>68.20</td><td>16.85</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6353.70	51.06	0.29	51.35	68.20	16.85	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	5946.70	50.12	0.43	50.55	68.20	17.65	Peak																																																																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	6353.70	51.06	0.29	51.35	68.20	16.85	Peak																																																																										
Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Level (dBuV/m) Frequency (MHz) PK AV <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10360.00</td><td>46.87</td><td>2.29</td><td>49.16</td><td>68.20</td><td>19.04</td><td>Peak</td></tr><tr><td>2</td><td>15540.00</td><td>47.70</td><td>3.87</td><td>51.57</td><td>74.00</td><td>22.43</td><td>Peak</td></tr><tr><td>3</td><td>17983.90</td><td>48.09</td><td>11.18</td><td>59.27</td><td>74.00</td><td>14.73</td><td>Peak</td></tr><tr><td>4</td><td>17983.90</td><td>36.28</td><td>11.18</td><td>47.46</td><td>54.00</td><td>6.54</td><td>Average</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10360.00	46.87	2.29	49.16	68.20	19.04	Peak	2	15540.00	47.70	3.87	51.57	74.00	22.43	Peak	3	17983.90	48.09	11.18	59.27	74.00	14.73	Peak	4	17983.90	36.28	11.18	47.46	54.00	6.54	Average	Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-1 low channel 5180MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Level (dBuV/m) Frequency (MHz) PK AV <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10360.00</td><td>47.56</td><td>2.29</td><td>49.85</td><td>68.20</td><td>18.35</td><td>Peak</td></tr><tr><td>2</td><td>15540.00</td><td>46.78</td><td>3.87</td><td>50.65</td><td>74.00</td><td>23.35</td><td>Peak</td></tr><tr><td>3</td><td>17951.70</td><td>48.36</td><td>10.96</td><td>59.32</td><td>74.00</td><td>14.68</td><td>Peak</td></tr><tr><td>4</td><td>17951.70</td><td>36.39</td><td>10.96</td><td>47.35</td><td>54.00</td><td>6.65</td><td>Average</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10360.00	47.56	2.29	49.85	68.20	18.35	Peak	2	15540.00	46.78	3.87	50.65	74.00	23.35	Peak	3	17951.70	48.36	10.96	59.32	74.00	14.68	Peak	4	17951.70	36.39	10.96	47.35	54.00	6.65	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	10360.00	46.87	2.29	49.16	68.20	19.04	Peak																																																																										
2	15540.00	47.70	3.87	51.57	74.00	22.43	Peak																																																																										
3	17983.90	48.09	11.18	59.27	74.00	14.73	Peak																																																																										
4	17983.90	36.28	11.18	47.46	54.00	6.54	Average																																																																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	10360.00	47.56	2.29	49.85	68.20	18.35	Peak																																																																										
2	15540.00	46.78	3.87	50.65	74.00	23.35	Peak																																																																										
3	17951.70	48.36	10.96	59.32	74.00	14.68	Peak																																																																										
4	17951.70	36.39	10.96	47.35	54.00	6.65	Average																																																																										

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 middle channel 5200MHz Chain1
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

Fundamental test with Filter Switch Unit

AV

PK

1

2026-01-23

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5766.30	50.05	0.24	50.29	68.20	17.91	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 middle channel 5200MHz Chain1
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

Fundamental test with Filter Switch Unit

AV

PK

1

2026-01-23

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5812.50	50.64	0.28	50.92	68.20	17.28	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 middle channel 5200MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

2

3

4

2026-01-23

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10400.00	46.39	2.30	48.69	68.20	19.51	Peak
2	15600.00	48.83	3.82	52.65	74.00	21.35	Peak
3	17862.00	49.41	10.24	59.65	74.00	14.35	Peak
4	17862.00	36.50	10.24	46.74	54.00	7.26	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 middle channel 5200MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

2

3

4

2026-01-23


Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10400.00	47.02	2.30	49.32	68.20	18.88	Peak
2	15600.00	47.28	3.82	51.10	74.00	22.90	Peak
3	18000.00	48.25	11.29	59.54	74.00	14.46	Peak
4	18000.00	36.34	11.29	47.63	54.00	6.37	Average

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain1
Peak:RBW:1MHz,VBW:30Hz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5943.40	50.00	0.42	50.42	68.20	17.78	Peak

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain1
Peak:RBW:1MHz,VBW:30Hz


Serial No.: 3FXP-9
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6003.90	50.21	0.45	50.66	68.20	17.54	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain1
Peak:RBW:1MHz,VBW:30Hz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3FXP-9
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.42	2.33	48.75	68.20	19.45	Peak
2	15720.00	47.75	3.59	51.34	74.00	22.66	Peak
3	17995.40	47.79	11.26	59.05	74.00	14.95	Peak
4	17995.40	36.26	11.26	47.52	54.00	6.48	Average


Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain1
Peak:RBW:1MHz,VBW:30Hz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.10	2.33	48.43	68.20	19.77	Peak
2	15720.00	46.49	3.59	50.08	74.00	23.92	Peak
3	17974.70	48.10	11.10	59.20	74.00	14.80	Peak
4	17974.70	36.36	11.10	47.46	54.00	6.54	Average

802.11ac20, Low Channel, Horizontal



802.11ac20, Low Channel, Vertical



802.11ac20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 middle channel 5200MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

AV

PK

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6363.60	50.04	0.28	50.32	68.20	17.88	Peak

802.11ac20, Middle Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 middle channel 5200MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

AV

PK

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6052.30	50.30	0.38	50.68	68.20	17.52	Peak

802.11ac20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 middle channel 5200MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

1

2

3

4

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10400.00	47.10	2.30	49.40	68.20	18.80	Peak
2	15600.00	47.91	3.82	51.73	74.00	22.27	Peak
3	17995.40	47.95	11.26	59.21	74.00	14.79	Peak
4	17995.40	36.32	11.26	47.58	54.00	6.42	Average

802.11ac20, Middle Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 middle channel 5200MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

1

2

3

4

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10400.00	46.00	2.30	48.30	68.20	19.90	Peak
2	15600.00	49.04	3.82	52.86	74.00	21.14	Peak
3	17995.40	48.84	11.26	60.10	74.00	13.90	Peak
4	17995.40	36.37	11.26	47.63	54.00	6.37	Average

802.11ac20, High Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz

2026-01-23

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6243.70	50.30	0.01	50.31	68.20	17.89	Peak

802.11ac20, High Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz

2026-01-23

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6003.90	50.23	0.45	50.68	68.20	17.52	Peak

802.11ac20, High Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

2026-01-23

Level (dBuV/m)

Frequency (MHz)

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.48	2.33	48.81	68.20	19.39	Peak
2	15720.00	47.20	3.59	50.79	74.00	23.21	Peak
3	17981.60	48.68	11.17	59.85	74.00	14.15	Peak
4	17981.60	36.43	11.17	47.60	54.00	6.40	Average

802.11ac20, High Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

2026-01-23

Level (dBuV/m)

Frequency (MHz)

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	47.67	2.33	50.00	68.20	18.20	Peak
2	15720.00	48.20	3.59	51.79	74.00	22.21	Peak
3	17995.40	47.81	11.26	59.07	74.00	14.93	Peak
4	17995.40	36.34	11.26	47.60	54.00	6.40	Average

802.11ac40, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 low channel 5190MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090

PK

AV

1

2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5891.70	50.63	0.39	51.02	68.20	17.18	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 low channel 5190MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090

PK

AV

1

2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6463.70	50.37	0.21	50.58	68.20	17.62	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 low channel 5190MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

6500880011100134001570018000

2030405060708090

PK

1

2

3

2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10380.00	47.66	2.27	49.93	68.20	18.27	Peak
2	15570.00	48.92	3.91	52.83	74.00	21.17	Peak
3	17986.20	48.52	11.19	59.71	74.00	14.29	Peak
4	17986.20	36.52	11.19	47.71	54.00	6.29	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 low channel 5190MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie

Level (dBuV/m)

6500880011100134001570018000

2030405060708090

PK

1

2

3

2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10380.00	48.44	2.27	50.71	68.20	17.49	Peak
2	15570.00	48.13	3.91	52.04	74.00	21.96	Peak
3	17944.80	48.90	10.92	59.82	74.00	14.18	Peak
4	17944.80	36.45	10.92	47.37	54.00	6.63	Average

802.11ac40, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 high channel 5230MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6051.20	50.39	0.39	50.78	68.20	17.42	Peak

802.11ac40, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 high channel 5230MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Alan Xie

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5703.60	50.32	0.15	50.47	68.20	17.73	Peak

802.11ac40, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 high channel 5230MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10460.00	47.13	2.35	49.48	68.20	18.72	Peak
2	15690.00	48.39	3.64	52.03	74.00	21.97	Peak
3	17993.10	48.18	11.25	59.43	74.00	14.57	Peak
4	17993.10	36.36	11.25	47.61	54.00	6.39	Average

802.11ac40, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-1 high channel 5230MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10460.00	46.73	2.35	49.08	68.20	19.12	Peak
2	15690.00	48.23	3.64	51.87	74.00	22.13	Peak
3	18000.00	49.12	11.29	60.41	74.00	13.59	Peak
4	18000.00	36.54	11.29	47.83	54.00	6.17	Average

802.11ac80, Middle Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac80_U-NII-1 middle channel 5210MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5074.40	51.99	-1.28	50.71	74.00	23.29	Peak

802.11ac80, Middle Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac80_U-NII-1 middle channel 5210MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5843.30	49.83	0.32	50.15	68.20	18.05	Peak


Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac80_U-NII-1 middle channel 5210MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10420.00	46.46	2.31	48.77	68.20	19.43	Peak
2	15630.00	47.68	3.74	51.42	74.00	22.58	Peak
3	17912.60	48.54	10.69	59.23	74.00	14.77	Peak
4	17912.60	36.37	10.69	47.06	54.00	6.94	Average

Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac80_U-NII-1 middle channel 5210MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10420.00	46.66	2.31	48.97	68.20	19.23	Peak
2	15630.00	48.58	3.74	52.32	74.00	21.68	Peak
3	17995.40	49.38	11.26	60.64	74.00	13.36	Peak
4	17995.40	36.46	11.26	47.72	54.00	6.28	Average




802.11ax20, Low Channel, Horizontal								802.11ax20, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-1 low channel 5180MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-1 low channel 5180MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6183.20	50.64	0.22	50.86	68.20	17.34	Peak	1	5863.10	50.21	0.35	50.56	68.20	17.64	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-1 low channel 5180MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz								Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-1 low channel 5180MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							
Serial No.: 3FXP-9 Tester: Alan Xie								Serial No.: 3FXP-9 Tester: Alan Xie							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10360.00	47.91	2.29	50.20	68.20	18.00	Peak	1	10360.00	47.91	2.29	50.20	68.20	18.00	Peak
2	15540.00	48.81	3.87	52.68	74.00	21.32	Peak	2	15540.00	48.12	3.87	51.99	74.00	22.01	Peak
3	17974.70	48.88	11.10	59.98	74.00	14.02	Peak	3	17967.80	48.77	11.06	59.83	74.00	14.17	Peak
4	17974.70	36.36	11.10	47.46	54.00	6.54	Average	4	17967.80	36.42	11.06	47.48	54.00	6.52	Average

802.11ax20, Middle Channel, Horizontal



802.11ax20, Middle Channel, Vertical



802.11ax20, High Channel, Horizontal

Project No.: 2602P41234E-RF

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ax20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9

Tester: Alan Xie

Level (dBuV/m)

100

90.0

80.0

70.0

60.0

50.0

40.0

30.0

20

1000

2100

3200

4300

5400

6500

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5519.90	50.38	-0.09	50.29	68.20	17.91	Peak

802.11ax20, High Channel, Vertical

Project No.: 2602P41234E-RF

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ax20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9

Tester: Alan Xie

Level (dBuV/m)

100

90.0

80.0

70.0

60.0

50.0

40.0

30.0

20

1000

2100

3200

4300

5400

6500

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5556.20	50.54	-0.05	50.49	68.20	17.71	Peak

Project No.: 2602P41234E-RF

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ax20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9

Tester: Alan Xie

Level (dBuV/m)

100

90.0

80.0

70.0

60.0

50.0

40.0

30.0

20

6500

8800

11100

13400

15700

18000

Frequency (MHz)

PK

3

2

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	47.05	2.33	49.38	68.20	18.82	Peak
2	15720.00	48.53	3.59	52.12	74.00	21.88	Peak
3	17979.30	49.26	11.14	60.40	74.00	13.60	Peak
4	17979.30	36.62	11.14	47.76	54.00	6.24	Average

Project No.: 2602P41234E-RF

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ax20_U-NII-1 high channel 5240MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9

Tester: Alan Xie

Level (dBuV/m)

100

90.0

80.0

70.0

60.0

50.0

40.0

30.0

20

6500

8800

11100

13400

15700

18000

Frequency (MHz)



PK



3

2

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10480.00	46.79	2.33	49.12	68.20	19.08	Peak
2	15720.00	48.19	3.59	51.78	74.00	22.22	Peak
3	18000.00	48.44	11.29	59.73	74.00	14.27	Peak
4	18000.00	36.38	11.29	47.67	54.00	6.33	Average

802.11ax40, Low Channel, Horizontal							802.11ax40, Low Channel, Vertical								
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-1 low channel 5190MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-1 low channel 5190MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie				
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5943.40	50.12	0.42	50.54	68.20	17.66	Peak	1	6262.40	50.87	0.13	51.00	68.20	17.20	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-1 low channel 5190MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Alan Xie			Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-1 low channel 5190MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Alan Xie				
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10380.00	47.83	2.27	50.10	68.20	18.10	Peak	1	10380.00	47.64	2.27	49.91	68.20	18.29	Peak
2	15570.00	47.32	3.91	51.23	74.00	22.77	Peak	2	15570.00	49.10	3.91	53.01	74.00	20.99	Peak
3	17988.50	49.03	11.21	60.24	74.00	13.76	Peak	3	17988.50	48.50	11.21	59.71	74.00	14.29	Peak
4	17988.50	36.68	11.21	47.89	54.00	6.11	Average	4	17988.50	36.37	11.21	47.58	54.00	6.42	Average

802.11ax40, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-1 high channel 5230MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5782.80	50.24	0.25	50.49	68.20	17.71	Peak

802.11ax40, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-1 high channel 5230MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6201.90	50.77	0.14	50.91	68.20	17.29	Peak

802.11ax40, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-1 high channel 5230MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10460.00	46.66	2.35	49.01	68.20	19.19	Peak
2	15690.00	47.86	3.64	51.50	74.00	22.50	Peak
3	17981.60	49.67	11.17	60.84	74.00	13.16	Peak
4	17981.60	36.38	11.17	47.55	54.00	6.45	Average

802.11ax40, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-1 high channel 5230MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Alan Xie			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10460.00	47.21	2.35	49.56	68.20	18.64	Peak
2	15690.00	48.07	3.64	51.71	74.00	22.29	Peak
3	17993.10	49.11	11.25	60.36	74.00	13.64	Peak
4	17993.10	36.41	11.25	47.66	54.00	6.34	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11ax80_U-NII-1 middle channel 5210MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6486.80	50.49	0.25	50.74	68.20	17.46	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11ax80_U-NII-1 middle channel 5210MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6132.60	50.90	0.09	50.99	68.20	17.21	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11ax80_U-NII-1 middle channel 5210MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

1

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10420.00	46.94	2.31	49.25	68.20	18.95	Peak
2	15630.00	48.46	3.74	52.20	74.00	21.80	Peak
3	17977.00	48.08	11.12	59.20	74.00	14.80	Peak
4	17977.00	36.43	11.12	47.55	54.00	6.45	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Tester: Alan Xie

Test Mode: Transmitting

Note: 802.11ax80_U-NII-1 middle channel 5210MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

1

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10420.00	47.58	2.31	49.89	68.20	18.31	Peak
2	15630.00	47.85	3.74	51.59	74.00	22.41	Peak
3	17981.60	48.13	11.17	59.30	74.00	14.70	Peak
4	17981.60	36.36	11.17	47.53	54.00	6.47	Average

5250-5350MHz:
Chain 0

802.11a, Low Channel, Horizontal	802.11a, Low Channel, Vertical																																																																																
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Frequency (MHz) Fundamental test with Filter Switch Unit PK AV <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6458.20</td><td>50.80</td><td>0.23</td><td>51.03</td><td>68.20</td><td>17.17</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6458.20	50.80	0.23	51.03	68.20	17.17	Peak	Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Frequency (MHz) Fundamental test with Filter Switch Unit PK AV <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>5947.80</td><td>50.37</td><td>0.43</td><td>50.80</td><td>68.20</td><td>17.40</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	5947.80	50.37	0.43	50.80	68.20	17.40	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	6458.20	50.80	0.23	51.03	68.20	17.17	Peak																																																																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	5947.80	50.37	0.43	50.80	68.20	17.40	Peak																																																																										
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Frequency (MHz) PK 1 2 3 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10520.00</td><td>48.15</td><td>2.29</td><td>50.44</td><td>68.20</td><td>17.76</td><td>Peak</td></tr><tr><td>2</td><td>15780.00</td><td>48.81</td><td>3.55</td><td>52.36</td><td>74.00</td><td>21.64</td><td>Peak</td></tr><tr><td>3</td><td>17951.70</td><td>48.56</td><td>10.96</td><td>59.52</td><td>74.00</td><td>14.48</td><td>Peak</td></tr><tr><td>4</td><td>17951.70</td><td>36.45</td><td>10.96</td><td>47.41</td><td>54.00</td><td>6.59</td><td>Average</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10520.00	48.15	2.29	50.44	68.20	17.76	Peak	2	15780.00	48.81	3.55	52.36	74.00	21.64	Peak	3	17951.70	48.56	10.96	59.52	74.00	14.48	Peak	4	17951.70	36.45	10.96	47.41	54.00	6.59	Average	Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Frequency (MHz) PK 1 2 3 4 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10520.00</td><td>47.79</td><td>2.29</td><td>50.08</td><td>68.20</td><td>18.12</td><td>Peak</td></tr><tr><td>2</td><td>15780.00</td><td>48.57</td><td>3.55</td><td>52.12</td><td>74.00</td><td>21.88</td><td>Peak</td></tr><tr><td>3</td><td>17988.50</td><td>49.16</td><td>11.21</td><td>60.37</td><td>74.00</td><td>13.63</td><td>Peak</td></tr><tr><td>4</td><td>17988.50</td><td>36.70</td><td>11.21</td><td>47.91</td><td>54.00</td><td>6.09</td><td>Average</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10520.00	47.79	2.29	50.08	68.20	18.12	Peak	2	15780.00	48.57	3.55	52.12	74.00	21.88	Peak	3	17988.50	49.16	11.21	60.37	74.00	13.63	Peak	4	17988.50	36.70	11.21	47.91	54.00	6.09	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	10520.00	48.15	2.29	50.44	68.20	17.76	Peak																																																																										
2	15780.00	48.81	3.55	52.36	74.00	21.64	Peak																																																																										
3	17951.70	48.56	10.96	59.52	74.00	14.48	Peak																																																																										
4	17951.70	36.45	10.96	47.41	54.00	6.59	Average																																																																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	10520.00	47.79	2.29	50.08	68.20	18.12	Peak																																																																										
2	15780.00	48.57	3.55	52.12	74.00	21.88	Peak																																																																										
3	17988.50	49.16	11.21	60.37	74.00	13.63	Peak																																																																										
4	17988.50	36.70	11.21	47.91	54.00	6.09	Average																																																																										

802.11a, Middle Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A middle channel 5280MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6274.50	50.57	0.27	50.84	68.20	17.36	Peak

802.11a, Middle Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A middle channel 5280MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6493.40	50.57	0.27	50.84	68.20	17.36	Peak


802.11a, Middle Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A middle channel 5280MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10560.00	48.44	2.29	50.73	68.20	17.47	Peak
2	15840.00	47.79	3.44	51.23	74.00	22.77	Peak
3	17947.10	48.64	10.93	59.57	74.00	14.43	Peak
4	17947.10	36.51	10.93	47.44	54.00	6.56	Average

802.11a, Middle Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A middle channel 5280MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10560.00	48.69	2.29	50.98	68.20	17.22	Peak
2	15840.00	48.21	3.44	51.65	74.00	22.35	Peak
3	17988.50	48.36	11.21	59.57	74.00	14.43	Peak
4	17988.50	36.40	11.21	47.61	54.00	6.39	Average

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2A high channel 5320MHz Chain0
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6359.20	50.87	0.30	51.17	68.20	17.03	Peak

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2A high channel 5320MHz Chain0
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6326.20	49.99	0.21	50.20	68.20	18.00	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2A high channel 5320MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10640.00	48.28	2.48	50.76	74.00	23.24	Peak
2	15960.00	49.33	3.54	52.87	74.00	21.13	Peak
3	17981.60	48.98	11.17	60.15	74.00	13.85	Peak
4	17981.60	36.77	11.17	47.94	54.00	6.06	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2A high channel 5320MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10640.00	48.08	2.48	50.56	74.00	23.44	Peak
2	15960.00	47.35	3.54	50.89	74.00	23.11	Peak
3	17979.30	48.26	11.14	59.40	74.00	14.60	Peak
4	17979.30	36.53	11.14	47.67	54.00	6.33	Average

Chain 1




802.11a, Low Channel, Horizontal								802.11a, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Level (dBuV/m) Fundamental test with Filter Switch Unit AV PK 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 1000 2100 3200 4300 5400 6500 Frequency (MHz)								Level (dBuV/m) Fundamental test with Filter Switch Unit AV PK 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 1000 2100 3200 4300 5400 6500 Frequency (MHz)							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6471.40	50.19	0.22	50.41	68.20	17.79	Peak	1	6105.10	50.15	0.12	50.27	68.20	17.93	Peak



Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A low channel 5260MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Level (dBuV/m) 1 2 3 PK 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 6500 8800 11100 13400 15700 18000 Frequency (MHz)								Level (dBuV/m) 1 2 3 PK 100 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20 6500 8800 11100 13400 15700 18000 Frequency (MHz)							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10520.00	47.58	2.29	49.87	68.20	18.33	Peak	1	10520.00	47.92	2.29	50.21	68.20	17.99	Peak
2	15780.00	48.40	3.55	51.95	74.00	22.05	Peak	2	15780.00	48.66	3.55	52.21	74.00	21.79	Peak
3	17979.30	48.58	11.14	59.72	74.00	14.28	Peak	3	17990.80	48.62	11.23	59.85	74.00	14.15	Peak
4	17979.30	36.44	11.14	47.58	54.00	6.42	Average	4	17990.80	36.22	11.23	47.45	54.00	6.55	Average



802.11a, Middle Channel, Horizontal







802.11a, Middle Channel, Vertical



802.11a, High Channel, Horizontal								802.11a, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A high channel 5320MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A high channel 5320MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6116.10	50.02	0.12	50.14	68.20	18.06	Peak	1	6468.10	50.48	0.20	50.68	68.20	17.52	Peak


Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2A high channel 5320MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz								Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2A high channel 5320MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10640.00	48.88	2.48	51.36	74.00	22.64	Peak	1	10640.00	49.10	2.48	51.58	74.00	22.42	Peak
2	15960.00	48.23	3.54	51.77	74.00	22.23	Peak	2	15960.00	47.61	3.54	51.15	74.00	22.85	Peak
3	17990.80	48.47	11.23	59.70	74.00	14.30	Peak	3	17990.80	48.06	11.23	59.29	74.00	14.71	Peak
4	17990.80	36.69	11.23	47.92	54.00	6.08	Average	4	17990.80	36.32	11.23	47.55	54.00	6.45	Average

802.11ac20, Low Channel, Horizontal								802.11ac20, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6385.60	50.93	0.18	51.11	68.20	17.09	Peak	1	5970.90	49.96	0.44	50.40	68.20	17.80	Peak




Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz								Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							
Serial No.: 3FXP-9 Tester: Leo Xiao								Serial No.: 3FXP-9 Tester: Leo Xiao							
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10520.00	48.39	2.29	50.68	68.20	17.52	Peak	1	10520.00	48.87	2.29	51.16	68.20	17.04	Peak
2	15780.00	49.11	3.55	52.66	74.00	21.34	Peak	2	15780.00	48.70	3.55	52.25	74.00	21.75	Peak
3	17937.90	48.83	10.85	59.68	74.00	14.32	Peak	3	17993.10	48.18	11.25	59.43	74.00	14.57	Peak
4	17937.90	36.60	10.85	47.45	54.00	6.55	Average	4	17993.10	36.73	11.25	47.98	54.00	6.02	Average

802.11ac20, Middle Channel, Horizontal				802.11ac20, Middle Channel, Vertical																																																																																			
Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Horizontal Tester: Leo Xiao Test Mode: Transmitting Note: 802.11ac20_U-NII-2A middle channel 5280MHz Peak:RBW:1MHz,VBW:3MHz Level (dBuV/m) Frequency (MHz) Fundamental test with Filter Switch Unit AV PK 1 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6165.60</td><td>50.19</td><td>0.18</td><td>50.37</td><td>68.20</td><td>17.83</td><td>Peak</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6165.60	50.19	0.18	50.37	68.20	17.83	Peak	Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Vertical Tester: Leo Xiao Test Mode: Transmitting Note: 802.11ac20_U-NII-2A middle channel 5280MHz Peak:RBW:1MHz,VBW:3MHz Level (dBuV/m) Frequency (MHz) Fundamental test with Filter Switch Unit AV PK 1 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6492.30</td><td>50.51</td><td>0.26</td><td>50.77</td><td>68.20</td><td>17.43</td><td>Peak</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6492.30	50.51	0.26	50.77	68.20	17.43	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	6165.60	50.19	0.18	50.37	68.20	17.83	Peak																																																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	6492.30	50.51	0.26	50.77	68.20	17.43	Peak																																																																																
Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Horizontal Tester: Leo Xiao Test Mode: Transmitting Note: 802.11ac20_U-NII-2A middle channel 5280MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Level (dBuV/m) Frequency (MHz) 1 2 3 PK <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10560.00</td><td>49.93</td><td>2.29</td><td>52.22</td><td>68.20</td><td>15.98</td><td>Peak</td></tr><tr><td>2</td><td>15840.00</td><td>48.41</td><td>3.44</td><td>51.85</td><td>74.00</td><td>22.15</td><td>Peak</td></tr><tr><td>3</td><td>17990.80</td><td>48.22</td><td>11.23</td><td>59.45</td><td>74.00</td><td>14.55</td><td>Peak</td></tr><tr><td>4</td><td>17990.80</td><td>36.48</td><td>11.23</td><td>47.71</td><td>54.00</td><td>6.29</td><td>Average</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10560.00	49.93	2.29	52.22	68.20	15.98	Peak	2	15840.00	48.41	3.44	51.85	74.00	22.15	Peak	3	17990.80	48.22	11.23	59.45	74.00	14.55	Peak	4	17990.80	36.48	11.23	47.71	54.00	6.29	Average	Project No.: 2602P41234E-RF Serial No.: 3FXP-9 Polarization: Vertical Tester: Leo Xiao Test Mode: Transmitting Note: 802.11ac20_U-NII-2A middle channel 5280MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Level (dBuV/m) Frequency (MHz) 1 2 3 PK <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10560.00</td><td>48.61</td><td>2.29</td><td>50.90</td><td>68.20</td><td>17.30</td><td>Peak</td></tr><tr><td>2</td><td>15840.00</td><td>47.56</td><td>3.44</td><td>51.00</td><td>74.00</td><td>23.00</td><td>Peak</td></tr><tr><td>3</td><td>17988.50</td><td>49.24</td><td>11.21</td><td>60.45</td><td>74.00</td><td>13.55</td><td>Peak</td></tr><tr><td>4</td><td>17988.50</td><td>36.41</td><td>11.21</td><td>47.62</td><td>54.00</td><td>6.38</td><td>Average</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10560.00	48.61	2.29	50.90	68.20	17.30	Peak	2	15840.00	47.56	3.44	51.00	74.00	23.00	Peak	3	17988.50	49.24	11.21	60.45	74.00	13.55	Peak	4	17988.50	36.41	11.21	47.62	54.00	6.38	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	10560.00	49.93	2.29	52.22	68.20	15.98	Peak																																																																																
2	15840.00	48.41	3.44	51.85	74.00	22.15	Peak																																																																																
3	17990.80	48.22	11.23	59.45	74.00	14.55	Peak																																																																																
4	17990.80	36.48	11.23	47.71	54.00	6.29	Average																																																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	10560.00	48.61	2.29	50.90	68.20	17.30	Peak																																																																																
2	15840.00	47.56	3.44	51.00	74.00	23.00	Peak																																																																																
3	17988.50	49.24	11.21	60.45	74.00	13.55	Peak																																																																																
4	17988.50	36.41	11.21	47.62	54.00	6.38	Average																																																																																

802.11ac20, High Channel, Horizontal



802.11ac20, High Channel, Vertical



802.11ac40, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	5974.20	50.35	0.43	50.78	68.20	17.42	Peak

802.11ac40, Low Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	6487.90	50.12	0.25	50.37	68.20	17.83	Peak

802.11ac40, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	10540.00	48.38	2.29	50.67	68.20	17.53	Peak
2	15810.00	48.41	3.49	51.90	74.00	22.10	Peak
3	17993.10	48.82	11.25	60.07	74.00	13.93	Peak
4	17993.10	36.34	11.25	47.59	54.00	6.41	Average

802.11ac40, Low Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	10540.00	48.87	2.29	51.16	68.20	17.04	Peak
2	15810.00	48.37	3.49	51.86	74.00	22.14	Peak
3	17986.20	48.67	11.19	59.86	74.00	14.14	Peak
4	17986.20	36.77	11.19	47.96	54.00	6.04	Average

802.11ac40, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac40_U-NII-2A high channel 5310MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6097.40	50.61	0.13	50.74	68.20	17.46	Peak

802.11ac40, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac40_U-NII-2A high channel 5310MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6069.90	50.14	0.31	50.45	68.20	17.75	Peak


Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac40_U-NII-2A high channel 5310MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10620.00	49.13	2.40	51.53	74.00	22.47	Peak
2	15930.00	48.04	3.59	51.63	74.00	22.37	Peak
3	17988.50	48.58	11.21	59.79	74.00	14.21	Peak
4	17988.50	36.70	11.21	47.91	54.00	6.09	Average

Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac40_U-NII-2A high channel 5310MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-29							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10620.00	48.71	2.40	51.11	74.00	22.89	Peak
2	15930.00	47.55	3.59	51.14	74.00	22.86	Peak
3	17990.80	48.64	11.23	59.87	74.00	14.13	Peak
4	17990.80	36.38	11.23	47.61	54.00	6.39	Average

802.11ac80, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6111.70	50.34	0.12	50.46	68.20	17.74	Peak

802.11ac80, Low Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6362.50	50.47	0.29	50.76	68.20	17.44	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10580.00	50.04	2.30	52.34	68.20	15.86	Peak
2	15870.00	48.26	3.43	51.69	74.00	22.31	Peak
3	17977.00	48.30	11.12	59.42	74.00	14.58	Peak
4	17977.00	36.84	11.12	47.96	54.00	6.04	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2A middle channel 5290MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10580.00	48.85	2.30	51.15	68.20	17.05	Peak
2	15870.00	48.24	3.43	51.67	74.00	22.33	Peak
3	17993.10	48.08	11.25	59.33	74.00	14.67	Peak
4	17993.10	36.33	11.25	47.58	54.00	6.42	Average

802.11ax20, Low Channel, Horizontal								802.11ax20, Low Channel, Vertical																																																																																							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao																																																																																			
Level (dBuV/m) Fundamental test with Filter Switch Unit Date: 2026-01-29 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6460.40</td><td>50.56</td><td>0.22</td><td>50.78</td><td>68.20</td><td>17.42</td><td>Peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6460.40	50.56	0.22	50.78	68.20	17.42	Peak	Level (dBuV/m) Fundamental test with Filter Switch Unit Date: 2026-01-29 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6340.50</td><td>50.60</td><td>0.26</td><td>50.86</td><td>68.20</td><td>17.34</td><td>Peak</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6340.50	50.60	0.26	50.86	68.20	17.34	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																								
1	6460.40	50.56	0.22	50.78	68.20	17.42	Peak																																																																																								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																								
1	6340.50	50.60	0.26	50.86	68.20	17.34	Peak																																																																																								
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Date: 2026-01-29 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10520.00</td><td>48.43</td><td>2.29</td><td>50.72</td><td>68.20</td><td>17.48</td><td>Peak</td></tr><tr><td>2</td><td>15780.00</td><td>48.68</td><td>3.55</td><td>52.23</td><td>74.00</td><td>21.77</td><td>Peak</td></tr><tr><td>3</td><td>17988.50</td><td>48.39</td><td>11.21</td><td>59.60</td><td>74.00</td><td>14.40</td><td>Peak</td></tr><tr><td>4</td><td>17988.50</td><td>36.34</td><td>11.21</td><td>47.55</td><td>54.00</td><td>6.45</td><td>Average</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10520.00	48.43	2.29	50.72	68.20	17.48	Peak	2	15780.00	48.68	3.55	52.23	74.00	21.77	Peak	3	17988.50	48.39	11.21	59.60	74.00	14.40	Peak	4	17988.50	36.34	11.21	47.55	54.00	6.45	Average	Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-2A low channel 5260MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Date: 2026-01-29 <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>10520.00</td><td>48.53</td><td>2.29</td><td>50.82</td><td>68.20</td><td>17.38</td><td>Peak</td></tr><tr><td>2</td><td>15780.00</td><td>48.22</td><td>3.55</td><td>51.77</td><td>74.00</td><td>22.23</td><td>Peak</td></tr><tr><td>3</td><td>17995.40</td><td>48.29</td><td>11.26</td><td>59.55</td><td>74.00</td><td>14.45</td><td>Peak</td></tr><tr><td>4</td><td>17995.40</td><td>36.41</td><td>11.26</td><td>47.67</td><td>54.00</td><td>6.33</td><td>Average</td></tr></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	10520.00	48.53	2.29	50.82	68.20	17.38	Peak	2	15780.00	48.22	3.55	51.77	74.00	22.23	Peak	3	17995.40	48.29	11.26	59.55	74.00	14.45	Peak	4	17995.40	36.41	11.26	47.67	54.00	6.33	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																								
1	10520.00	48.43	2.29	50.72	68.20	17.48	Peak																																																																																								
2	15780.00	48.68	3.55	52.23	74.00	21.77	Peak																																																																																								
3	17988.50	48.39	11.21	59.60	74.00	14.40	Peak																																																																																								
4	17988.50	36.34	11.21	47.55	54.00	6.45	Average																																																																																								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																								
1	10520.00	48.53	2.29	50.82	68.20	17.38	Peak																																																																																								
2	15780.00	48.22	3.55	51.77	74.00	22.23	Peak																																																																																								
3	17995.40	48.29	11.26	59.55	74.00	14.45	Peak																																																																																								
4	17995.40	36.41	11.26	47.67	54.00	6.33	Average																																																																																								

802.11ax20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A middle channel 5280MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-29

Fundamental test with Filter Switch Unit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5974.20	50.38	0.43	50.81	68.20	17.39	Peak

802.11ax20, Middle Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A middle channel 5280MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-29

Fundamental test with Filter Switch Unit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6298.70	50.60	0.19	50.79	68.20	17.41	Peak

802.11ax20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A middle channel 5280MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10560.00	48.26	2.29	50.55	68.20	17.65	Peak
2	15840.00	48.57	3.44	52.01	74.00	21.99	Peak
3	17972.40	48.43	11.09	59.52	74.00	14.48	Peak
4	17972.40	36.65	11.09	47.74	54.00	6.26	Average

802.11ax20, Middle Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A middle channel 5280MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10560.00	48.26	2.29	50.55	68.20	17.65	Peak
2	15840.00	48.04	3.44	51.48	74.00	22.52	Peak
3	17990.80	48.35	11.23	59.58	74.00	14.42	Peak
4	17990.80	36.19	11.23	47.42	54.00	6.58	Average

802.11ax20, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A high channel 5320MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6390.00	51.33	0.19	51.52	68.20	16.68	Peak

802.11ax20, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A high channel 5320MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6470.30	51.14	0.22	51.36	68.20	16.84	Peak

802.11ax20, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A high channel 5320MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10640.00	48.71	2.48	51.19	74.00	22.81	Peak
2	15960.00	48.12	3.54	51.66	74.00	22.34	Peak
3	17981.60	48.27	11.17	59.44	74.00	14.56	Peak
4	17981.60	36.27	11.17	47.44	54.00	6.56	Average

802.11ax20, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2A high channel 5320MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-29

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10640.00	48.73	2.48	51.21	74.00	22.79	Peak
2	15960.00	48.46	3.54	52.00	74.00	22.00	Peak
3	17990.80	48.47	11.23	59.70	74.00	14.30	Peak
4	17990.80	36.37	11.23	47.60	54.00	6.40	Average

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090100

Frequency (MHz)

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6456.00	50.28	0.23	50.51	68.20	17.69	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090100

Frequency (MHz)

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6111.70	50.86	0.12	50.98	68.20	17.22	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

6500880011100134001570018000

2030405060708090100

Frequency (MHz)

PK

1

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10540.00	49.13	2.29	51.42	68.20	16.78	Peak
2	15810.00	48.39	3.49	51.88	74.00	22.12	Peak
3	17942.50	49.00	10.90	59.90	74.00	14.10	Peak
4	17942.50	36.48	10.90	47.38	54.00	6.62	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2A low channel 5270MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

6500880011100134001570018000

2030405060708090100

Frequency (MHz)

PK


1

2




3



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10540.00	48.68	2.29	50.97	68.20	17.23	Peak
2	15810.00	48.53	3.49	52.02	74.00	21.98	Peak
3	17979.30	48.94	11.14	60.08	74.00	13.92	Peak
4	17979.30	36.28	11.14	47.42	54.00	6.58	Average

802.11ax40, High Channel, Horizontal



802.11ax40, High Channel, Vertical



802.11ax80, Middle Channel, Horizontal				802.11ax80, Middle Channel, Vertical			
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax80_U-NII-2A middle channel 5290MHz Peak:RBW:1MHz,VBW:3MHz		Serial No.: 3FXP-9 Tester: Leo Xiao		Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax80_U-NII-2A middle channel 5290MHz Peak:RBW:1MHz,VBW:3MHz		Serial No.: 3FXP-9 Tester: Leo Xiao	
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6001.70	50.41	0.45	50.86	68.20	17.34	Peak

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6293.20	50.61	0.23	50.84	68.20	17.36	Peak

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10580.00	48.83	2.30	51.13	68.20	17.07	Peak
2	15870.00	48.86	3.43	52.29	74.00	21.71	Peak
3	17942.50	48.67	10.90	59.57	74.00	14.43	Peak
4	17942.50	36.49	10.90	47.39	54.00	6.61	Average

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	10580.00	48.87	2.30	51.17	68.20	17.03	Peak
2	15870.00	49.14	3.43	52.57	74.00	21.43	Peak
3	17986.20	48.58	11.19	59.77	74.00	14.23	Peak
4	17986.20	36.25	11.19	47.44	54.00	6.56	Average

5470-5725MHz:
Chain 0


Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C low channel 5500MHz Chain0
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Date: 2026-01-30



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6328.40	50.19	0.22	50.41	68.20	17.79	Peak


Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C low channel 5500MHz Chain0
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Date: 2026-01-30




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6343.80	50.19	0.27	50.46	68.20	17.74	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C low channel 5500MHz Chain0
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-30




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11000.00	48.47	2.51	50.98	74.00	23.02	Peak
2	16500.00	48.58	4.45	53.03	68.20	15.17	Peak
3	17993.10	49.11	11.25	60.36	74.00	13.64	Peak
4	17993.10	36.66	11.25	47.91	54.00	6.09	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C low channel 5500MHz Chain0
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



Serial No.: 3FXP-9
Tester: Leo Xiao



Level (dBuV/m)

Date: 2026-01-30



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11000.00	48.05	2.51	50.56	74.00	23.44	Peak
2	16500.00	48.95	4.45	53.40	68.20	14.80	Peak
3	17970.10	48.31	11.07	59.38	74.00	14.62	Peak
4	17970.10	36.43	11.07	47.50	54.00	6.50	Average

802.11a, Middle Channel, Horizontal								802.11a, Middle Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2C middle channel 5600MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2C middle channel 5600MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6467.00	50.68	0.20	50.88	68.20	17.32	Peak	1	5973.10	50.55	0.44	50.99	68.20	17.21	Peak

															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11200.00	48.02	2.90	50.92	74.00	23.08	Peak	1	11200.00	48.01	2.90	50.91	74.00	23.09	Peak
2	16800.00	48.49	5.31	53.80	68.20	14.40	Peak	2	16800.00	48.01	5.31	53.32	68.20	14.88	Peak
3	17822.90	49.82	9.90	59.72	74.00	14.28	Peak	3	17908.00	48.72	10.66	59.38	74.00	14.62	Peak
4	17822.90	36.69	9.90	46.59	54.00	7.41	Average	4	17908.00	36.29	10.66	46.95	54.00	7.05	Average

802.11a, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2C high channel 5700MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6280.00	50.55	0.33	50.88	68.20	17.32	Peak


802.11a, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2C high channel 5700MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6368.00	50.30	0.26	50.56	68.20	17.64	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2C high channel 5700MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	47.35	3.47	50.82	74.00	23.18	Peak
2	17100.00	48.73	6.43	55.16	68.20	13.04	Peak
3	17986.20	48.43	11.19	59.62	74.00	14.38	Peak
4	17986.20	36.43	11.19	47.62	54.00	6.38	Average




Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2C high channel 5700MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	47.62	3.47	51.09	74.00	22.91	Peak
2	17100.00	47.71	6.43	54.14	68.20	14.06	Peak
3	17993.10	47.89	11.25	59.14	74.00	14.86	Peak
4	17993.10	36.32	11.25	47.57	54.00	6.43	Average



Chain 1



802.11a, Low Channel, Horizontal



802.11a, Low Channel, Vertical



802.11a, Middle Channel, Horizontal								802.11a, Middle Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2C middle channel 5600MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2C middle channel 5600MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6148.00	50.44	0.06	50.50	68.20	17.70	Peak	1	6489.00	50.88	0.26	51.14	68.20	17.06	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-2C middle channel 5600MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz								Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-2C middle channel 5600MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							
Serial No.: 3FXP-9 Tester: Leo Xiao								Serial No.: 3FXP-9 Tester: Leo Xiao							
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11200.00	47.72	2.90	50.62	74.00	23.38	Peak	1	11200.00	49.16	2.90	52.06	74.00	21.94	Peak
2	16800.00	48.36	5.31	53.67	68.20	14.53	Peak	2	16800.00	48.48	5.31	53.79	68.20	14.41	Peak
3	17995.40	49.08	11.26	60.34	74.00	13.66	Peak	3	17974.70	49.00	11.10	60.10	74.00	13.90	Peak
4	17995.40	36.69	11.26	47.95	54.00	6.05	Average	4	17974.70	36.50	11.10	47.60	54.00	6.40	Average

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C high channel 5700MHz Chain1
Peak:RBW:1MHz,VBW:30Hz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)
Date: 2026-01-30

Fundamental test with Filter Switch Unit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5947.80	50.11	0.43	50.54	68.20	17.66	Peak

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C high channel 5700MHz Chain1
Peak:RBW:1MHz,VBW:30Hz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)
Date: 2026-01-30

Fundamental test with Filter Switch Unit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6339.40	50.04	0.25	50.29	68.20	17.91	Peak

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C high channel 5700MHz Chain1
Peak:RBW:1MHz,VBW:30Hz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)
Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	47.26	3.47	50.73	74.00	23.27	Peak
2	17100.00	47.86	6.43	54.29	68.20	13.91	Peak
3	17972.40	48.37	11.09	59.46	74.00	14.54	Peak
4	17972.40	36.48	11.09	47.57	54.00	6.43	Average



802.11a, High Channel, Vertical



Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C high channel 5700MHz Chain1
Peak:RBW:1MHz,VBW:30Hz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao


Level (dBuV/m)
Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	46.89	3.47	50.36	74.00	23.64	Peak
2	17100.00	47.57	6.43	54.00	68.20	14.20	Peak
3	17983.90	48.27	11.18	59.45	74.00	14.55	Peak
4	17983.90	36.73	11.18	47.91	54.00	6.09	Average




802.11ac20, Low Channel, Horizontal								802.11ac20, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac20_U-NII-2C low channel 5500MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac20_U-NII-2C low channel 5500MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6492.30	50.58	0.26	50.84	68.20	17.36	Peak	1	6439.50	50.01	0.26	50.27	68.20	17.93	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac20_U-NII-2C low channel 5500MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz								Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac20_U-NII-2C low channel 5500MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							
Serial No.: 3FXP-9 Tester: Leo Xiao								Serial No.: 3FXP-9 Tester: Leo Xiao							
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11000.00	48.80	2.51	51.31	74.00	22.69	Peak	1	11000.00	48.57	2.51	51.08	74.00	22.92	Peak
2	16500.00	48.90	4.45	53.35	68.20	14.85	Peak	2	16500.00	48.52	4.45	52.97	68.20	15.23	Peak
3	17983.90	48.01	11.18	59.19	74.00	14.81	Peak	3	17990.80	48.62	11.23	59.85	74.00	14.15	Peak
4	17983.90	36.47	11.18	47.65	54.00	6.35	Average	4	17990.80	36.60	11.23	47.83	54.00	6.17	Average

802.11ac20, Middle Channel, Horizontal




802.11ac20, Middle Channel, Vertical



802.11ac20, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac20 U-NII-2C high channel 5700MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6469.20	50.22	0.22	50.44	68.20	17.76	Peak

802.11acn20, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac20 U-NII-2C high channel 5700MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6264.60	50.36	0.16	50.52	68.20	17.68	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac20 U-NII-2C high channel 5700MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	46.93	3.47	50.40	74.00	23.60	Peak
2	17100.00	48.22	6.43	54.65	68.20	13.55	Peak
3	17990.80	49.07	11.23	60.30	74.00	13.70	Peak
4	17990.80	36.49	11.23	47.72	54.00	6.28	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac20 U-NII-2C high channel 5700MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	48.08	3.47	51.55	74.00	22.45	Peak
2	17100.00	47.83	6.43	54.26	68.20	13.94	Peak
3	17951.70	48.69	10.96	59.65	74.00	14.35	Peak
4	17951.70	36.31	10.96	47.27	54.00	6.73	Average

802.11ac40, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2C low channel 5510MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30

Fundamental test with
Filter Switch Unit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6064.40	50.22	0.33	50.55	68.20	17.65	Peak

802.11ac40, Low Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2C low channel 5510MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30

Fundamental test with
Filter Switch Unit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5966.50	50.38	0.43	50.81	68.20	17.39	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2C low channel 5510MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11020.00	48.81	2.53	51.34	74.00	22.66	Peak
2	16530.00	48.62	4.56	53.18	68.20	15.02	Peak
3	17990.80	48.93	11.23	60.16	74.00	13.84	Peak
4	17990.80	36.30	11.23	47.53	54.00	6.47	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-2C low channel 5510MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11020.00	49.31	2.53	51.84	74.00	22.16	Peak
2	16530.00	48.61	4.56	53.17	68.20	15.03	Peak
3	17993.10	48.75	11.25	60.00	74.00	14.00	Peak
4	17993.10	36.43	11.25	47.68	54.00	6.32	Average

802.11ac40, Middle Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C middle channel 5590MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6322.90	50.49	0.19	50.68	68.20	17.52	Peak

802.11ac40, Middle Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C middle channel 5590MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6445.00	50.60	0.25	50.85	68.20	17.35	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C middle channel 5590MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11180.00	48.48	2.87	51.35	74.00	22.65	Peak
2	16770.00	48.02	5.25	53.27	68.20	14.93	Peak
3	17995.40	48.30	11.26	59.56	74.00	14.44	Peak
4	17995.40	36.59	11.26	47.85	54.00	6.15	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C middle channel 5590MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11180.00	48.36	2.87	51.23	74.00	22.77	Peak
2	16770.00	48.47	5.25	53.72	68.20	14.48	Peak
3	17974.70	48.77	11.10	59.87	74.00	14.13	Peak
4	17974.70	36.55	11.10	47.65	54.00	6.35	Average

802.11ac40, High Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5975.30	49.97	0.43	50.40	68.20	17.80	Peak

802.11ac40, High Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6145.80	50.47	0.07	50.54	68.20	17.66	Peak

802.11ac40, High Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11340.00	49.22	3.20	52.42	74.00	21.58	Peak
2	17010.00	48.46	6.12	54.58	68.20	13.62	Peak
3	17988.50	49.73	11.21	60.94	74.00	13.06	Peak
4	17988.50	36.33	11.21	47.54	54.00	6.46	Average

802.11ac40, High Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac40_U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11340.00	48.32	3.20	51.52	74.00	22.48	Peak
2	17010.00	47.84	6.12	53.96	68.20	14.24	Peak
3	17993.10	48.61	11.25	59.86	74.00	14.14	Peak
4	17993.10	36.74	11.25	47.99	54.00	6.01	Average

802.11ac80, Low Channel, Horizontal							802.11ac80, Low Channel, Vertical								
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac80_U-NII-2C low channel 5530MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac80_U-NII-2C low channel 5530MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				
Level (dBuV/m) Fundamental test with Filter Switch Unit							Level (dBuV/m) Fundamental test with Filter Switch Unit								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6305.30	50.45	0.13	50.58	68.20	17.62	Peak	1	5945.60	49.80	0.42	50.22	68.20	17.98	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac80_U-NII-2C low channel 5530MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac80_U-NII-2C low channel 5530MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao				
Level (dBuV/m)							Level (dBuV/m)								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11060.00	48.73	2.62	51.35	74.00	22.65	Peak	1	11060.00	48.84	2.62	51.46	74.00	22.54	Peak
2	16590.00	49.15	4.68	53.83	68.20	14.37	Peak	2	16590.00	49.81	4.68	54.49	68.20	13.71	Peak
3	17981.60	48.18	11.17	59.35	74.00	14.65	Peak	3	17974.70	49.33	11.10	60.43	74.00	13.57	Peak
4	17981.60	36.64	11.17	47.81	54.00	6.19	Average	4	17974.70	36.47	11.10	47.57	54.00	6.43	Average


802.11ac80, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2C high channel 5610MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30

Fundamental test with Filter Switch Unit



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6289.90	50.06	0.27	50.33	68.20	17.87	Peak


802.11ac80, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2C high channel 5610MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30

Fundamental test with Filter Switch Unit




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5941.20	50.40	0.42	50.82	68.20	17.38	Peak

802.11ac80, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2C high channel 5610MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11220.00	47.98	2.94	50.92	74.00	23.08	Peak
2	16830.00	48.40	5.41	53.81	68.20	14.39	Peak
3	17931.00	48.51	10.80	59.31	74.00	14.69	Peak
4	17931.00	36.33	10.80	47.13	54.00	6.87	Average

802.11ac80, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac80_U-NII-2C high channel 5610MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-30



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11220.00	48.21	2.94	51.15	74.00	22.85	Peak
2	16830.00	48.22	5.41	53.63	68.20	14.57	Peak
3	17958.60	49.24	11.00	60.24	74.00	13.76	Peak
4	17958.60	36.59	11.00	47.59	54.00	6.41	Average

802.11ax20, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2C low channel 5500MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5992.90	50.34	0.44	50.78	68.20	17.42	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2C low channel 5500MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6489.00	50.07	0.26	50.33	68.20	17.87	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2C low channel 5500MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11000.00	48.08	2.51	50.59	74.00	23.41	Peak
2	16500.00	48.95	4.45	53.40	68.20	14.80	Peak
3	17977.00	48.44	11.12	59.56	74.00	14.44	Peak
4	17977.00	36.51	11.12	47.63	54.00	6.37	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-2C low channel 5500MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Date: 2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11000.00	48.51	2.51	51.02	74.00	22.98	Peak
2	16500.00	49.21	4.45	53.66	68.20	14.54	Peak
3	17990.80	49.16	11.23	60.39	74.00	13.61	Peak
4	17990.80	36.42	11.23	47.65	54.00	6.35	Average

802.11ax20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C middle channel 5600MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

1

6461.50

50.45

0.21

50.66

68.20

17.54

Peak

802.11ax20, Middle Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C middle channel 5600MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

1

6163.40

50.29

0.17

50.46

68.20

17.74

Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C middle channel 5600MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

1

11200.00

48.12

2.90

51.02

74.00

22.98

Peak

2

16800.00

47.68

5.31

52.99

68.20

15.21

Peak

3

17963.20

48.08

11.03

59.11

74.00

14.89

Peak

4

17963.20

36.39

11.03

47.42

54.00

6.58

Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C middle channel 5600MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

1

11200.00

47.65

2.90

50.55

74.00

23.45

Peak

2

16800.00

48.07

5.31

53.38

68.20

14.82

Peak

3

17986.20

48.89

11.19

60.08

74.00

13.92

Peak

4

17986.20

36.73

11.19

47.92

54.00

6.08

Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Tester: Leo Xiao

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C high channel 5700MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6120.50	50.54	0.12	50.66	68.20	17.54	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Tester: Leo Xiao

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C high channel 5700MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6056.70	49.71	0.37	50.08	68.20	18.12	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Tester: Leo Xiao

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C high channel 5700MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

1

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	47.08	3.47	50.55	74.00	23.45	Peak
2	17100.00	48.25	6.43	54.68	68.20	13.52	Peak
3	17981.60	49.04	11.17	60.21	74.00	13.79	Peak
4	17981.60	36.29	11.17	47.46	54.00	6.54	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Tester: Leo Xiao

Test Mode: Transmitting

Note: 802.11ax20_U-NII-2C high channel 5700MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)



PK



1

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11400.00	46.67	3.47	50.14	74.00	23.86	Peak
2	17100.00	47.97	6.43	54.40	68.20	13.80	Peak
3	17940.20	48.49	10.87	59.36	74.00	14.64	Peak
4	17940.20	36.59	10.87	47.46	54.00	6.54	Average

802.11ax40, Low Channel, Horizontal								802.11ax40, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-2C low channel 5510MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-2C low channel 5510MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6492.30	50.69	0.26	50.95	68.20	17.25	Peak	1	6039.10	50.03	0.43	50.46	68.20	17.74	Peak

															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11020.00	48.45	2.53	50.98	74.00	23.02	Peak	1	11020.00	48.02	2.53	50.55	74.00	23.45	Peak
2	16530.00	48.96	4.56	53.52	68.20	14.68	Peak	2	16530.00	48.93	4.56	53.49	68.20	14.71	Peak
3	17979.30	48.63	11.14	59.77	74.00	14.23	Peak	3	17977.00	48.51	11.12	59.63	74.00	14.37	Peak
4	17979.30	36.30	11.14	47.44	54.00	6.56	Average	4	17977.00	36.41	11.12	47.53	54.00	6.47	Average

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2C middle channel 5590MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100
90.0
80.0
70.0
60.0
50.0
40.0
30.0
20

100021003200430054006500

Frequency (MHz)

2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6379.00	50.62	0.21	50.83	68.20	17.37	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2C middle channel 5590MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100
90.0
80.0
70.0
60.0
50.0
40.0
30.0
20

100021003200430054006500

Frequency (MHz)

2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6351.50	50.62	0.28	50.90	68.20	17.30	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2C middle channel 5590MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

100
90.0
80.0
70.0
60.0
50.0
40.0
30.0
20

6500880011100134001570018000

Frequency (MHz)

2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11180.00	48.21	2.87	51.08	74.00	22.92	Peak
2	16770.00	48.51	5.25	53.76	68.20	14.44	Peak
3	17993.10	48.22	11.25	59.47	74.00	14.53	Peak
4	17993.10	36.33	11.25	47.58	54.00	6.42	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40_U-NII-2C middle channel 5590MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

100
90.0
80.0
70.0
60.0
50.0
40.0
30.0
20

6500880011100134001570018000

Frequency (MHz)

2026-01-30

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11180.00	49.04	2.87	51.91	74.00	22.09	Peak
2	16770.00	49.53	5.25	54.78	68.20	13.42	Peak
3	17931.00	48.78	10.80	59.58	74.00	14.42	Peak
4	17931.00	36.69	10.80	47.49	54.00	6.51	Average

802.11ax40, High Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ax40 U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6335.00	50.26	0.25	50.51	68.20	17.69	Peak

802.11ax40, High Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ax40 U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6475.80	50.41	0.23	50.64	68.20	17.56	Peak

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ax40 U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11340.00	48.25	3.20	51.45	74.00	22.55	Peak
2	17010.00	48.26	6.12	54.38	68.20	13.82	Peak
3	17977.00	48.50	11.12	59.62	74.00	14.38	Peak
4	17977.00	36.35	11.12	47.47	54.00	6.53	Average

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ax40 U-NII-2C high channel 5670MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)


Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11340.00	48.29	3.20	51.49	74.00	22.51	Peak
2	17010.00	48.41	6.12	54.53	68.20	13.67	Peak
3	17951.70	49.14	10.96	60.10	74.00	13.90	Peak
4	17951.70	36.38	10.96	47.34	54.00	6.66	Average

802.11ax80, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax80_U-NII-2C low channel 5530MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6352.60	50.03	0.28	50.31	68.20	17.89	Peak

802.11ax80, Low Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax80_U-NII-2C low channel 5530MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6463.70	50.83	0.21	51.04	68.20	17.16	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax80_U-NII-2C low channel 5530MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11060.00	48.83	2.62	51.45	74.00	22.55	Peak
2	16590.00	48.86	4.68	53.54	68.20	14.66	Peak
3	17944.80	48.20	10.92	59.12	74.00	14.88	Peak
4	17944.80	36.37	10.92	47.29	54.00	6.71	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax80_U-NII-2C low channel 5530MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11060.00	49.19	2.62	51.81	74.00	22.19	Peak
2	16590.00	48.77	4.68	53.45	68.20	14.75	Peak
3	17983.90	48.34	11.18	59.52	74.00	14.48	Peak
4	17983.90	36.57	11.18	47.75	54.00	6.25	Average


802.11ax80, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax80_U-NII-2C high channel 5610MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5950.00	50.04	0.42	50.46	68.20	17.74	Peak


802.11ax80, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax80_U-NII-2C high channel 5610MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6414.20	50.42	0.24	50.66	68.20	17.54	Peak


Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax80_U-NII-2C high channel 5610MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11220.00	48.53	2.94	51.47	74.00	22.53	Peak
2	16830.00	48.57	5.41	53.98	68.20	14.22	Peak
3	17931.00	49.09	10.80	59.89	74.00	14.11	Peak
4	17931.00	36.64	10.80	47.44	54.00	6.56	Average


Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax80_U-NII-2C high channel 5610MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-30							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11220.00	48.05	2.94	50.99	74.00	23.01	Peak
2	16830.00	48.04	5.41	53.45	68.20	14.75	Peak
3	17993.10	48.14	11.25	59.39	74.00	14.61	Peak
4	17993.10	36.69	11.25	47.94	54.00	6.06	Average

5725-5850MHz:
Chain 0

802.11a, Low Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-3 low channel 5745MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6177.70	50.56	0.24	50.80	68.20	17.40	Peak

802.11a, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-3 low channel 5745MHz Chain0 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6199.70	49.78	0.15	49.93	68.20	18.27	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-3 low channel 5745MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11490.00	46.95	3.33	50.28	74.00	23.72	Peak
2	17235.00	48.32	6.93	55.25	68.20	12.95	Peak
3	17843.60	49.23	10.08	59.31	74.00	14.69	Peak
4	17843.60	36.46	10.08	46.54	54.00	7.46	Average


Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-3 low channel 5745MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11490.00	46.87	3.33	50.20	74.00	23.80	Peak
2	17235.00	48.62	6.93	55.55	68.20	12.65	Peak
3	17990.80	48.14	11.23	59.37	74.00	14.63	Peak
4	17990.80	36.26	11.23	47.49	54.00	6.51	Average

802.11a, Middle Channel, Horizontal	802.11a, Middle Channel, Vertical																																																																																
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Fundamental test with Filter Switch Unit PK AV 1 Frequency (MHz) <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6175.50</td><td>50.04</td><td>0.25</td><td>50.29</td><td>68.20</td><td>17.91</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6175.50	50.04	0.25	50.29	68.20	17.91	Peak	Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) Fundamental test with Filter Switch Unit PK AV 1 Frequency (MHz) <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6339.40</td><td>50.28</td><td>0.25</td><td>50.53</td><td>68.20</td><td>17.67</td><td>Peak</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6339.40	50.28	0.25	50.53	68.20	17.67	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	6175.50	50.04	0.25	50.29	68.20	17.91	Peak																																																																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	6339.40	50.28	0.25	50.53	68.20	17.67	Peak																																																																										
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) PK 1 2 3 Frequency (MHz) <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>11570.00</td><td>48.08</td><td>3.31</td><td>51.39</td><td>74.00</td><td>22.61</td><td>Peak</td></tr><tr><td>2</td><td>17355.00</td><td>47.99</td><td>7.10</td><td>55.09</td><td>68.20</td><td>13.11</td><td>Peak</td></tr><tr><td>3</td><td>17967.80</td><td>48.56</td><td>11.06</td><td>59.62</td><td>74.00</td><td>14.38</td><td>Peak</td></tr><tr><td>4</td><td>17967.80</td><td>36.41</td><td>11.06</td><td>47.47</td><td>54.00</td><td>6.53</td><td>Average</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	11570.00	48.08	3.31	51.39	74.00	22.61	Peak	2	17355.00	47.99	7.10	55.09	68.20	13.11	Peak	3	17967.80	48.56	11.06	59.62	74.00	14.38	Peak	4	17967.80	36.41	11.06	47.47	54.00	6.53	Average	Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain0 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Level (dBuV/m) PK 1 2 3 Frequency (MHz) <table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>11570.00</td><td>48.06</td><td>3.31</td><td>51.37</td><td>74.00</td><td>22.63</td><td>Peak</td></tr><tr><td>2</td><td>17355.00</td><td>48.73</td><td>7.10</td><td>55.83</td><td>68.20</td><td>12.37</td><td>Peak</td></tr><tr><td>3</td><td>17981.60</td><td>47.76</td><td>11.17</td><td>58.93</td><td>74.00</td><td>15.07</td><td>Peak</td></tr><tr><td>4</td><td>17981.60</td><td>36.39</td><td>11.17</td><td>47.56</td><td>54.00</td><td>6.44</td><td>Average</td></tr></table>	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	11570.00	48.06	3.31	51.37	74.00	22.63	Peak	2	17355.00	48.73	7.10	55.83	68.20	12.37	Peak	3	17981.60	47.76	11.17	58.93	74.00	15.07	Peak	4	17981.60	36.39	11.17	47.56	54.00	6.44	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	11570.00	48.08	3.31	51.39	74.00	22.61	Peak																																																																										
2	17355.00	47.99	7.10	55.09	68.20	13.11	Peak																																																																										
3	17967.80	48.56	11.06	59.62	74.00	14.38	Peak																																																																										
4	17967.80	36.41	11.06	47.47	54.00	6.53	Average																																																																										
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																										
1	11570.00	48.06	3.31	51.37	74.00	22.63	Peak																																																																										
2	17355.00	48.73	7.10	55.83	68.20	12.37	Peak																																																																										
3	17981.60	47.76	11.17	58.93	74.00	15.07	Peak																																																																										
4	17981.60	36.39	11.17	47.56	54.00	6.44	Average																																																																										

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain0
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6431.80	50.28	0.26	50.54	68.20	17.66	Peak

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6069.90	50.23	0.31	50.54	68.20	17.66	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3FXP-9
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	48.54	3.38	51.92	74.00	22.08	Peak
2	17475.00	48.23	7.80	56.03	68.20	12.17	Peak
3	17981.60	49.43	11.17	60.60	74.00	13.40	Peak
4	17981.60	36.41	11.17	47.58	54.00	6.42	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain0
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 3FXP-9
Tester: Leo Xiao






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	48.46	3.38	51.84	74.00	22.16	Peak
2	17475.00	48.90	7.80	56.70	68.20	11.50	Peak
3	17993.10	48.30	11.25	59.55	74.00	14.45	Peak
4	17993.10	36.26	11.25	47.51	54.00	6.49	Average



Chain 1



802.11a, Low Channel, Horizontal



802.11a, Low Channel, Vertical



802.11a, Middle Channel, Horizontal								802.11a, Middle Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain1 Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6364.70	50.02	0.28	50.30	68.20	17.90	Peak	1	6491.20	50.30	0.26	50.56	68.20	17.64	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11a_U-NII-3 middle channel 5785MHz Chain1 Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
															
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11570.00	47.35	3.31	50.66	74.00	23.34	Peak	1	11570.00	47.19	3.31	50.50	74.00	23.50	Peak
2	17355.00	49.65	7.10	56.75	68.20	11.45	Peak	2	17355.00	48.72	7.10	55.82	68.20	12.38	Peak
3	17993.10	47.80	11.25	59.05	74.00	14.95	Peak	3	17820.60	49.08	9.88	58.96	74.00	15.04	Peak
4	17993.10	36.21	11.25	47.46	54.00	6.54	Average	4	17820.60	36.40	9.88	46.28	54.00	7.72	Average

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain1
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6388.90	50.16	0.18	50.34	68.20	17.86	Peak

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain1
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6166.70	50.19	0.19	50.38	68.20	17.82	Peak

802.11a, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	47.75	3.38	51.13	74.00	22.87	Peak
2	17475.00	48.52	7.80	56.32	68.20	11.88	Peak
3	17990.80	47.77	11.23	59.00	74.00	15.00	Peak
4	17990.80	36.36	11.23	47.59	54.00	6.41	Average

802.11a, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-3 high channel 5825MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	48.05	3.38	51.43	74.00	22.57	Peak
2	17475.00	48.70	7.80	56.50	68.20	11.70	Peak
3	17993.10	47.84	11.25	59.09	74.00	14.91	Peak
4	17993.10	36.15	11.25	47.40	54.00	6.60	Average

802.11ac20, Low Channel, Horizontal							802.11ac20, Low Channel, Vertical																																																																																						
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao																																																																																		
Level (dBuV/m) Fundamental test with Filter Switch Unit PK AV Frequency (MHz)							Level (dBuV/m) Fundamental test with Filter Switch Unit PK AV Frequency (MHz)																																																																																						
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6129.30</td><td>50.64</td><td>0.09</td><td>50.73</td><td>68.20</td><td>17.47</td><td>Peak</td></tr></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6129.30	50.64	0.09	50.73	68.20	17.47	Peak	<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6157.90</td><td>50.72</td><td>0.13</td><td>50.85</td><td>68.20</td><td>17.35</td><td>Peak</td></tr></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6157.90	50.72	0.13	50.85	68.20	17.35	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																						
1	6129.30	50.64	0.09	50.73	68.20	17.47	Peak																																																																																						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																						
1	6157.90	50.72	0.13	50.85	68.20	17.35	Peak																																																																																						
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz							Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz																																																																																						
Level (dBuV/m) PK 3 Frequency (MHz)							Level (dBuV/m) PK 3 Frequency (MHz)																																																																																						
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>11490.00</td><td>47.68</td><td>3.33</td><td>51.01</td><td>74.00</td><td>22.99</td><td>Peak</td></tr><tr><td>2</td><td>17235.00</td><td>47.99</td><td>6.93</td><td>54.92</td><td>68.20</td><td>13.28</td><td>Peak</td></tr><tr><td>3</td><td>17981.60</td><td>47.78</td><td>11.17</td><td>58.95</td><td>74.00</td><td>15.05</td><td>Peak</td></tr><tr><td>4</td><td>17981.60</td><td>36.44</td><td>11.17</td><td>47.61</td><td>54.00</td><td>6.39</td><td>Average</td></tr></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	11490.00	47.68	3.33	51.01	74.00	22.99	Peak	2	17235.00	47.99	6.93	54.92	68.20	13.28	Peak	3	17981.60	47.78	11.17	58.95	74.00	15.05	Peak	4	17981.60	36.44	11.17	47.61	54.00	6.39	Average	<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>11490.00</td><td>47.90</td><td>3.33</td><td>51.23</td><td>74.00</td><td>22.77</td><td>Peak</td></tr><tr><td>2</td><td>17235.00</td><td>47.58</td><td>6.93</td><td>54.51</td><td>68.20</td><td>13.69</td><td>Peak</td></tr><tr><td>3</td><td>17995.40</td><td>47.95</td><td>11.26</td><td>59.21</td><td>74.00</td><td>14.79</td><td>Peak</td></tr><tr><td>4</td><td>17995.40</td><td>36.44</td><td>11.26</td><td>47.70</td><td>54.00</td><td>6.30</td><td>Average</td></tr></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	11490.00	47.90	3.33	51.23	74.00	22.77	Peak	2	17235.00	47.58	6.93	54.51	68.20	13.69	Peak	3	17995.40	47.95	11.26	59.21	74.00	14.79	Peak	4	17995.40	36.44	11.26	47.70	54.00	6.30	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																						
1	11490.00	47.68	3.33	51.01	74.00	22.99	Peak																																																																																						
2	17235.00	47.99	6.93	54.92	68.20	13.28	Peak																																																																																						
3	17981.60	47.78	11.17	58.95	74.00	15.05	Peak																																																																																						
4	17981.60	36.44	11.17	47.61	54.00	6.39	Average																																																																																						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																						
1	11490.00	47.90	3.33	51.23	74.00	22.77	Peak																																																																																						
2	17235.00	47.58	6.93	54.51	68.20	13.69	Peak																																																																																						
3	17995.40	47.95	11.26	59.21	74.00	14.79	Peak																																																																																						
4	17995.40	36.44	11.26	47.70	54.00	6.30	Average																																																																																						

802.11ac20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac20_U-NII-3 middle channel 5785MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6011.60	49.69	0.46	50.15	68.20	18.05	Peak

802.11ac20, Middle Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac20_U-NII-3 middle channel 5785MHz

Peak:RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6134.80	50.29	0.09	50.38	68.20	17.82	Peak

802.11ac20, Middle Channel, Horizontal

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Horizontal

Test Mode: Transmitting

Note: 802.11ac20_U-NII-3 middle channel 5785MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

3

2

4

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11570.00	47.65	3.31	50.96	74.00	23.04	Peak
2	17355.00	48.30	7.10	55.40	68.20	12.80	Peak
3	17993.10	48.02	11.25	59.27	74.00	14.73	Peak
4	17993.10	36.36	11.25	47.61	54.00	6.39	Average

802.11ac20, Middle Channel, Vertical

Project No.: 2602P41234E-RF

Serial No.: 3FXP-9

Polarization: Vertical

Test Mode: Transmitting

Note: 802.11ac20_U-NII-3 middle channel 5785MHz

Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Level (dBuV/m)

Frequency (MHz)

PK

3

2

4


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11570.00	47.41	3.31	50.72	74.00	23.28	Peak
2	17355.00	48.67	7.10	55.77	68.20	12.43	Peak
3	17958.60	48.39	11.00	59.39	74.00	14.61	Peak
4	17958.60	36.47	11.00	47.47	54.00	6.53	Average

802.11ac20, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6491.20	50.02	0.26	50.28	68.20	17.92	Peak

802.11acn20, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6131.50	50.12	0.10	50.22	68.20	17.98	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	48.55	3.38	51.93	74.00	22.07	Peak
2	17475.00	48.14	7.80	55.94	68.20	12.26	Peak
3	17993.10	47.97	11.25	59.22	74.00	14.78	Peak
4	17993.10	36.14	11.25	47.39	54.00	6.61	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	48.49	3.38	51.87	74.00	22.13	Peak
2	17475.00	48.07	7.80	55.87	68.20	12.33	Peak
3	17848.20	49.30	10.12	59.42	74.00	14.58	Peak
4	17848.20	36.28	10.12	46.40	54.00	7.60	Average

802.11ac40, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090100

PK

AV

2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6330.60	50.58	0.23	50.81	68.20	17.39	Peak

802.11ac40, Low Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090100

PK

AV

2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6076.50	50.28	0.26	50.54	68.20	17.66	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

6500880011100134001570018000

2030405060708090100

PK

2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11510.00	46.86	3.33	50.19	74.00	23.81	Peak
2	17265.00	47.82	6.96	54.78	68.20	13.42	Peak
3	17983.90	47.73	11.18	58.91	74.00	15.09	Peak
4	17983.90	36.25	11.18	47.43	54.00	6.57	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

6500880011100134001570018000

2030405060708090100

PK

2026-01-24

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11510.00	48.03	3.33	51.36	74.00	22.64	Peak
2	17265.00	47.99	6.96	54.95	68.20	13.25	Peak
3	17995.40	48.54	11.26	59.80	74.00	14.20	Peak
4	17995.40	36.19	11.26	47.45	54.00	6.55	Average

802.11ac40, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 high channel 5795MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

PK

AV

Frequency (MHz)

No.

Frequency (MHz)

Reading (dBuV)

Factor (dB/m)

Result (dBuV/m)

Limit (dBuV/m)

Margin (dB)

Measurement

1	6483.50	50.26	0.25	50.51	68.20	17.69	Peak
---	---------	-------	------	-------	-------	-------	------

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 high channel 5795MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

PK

AV

Frequency (MHz)

No.

Frequency (MHz)

Reading (dBuV)

Factor (dB/m)

Result (dBuV/m)

Limit (dBuV/m)

Margin (dB)

Measurement

1	6130.40	49.95	0.09	50.04	68.20	18.16	Peak
---	---------	-------	------	-------	-------	-------	------

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 high channel 5795MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

PK

Frequency (MHz)

No.

Frequency (MHz)

Reading (dBuV)

Factor (dB/m)

Result (dBuV/m)

Limit (dBuV/m)

Margin (dB)

Measurement

1	11590.00	48.29	3.28	51.57	74.00	22.43	Peak
2	17385.00	48.78	7.25	56.03	68.20	12.17	Peak
3	17993.10	48.14	11.25	59.39	74.00	14.61	Peak
4	17993.10	36.27	11.25	47.52	54.00	6.48	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac40_U-NII-3 high channel 5795MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

PK

Frequency (MHz)

No.

Frequency (MHz)

Reading (dBuV)

Factor (dB/m)





Result (dBuV/m)

Limit (dBuV/m)

Margin (dB)

Measurement

1	11590.00	47.99	3.28	51.27	74.00	22.73	Peak
2	17385.00	50.07	7.25	57.32	68.20	10.88	Peak
3	17988.50	48.06	11.21	59.27	74.00	14.73	Peak
4	17988.50	36.46	11.21	47.67	54.00	6.33	Average

802.11ac80, Middle Channel, Horizontal				802.11ac80, Middle Channel, Vertical																																																																																			
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac80_U-NII-3 middle channel 5775MHz Peak:RBW:1MHz,VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac80_U-NII-3 middle channel 5775MHz Peak:RBW:1MHz,VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24																																																																																			
																																																																																							
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6017.10</td><td>50.19</td><td>0.46</td><td>50.65</td><td>68.20</td><td>17.55</td><td>Peak</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6017.10	50.19	0.46	50.65	68.20	17.55	Peak	<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>6412.00</td><td>50.51</td><td>0.24</td><td>50.75</td><td>68.20</td><td>17.45</td><td>Peak</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	6412.00	50.51	0.24	50.75	68.20	17.45	Peak																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	6017.10	50.19	0.46	50.65	68.20	17.55	Peak																																																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	6412.00	50.51	0.24	50.75	68.20	17.45	Peak																																																																																
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ac80_U-NII-3 middle channel 5775MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ac80_U-NII-3 middle channel 5775MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24																																																																																			
																																																																																							
<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>11550.00</td><td>47.52</td><td>3.32</td><td>50.84</td><td>74.00</td><td>23.16</td><td>Peak</td></tr><tr><td>2</td><td>17325.00</td><td>49.48</td><td>6.94</td><td>56.42</td><td>68.20</td><td>11.78</td><td>Peak</td></tr><tr><td>3</td><td>17990.80</td><td>48.61</td><td>11.23</td><td>59.84</td><td>74.00</td><td>14.16</td><td>Peak</td></tr><tr><td>4</td><td>17990.80</td><td>36.38</td><td>11.23</td><td>47.61</td><td>54.00</td><td>6.39</td><td>Average</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	11550.00	47.52	3.32	50.84	74.00	23.16	Peak	2	17325.00	49.48	6.94	56.42	68.20	11.78	Peak	3	17990.80	48.61	11.23	59.84	74.00	14.16	Peak	4	17990.80	36.38	11.23	47.61	54.00	6.39	Average	<table><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Result (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Measurement</th></tr><tr><td>1</td><td>11550.00</td><td>47.61</td><td>3.32</td><td>50.93</td><td>74.00</td><td>23.07</td><td>Peak</td></tr><tr><td>2</td><td>17325.00</td><td>49.06</td><td>6.94</td><td>56.00</td><td>68.20</td><td>12.20</td><td>Peak</td></tr><tr><td>3</td><td>17983.90</td><td>47.64</td><td>11.18</td><td>58.82</td><td>74.00</td><td>15.18</td><td>Peak</td></tr><tr><td>4</td><td>17983.90</td><td>36.30</td><td>11.18</td><td>47.48</td><td>54.00</td><td>6.52</td><td>Average</td></tr></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	1	11550.00	47.61	3.32	50.93	74.00	23.07	Peak	2	17325.00	49.06	6.94	56.00	68.20	12.20	Peak	3	17983.90	47.64	11.18	58.82	74.00	15.18	Peak	4	17983.90	36.30	11.18	47.48	54.00	6.52	Average
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	11550.00	47.52	3.32	50.84	74.00	23.16	Peak																																																																																
2	17325.00	49.48	6.94	56.42	68.20	11.78	Peak																																																																																
3	17990.80	48.61	11.23	59.84	74.00	14.16	Peak																																																																																
4	17990.80	36.38	11.23	47.61	54.00	6.39	Average																																																																																
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement																																																																																
1	11550.00	47.61	3.32	50.93	74.00	23.07	Peak																																																																																
2	17325.00	49.06	6.94	56.00	68.20	12.20	Peak																																																																																
3	17983.90	47.64	11.18	58.82	74.00	15.18	Peak																																																																																
4	17983.90	36.30	11.18	47.48	54.00	6.52	Average																																																																																

802.11ax20, Low Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6020.40	50.06	0.46	50.52	68.20	17.68	Peak

802.11ax20, Low Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6294.30	49.86	0.23	50.09	68.20	18.11	Peak

802.11ax20, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11490.00	47.32	3.33	50.65	74.00	23.35	Peak
2	17235.00	49.63	6.93	56.56	68.20	11.64	Peak
3	17990.80	48.01	11.23	59.24	74.00	14.76	Peak
4	17990.80	36.18	11.23	47.41	54.00	6.59	Average

802.11ax20, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-3 low channel 5745MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11490.00	48.69	3.33	52.02	74.00	21.98	Peak
2	17235.00	47.82	6.93	54.75	68.20	13.45	Peak
3	17990.80	47.86	11.23	59.09	74.00	14.91	Peak
4	17990.80	36.51	11.23	47.74	54.00	6.26	Average

802.11ax20, Middle Channel, Horizontal				802.11ax20, Middle Channel, Vertical											
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-3 middle channel 5785MHz Peak:RBW:1MHz,VBW:3MHz				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-3 middle channel 5785MHz Peak:RBW:1MHz,VBW:3MHz											
Serial No.: 3FXP-9 Tester: Leo Xiao				Serial No.: 3FXP-9 Tester: Leo Xiao											
Date: 2026-01-24				Date: 2026-01-24											
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6193.10	50.31	0.17	50.48	68.20	17.72	Peak	1	6153.50	50.03	0.10	50.13	68.20	18.07	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax20_U-NII-3 middle channel 5785MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax20_U-NII-3 middle channel 5785MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz											
Serial No.: 3FXP-9 Tester: Leo Xiao				Serial No.: 3FXP-9 Tester: Leo Xiao											
Date: 2026-01-24				Date: 2026-01-24											
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement	No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11570.00	47.67	3.31	50.98	74.00	23.02	Peak	1	11570.00	47.90	3.31	51.21	74.00	22.79	Peak
2	17355.00	49.11	7.10	56.21	68.20	11.99	Peak	2	17355.00	48.15	7.10	55.25	68.20	12.95	Peak
3	17986.20	48.41	11.19	59.60	74.00	14.40	Peak	3	17981.60	48.02	11.17	59.19	74.00	14.81	Peak
4	17986.20	36.32	11.19	47.51	54.00	6.49	Average	4	17981.60	36.33	11.17	47.50	54.00	6.50	Average

802.11ax20, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

Level (dBuV/m)

Fundamental test with Filter Switch Unit

PK

AV

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5975.30	50.28	0.43	50.71	68.20	17.49	Peak

802.11ax20, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

Level (dBuV/m)

Fundamental test with Filter Switch Unit

PK

AV

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6453.80	50.50	0.24	50.74	68.20	17.46	Peak

802.11ax20, High Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

Level (dBuV/m)

PK

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	48.89	3.38	52.27	74.00	21.73	Peak
2	17475.00	48.54	7.80	56.34	68.20	11.86	Peak
3	17995.40	47.97	11.26	59.23	74.00	14.77	Peak
4	17995.40	36.30	11.26	47.56	54.00	6.44	Average

802.11ax20, High Channel, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax20_U-NII-3 high channel 5825MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Date: 2026-01-24

Level (dBuV/m)

PK

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11650.00	47.86	3.38	51.24	74.00	22.76	Peak
2	17475.00	48.40	7.80	56.20	68.20	12.00	Peak
3	17993.10	48.03	11.25	59.28	74.00	14.72	Peak
4	17993.10	36.32	11.25	47.57	54.00	6.43	Average

802.11ax40, Low Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6355.90	50.58	0.29	50.87	68.20	17.33	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Fundamental test with Filter Switch Unit

100021003200430054006500

2030405060708090

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6166.70	50.48	0.19	50.67	68.20	17.53	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

6500880011100134001570018000

2030405060708090

PK

3

2

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11510.00	47.59	3.33	50.92	74.00	23.08	Peak
2	17265.00	47.54	6.96	54.50	68.20	13.70	Peak
3	17859.70	48.79	10.22	59.01	74.00	14.99	Peak
4	17859.70	36.36	10.22	46.58	54.00	7.42	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40_U-NII-3 low channel 5755MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

6500880011100134001570018000

2030405060708090

PK

3

2

1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11510.00	47.14	3.33	50.47	74.00	23.53	Peak
2	17265.00	47.74	6.96	54.70	68.20	13.50	Peak
3	17993.10	48.04	11.25	59.29	74.00	14.71	Peak
4	17993.10	36.17	11.25	47.42	54.00	6.58	Average

802.11ax40, High Channel, Horizontal							
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-3 high channel 5795MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6463.70	50.60	0.21	50.81	68.20	17.39	Peak

802.11ax40, High Channel, Vertical							
Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-3 high channel 5795MHz Peak:RBW:1MHz,VBW:3MHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6348.20	50.34	0.27	50.61	68.20	17.59	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 802.11ax40_U-NII-3 high channel 5795MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11590.00	47.86	3.28	51.14	74.00	22.86	Peak
2	17385.00	48.91	7.25	56.16	68.20	12.04	Peak
3	17977.00	47.83	11.12	58.95	74.00	15.05	Peak
4	17977.00	36.35	11.12	47.47	54.00	6.53	Average

Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 802.11ax40_U-NII-3 high channel 5795MHz Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz				Serial No.: 3FXP-9 Tester: Leo Xiao			
Date: 2026-01-24							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11590.00	47.97	3.28	51.25	74.00	22.75	Peak
2	17385.00	49.07	7.25	56.32	68.20	11.88	Peak
3	17983.90	48.31	11.18	59.49	74.00	14.51	Peak
4	17983.90	36.38	11.18	47.56	54.00	6.44	Average

802.11ax80, Middle Channel, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax80_U-NII-3 middle channel 5775MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5946.70	50.09	0.43	50.52	68.20	17.68	Peak

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax80_U-NII-3 middle channel 5775MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Frequency (MHz)

Fundamental test with Filter Switch Unit

PK

AV

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	6003.90	49.80	0.45	50.25	68.20	17.95	Peak

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax80_U-NII-3 middle channel 5775MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Frequency (MHz)

PK

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11550.00	47.92	3.32	51.24	74.00	22.76	Peak
2	17325.00	48.99	6.94	55.93	68.20	12.27	Peak
3	17995.40	48.03	11.26	59.29	74.00	14.71	Peak
4	17995.40	36.32	11.26	47.58	54.00	6.42	Average

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax80_U-NII-3 middle channel 5775MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Leo Xiao

Level (dBuV/m)

Frequency (MHz)



PK

2

3

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	11550.00	48.23	3.32	51.55	74.00	22.45	Peak
2	17325.00	49.85	6.94	56.79	68.20	11.41	Peak
3	17977.00	47.99	11.12	59.11	74.00	14.89	Peak
4	17977.00	36.37	11.12	47.49	54.00	6.51	Average


18GHz-40GHz:
No Emission was detected in the range 18-40GHz, test was performed on the mode and channel which with the maximum power.

802.11ax80 mode 5775MHz, Horizontal				802.11ax80 mode 5775MHz, Vertical			
Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 5G WiFi Peak: RBW:1MHz, VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 5G WiFi Peak: RBW:1MHz, VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24			
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19268.20	46.45	0.13	46.58	74.00	27.42	Peak


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	19375.30	46.96	0.20	47.16	74.00	26.84	Peak

Project No.: 2602P41234E-RF Polarization: Horizontal Test Mode: Transmitting Note: 5G WiFi Peak: RBW:1MHz, VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24				Project No.: 2602P41234E-RF Polarization: Vertical Test Mode: Transmitting Note: 5G WiFi Peak: RBW:1MHz, VBW:3MHz Serial No.: 3FXP-9 Tester: Leo Xiao Date: 2026-01-24			
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	39343.90	42.42	8.57	50.99	74.00	23.01	Peak


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	39068.50	42.99	8.71	51.70	74.00	22.30	Peak

Test plots for Bandedge:
5150-5250MHz:**802.11a, Low Channel, Chain 0, Bandedge, Horizontal**


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5145.68	51.34	7.44	58.78	74.00	15.22	Peak
2	5145.68	38.19	7.44	45.63	54.00	8.37	Average
3	5150.00	50.01	7.47	57.48	74.00	16.52	Peak
4	5150.00	38.22	7.47	45.69	54.00	8.31	Average

802.11a, Low Channel, Chain 0,Bandedge, Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5131.26	51.13	7.32	58.45	74.00	15.55	Peak
2	5131.26	38.32	7.32	45.64	54.00	8.36	Average
3	5150.00	49.01	7.47	56.48	74.00	17.52	Peak
4	5150.00	38.48	7.47	45.95	54.00	8.05	Average

802.11a, High Channel, Chain 0, Bandedge, Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5350.00	48.91	8.01	56.92	74.00	17.08	Peak
2	5350.00	37.66	8.01	45.67	54.00	8.33	Average
3	5371.45	51.77	7.99	59.76	74.00	14.24	Peak
4	5371.45	37.86	7.99	45.85	54.00	8.15	Average


802.11a,High Channel, Chain 0, Bandedge, Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5350.00	48.89	8.01	56.90	74.00	17.10	Peak
2	5350.00	37.88	8.01	45.89	54.00	8.11	Average
3	5364.43	51.19	7.99	59.18	74.00	14.82	Peak
4	5364.43	38.17	7.99	46.16	54.00	7.84	Average

802.11a, Low Channel, Chain 1, Bandedge, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 low channel 5180MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5137.38	51.30	7.37	58.67	74.00	15.33	Peak
2	5137.38	38.07	7.37	45.44	54.00	8.56	Average
3	5150.00	49.39	7.47	56.86	74.00	17.14	Peak
4	5150.00	38.28	7.47	45.75	54.00	8.25	Average

802.11a, Low Channel, Chain 1, Bandedge, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 low channel 5180MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5128.74	51.59	7.30	58.89	74.00	15.11	Peak
2	5128.74	37.67	7.30	44.97	54.00	9.03	Average
3	5150.00	48.33	7.47	55.80	74.00	18.20	Peak
4	5150.00	38.15	7.47	45.62	54.00	8.38	Average

802.11a, High Channel, Chain 1, Bandedge, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5350.00	49.39	8.01	57.40	74.00	16.60	Peak
2	5350.00	38.21	8.01	46.22	54.00	7.78	Average
3	5399.03	51.34	7.97	59.31	74.00	14.69	Peak
4	5399.03	37.77	7.97	45.74	54.00	8.26	Average

802.11a, High Channel, Chain 1, Bandedge, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-1 high channel 5240MHz Chain1
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5350.00	49.29	8.01	57.30	74.00	16.70	Peak
2	5350.00	37.75	8.01	45.76	54.00	8.24	Average
3	5387.04	51.32	7.98	59.30	74.00	14.70	Peak
4	5387.04	38.10	7.98	46.08	54.00	7.92	Average

802.11ac20, Low Channel, Bandedge, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac20_U-NII-1 low channel 5180MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5139.02	51.03	7.38	58.41	74.00	15.59	Peak
2	5139.02	38.61	7.38	45.99	54.00	8.01	Average
3	5150.00	48.93	7.47	56.40	74.00	17.60	Peak
4	5150.00	38.63	7.47	46.10	54.00	7.90	Average

802.11ac20, Low Channel, Bandedge, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac20_U-NII-1 low channel 5180MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5149.10	51.74	7.47	59.21	74.00	14.79	Peak
2	5149.10	38.15	7.47	45.62	54.00	8.38	Average
3	5150.00	49.15	7.47	56.62	74.00	17.38	Peak
4	5150.00	38.37	7.47	45.84	54.00	8.16	Average

802.11ac20,High Channel, Bandedge, Horizontal

Project No.: 2602P41234E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ac20_U-NII-1 high channel 5240MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5350.00	48.83	8.01	56.84	74.00	17.16	Peak
2	5350.00	37.95	8.01	45.96	54.00	8.04	Average
3	5384.38	51.24	7.98	59.22	74.00	14.78	Peak
4	5384.38	38.06	7.98	46.04	54.00	7.96	Average

802.11ac20,High Channel, Bandedge, Vertical

Project No.: 2602P41234E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ac20_U-NII-1 high channel 5240MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 3FXP-9
Tester: Alan Xie



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	5350.00	48.43	8.01	56.44	74.00	17.56	Peak
2	5350.00	38.09	8.01	46.10	54.00	7.90	Average
3	5382.79	51.26	7.98	59.24	74.00	14.76	Peak
4	5382.79	38.02	7.98	46.00	54.00	8.00	Average