



REPORT No.: SZ26090251W02

TEST REPORT

APPLICANT : Aptiv Services Poland S.A.

PRODUCT NAME : P-MIB4

MODEL NAME : P-MIB4

BRAND NAME : APTIV

FCC ID : 2BU79PMIB4

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2026-01-19

TEST DATE : 2026-03-10 to 2026-03-17

ISSUE DATE : 2026-09-21



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	11
2.4. Test Configuration of EUT	12
2.5. Test Conditions	12
2.6. Test Setup Layout Diagram	12
3. Test Results	15
3.1. Antenna Requirement	15
3.2. Hopping Mechanism	16
3.3. Number of Hopping Frequency	17
3.4. Duty Cycle of Test Signal	18
3.5. Maximum Peak Conducted Output Power	19
3.6. Maximum Average Conducted Output Power	20
3.7. 20 dB Bandwidth	21
3.8. Carried Frequency Separation	22
3.9. Time of Occupancy (Dwell time)	23
3.10. Conducted Spurious Emissions and Band Edge	24
3.11. Conducted Emission	25
3.12. Restricted Frequency Bands	26
3.13. Radiated Emission	27



Annex A Test Data and Result	29
Notes	147

Change History		
Version	Date	Reason for change
1.0	2026-09-21	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS _{Note4}	/
2	15.247(a) 15.247(h)	Hopping Mechanism	N/A	N/A	PASS _{Note4}	/
3	15.247(a)	Number of Hopping Frequency	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
4	ANSI C63.10	Duty Cycle	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
5	15.247(b)	Maximum Peak Conducted Output Power	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
6	15.247(b)	Maximum Average Conducted Output Power	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
7	15.247(a)	20dB Bandwidth	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
8	15.247(a)	Carrier Frequency Separation	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
9	15.247(a)	Time of Occupancy (Dwell time)	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
10	15.247(d)	Conducted Spurious Emission and Band Edge	Mar. 10, 2026	Lin Haoyang	PASS _{Note4}	/
11	15.207	Conducted Emission	N/A	N/A	N/A _{Note1}	/
12	15.247(d)	Restricted Frequency Bands	Mar. 13, 2026	Tian Xin	PASS _{Note4}	/
13	15.209, 15.247(d)	Radiated Emission	Mar. 13, 2026	Tian Xin	PASS _{Note4}	/

Note 1: Measurements to demonstrate compliance with the conducted limits are not required for



devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

Note 2: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020, KDB 558074 D01 v05r02 and DA 00-075.

Note 3: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

Note 4: The test results of these test items in this report refer to the test report (Report No.: SZ26030114W02).

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.12.23	2026.12.22
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	EMC-CE-00514	N/A	N/A	2025.05.06	2026.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2025.06.28	2026.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	9120D-963	BBHA 9120D	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2025.09.03	2026.09.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Number of Hopping Frequency	±5%	Confidence levels of 95%
Peak Output Power	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Carrier Frequency Separation	±5%	Confidence levels of 95%
Time of Occupancy (Dwell time)	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Aptiv Services Poland S.A.
Applicant Address:	ul. Podgórk Tynieckie 2,30-399 Kraków, Poland
Manufacturer:	Aptiv Services Poland S.A.
Manufacturer Address:	ul. Podgórk Tynieckie 2,30-399 Kraków, Poland

2.2. Information of EUT

Product Name:	P-MIB4
Sample No.:	13#, 14#, 19#
Hardware Version:	6
Software Version:	X021
Blockchain log:	
Equipment Type:	Bluetooth classic
Bluetooth Version:	5.3
Modulation Type:	FHSS (GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))
Operating Frequency Range:	2402MHz-2480MHz
Antenna Type:	Internal Antenna
Antenna Gain:	ANT1: 2.40dBi; ANT2: 2.51dBi

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The EUT has two antennas and it operates in single antenna. Both of the two antennas were evaluated separately, only the worst test result (ANT1) were recorded in the test report.

Note 3: This is a variant report of original report (Report No.: SZ26030114W01, FCC ID: 2BU79PMIB4) to request a Class II Permissive change, based on the similarity between before, made the following changes:

- Nexperia shortage mitigation many component swaps across RSC/MMX (transistors, MOSFETs, diodes, and logic ICs) replaced with alternates from Diodes Inc., TI, Yangjie, Panjit.
- Smaller design fixes and improvements (I2C fixes, SI tuning, USB fixes, coding updates)



c) A few component robustness updates (e.g., higher temperature-rated crystals)

And Strongbox removal, the others are the same as before.

d) Change the hardware version.

Due to the above changes, we have evaluated and retested worst case of RF output power and radiated emissions, the test results are better than before, all other test items are no need to be retested. The changes do not affect the test results in this report.

2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☒ Internal Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☒ Metal Shrapnel ☐ Layout



3.2. Hopping Mechanism

3.2.1. Requirement

According to FCC section 15.247(a)(1), a frequency hopping spread spectrum system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to FCC section 15.247(h), the incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3.2.2. Test Result

The hopping mechanism of the EUT is in compliance with the document "**Bluetooth core specification v5.1**".



3.3. Number of Hopping Frequency

3.3.1. Requirement

According to FCC section 15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

3.3.2. Test Procedures

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.1 in this report.

3.4. Duty Cycle of Test Signal

3.4.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.4.2. Test Result

Refer to Annex A.2 in this report.



3.5. Maximum Peak Conducted Output Power

3.5.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.5.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.3 in this report.



3.6. Maximum Average Conducted Output Power

3.6.1. Requirement

According to FCC section 15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

3.6.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.4 in this report.



3.7.20 dB Bandwidth

3.7.1.Requirement

According to FCC section 15.247(a)(1), the 20 dB bandwidth is known as the 99% emission bandwidth, or 20 dB bandwidth ($10 \cdot \log 1\% = 20 \text{ dB}$) taking the total RF output power.

3.7.1.Test Procedures

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW, centered on the test channel

RBW= 1% to 5% of the OBW

VBW $\geq 3 \times$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

3.7.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.3.Test Result

Refer to Annex A.5 in this report.



3.8. Carried Frequency Separation

3.8.1. Requirement

According to FCC section 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

3.8.2. Test Procedures

The EUT must have its hopping function enabled. According to DA 00-705, use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.8.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.8.4. Test Result

Refer to Annex A.6 in this report.



3.9. Time of Occupancy (Dwell time)

3.9.1. Requirement

According to FCC section 15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

3.9.2. Test Procedures

Normal Mode:

DH1: Dwell time equal to Pulse time (ms) $\times (1600 / 2 / 79) \times 31.6$ Millisecond
DH3: Dwell time equal to Pulse time (ms) $\times (1600 / 4 / 79) \times 31.6$ Millisecond
DH5: Dwell time equal to Pulse Time (ms) $\times (1600 / 6 / 79) \times 31.6$ Millisecond

AFH Mode:

DH1: Dwell time equal to Pulse time (ms) $\times (800 / 2 / 20) \times (0.4 \times 20)$ Millisecond
DH3: Dwell time equal to Pulse time (ms) $\times (800 / 4 / 20) \times (0.4 \times 20)$ Millisecond
DH5: Dwell time equal to Pulse Time (ms) $\times (800 / 6 / 20) \times (0.4 \times 20)$ Millisecond.

3.9.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.9.4. Test Result

Refer to Annex A.7 in this report.



3.10. Conducted Spurious Emissions and Band Edge

3.10.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.10.2.Test Procedures

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

3.10.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.10.4.Test Result

Refer to Annex A.8 and A.9 in this report.

3.11. Conducted Emission

3.11.1.Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.11.2.Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

3.11.3.Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.11.4.Test Result

This test case does not apply this kind of EUT.

3.12. Restricted Frequency Bands

3.12.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.12.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.12.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.12.4.Test Result

Refer to Annex A.10 in this report.

3.13. Radiated Emission

3.13.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2:For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.13.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.13.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.13.4.Test Result

Refer to Annex A.11 in this report.




Annex A Test Data and Result


A.1. Number of Hopping Frequency

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass
NVNT	1-DH5	Ant2	79	15	Pass
NVNT	2-DH5	Ant2	79	15	Pass
NVNT	3-DH5	Ant2	79	15	Pass







Hopping No. NVNT 1-DH5 2441MHz Ant1




Hopping No. NVNT 1-DH5 2441MHz Ant2




Hopping No. NVNT 2-DH5 2441MHz Ant1



Hopping No. NVNT 2-DH5 2441MHz Ant2




Hopping No. NVNT 3-DH5 2441MHz Ant1




Hopping No. NVNT 3-DH5 2441MHz Ant2

**A.2. Duty Cycle of Test Signal**


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	1-DH5	2402	Ant1	76.93	1.14	0.35
NVNT	1-DH5	2441	Ant1	76.91	1.14	0.35
NVNT	1-DH5	2480	Ant1	76.93	1.14	0.35
NVNT	1-DH5	2402	Ant2	76.94	1.14	0.35
NVNT	1-DH5	2441	Ant2	76.93	1.14	0.35
NVNT	1-DH5	2480	Ant2	76.94	1.14	0.35
NVNT	2-DH5	2402	Ant1	76.96	1.14	0.35
NVNT	2-DH5	2441	Ant1	76.96	1.14	0.35
NVNT	2-DH5	2480	Ant1	76.96	1.14	0.35
NVNT	2-DH5	2402	Ant2	76.94	1.14	0.35
NVNT	2-DH5	2441	Ant2	76.98	1.14	0.35
NVNT	2-DH5	2480	Ant2	76.98	1.14	0.35
NVNT	3-DH5	2402	Ant1	77.07	1.13	0.35
NVNT	3-DH5	2441	Ant1	77.07	1.13	0.35
NVNT	3-DH5	2480	Ant1	77.07	1.13	0.35
NVNT	3-DH5	2402	Ant2	77.11	1.13	0.35
NVNT	3-DH5	2441	Ant2	77.06	1.13	0.35
NVNT	3-DH5	2480	Ant2	77.1	1.13	0.35




Duty Cycle NVNT 1-DH5 2402MHz Ant1




Duty Cycle NVNT 1-DH5 2441MHz Ant1




Duty Cycle NVNT 1-DH5 2480MHz Ant1




Duty Cycle NVNT 1-DH5 2402MHz Ant2




Duty Cycle NVNT 1-DH5 2441MHz Ant2




Duty Cycle NVNT 1-DH5 2480MHz Ant2




Duty Cycle NVNT 2-DH5 2402MHz Ant1




Duty Cycle NVNT 2-DH5 2441MHz Ant1




Duty Cycle NVNT 2-DH5 2480MHz Ant1




Duty Cycle NVNT 2-DH5 2402MHz Ant2




Duty Cycle NVNT 2-DH5 2441MHz Ant2




Duty Cycle NVNT 2-DH5 2480MHz Ant2




Duty Cycle NVNT 3-DH5 2402MHz Ant1




Duty Cycle NVNT 3-DH5 2441MHz Ant1




Duty Cycle NVNT 3-DH5 2480MHz Ant1



Duty Cycle NVNT 3-DH5 2402MHz Ant2



Duty Cycle NVNT 3-DH5 2441MHz Ant2



Duty Cycle NVNT 3-DH5 2480MHz Ant2

**A.3. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	7.96	0	7.96	0.00625	30	Pass
NVNT	1-DH5	2441	Ant1	7.72	0	7.72	0.00592	30	Pass
NVNT	1-DH5	2480	Ant1	8.66	0	8.66	0.00735	30	Pass
NVNT	1-DH5	2402	Ant2	8.74	0	8.74	0.00748	30	Pass
NVNT	1-DH5	2441	Ant2	8.87	0	8.87	0.00771	30	Pass
NVNT	1-DH5	2480	Ant2	9.79	0	9.79	0.00953	30	Pass
NVNT	2-DH5	2402	Ant1	9.04	0	9.04	0.00802	30	Pass
NVNT	2-DH5	2441	Ant1	8.91	0	8.91	0.00778	30	Pass
NVNT	2-DH5	2480	Ant1	9.69	0	9.69	0.00931	30	Pass
NVNT	2-DH5	2402	Ant2	9.8	0	9.8	0.00955	30	Pass
NVNT	2-DH5	2441	Ant2	10.14	0	10.14	0.01033	30	Pass
NVNT	2-DH5	2480	Ant2	10.88	0	10.88	0.01225	30	Pass
NVNT	3-DH5	2402	Ant1	9.28	0	9.28	0.00847	30	Pass
NVNT	3-DH5	2441	Ant1	9.29	0	9.29	0.00849	30	Pass
NVNT	3-DH5	2480	Ant1	9.98	0	9.98	0.00995	30	Pass
NVNT	3-DH5	2402	Ant2	10.27	0	10.27	0.01064	30	Pass
NVNT	3-	2441	Ant2	10.56	0	10.56	0.01138	30	Pass




REPORT No.: SZ26090251W02

	DH5								
NVNT	3-DH5	2480	Ant2	11.18	0	11.18	0.01312	30	Pass







Peak Power NVNT 1-DH5 2402MHz Ant1




Peak Power NVNT 1-DH5 2441MHz Ant1




Peak Power NVNT 1-DH5 2480MHz Ant1




Peak Power NVNT 1-DH5 2402MHz Ant2




Peak Power NVNT 1-DH5 2441MHz Ant2




Peak Power NVNT 1-DH5 2480MHz Ant2




Peak Power NVNT 2-DH5 2402MHz Ant1




Peak Power NVNT 2-DH5 2441MHz Ant1




Peak Power NVNT 2-DH5 2480MHz Ant1




Peak Power NVNT 2-DH5 2402MHz Ant2




Peak Power NVNT 2-DH5 2441MHz Ant2




Peak Power NVNT 2-DH5 2480MHz Ant2




Peak Power NVNT 3-DH5 2402MHz Ant1




Peak Power NVNT 3-DH5 2441MHz Ant1




Peak Power NVNT 3-DH5 2480MHz Ant1



Peak Power NVNT 3-DH5 2402MHz Ant2



Peak Power NVNT 3-DH5 2441MHz Ant2



Peak Power NVNT 3-DH5 2480MHz Ant2

**A.4. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	6.48	1.14	7.62	0.00578	30	Pass
NVNT	1-DH5	2441	Ant1	6.12	1.14	7.26	0.00532	30	Pass
NVNT	1-DH5	2480	Ant1	7.51	1.14	8.65	0.00733	30	Pass
NVNT	1-DH5	2402	Ant2	6.99	1.14	8.13	0.0065	30	Pass
NVNT	1-DH5	2441	Ant2	7.02	1.14	8.16	0.00655	30	Pass
NVNT	1-DH5	2480	Ant2	8.32	1.14	9.46	0.00883	30	Pass
NVNT	2-DH5	2402	Ant1	5.5	1.14	6.64	0.00461	30	Pass
NVNT	2-DH5	2441	Ant1	5.4	1.14	6.54	0.00451	30	Pass
NVNT	2-DH5	2480	Ant1	6.23	1.14	7.37	0.00546	30	Pass
NVNT	2-DH5	2402	Ant2	4.63	1.14	5.77	0.00378	30	Pass
NVNT	2-DH5	2441	Ant2	6.54	1.14	7.68	0.00586	30	Pass
NVNT	2-DH5	2480	Ant2	7.38	1.14	8.52	0.00711	30	Pass
NVNT	3-DH5	2402	Ant1	5.55	1.13	6.68	0.00466	30	Pass
NVNT	3-DH5	2441	Ant1	5.27	1.13	6.4	0.00437	30	Pass
NVNT	3-DH5	2480	Ant1	6.16	1.13	7.29	0.00536	30	Pass
NVNT	3-DH5	2402	Ant2	4.58	1.13	5.71	0.00372	30	Pass
NVNT	3-	2441	Ant2	6.38	1.13	7.51	0.00564	30	Pass




REPORT No.: SZ26090251W02

	DH5								
NVNT	3-DH5	2480	Ant2	7.23	1.13	8.36	0.00685	30	Pass


on
A B

if


AL
ste




Average Power NVNT 1-DH5 2402MHz Ant1




Average Power NVNT 1-DH5 2441MHz Ant1




Average Power NVNT 1-DH5 2480MHz Ant1




Average Power NVNT 1-DH5 2402MHz Ant2




Average Power NVNT 1-DH5 2441MHz Ant2




Average Power NVNT 1-DH5 2480MHz Ant2




Average Power NVNT 2-DH5 2402MHz Ant1




Average Power NVNT 2-DH5 2441MHz Ant1




Average Power NVNT 2-DH5 2480MHz Ant1




Average Power NVNT 2-DH5 2402MHz Ant2




Average Power NVNT 2-DH5 2441MHz Ant2




Average Power NVNT 2-DH5 2480MHz Ant2




Average Power NVNT 3-DH5 2402MHz Ant1




Average Power NVNT 3-DH5 2441MHz Ant1




Average Power NVNT 3-DH5 2480MHz Ant1



Average Power NVNT 3-DH5 2402MHz Ant2




Average Power NVNT 3-DH5 2441MHz Ant2




Average Power NVNT 3-DH5 2480MHz Ant2

**A.5. 20 dB Bandwidth**


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)
NVNT	1-DH5	2402	Ant1	0.9257
NVNT	1-DH5	2441	Ant1	0.9355
NVNT	1-DH5	2480	Ant1	0.9321
NVNT	1-DH5	2402	Ant2	0.9382
NVNT	1-DH5	2441	Ant2	0.9261
NVNT	1-DH5	2480	Ant2	0.9407
NVNT	2-DH5	2402	Ant1	1.316
NVNT	2-DH5	2441	Ant1	1.321
NVNT	2-DH5	2480	Ant1	1.276
NVNT	2-DH5	2402	Ant2	1.308
NVNT	2-DH5	2441	Ant2	1.35
NVNT	2-DH5	2480	Ant2	1.313
NVNT	3-DH5	2402	Ant1	1.308
NVNT	3-DH5	2441	Ant1	1.307
NVNT	3-DH5	2480	Ant1	1.303
NVNT	3-DH5	2402	Ant2	1.31
NVNT	3-DH5	2441	Ant2	1.311
NVNT	3-DH5	2480	Ant2	1.293




-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2402MHz Ant2




-20dB Bandwidth NVNT 1-DH5 2441MHz Ant2




-20dB Bandwidth NVNT 1-DH5 2480MHz Ant2




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant2




-20dB Bandwidth NVNT 2-DH5 2441MHz Ant2




-20dB Bandwidth NVNT 2-DH5 2480MHz Ant2




-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2402MHz Ant2




-20dB Bandwidth NVNT 3-DH5 2441MHz Ant2




-20dB Bandwidth NVNT 3-DH5 2480MHz Ant2

**A.6. Carried Frequency Separation**


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2440.994	2441.972	0.978	0.624	Pass
NVNT	1-DH5	Ant2	2440.986	2441.97	0.984	0.617	Pass
NVNT	2-DH5	Ant1	2440.966	2441.944	0.978	0.881	Pass
NVNT	2-DH5	Ant2	2440.88	2441.998	1.118	0.9	Pass
NVNT	3-DH5	Ant1	2440.916	2442.062	1.146	0.871	Pass
NVNT	3-DH5	Ant2	2441.164	2442.094	0.93	0.874	Pass




CFS NVNT 1-DH5 2441MHz Ant1




CFS NVNT 1-DH5 2441MHz Ant2




CFS NVNT 2-DH5 2441MHz Ant1



CFS NVNT 2-DH5 2441MHz Ant2



CFS NVNT 3-DH5 2441MHz Ant1




CFS NVNT 3-DH5 2441MHz Ant2


**A.7. Time of Occupancy (Dwell time)**

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2441	Ant1	2.881	314.029	109	31600	400	Pass
NVNT	1-DH5	2441	Ant2	2.88	290.88	101	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.873	264.316	92	31600	400	Pass
NVNT	2-DH5	2441	Ant2	2.87	284.13	99	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.873	318.903	111	31600	400	Pass
NVNT	3-DH5	2441	Ant2	2.873	264.316	92	31600	400	Pass







Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




Dwell NVNT 1-DH5 2441MHz Ant2 One Burst



Dwell NVNT 1-DH5 2441MHz Ant2 Accumulated





Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated






E-mail: service@morlab.cn



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated

