



Radio Test Report

Report No.: STS2604056W10

Issued for

JIAHANG TECHNOLOGY (HONG KONG) CO., LIMITED
19H MAXGRAND PLAZA 3 TAI YAU STREET SAN PO
KONG KL HONG KONG China

Product Name: TABLET

Brand Name: N/A

Model Name: W90

Series Model(s): N/A

FCC ID: 2BU85-W90

Test Standards: FCC Part15.407

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name: JIAHANG TECHNOLOGY (HONG KONG) CO.,LIMITED
Address: 19H MAXGRAND PLAZA 3 TAI YAU STREET SAN PO KONG KL
HONG KONG China
Manufacturer's Name: LUZHENG TECHNOLOGY HONGKONG LIMITED
Address: ROOM A08, 2/F LEE KA INDUSTRIAL BUILDING 8 NG FONG
STREET SAN PO KONG HK China

Product Description

Product Name: Tablet PC
Brand Name: N/A
Model Name: W90
Series Model(s): N/A

Test Standards: FCC Part15.407

Test Procedure ANSI C63.10-2020+Cor 1-2023

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item: 13 Apr. 2026
Date (s) of performance of tests: 13 Apr. 2026~11 May 2026
Date of Issue: 11 May 2026
Test Result: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	11
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	13
2.6 EQUIPMENTS LIST	14
3. EMC EMISSION TEST	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION AND MEASUREMENT	19
4. POWER SPECTRAL DENSITY TEST	65
4.1 LIMIT	65
4.2 TEST PROCEDURE	65
4.3 DEVIATION FROM STANDARD	66
4.4 TEST SETUP	66
4.5 EUT OPERATION CONDITIONS	66
4.6 TEST RESULTS	66
5. DUTY CYCLE	67
5.1 TEST STANDARD	67
5.2 TEST PROCEDURE	67
5.3 DEVIATION FROM STANDARD	67
5.4 TEST SETUP	67
5.5 EUT OPERATION CONDITIONS	67
5.6 TEST RESULTS	67
6. BANDWIDTH MEASUREMENT	68
6.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	68
6.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	69
6.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	70
7. MAXIMUM OUTPUT POWER	71
7.1 LIMIT	71
7.2 TEST PROCEDURE	71
7.3 DEVIATION FROM STANDARD	71



Table of Contents	Page
7.4 TEST SETUP	71
7.5 EUT OPERATION CONDITIONS	71
7.6 TEST RESULTS	71
8. AUTOMATICALLY DISCONTINUE TRANSMISSION	72
8.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	72
8.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	72
9. ANTENNA REQUIREMENT	73
9.1 STANDARD REQUIREMENT	73
9.2 EUT ANTENNA	73
10. FREQUENCY STABILITY	74
10.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	74
10.2 TEST PROCEDURE	74
10.3 TEST STEUP	74
10.4 TEST RESULT	75
APPENDIX - PHOTOS OF TEST SETUP	77

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	11 May 2026	STS2604066W10	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203	Antenna Requirement	PASS
15.407(g)	Frequency Stability	PASS

Note:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020+Cor 1-2023.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add.: 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	TABLET	
Brand Name	N/A	
Model Name	W90	
Series Model(s)	N/A	
Model Difference	N/A	
Product Description	The EUT is TABLET	
	Operation Frequency:	IEEE 802.11a/n/ac (20M): 5.180GHz-5.240GHz IEEE 802.11n/ac (40M): 5.190GHz-5.230GHz IEEE 802.11 ac (80M): 5.210GHz
		IEEE 802.11 a/n/ac (20M): 5.745GHz-5.825GHz IEEE 802.11n/ac (40M): 5.755GHz-5.795GHz IEEE 802.11 ac (80M): 5.775GHz
	Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM
	Antenna Type:	FPC
	Antenna Gain:	5.2G RLAN: 2.33dBi 5.8G RLAN: 2.11dBi
More details of EUT technical specification, please refer to the User Manual.		
Test Channel	Please refer to the Note 3.	
Power Rating	Input: DC 9V/2.22A	
Adapter	Model: KWY-PD20U Input: 100-240V 50/60Hz 0.5A Output:USB-C 5V== 3A,9V== 2.22A,12V== 1.67A	
Battery	Model: 2767130-2P Rated Voltage: 3.85V Charge Limit Voltage: 4.35V Capacity: 8000mAh	
Hardware version number	L30-T620-V1.0	
Software version number	V1.0	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna details in this report are based on the manufacturer provided antenna specification documents and apply only to the tested sample identified herein.
Any discrepancies in the antenna information may affect the accuracy of the test results, and the customer assumes responsibility for any related issues.



3.

Operation Frequency of channel			
5.180GHz-5.240GHz		5.745GHz-5.825GHz	
Channel	Frequency	Channel	Frequency
36	5180	149	5745
38	5190	151	5755
40	5200	153	5765
42	5210	155	5775
44	5220	157	5785
46	5230	159	5795
48	5240	161	5805
		165	5825

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n/ac (20M)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	149	5745
40	5200	157	5785
48	5240	165	5825

For 802.11 n/ac (40M)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	151	5755
46	5230	159	5795

For 802.11 ac (80M)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	155	5775



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 3	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 4	TX IEEE 802.11ac VHT20 CH36&CH40&CH48	NSS1 MCS0
Mode 5	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 6	TX IEEE 802.11ac VHT20 CH149&CH157&CH165	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 8	TX IEEE 802.11ac VHT40 CH38&CH46	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 10	TX IEEE 802.11ac VHT40 CH151&CH159	NSS1 MCS0
Mode 11	TX IEEE 802.11ac VHT80 CH42	NSS1 MCS0
Mode 12	TX IEEE 802.11ac VHT80 CH155	NSS1 MCS0

Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 13: Keeping WLAN TX



2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	U-NII-1 (5150MHz-5250MHz)	802.11a	2.33	7	Engineering mode
		802.11n(HT20)		6	
		802.11n(HT40)		6	
		802.11ac(VHT20)		6	
		802.11ac(VHT40)		6	
		802.11ac(VHT80)		6	

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	U-NII-3 (5725MHz-5850MHz)	802.11a	2.11	7	Engineering mode
		802.11n(HT20)		6	
		802.11n(HT40)		6	
		802.11ac(VHT20)		6	
		802.11ac(VHT40)		6	
		802.11ac(VHT80)		6	




2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



RF Conducted Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Adapter	N/A	KWY-PD20U	N/A
C-1	USB Cable	N/A	KWY-PD20U	N/A

Item	Equipment	Mfr/Brand	Length	Note
C-1	Shielded	NO	100cm	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.6 EQUIPMENTS LIST

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2026.02.04	2027.02.03
Pre-Amplifier(0.1M-3G Hz)	EM	EM330	060665	2026.02.04	2027.02.03
Pre-Amplifier(1G-18G Hz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40 GHz)	SKET	LNPA_1840-50	SK2018101801	2026.03.04	2027.03.03
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Band 5.1G-5.8G Filter	HX MICROWAVE	HXLBQ-DZA62	N/A	2025.09.23	2026.09.22
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENGFENG	DPS-305AF	17064939	2025.09.22	2026.09.21
RF Coaxial Cable	LEITAI M-WAVE	CA360	DC-18G	2025.09.26	2026.09.25
RF Coaxial Cable	LEITAI M-WAVE	CA360	DC-18G	2025.09.26	2026.09.25
RF Coaxial Cable	LEITAI M-WAVE	CA3507	DC-40G	2025.09.26	2026.09.25
RF Coaxial Cable	LEITAI M-WAVE	CA3507	DC-40G	2025.09.26	2026.09.25
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.26	2026.09.25
Limiter	CYBERTEK	EM5010	N/A	2025.09.25	2026.09.24
LISN	R&S	ENV216	101242	2025.09.25	2026.09.24
LISN	EMCO	3810/2NM	23625	2025.09.25	2026.09.24
Temperature & Humidity	SW-108	SuWei	N/A	2026.02.04	2027.02.03
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2026.02.04	2027.02.03
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
RF Coaxial Cable	XINQY	CT26PE	DC-26.5G	2026.02.04	2027.02.03
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2026.02.04	2027.02.03
Temperature & Humidity	SW-108	SuWei	N/A	2026.02.04	2027.02.03
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

Temperature:	25.6°C	Relative Humidity:	60.7%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3780	25.55	19.36	44.91	58.32	-13.41	QP
2	0.3780	18.23	19.36	37.59	48.32	-10.73	AVG
3	0.5020	30.47	19.34	49.81	56.00	-6.19	QP
4	0.5020	20.96	19.34	40.30	46.00	-5.70	AVG
5	0.6580	26.74	19.40	46.14	56.00	-9.86	QP
6	0.6580	15.93	19.40	35.33	46.00	-10.67	AVG
7	0.7660	26.22	19.41	45.63	56.00	-10.37	QP
8	0.7660	15.05	19.41	34.46	46.00	-11.54	AVG
9	1.2980	25.98	19.39	45.37	56.00	-10.63	QP
10	1.2980	14.01	19.39	33.40	46.00	-12.60	AVG
11	6.2620	26.56	19.45	46.01	60.00	-13.99	QP
12	6.2620	14.58	19.45	34.03	50.00	-15.97	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)






Temperature:	25.6°C	Relative Humidity:	60.7%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode :	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1700	25.16	19.39	44.55	64.96	-20.41	QP
2	0.1700	11.75	19.39	31.14	54.96	-23.82	AVG
3	0.2860	22.16	19.38	41.54	60.64	-19.10	QP
4	0.2860	7.43	19.38	26.81	50.64	-23.83	AVG
5	0.5180	21.24	19.35	40.59	56.00	-15.41	QP
6	0.5180	13.17	19.35	32.52	46.00	-13.48	AVG
7	0.6660	20.40	19.40	39.80	56.00	-16.20	QP
8	0.6660	8.59	19.40	27.99	46.00	-18.01	AVG
9	0.8180	19.76	19.40	39.16	56.00	-16.84	QP
10	0.8180	6.66	19.40	26.06	46.00	-19.94	AVG
11	5.7540	25.10	19.45	44.55	60.00	-15.45	QP
12	5.7540	6.78	19.45	26.23	50.00	-23.77	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)

100.0 dBuV





3.2 RADIATED EMISSION AND MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: dBuV/m(at 3M) = EIRP(dBm) + 95.2.

Peak Limit = -27dBm/MHz + 95.2 = 68.2 dBuV/m.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge



Spectrum Parameter	Setting
Detector	Peak/AV
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested with a band-stop filter and performed pretest to three orthogonal axis. The worst-case emissions were reported.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.7 TEST RESULTS (Between 9KHz – 30 MHz)

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 3.85V	Polarization :	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.2.8 TEST RESULTS (Between 30MHz – 1GHz)


U-NII-1

Temperature	23.4°C	Relative Humidity:	60%
Test Voltage	DC 3.85V	Polarization:	Horizontal
Test Mode	(n20 worst mode) – High Channel		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	188.1100	42.12	-20.76	21.36	43.50	-22.14	peak
2	235.6400	42.36	-18.62	23.74	46.00	-22.26	peak
3	424.7900	32.23	-10.12	22.11	46.00	-23.89	peak
4	497.5400	35.38	-8.06	27.32	46.00	-18.68	peak
5	733.2500	33.68	-2.35	31.33	46.00	-14.67	peak
6	869.0500	33.21	-0.52	32.69	46.00	-13.31	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain





Temperature	23.4℃	Relative Humidity:	60%
Test Voltage	DC 3.85V	Polarization:	Vertical
Test Mode	(n20 worst mode) – High Channel		


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.3992	28.79	-13.57	15.22	40.00	-24.78	peak
2	323.9100	29.57	-13.88	15.69	46.00	-30.31	peak
3	433.5200	38.70	-10.13	28.57	46.00	-17.43	peak
4	624.6100	30.22	-5.29	24.93	46.00	-21.07	peak
5	776.9000	30.81	-2.25	28.56	46.00	-17.44	peak
6	959.2600	29.62	1.75	31.37	46.00	-14.63	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit

2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain

80.0 dBuV/m






Temperature	23.4℃	Relative Humidity:	60%
Test Voltage	DC 3.85V	Polarization:	Horizontal
Test Mode	(n20 worst mode) – Low Channel		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.9700	29.56	-13.35	16.21	40.00	-23.79	peak
2	189.0800	43.66	-20.87	22.79	43.50	-20.71	peak
3	235.6400	42.78	-18.62	24.16	46.00	-21.84	peak
4	497.5400	35.69	-8.06	27.63	46.00	-18.37	peak
5	733.2500	33.35	-2.35	31.00	46.00	-15.00	peak
6	958.2900	30.56	1.73	32.29	46.00	-13.71	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit

2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain





Temperature	23.4℃	Relative Humidity:	60%
Test Voltage	DC 3.85V	Polarization:	Vertical
Test Mode	(n20 worst mode) – Low Channel		


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.9400	29.32	-13.86	15.46	40.00	-24.54	peak
2	358.8300	30.17	-12.90	17.27	46.00	-28.73	peak
3	464.5600	30.09	-9.25	20.84	46.00	-25.16	peak
4	550.8900	29.49	-5.74	23.75	46.00	-22.25	peak
5	790.4800	30.60	-1.97	28.63	46.00	-17.37	peak
6	945.6800	30.05	1.50	31.55	46.00	-14.45	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit

2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain


80.0 dBuV/m






3.2.8 TEST RESULTS (Above 1000 MHz)


U-NII-1
802.11 n20
Low Channel
Horizontal




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2245.000	45.24	2.09	74.0	-28.76	Peak	338.10	Horizontal	Pass
1**	2245.000	34.18	2.09	54.0	-19.82	AV	338.10	Horizontal	Pass
2	2965.500	48.72	5.29	68.2	-19.48	Peak	277.80	Horizontal	Pass
2**	2965.500	37.89	5.29	54.0	-16.11	AV	277.80	Horizontal	Pass
3	6987.000	53.50	1.21	68.2	-14.70	Peak	54.10	Horizontal	Pass
3**	6987.000	43.20	1.21	54.0	-10.80	AV	54.10	Horizontal	Pass
4	12214.000	55.64	2.79	74.0	-18.36	Peak	122.60	Horizontal	Pass
4**	12214.000	44.29	2.79	54.0	-9.71	AV	122.60	Horizontal	Pass
5	14427.750	60.13	6.79	68.2	-8.07	Peak	93.30	Horizontal	Pass
5**	14427.750	49.23	6.79	54.0	-4.77	AV	93.30	Horizontal	Pass
6	17878.999	59.81	7.06	74.0	-14.19	Peak	44.20	Horizontal	Pass
6**	17878.999	48.96	7.06	54.0	-5.04	AV	44.20	Horizontal	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32652.000	43.10	9.13	52.23	68.20	-15.97	peak
2	32652.000	32.73	9.13	41.86	54.00	-12.14	AVG

Vertical
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2196.500	44.79	1.52	68.2	-23.41	Peak	344.30	Vertical	Pass
1**	2196.500	33.95	1.52	54.0	-20.05	AV	344.30	Vertical	Pass
2	2518.500	55.10	3.29	68.2	-13.10	Peak	117.40	Vertical	Pass
2**	2518.500	49.10	3.29	54.0	-4.90	AV	117.40	Vertical	Pass
3	6968.000	53.68	1.06	68.2	-14.52	Peak	231.10	Vertical	Pass
3**	6968.000	42.95	1.06	54.0	-11.05	AV	231.10	Vertical	Pass
4	12450.500	56.35	2.67	74.0	-17.65	Peak	172.10	Vertical	Pass
4**	12450.500	44.80	2.67	54.0	-9.20	AV	172.10	Vertical	Pass
5	14416.750	59.85	6.87	68.2	-8.35	Peak	352.70	Vertical	Pass
5**	14416.750	48.91	6.87	54.0	-5.09	AV	352.70	Vertical	Pass
6	17920.250	59.57	7.08	74.0	-14.43	Peak	359.40	Vertical	Pass
6**	17920.250	49.63	7.08	54.0	-4.37	AV	359.40	Vertical	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	24270.000	47.06	4.68	51.74	68.20	-16.46	peak
2	24270.000	38.63	4.68	43.31	54.00	-10.69	AVG

Mid Channel
Horizontal
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2583.500	47.32	3.48	68.2	-20.88	Peak	327.20	Horizontal	Pass
1**	2583.500	35.49	3.48	54.0	-18.51	AV	327.20	Horizontal	Pass
2	2815.500	48.31	4.83	74.0	-25.69	Peak	306.40	Horizontal	Pass
2**	2815.500	37.09	4.83	54.0	-16.91	AV	306.40	Horizontal	Pass
3	6983.000	54.12	1.18	68.2	-14.08	Peak	282.10	Horizontal	Pass
3**	6983.000	43.05	1.18	54.0	-10.95	AV	282.10	Horizontal	Pass
4	12442.250	55.45	2.75	74.0	-18.55	Peak	34.50	Horizontal	Pass
4**	12442.250	45.42	2.75	54.0	-8.58	AV	34.50	Horizontal	Pass
5	14449.750	59.31	6.64	68.2	-8.89	Peak	360.00	Horizontal	Pass
5**	14449.750	48.66	6.64	54.0	-5.34	AV	360.00	Horizontal	Pass
6	16600.250	59.43	5.16	68.2	-8.77	Peak	152.80	Horizontal	Pass
6**	16600.250	47.63	5.16	54.0	-6.37	AV	152.80	Horizontal	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34786.000	43.08	9.64	52.72	68.20	-15.48	peak
2	34786.000	33.39	9.64	43.03	54.00	-10.97	AVG

Vertical
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2435.500	46.32	3.19	68.2	-21.88	Peak	241.90	Vertical	Pass
1**	2435.500	35.41	3.19	54.0	-18.59	AV	241.90	Vertical	Pass
2	2945.500	48.94	5.19	68.2	-19.26	Peak	61.20	Vertical	Pass
2**	2945.500	37.77	5.19	54.0	-16.23	AV	61.20	Vertical	Pass
3	7000.000	53.50	1.32	68.2	-14.70	Peak	50.80	Vertical	Pass
3**	7000.000	43.69	1.32	54.0	-10.31	AV	50.80	Vertical	Pass
4	11202.000	55.07	2.61	74.0	-18.93	Peak	109.10	Vertical	Pass
4**	11202.000	45.33	2.61	54.0	-8.67	AV	109.10	Vertical	Pass
5	14191.250	59.09	6.95	68.2	-9.11	Peak	253.40	Vertical	Pass
5**	14191.250	47.95	6.95	54.0	-6.05	AV	253.40	Vertical	Pass
6	17895.500	59.25	7.20	74.0	-14.75	Peak	18.10	Vertical	Pass
6**	17895.500	49.23	7.20	54.0	-4.77	AV	18.10	Vertical	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	25964.000	46.43	5.79	52.22	68.20	-15.98	peak
2	25964.000	36.41	5.79	42.20	54.00	-11.80	AVG

High Channel
Horizontal
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2390.000	45.21	3.01	68.2	-22.99	Peak	341.20	Horizontal	Pass
1**	2390.000	34.89	3.01	54.0	-19.11	AV	341.20	Horizontal	Pass
2	2831.500	48.11	4.90	74.0	-25.89	Peak	0.90	Horizontal	Pass
2**	2831.500	37.39	4.90	54.0	-16.61	AV	0.90	Horizontal	Pass
3	6986.000	53.80	1.21	68.2	-14.40	Peak	147.90	Horizontal	Pass
3**	6986.000	43.56	1.21	54.0	-10.44	AV	147.90	Horizontal	Pass
4	11163.500	55.37	2.42	74.0	-18.63	Peak	197.40	Horizontal	Pass
4**	11163.500	45.27	2.42	54.0	-8.73	AV	197.40	Horizontal	Pass
5	14408.500	60.05	6.93	68.2	-8.15	Peak	360.00	Horizontal	Pass
5**	14408.500	48.49	6.93	54.0	-5.51	AV	360.00	Horizontal	Pass
6	17890.001	60.01	7.15	74.0	-13.99	Peak	226.00	Horizontal	Pass
6**	17890.001	49.20	7.15	54.0	-4.80	AV	226.00	Horizontal	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	22268.000	48.52	3.68	52.20	74.00	-21.80	peak
2	22268.000	38.79	3.68	42.47	54.00	-11.53	AVG

Vertical
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	1991.500	44.86	0.32	68.2	-23.34	Peak	263.30	Vertical	Pass
1**	1991.500	34.97	0.32	54.0	-19.03	AV	263.30	Vertical	Pass
2	2954.500	48.59	5.24	68.2	-19.61	Peak	79.10	Vertical	Pass
2**	2954.500	37.85	5.24	54.0	-16.15	AV	79.10	Vertical	Pass
3	6993.000	53.79	1.26	68.2	-14.41	Peak	72.50	Vertical	Pass
3**	6993.000	43.49	1.26	54.0	-10.51	AV	72.50	Vertical	Pass
4	11257.000	55.41	2.43	74.0	-18.59	Peak	97.60	Vertical	Pass
4**	11257.000	45.13	2.43	54.0	-8.87	AV	97.60	Vertical	Pass
5	13952.000	59.96	7.85	68.2	-8.24	Peak	330.60	Vertical	Pass
5**	13952.000	48.58	7.85	54.0	-5.42	AV	330.60	Vertical	Pass
6	17925.751	59.16	7.04	74.0	-14.84	Peak	25.80	Vertical	Pass
6**	17925.751	49.15	7.04	54.0	-4.85	AV	25.80	Vertical	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	21234.000	49.46	2.79	52.25	74.00	-21.75	peak
2	21234.000	38.56	2.79	41.35	54.00	-12.65	AVG




U-NII-3
802.11 n20
Low Channel
Horizontal




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2180.000	44.79	1.64	68.2	-23.41	Peak	0.90	Horizontal	Pass
1**	2180.000	33.87	1.64	54.0	-20.13	AV	0.90	Horizontal	Pass
2	2895.000	48.45	4.91	74.0	-25.55	Peak	201.50	Horizontal	Pass
2**	2895.000	37.37	4.91	54.0	-16.63	AV	201.50	Horizontal	Pass
3	6976.000	53.51	1.13	68.2	-14.69	Peak	272.90	Horizontal	Pass
3**	6976.000	43.42	1.13	54.0	-10.58	AV	272.90	Horizontal	Pass
4	11193.750	54.95	2.59	74.0	-19.05	Peak	250.60	Horizontal	Pass
4**	11193.750	45.20	2.59	54.0	-8.80	AV	250.60	Horizontal	Pass
5	14155.500	58.98	6.91	68.2	-9.22	Peak	293.80	Horizontal	Pass
5**	14155.500	47.88	6.91	54.0	-6.12	AV	293.80	Horizontal	Pass
6	17408.750	59.47	6.83	68.2	-8.73	Peak	33.30	Horizontal	Pass
6**	17408.750	48.28	6.83	54.0	-5.72	AV	33.30	Horizontal	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34236.000	43.00	9.47	52.47	68.20	-15.73	peak
2	34236.000	34.05	9.47	43.52	54.00	-10.48	AVG

Vertical
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2480.000	46.97	3.18	68.2	-21.23	Peak	283.30	Vertical	Pass
1**	2480.000	35.87	3.18	54.0	-18.13	AV	283.30	Vertical	Pass
2	2843.000	48.56	4.96	74.0	-25.44	Peak	160.60	Vertical	Pass
2**	2843.000	37.51	4.96	54.0	-16.49	AV	160.60	Vertical	Pass
3	6998.000	53.81	1.30	68.2	-14.39	Peak	307.10	Vertical	Pass
3**	6998.000	43.59	1.30	54.0	-10.41	AV	307.10	Vertical	Pass
4	11246.000	55.38	2.46	74.0	-18.62	Peak	109.90	Vertical	Pass
4**	11246.000	44.88	2.46	54.0	-9.12	AV	109.90	Vertical	Pass
5	14499.250	59.13	6.29	74.0	-14.87	Peak	244.50	Vertical	Pass
5**	14499.250	48.22	6.29	54.0	-5.78	AV	244.50	Vertical	Pass
6	17903.749	59.35	7.21	74.0	-14.65	Peak	328.90	Vertical	Pass
6**	17903.749	49.20	7.21	54.0	-4.80	AV	328.90	Vertical	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	21718.000	48.53	3.14	51.67	68.20	-16.53	peak
2	21718.000	38.04	3.14	41.18	54.00	-12.82	AVG

Mid Channel
Horizontal
1GHz-18GHz


No	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2453.000	47.30	3.23	68.2	-20.90	Peak	122.00	Horizontal	Pass
1**	2453.000	35.16	3.23	54.0	-18.84	AV	122.00	Horizontal	Pass
2	2893.500	48.67	4.91	74.0	-25.33	Peak	244.60	Horizontal	Pass
2**	2893.500	37.38	4.91	54.0	-16.62	AV	244.60	Horizontal	Pass
3	6977.000	53.72	1.13	68.2	-14.48	Peak	139.30	Horizontal	Pass
3**	6977.000	43.33	1.13	54.0	-10.67	AV	139.30	Horizontal	Pass
4	11281.750	55.70	2.34	74.0	-18.30	Peak	210.80	Horizontal	Pass
4**	11281.750	44.54	2.34	54.0	-9.46	AV	210.80	Horizontal	Pass
5	14392.001	58.95	6.98	68.2	-9.25	Peak	74.30	Horizontal	Pass
5**	14392.001	48.54	6.98	54.0	-5.46	AV	74.30	Horizontal	Pass
6	17890.001	60.23	7.15	74.0	-13.77	Peak	359.60	Horizontal	Pass
6**	17890.001	49.39	7.15	54.0	-4.61	AV	359.60	Horizontal	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	26118.000	45.92	5.85	51.77	68.20	-16.43	peak
2	26118.000	35.64	5.85	41.49	54.00	-12.51	AVG

Vertical
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2035.000	44.26	0.69	68.2	-23.94	Peak	9.80	Vertical	Pass
1**	2035.000	32.89	0.69	54.0	-21.11	AV	9.80	Vertical	Pass
2	2863.000	48.85	4.97	74.0	-25.15	Peak	359.50	Vertical	Pass
2**	2863.000	37.50	4.97	54.0	-16.50	AV	359.50	Vertical	Pass
3	6999.000	53.68	1.31	68.2	-14.52	Peak	152.00	Vertical	Pass
3**	6999.000	44.13	1.31	54.0	-9.87	AV	152.00	Vertical	Pass
4	11287.250	56.06	2.32	74.0	-17.94	Peak	43.70	Vertical	Pass
4**	11287.250	44.63	2.32	54.0	-9.37	AV	43.70	Vertical	Pass
5	14007.000	58.83	8.34	68.2	-9.37	Peak	287.80	Vertical	Pass
5**	14007.000	48.64	8.34	54.0	-5.36	AV	287.80	Vertical	Pass
6	17859.750	59.16	6.89	74.0	-14.84	Peak	278.90	Vertical	Pass
6**	17859.750	48.63	6.89	54.0	-5.37	AV	278.90	Vertical	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	29418.000	42.89	9.10	51.99	68.20	-16.21	peak
2	29418.000	33.84	9.10	42.94	54.00	-11.06	AVG

High Channel
Horizontal
1GHz-18GHz


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2576.500	47.25	3.49	68.2	-20.95	Peak	163.90	Horizontal	Pass
1**	2576.500	35.77	3.49	54.0	-18.23	AV	163.90	Horizontal	Pass
2	2908.000	49.17	4.95	68.2	-19.03	Peak	134.50	Horizontal	Pass
2**	2908.000	37.53	4.95	54.0	-16.47	AV	134.50	Horizontal	Pass
3	6990.000	54.32	1.24	68.2	-13.88	Peak	301.40	Horizontal	Pass
3**	6990.000	43.31	1.24	54.0	-10.69	AV	301.40	Horizontal	Pass
4	11171.750	55.78	2.47	74.0	-18.22	Peak	251.70	Horizontal	Pass
4**	11171.750	45.06	2.47	54.0	-8.94	AV	251.70	Horizontal	Pass
5	14020.750	58.81	8.12	68.2	-9.39	Peak	236.40	Horizontal	Pass
5**	14020.750	48.37	8.12	54.0	-5.63	AV	236.40	Horizontal	Pass
6	17906.500	60.10	7.19	74.0	-13.90	Peak	358.30	Horizontal	Pass
6**	17906.500	49.38	7.19	54.0	-4.62	AV	358.30	Horizontal	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	29132.000	42.94	9.02	51.96	68.20	-16.24	peak
2	29132.000	31.15	9.02	40.17	54.00	-13.83	AVG

Vertical
1GHz-18GHz

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Antenna	Verdict
1	2481.000	46.71	3.18	68.2	-21.49	Peak	349.70	Vertical	Pass
1**	2481.000	36.13	3.18	54.0	-17.87	AV	349.70	Vertical	Pass
2	2816.500	49.56	4.83	74.0	-24.44	Peak	18.10	Vertical	Pass
2**	2816.500	36.96	4.83	54.0	-17.04	AV	18.10	Vertical	Pass
3	6961.000	53.97	1.00	68.2	-14.23	Peak	210.10	Vertical	Pass
3**	6961.000	43.22	1.00	54.0	-10.78	AV	210.10	Vertical	Pass
4	12450.500	55.93	2.67	74.0	-18.07	Peak	254.30	Vertical	Pass
4**	12450.500	45.24	2.67	54.0	-8.76	AV	254.30	Vertical	Pass
5	14449.750	59.47	6.64	68.2	-8.73	Peak	235.70	Vertical	Pass
5**	14449.750	48.91	6.64	54.0	-5.09	AV	235.70	Vertical	Pass
6	17925.751	59.64	7.04	74.0	-14.36	Peak	174.40	Vertical	Pass
6**	17925.751	48.77	7.04	54.0	-5.23	AV	174.40	Vertical	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33180.000	42.35	9.07	51.42	68.20	-16.78	peak
2	33180.000	32.80	9.07	41.87	54.00	-12.13	AVG

Note:


- 1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor.
- 2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.
- 3) All modes have been measured, only worst mode was reported.



3.2.9 TEST RESULTS(Band edge Requirements)


U-NII-1 (5.150-5.2500) GHz

802.11n20-L-H




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.750	62.40	-5.73	56.67	74.00	-17.33	peak
2	5142.750	51.62	-5.73	45.89	54.00	-8.11	AVG
3	5150.000	64.39	-5.77	58.62	74.00	-15.38	peak
4	5150.000	53.31	-5.77	47.54	54.00	-6.46	AVG

802.11n20-L-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.750	58.41	-5.73	52.68	74.00	-21.32	peak
2	5142.750	47.30	-5.73	41.57	54.00	-12.43	AVG
3	5150.000	63.00	-5.77	57.23	74.00	-16.77	peak
4	5150.000	51.99	-5.77	46.22	54.00	-7.78	AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	54.80	-5.33	49.47	74.00	-24.53	peak
2	5350.000	43.83	-5.33	38.50	54.00	-15.50	AVG
3	5360.320	55.65	-5.28	50.37	74.00	-23.63	peak
4	5360.320	44.96	-5.28	39.68	54.00	-14.32	AVG

802.11n20-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	55.21	-5.33	49.88	74.00	-24.12	peak
2	5350.000	43.52	-5.33	38.19	54.00	-15.81	AVG
3	5356.680	55.92	-5.29	50.63	74.00	-23.37	peak
4	5356.680	45.71	-5.29	40.42	54.00	-13.58	AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.750	64.88	-5.73	59.15	74.00	-14.85	peak
2	5142.750	52.23	-5.73	46.50	54.00	-7.50	AVG
3	5150.000	64.70	-5.77	58.93	74.00	-15.07	peak
4	5150.000	49.15	-5.77	43.38	54.00	-10.62	AVG

802.11ac40-L-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5139.750	60.79	-5.71	55.08	74.00	-18.92	peak
2	5139.750	48.73	-5.71	43.02	54.00	-10.98	AVG
3	5150.000	65.94	-5.77	60.17	74.00	-13.83	peak
4	5150.000	50.33	-5.77	44.56	54.00	-9.44	AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	54.74	-5.33	49.41	74.00	-24.59	peak
2	5350.000	44.95	-5.33	39.62	54.00	-14.38	AVG
3	5371.240	54.88	-5.23	49.65	74.00	-24.35	peak
4	5371.240	44.46	-5.23	39.23	54.00	-14.77	AVG

802.11ac40-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	53.62	-5.33	48.29	74.00	-25.71	peak
2	5350.000	43.74	-5.33	38.41	54.00	-15.59	AVG
3	5357.240	55.74	-5.29	50.45	74.00	-23.55	peak
4	5357.240	44.90	-5.29	39.61	54.00	-14.39	AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5133.250	65.05	-5.66	59.39	74.00	-14.61	peak
2	5133.250	50.88	-5.66	45.22	54.00	-8.78	AVG
3	5150.000	66.34	-5.77	60.57	74.00	-13.43	peak
4	5150.000	55.34	-5.77	49.57	54.00	-4.43	AVG

802.11ac80-L-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5134.100	61.18	-5.67	55.51	74.00	-18.49	peak
2	5134.100	47.33	-5.67	41.66	54.00	-12.34	AVG
3	5150.000	59.50	-5.77	53.73	74.00	-20.27	peak
4	5150.000	48.04	-5.77	42.27	54.00	-11.73	AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	56.36	-5.33	51.03	74.00	-22.97	peak
2	5350.000	47.19	-5.33	41.86	54.00	-12.14	AVG
3	5362.660	56.91	-5.27	51.64	74.00	-22.36	peak
4	5362.660	44.90	-5.27	39.63	54.00	-14.37	AVG

802.11ac80-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	56.36	-5.33	51.03	74.00	-22.97	peak
2	5350.000	43.86	-5.33	38.53	54.00	-15.47	AVG
3	5360.490	56.21	-5.28	50.93	74.00	-23.07	peak
4	5360.490	44.74	-5.28	39.46	54.00	-14.54	AVG


Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. All modes have been measured, only worst mode was reported.




U-NII-3 (5.725-5.850) GHz

802.11n20-L-H




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5642.750	56.27	-4.75	51.52	68.20	-16.68	peak
2	5695.625	59.71	-4.65	55.06	101.96	-46.90	peak
3	5725.000	69.10	-4.48	64.62	122.20	-57.58	peak
4	5850.000	55.45	-3.82	51.63	122.20	-70.57	peak
5	5876.000	56.09	-3.72	52.37	104.46	-52.09	peak
6	5926.250	54.76	-3.59	51.17	68.20	-17.03	peak

802.11n20-L-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5627.375	56.41	-4.79	51.62	68.20	-16.58	peak
2	5698.250	58.37	-4.64	53.73	103.91	-50.18	peak
3	5725.000	64.32	-4.48	59.84	122.20	-62.36	peak
4	5850.000	55.40	-3.82	51.58	122.20	-70.62	peak
5	5877.875	54.78	-3.71	51.07	103.07	-52.00	peak
6	5937.875	54.04	-3.57	50.47	68.20	-17.73	peak




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5646.500	54.80	-4.75	50.05	68.20	-18.15	peak
2	5695.625	56.04	-4.65	51.39	101.96	-50.57	peak
3	5725.000	55.56	-4.48	51.08	122.20	-71.12	peak
4	5850.000	65.82	-3.82	62.00	122.20	-60.20	peak
5	5877.125	59.36	-3.71	55.65	103.63	-47.98	peak
6	5926.625	55.45	-3.59	51.86	68.20	-16.34	peak

802.11n20-H-V




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5639.000	53.93	-4.76	49.17	68.20	-19.03	peak
2	5699.375	55.13	-4.64	50.49	104.74	-54.25	peak
3	5725.000	53.99	-4.48	49.51	122.20	-72.69	peak
4	5850.000	62.15	-3.82	58.33	122.20	-63.87	peak
5	5875.625	57.08	-3.72	53.36	104.74	-51.38	peak
6	5933.750	54.19	-3.58	50.61	68.20	-17.59	peak




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5639.375	56.20	-4.76	51.44	68.20	-16.76	peak
2	5696.375	59.88	-4.65	55.23	102.52	-47.29	peak
3	5725.000	69.14	-4.48	64.66	122.20	-57.54	peak
4	5850.000	54.67	-3.82	50.85	122.20	-71.35	peak
5	5893.250	54.22	-3.65	50.57	91.70	-41.13	peak
6	5924.000	53.80	-3.59	50.21	68.94	-18.73	peak

802.11ac40-L-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5644.250	54.95	-4.75	50.20	68.20	-18.00	peak
2	5697.875	59.63	-4.64	54.99	103.63	-48.64	peak
3	5725.000	65.08	-4.48	60.60	122.20	-61.60	peak
4	5850.000	54.56	-3.82	50.74	122.20	-71.46	peak
5	5876.375	53.71	-3.72	49.99	104.18	-54.19	peak
6	5924.375	53.25	-3.59	49.66	68.66	-19.00	peak




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5630.375	53.61	-4.78	48.83	68.20	-19.37	peak
2	5696.750	55.59	-4.65	50.94	102.80	-51.86	peak
3	5725.000	57.99	-4.48	53.51	122.20	-68.69	peak
4	5850.000	61.54	-3.82	57.72	122.20	-64.48	peak
5	5874.875	55.64	-3.72	51.92	105.23	-53.31	peak
6	5931.500	54.31	-3.58	50.73	68.20	-17.47	peak

802.11ac40-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5645.750	54.98	-4.75	50.23	68.20	-17.97	peak
2	5688.500	55.26	-4.66	50.60	96.69	-46.09	peak
3	5725.000	55.89	-4.48	51.41	122.20	-70.79	peak
4	5850.000	56.91	-3.82	53.09	122.20	-69.11	peak
5	5898.125	54.83	-3.62	51.21	88.09	-36.88	peak
6	5918.375	54.28	-3.60	50.68	73.10	-22.42	peak



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5640.125	57.16	-4.76	52.40	68.20	-15.80	peak
2	5699.000	67.58	-4.64	62.94	104.46	-41.52	peak
3	5725.000	71.37	-4.48	66.89	122.20	-55.31	peak
4	5850.000	69.70	-3.82	65.88	122.20	-56.32	peak
5	5874.875	64.34	-3.72	60.62	105.23	-44.61	peak
6	5931.125	55.77	-3.58	52.19	68.20	-16.01	peak

802.11ac80-V



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5649.125	54.91	-4.74	50.17	68.20	-18.03	peak
2	5690.000	60.24	-4.66	55.58	97.80	-42.22	peak
3	5725.000	63.81	-4.48	59.33	122.20	-62.87	peak
4	5850.000	60.87	-3.82	57.05	122.20	-65.15	peak
5	5875.250	57.62	-3.72	53.90	105.02	-51.12	peak
6	5923.250	53.81	-3.59	50.22	69.50	-19.28	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. All modes have been measurement, only worst mode was reported.



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3$ RBW.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.
- f) Please refer to ANSI C63.10-2020+Cor 1-2023 Section 12.6 Method SA-2.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

Note: The test data please reference to attachment “STS2604066W10_Appendix 5G RLAN”.

For U-NII 1:

1. $\text{Total PSD(dBm)} = \text{Conducted PSD (dBm)} + \text{Duty Factor(dB)}$

For U-NII 3:

1. $\text{Total PSD(dBm/500KHz)} = \text{Total PSD(dBm/510KHz)} + \text{RBW Factor} + \text{Duty Factor(dB)}$

2. $\text{RBW Factor} = 10 * \text{Log}(500/510)$



5. DUTY CYCLE

5.1 TEST STANDARD

Please refer to ANSI C63.10-2020+Cor 1-2023 Section 12.2


5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Zero
RB	set RBW to the largest available value
VB	$VBW \geq RBW$.
Detector	Peak
Trace	Clear Write
Sweep Time	Auto

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Note: The test data please reference to attachment "STS2604066W10_Appendix 5G RLAN".

6. BANDWIDTH MEASUREMENT

6.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth

6.1.1 TEST PROCEDURE

1. The testing follows ANSI C63.10-2020+Cor 1-2023 Section 12.5.
2. Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1% to 5%

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

Note: The test data please reference to attachment "STS2604066W10_Appendix 5G RLAN".



6.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

6.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.2.2 DEVIATION FROM STANDARD

No deviation.

6.2.3 TEST SETUP



6.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.2.5 TEST RESULTS

Note: The test data please reference to attachment “STS2604066W10_Appendix 5G RLAN”.

6.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth.

6.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3.2 DEVIATION FROM STANDARD

No deviation.

6.3.3 TEST SETUP



6.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.3.5 TEST RESULTS

Note: The test data please reference to attachment "STS2604066W10_Appendix 5G RLAN".



7. MAXIMUM OUTPUT POWER

7.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Max Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or 11 dBm + 10 log (26 dB emission bandwidth)	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5895	


7.2 TEST PROCEDURE

Please refer to ANSI C63.10-2020+Cor 1-2023 Section 12.4.2 Method SA-2

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

Note: 1.The test data please reference to attachment “STS2604066W10_Appendix 5G RLAN”.

2.Total Power(dBm) = Conducted Power (dBm) + Duty Factor(dB)



8. AUTOMATICALLY DISCONTINUE TRANSMISSION

8.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

8.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is FPC Antenna. It comply with the standard requirement.



10. FREQUENCY STABILITY


10.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

10.2 TEST PROCEDURE

1. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
2. Turn the EUT on and couple its output to spectrum analyzer.
3. Turn the EUT off and set the chamber to the highest temperature specified.
4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
6. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

10.3 TEST STEUP





10.4 TEST RESULT

5.2G RLAN

Channel 40(5200MHz)

Voltage vs. Frequency Stability

Voltage(V)	Measurement Frequency(MHz)
4.4275	5200.0027
3.85	5200.0026
3.2725	5200.0021
Max.Deviation(MHz)	0.0027
Frequency Range(Limit)	5150-5250

Rated working voltage: DC 3.85V

Temperature vs. Frequency Stability

Temperature(°C)	Measurement Frequency(MHz)
-30	5200.0031
-20	5200.0031
-10	5200.0025
0	5200.0029
10	5200.0021
20	5200.0023
30	5200.0030
40	5200.0024
50	5200.0030
Max.Deviation(MHz)	0.0031
Frequency Range(Limit)	5150-5250



5.8G RLAN

Channel 157(5785MHz)

Voltage vs. Frequency Stability

Voltage(V)	Measurement Frequency(MHz)
4.4275	5785.0035
3.85	5785.0027
3.2725	5785.0030
Max.Deviation(MHz)	0.0035
Frequency Range(Limit)	5725-5850

Rated working voltage: DC 3.85V

Temperature vs. Frequency Stability

Temperature(°C)	Measurement Frequency(MHz)
-30	5785.0037
-20	5785.0036
-10	5785.0035
0	5785.0028
10	5785.0033
20	5785.0031
30	5785.0034
40	5785.0028
50	5785.0031
Max.Deviation(MHz)	0.0037
Frequency Range(Limit)	5725-5850



APPENDIX - PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※END OF THE REPORT※※※※