

FCC TEST REPORT

Report No.....: AB26050211FW04

FCC ID.....: **2BU9W-B31-D**

Applicant.....: Shenzhen Gwell Times Technology Co., Ltd.

Address.....: 28th Floor, Building C, Minzhi Stock Commerce Center,North Station Community, Longhua District, Shenzhen, PR. China

Manufacturer.....: Shenzhen Gwell Times Technology Co., Ltd.

Address.....: 28th Floor, Building C, Minzhi Stock Commerce Center,North Station Community, Longhua District, Shenzhen, PR. China

Product Name.....: Smart WIFI Camera

Trade Mark.....: /

Test Model.....: B31-D

Additional Model(s).....: CA42, CA45, CA48, CA49, CA60, CA62, CA63, CA65, CA66, CA67, CA68, CA69, CA70
FCC Part 2 (Section 2.1091)

Standard.....: KDB 447498 D01
IEEE C95.1

Date of Receipt.....: 2026.05.15

Date of Test Date.....: 2026.05.15-2026.06.11

Date of Issue.....: 2026.06.11

Test Result.....: Pass

Compiled by: Huaijie Li
(Printed Name + Signature)



Supervised by: David Huang
(Printed Name + Signature)



Approved by: Jay Liu
(Printed Name + Signature)



Testing Laboratory Name.....: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address.....: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

FCC TEST REPORT

EUT.....	: Smart WIFI Camera
Test Model.....	: B31-D
Applicant.....	: Shenzhen Gwell Times Technology Co., Ltd.
Address.....	: 28th Floor, Building C, Minzhi Stock Commerce Center,North Station Community, Longhua District, Shenzhen, PR. China
Manufacturer.....	: Shenzhen Gwell Times Technology Co., Ltd.
Address.....	: 28th Floor, Building C, Minzhi Stock Commerce Center,North Station Community, Longhua District, Shenzhen, PR. China

Test Result	Positive
-------------	----------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

REPORT VERSION

Version No.	Issue Date	Description
01	2026.06.11	Initial Issue

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. GENERAL DESCRIPTION OF EUT	5
1.2. DESCRIPTION OF TEST FACILITY	6
2. RF EXPOSURE EVALUATION	8
2.1 LIMIT	8
2.2 EVALUATION RESULT	9

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name	Smart WIFI Camera
Trade Mark	/
Model/Type Reference	B31-D
Listed Model(s)	CA42, CA45, CA48, CA49, CA60, CA62, CA63, CA65, CA66, CA67, CA68, CA69, CA70
Model Difference	All models are the same circuit and RF module, except the model name
Hardware Version	TN-PTZ-fh8626v200-SC3336-V1.6
Software Version	/
Power Supply	Input: 100-240V, 50/60Hz, 0.3A Output:5V, 1.5A
Battery	/
EUT Supports Function: (Provided by the customer)	2.4GHz ISM Bands
Test Sample(s) Number:	AB26050211-01 (Engineer Sample) AB26050211-02 (Normal Sample)
Radio Specification Subject to this Report	
Bluetooth Version:	Bluetooth LE
Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Channel Number(s):	40
Antenna Type:	Internal Antenna
Antenna Gain:	2.41dBi
Radio Specification Subject to this Report	
Radio Specification:	IEEE 802.11b/g/n
Frequency Range:	2412MHz~2462MHz for IEEE 802.11b/g/n(HT20)/ax(HE20) 2422MHz~2452MHz for IEEE 802.11n(HT40)/ax(HE40)
Modulation Type:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n(HT20)/ax(HE20): OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40/ax(HE40): OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Channel Number(s):	11 Channels for IEEE 802.11b/g/n(HT20)/ax(HE20) 7 Channels for IEEE 802.11n(HT40)/ax(HE40)
Antenna Type:	Internal Antenna
Antenna Gain:	2.41dBi
Radio Specification Subject to this Report	
Radio Specification:	IEEE 802.11a/n/ax
Frequency Range:	5180MHz~5240MHz for U-NII Band1

	5260MHz~5320MHz for U-NII Band2A 5500MHz~5700MHz for U-NII Band2C 5745MHz~5825MHz for U-NII Band3	
Modulation Type:	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ax: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)	
Channel Spacing:	IEEE 802.11a/n(HT20)/ax(HE20): 20MHz IEEE 802.11n(HT40)/ax(HE40): 40MHz	
Channel Number(s):	U-NII Band1: 4 for IEEE 802.11a/n(HT20)/ax(HE20) 2 for IEEE 802.11n(HT40)/ax(HE40) U-NII Band2A: 4 for IEEE 802.11a/n(HT20)/ax(HE20) 2 for IEEE 802.11n(HT40)/ax(HE40) U-NII Band2C: 11 for IEEE 802.11a/n(HT20)/ax(HE20) 5 for IEEE 802.11n(HT40)/ax(HE40) U-NII Band3: 5 for IEEE 802.11a/n(HT20)/ax(HE20) 2 for IEEE 802.11n(HT40)/ax(HE40)	
Antenna Type:	Internal Antenna	
Antenna Gain:	U-NII Band1:	3.5dBi
	U-NII Band2A:	3.92dBi
	U-NII Band2C:	4.52dBi
	U-NII Band3:	4.02dBi
TPC Function:	Not Support	
DFS Function:	Slave without radar detection	

1.2. DESCRIPTION OF TEST FACILITY

Test Lab: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +86 755 85250797

E-mail: aibo@aibonorm.com

Website: www.aibonorm.com

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Certificate No.: 7514.01

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the

identified field of testing.

FCC Accredited Lab.

Designation Number: CN1411

Test Firm Registration Number: 567066

ISED Wireless Device Testing Laboratories

Company Number: 33924

CAB identifier: CN0185

2. RF EXPOSURE EVALUATION

2.1 Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale, $\pi = 3.1416$;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.2 Evaluation Result

Mode	Total Power (dBm)	Antenna Gain	Max.EIRP (dBm)	Max.EIRP (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
BLE	2.03	2.41	4.44	2.780	0.000553	1.0	PASS
2.4G WiFi	5.76	2.41	8.17	6.561	0.001305	1.0	PASS
5.1G WiFi	5.32	3.5	8.82	7.621	0.001516	1.0	PASS
5.2G WiFi	5.65	3.92	9.57	9.057	0.001802	1.0	PASS
5.6G WiFi	5.75	4.52	10.27	10.641	0.002117	1.0	PASS
5.8G WiFi	5.81	4.02	9.83	9.616	0.001913	1.0	PASS

Results for transmit simultaneously

No.	Configurations	Maximum MPE Value mW/cm ²		Transmit simultaneously	Limits
1	BLE+ 2.4GHz Wi-Fi	0.000553	0.001305	0.001858	1
2	BLE+ 5GHz Wi-Fi	0.000553	0.002117	0.00267	1
3	2.4GHz Wi-Fi + 5GHz Wi-Fi	0.001305	0.002117	0.003422	1

At the transmit simultaneously calculation method is as follows:

Transmit simultaneously MPE = $\sum$ of MPE ratios²

MPE ratios = Field strengths or power density / MPE limit at the test frequency

So a SAR test is not required

*****THE END*****