

TEST REPORT

Applicant: Shenzhen Ziwu Chuangxin Technology Co., Ltd.
Address: Room 225, Office Area, Floor 2, Xing He Ling
Chuang Tianxia Phase II, Nankeng Community,
Bantian Street, Longgang District, Shenzhen
Guangdong, P.R. China
Equipment Type: RESO PILOT PRO
Model Name: KR700 (refer to section 2.3)
Brand Name: Reso
FCC ID: 2BUIA-KR700
Test Standard: FCC 47 CFR Part 2.1093
(refer to section 3.1)
Maximum SAR: Near Head (1 g): 0.66 W/kg
Limbs (10 g): 1.53 W/kg
Sample Arrival Date: May 28, 2026
Test Date: Jun. 08, 2026 - Jun. 10, 2026
Date of Issue: Jul 14, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Guo Guangwei**Checked by:** Xu Rui**Approved by:** Liao Jianming
(Technical Director)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Jul. 02, 2026</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Jul. 14, 2026</u>	<u>Updated Chapter 5.2</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition.....	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Ancillary Equipment.....	5
2.5	Technical Information	6
2.6	EUT Antenna Location Sketch.....	7
3	SUMMARY OF TEST RESULT	9
3.1	Test Standards	9
3.2	Device Category and SAR Limit	10
3.3	Test Result Summary	11
3.4	Test Uncertainty	12
4	MEASUREMENT SYSTEM	13
4.1	Specific Absorption Rate (SAR) Definition	13
4.2	DASY SAR System	14
5	SYSTEM VERIFICATION	21
5.1	Purpose of System Check	21
5.2	System Check Setup	21
6	TEST POSITION CONFIGURATIONS	23
6.1	Body-worn Position Conditions	23

6.2	Limb-worn Position Conditions	23
6.3	Product Specific 10g Exposure Consideration	23
7	MEASUREMENT PROCEDURE	24
7.1	Measurement Process Diagram	24
7.2	SAR Scan General Requirement	25
7.3	Measurement Procedure	26
7.4	Area & Zoom Scan Procedure	26
8	CONDUCTED RF OUTPUT POWER	27
9	TEST RESULT	28
9.1	2.4GHz ISM Band.....	29
9.2	Bluetooth	30
9.3	WIFI 2.4GHz.....	31
9.4	WIFI 5.2GHz.....	32
9.5	WIFI 5.8GHz.....	33
10	SAR Measurement Variability	34
11	SIMULTANEOUS TRANSMISSION.....	35
11.1	Simultaneous Transmission Mode Considerations	35
11.2	Near Head Simultaneous Transmission SAR Evaluation	36
11.3	Limbs Simultaneous Transmission SAR Evaluation.....	36
12	TEST EQUIPMENTS LIST	37
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	38
ANNEX B	SYSTEM CHECK RESULT	39
ANNEX C	TEST DATA.....	40
ANNEX D	EUT EXTERNAL PHOTOS.....	40
ANNEX E	SAR TEST SETUP PHOTOS	40
ANNEX F	CALIBRATION REPORT	40
ANNEX G	TUNE-UP PROCEDURE.....	40

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	601, Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong
	☒ 1/F., Building B, Ganghongji High-Tech Intelligent Industrial Park, No.1008, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Ziwu Chuangxin Technology Co., Ltd.
Address	Room 225, Office Area, Floor 2, Xing He Ling Chuang Tianxia Phase II, Nankeng Community, Bantian Street, Longgang District, Shenzhen Guangdong, P.R. China

2.2 Manufacturer Information

Manufacturer	Shenzhen Ziwu Chuangxin Technology Co., Ltd.
Address	Room 225, Office Area, Floor 2, Xing He Ling Chuang Tianxia Phase II, Nankeng Community, Bantian Street, Longgang District, Shenzhen Guangdong, P.R. China

2.3 General Description for Equipment under Test (EUT)

EUT Name	RESO PILOT PRO
Model Name Under Test	KR700
Series Model Name	KR701 (Product Name: RESO SYNC PRO)
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in product name and model name. All other functional, electrical, and environmental characteristics are identical between the two bases. The only differences are the mechanical interface dimensions and alignment features required to physically mate with the two distinct host bottom case designs. (this information provided by the applicant)
Hardware Version	V4
Software Version	0.2.4.84
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Note: Not Applicable.

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g and 802.11n 5.8G SRD, 2.4G ISM Band, GPS, GLONASS, Galileo, BDS
-----------------------------------	---


The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WIFI, Bluetooth, 2.4G ISM Band	
Frequency Range	802.11b/g	2400 ~ 2483.5 MHz
	802.11n(HT20/HT40)	2400 ~ 2483.5 MHz
	802.11a	5150 ~ 5250 MHz
		5725 ~ 5850 MHz
	802.11n(HT20/HT40)	5150 ~ 5250 MHz
		5725 ~ 5850 MHz
	Bluetooth	2400 ~ 2483.5 MHz
	2.4G ISM Band	2400 ~ 2483.5 MHz
Antenna Type	WIFI	PCB Antenna
	Bluetooth	PCB Antenna
	2.4G ISM Band	FPC Antenna
Exposure Category	General Population/Uncontrolled exposure	
EUT Type	Portable Device	

QCC3024 Module

Operating Mode	Bluetooth	
Frequency Range	Bluetooth	2400 ~ 2483.5 MHz
Antenna Type	Bluetooth	FPC Antenna
Exposure Category	General Population/Uncontrolled exposure	
EUT Type	Portable Device	

2.6 EUT Antenna Location Sketch



Antenna	Support Bands
ANT1	Bluetooth, 2.4G WIFI, 5G WIFI
ANT0	2.4G ISM Band
ANT2	Bluetooth



Note: The prototype is actually used at a distance of 15mm from the human head.

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI/IEEE Std. C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	KDB 865664 D02 v01r02	RF Exposure Reporting
7	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR

Equipment Class	Band	Maximum Scaled SAR (W/kg)		Maximum Report SAR (W/kg)	
		Near Head	Limbs	Near Head	Limbs
		(15mm)	(0mm)	(15mm)	(0mm)
		1g SAR	10g SAR	1g SAR	10g SAR
DTS	2.4G ISM Band	0.09	0.11	0.66	1.53
	2.4G WIFI	0.05	0.10		
NII	5.2G WIFI	0.33	0.47		
	5.8G WIFI	0.66	1.53		
DSS	Bluetooth	0.11	0.47		
Limit (W/kg)		1.60	4.00	1.60	4.00
Verdict		Pass			

3.3.2 Highest Simultaneous Transmission SAR Values

Equipment Class	Maximum Simultaneous Transmission SAR (W/kg)	
	Near Head	Limbs
	(15mm)	(0mm)
	1g SAR	10g SAR
DTS	0.81	2.05
NII	0.81	2.05
DSS	0.81	2.05
Limit (W/Kg)	1.60	4.00
Verdict	Pass	

Note: The simultaneous transmission SAR detail please refer to section 11.

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 0.66 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

The maximum 10 g SAR for the EUT in this report is 1.53 W/kg, which is lower than 3.75 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY measurement server.
6. The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycoether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with IEC/IEEE 62209-1528 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC/IEEE 62209-1528 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics


The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω m
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left hand
- Right hand
- Flat phantom



4.2.6 Device Holder


The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:





6 TEST POSITION CONFIGURATIONS

6.1 Body-worn Position Conditions

Devices that support transmission while used with body-worn accessories must be tested for SAR compliance related to each body-worn condition of use. SAR evaluation is required for body-worn accessories supplied with the device they are attached to.

The general informing principle is that the selected test configurations must conservatively capture the various body-worn accessory use conditions expected by users. For instance, devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, must be tested for SAR compliance using a conservative minimum test separation distance not to exceed 5 mm for all use conditions required by the device.

6.2 Limb-worn Position Conditions

Devices that are designed or intended for use on extremities (i.e., hands, wrists, feet and ankles), or mainly operated in extremity-only exposure conditions, may require extremity SAR evaluation.


6.3 Product Specific 10g Exposure Consideration

According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

Please refer the document “Ti-EE26040641-AP.pdf”.

9 TEST RESULT

1. The reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WIFI signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".
 - c. For WIFI/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements.
3. Per KDB 447498 D04, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
4. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg

Note: Refer to ANNEX C for the detailed test data for each test configuration.

9.1 2.4GHz ISM Band

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No
Near Head														
250Kbps	ANT0	Front Side	15	High	2475	-0.13	0.041	10.34	10.50	1.038	100.00	1.000	0.043	/
		Back Side	15	High	2475	-0.01	0.052	10.34	10.50	1.038	100.00	1.000	0.054	/
		Left Edge	15	High	2475	-0.15	0.031	10.34	10.50	1.038	100.00	1.000	0.032	/
		Right Edge	15	High	2475	-0.01	0.090	10.34	10.50	1.038	100.00	1.000	0.093	1#
		Top Edge	15	High	2475	0.08	0.013	10.34	10.50	1.038	100.00	1.000	0.013	/
		Bottom Edge	15	High	2475	-0.15	0.008	10.34	10.50	1.038	100.00	1.000	0.008	/
Note: Because the prototype is actually used at a distance of 15mm from the human head, 15mm was used for testing in the Near Head state laboratory														

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No
Limbs														
250Kbps	ANT0	Front Side	0	High	2475	-0.18	0.046	10.34	10.50	1.038	100.00	1.000	0.048	/
		Back Side	0	High	2475	0.18	0.047	10.34	10.50	1.038	100.00	1.000	0.049	/
		Left Edge	0	High	2475	-0.03	0.023	10.34	10.50	1.038	100.00	1.000	0.024	/
		Right Edge	0	High	2475	0.00	0.105	10.34	10.50	1.038	100.00	1.000	0.109	6#
		Top Edge	0	High	2475	0.08	0.034	10.34	10.50	1.038	100.00	1.000	0.035	/
		Bottom Edge	0	High	2475	-0.16	0.015	10.34	10.50	1.038	100.00	1.000	0.016	/

9.2 Bluetooth

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No
Near Head														
DH5	ANT1	Front Side	15	39	2441	0.05	0.031	6.64	7.50	1.219	57.55	1.738	0.066	/
		Back Side	15	39	2441	-0.18	0.023	6.64	7.50	1.219	57.55	1.738	0.049	/
		Left Edge	15	39	2441	-0.06	0.013	6.64	7.50	1.219	57.55	1.738	0.028	/
		Right Edge	15	39	2441	0.01	0.009	6.64	7.50	1.219	57.55	1.738	0.019	/
		Top Edge	15	39	2441	0.13	0.021	6.64	7.50	1.219	57.55	1.738	0.044	/
		Bottom Edge	15	39	2441	-0.08	0.014	6.64	7.50	1.219	57.55	1.738	0.030	/
	ANT2	Front Side	15	39	2441	0.09	0.065	6.44	7.50	1.276	76.88	1.301	0.108	2#
		Back Side	15	39	2441	-0.19	0.056	6.44	7.50	1.276	76.88	1.301	0.093	/
		Left Edge	15	39	2441	-0.08	0.013	6.44	7.50	1.276	76.88	1.301	0.022	/
		Right Edge	15	39	2441	-0.07	0.021	6.44	7.50	1.276	76.88	1.301	0.035	/
		Top Edge	15	39	2441	-0.01	0.011	6.44	7.50	1.276	76.88	1.301	0.018	/
		Bottom Edge	15	39	2441	0.02	0.026	6.44	7.50	1.276	76.88	1.301	0.043	/
Note: Because the prototype is actually used at a distance of 15mm from the human head, 15mm was used for testing in the Near Head state laboratory														

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No
Limbs														
DH5	ANT1	Front Side	0	39	2441	0.08	0.130	6.64	7.50	1.219	57.55	1.738	0.275	/
		Back Side	0	39	2441	0.10	0.103	6.64	7.50	1.219	57.55	1.738	0.218	/
		Left Edge	0	39	2441	0.00	0.045	6.64	7.50	1.219	57.55	1.738	0.095	/
		Right Edge	0	39	2441	0.17	0.052	6.64	7.50	1.219	57.55	1.738	0.110	/
		Top Edge	0	39	2441	-0.01	0.062	6.64	7.50	1.219	57.55	1.738	0.131	/
		Bottom Edge	0	39	2441	-0.03	0.035	6.64	7.50	1.219	57.55	1.738	0.074	/
	ANT2	Front Side	0	39	2441	0.04	0.282	6.44	7.50	1.276	76.88	1.301	0.468	7#
		Back Side	0	39	2441	-0.07	0.211	6.44	7.50	1.276	76.88	1.301	0.350	/
		Left Edge	0	39	2441	0.16	0.094	6.44	7.50	1.276	76.88	1.301	0.156	/
		Right Edge	0	39	2441	0.07	0.103	6.44	7.50	1.276	76.88	1.301	0.171	/
		Top Edge	0	39	2441	0.08	0.065	6.44	7.50	1.276	76.88	1.301	0.108	/
		Bottom Edge	0	39	2441	0.04	0.131	6.44	7.50	1.276	76.88	1.301	0.217	/

9.3 WIFI 2.4GHz

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No
Near Head														
11b	ANT1	Front Side	15	11	2462	-0.05	0.043	9.70	10.00	1.072	100.00	1.000	0.046	3#
		Back Side	15	11	2462	-0.12	0.023	9.70	10.00	1.072	100.00	1.000	0.025	/
		Left Edge	15	11	2462	0.13	0.010	9.70	10.00	1.072	100.00	1.000	0.011	/
		Right Edge	15	11	2462	-0.08	0.013	9.70	10.00	1.072	100.00	1.000	0.014	/
		Top Edge	15	11	2462	0.02	0.008	9.70	10.00	1.072	100.00	1.000	0.009	/
		Bottom Edge	15	11	2462	-0.13	0.015	9.70	10.00	1.072	100.00	1.000	0.016	/
Note: Because the prototype is actually used at a distance of 15mm from the human head, 15mm was used for testing in the Near Head state laboratory														

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No
Limbs														
11b	ANT1	Front Side	0	11	2462	-0.17	0.093	9.70	10.00	1.072	100.00	1.000	0.100	8#
		Back Side	0	11	2462	-0.09	0.043	9.70	10.00	1.072	100.00	1.000	0.046	/
		Left Edge	0	11	2462	0.12	0.023	9.70	10.00	1.072	100.00	1.000	0.025	/
		Right Edge	0	11	2462	0.19	0.030	9.70	10.00	1.072	100.00	1.000	0.032	/
		Top Edge	0	11	2462	0.00	0.015	9.70	10.00	1.072	100.00	1.000	0.016	/
		Bottom Edge	0	11	2462	0.09	0.041	9.70	10.00	1.072	100.00	1.000	0.044	/

9.4 WIFI 5.2GHz

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No
Near Head														
11a	ANT1	Front Side	15	44	5220	-0.19	0.220	9.87	10.00	1.030	100.00	1.000	0.227	/
		Back Side	15	44	5220	-0.16	0.120	9.87	10.00	1.030	100.00	1.000	0.124	/
		Left Edge	15	44	5220	-0.12	0.318	9.87	10.00	1.030	100.00	1.000	0.328	4#
		Right Edge	15	44	5220	0.16	0.095	9.87	10.00	1.030	100.00	1.000	0.098	/
		Top Edge	15	44	5220	-0.07	0.023	9.87	10.00	1.030	100.00	1.000	0.024	/
		Bottom Edge	15	44	5220	0.03	0.185	9.87	10.00	1.030	100.00	1.000	0.191	/
Note: Because the prototype is actually used at a distance of 15mm from the human head, 15mm was used for testing in the Near Head state laboratory														

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No
Limbs														
11a	ANT1	Front Side	0	44	5220	0.06	0.410	9.87	10.00	1.030	100.00	1.000	0.422	/
		Back Side	0	44	5220	-0.09	0.380	9.87	10.00	1.030	100.00	1.000	0.391	/
		Left Edge	0	44	5220	-0.08	0.455	9.87	10.00	1.030	100.00	1.000	0.469	9#
		Right Edge	0	44	5220	-0.19	0.174	9.87	10.00	1.030	100.00	1.000	0.179	/
		Top Edge	0	44	5220	0.08	0.094	9.87	10.00	1.030	100.00	1.000	0.097	/
		Bottom Edge	0	44	5220	-0.02	0.221	9.87	10.00	1.030	100.00	1.000	0.228	/

9.5 WIFI 5.8GHz

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No
Near Head														
11a	ANT1	Front Side	15	157	5785	0.01	0.559	9.79	10.50	1.178	100.00	1.000	0.659	5#
		Back Side	15	157	5785	-0.11	0.376	9.79	10.50	1.178	100.00	1.000	0.443	/
		Left Edge	15	157	5785	0.01	0.481	9.79	10.50	1.178	100.00	1.000	0.567	/
		Right Edge	15	157	5785	0.08	0.112	9.79	10.50	1.178	100.00	1.000	0.132	/
		Top Edge	15	157	5785	0.18	0.097	9.79	10.50	1.178	100.00	1.000	0.114	/
		Bottom Edge	15	157	5785	-0.01	0.331	9.79	10.50	1.178	100.00	1.000	0.390	/
Note: Because the prototype is actually used at a distance of 15mm from the human head, 15mm was used for testing in the Near Head state laboratory														

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No
Limbs														
11a	ANT1	Front Side	0	157	5785	0.04	1.300	9.79	10.50	1.178	100.00	1.000	1.531	10#
		Back Side	0	157	5785	0.02	1.120	9.79	10.50	1.178	100.00	1.000	1.319	/
		Left Edge	0	157	5785	0.00	1.230	9.79	10.50	1.178	100.00	1.000	1.449	/
		Right Edge	0	157	5785	0.15	0.680	9.79	10.50	1.178	100.00	1.000	0.801	/
		Top Edge	0	157	5785	-0.15	0.260	9.79	10.50	1.178	100.00	1.000	0.306	/
		Bottom Edge	0	157	5785	-0.14	0.710	9.79	10.50	1.178	100.00	1.000	0.836	/

10 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.66 < 0.80$ W/kg, repeated measurement is not required.

11 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According KDB 447498 D04, simultaneous transmission:

- a) $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$ (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.
SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

11.1 Simultaneous Transmission Mode Considerations

No.	Simultaneous Tx Combination	Near Head	Limbs
1	2.4G ISM Band + BT(ANT2) + 2.4G WIFI(ANT1)	Yes	Yes
2	2.4G ISM Band + BT(ANT2) + 5G WIFI(ANT1)	Yes	Yes
3	2.4G ISM Band + BT(ANT1) + BT(ANT2)	Yes	Yes

Note:

1. WiFi and Bluetooth share the same antenna, and can't transmit simultaneously.
2. The maximum SAR summation is calculated based on the same configuration and test position.
3. The simultaneous transmission combinations of the more antennas contain combinations of less antennas, so only the worst simultaneous transmission combinations is shown in this report.

11.2 Near Head Simultaneous Transmission SAR Evaluation

Position	Stand alone SAR					SUM SAR		
	1	2	3	4	5			
	2.4G ISM Band (ANT 0)	Bluetooth (ANT 1)	Bluetooth (ANT 2)	WLAN 2.4GHz (ANT 1)	WLAN 5GHz MAX. (ANT 1)	Sum SAR (1+3+4)	Sum SAR (1+3+5)	Sum SAR (1+2+3)
Front Side 15mm	0.043	0.066	0.108	0.046	0.659	0.197	0.810	0.217
Back Side 15mm	0.054	0.049	0.093	0.025	0.443	0.172	0.590	0.196
Left Edge 15mm	0.032	0.023	0.013	0.011	0.567	0.056	0.612	0.068
Right Edge 15mm	0.093	0.017	0.032	0.014	0.132	0.139	0.257	0.142
Top Edge 15mm	0.008	0.023	0.012	0.009	0.114	0.029	0.134	0.043
Bottom Edge 15mm	0.013	0.011	0.040	0.016	0.390	0.069	0.443	0.064

Note:

- 1: The highest Summed 1g SAR is 0.810 W/Kg < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.
- 2: The simultaneous transmission combinations of the more ANT's contain combinations of less ANT's, so only the worst simultaneous transmission combinations is shown in this report.

11.3 Limbs Simultaneous Transmission SAR Evaluation

Position	Stand alone SAR					SUM SAR		
	1	2	3	4	5			
	2.4G ISM Band (ANT 0)	Bluetooth (ANT 1)	Bluetooth (ANT 2)	WLAN 2.4GHz (ANT 1)	WLAN 5GHz MAX. (ANT 1)	Sum SAR (1+3+4)	Sum SAR (1+3+5)	Sum SAR (1+2+3)
Front Side 0mm	0.048	0.275	0.468	0.100	1.531	0.616	2.047	0.791
Back Side 0mm	0.049	0.218	0.350	0.046	1.319	0.445	1.718	0.617
Left Edge 0mm	0.024	0.095	0.156	0.025	1.449	0.205	1.629	0.275
Right Edge 0mm	0.109	0.110	0.171	0.032	0.801	0.312	1.081	0.390
Top Edge 0mm	0.035	0.131	0.108	0.016	0.306	0.159	0.449	0.274
Bottom Edge 0mm	0.016	0.074	0.217	0.044	0.836	0.277	1.069	0.307

Note:

- 1: The highest Summed 10g SAR is 2.047 W/Kg < 4.0 W/kg, so Simultaneous Transmission SAR test is not required.
- 2: The simultaneous transmission combinations of the more ANT's contain combinations of less ANT's, so only the worst simultaneous transmission combinations is shown in this report.

12 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY8	16.2.2.1588	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2024/05/07	2027/05/06
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2024/05/09	2027/05/08
Data Acquisition Electronics	Speag	DAE4	SN: 1711	2025/11/11	2026/11/10
E-Field Probe	Speag	EX3DV4	SN: 7510	2025/11/11	2026/11/10
Signal Generator	Keysight	N5173B	MY62150163	2025/07/15	2026/07/14
Power Meter	R&S	NRVD-B2	835843/014	2025/07/15	2026/07/14
Power Sensor	R&S	NRV-Z4	100381	2025/07/15	2026/07/14
Power Sensor	R&S	NRV-Z2	100211	2025/07/15	2026/07/14
Network Analyzer	Agilent	E5071C	MY46103472	2025/08/13	2026/08/12
Thermometer	Elitech	RC-4HC	EF7239002655	2025/10/29	2026/10/28
Thermometer	Elitech	RC-4HC	EF7216002974	2025/10/30	2026/10/29
Power Amplifier	Mini-Circuits	ZVA-183W-S+	932502132	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	SAM	SN: 2090	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5 Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2026.06.08	Head	2450	21.7	1.78	39.60	1.80	39.20	-1.11	1.02
2026.06.10	Head	2450	21.8	1.79	39.53	1.80	39.20	-0.56	0.84
2026.06.09	Head	5250	21.8	4.82	35.26	4.71	35.93	2.34	-1.86
2026.06.09	Head	5750	21.8	5.17	35.72	5.22	35.36	-0.96	1.02
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %.

Head liquid 1g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2026.06.08	Head	2450	100	5.340	53.40	52.60	1.52
2026.06.10	Head	2450	100	5.330	53.30	52.60	1.33
2026.06.09	Head	5250	100	7.640	76.40	77.70	-1.67
2026.06.09	Head	5750	100	7.740	77.40	77.60	-0.26

Note: The tolerance limit of System validation $\pm 10\%$.

Head liquid 10g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2026.06.08	Head	2450	100	2.510	25.10	24.70	1.62
2026.06.10	Head	2450	100	2.550	25.50	24.70	3.24
2026.06.09	Head	5250	100	2.130	21.30	22.00	-3.18
2026.06.09	Head	5750	100	2.050	20.50	21.90	-6.39

Note: The tolerance limit of System validation $\pm 10\%$.

Please refer the document "Ti-EE26040641-ASC.pdf".

ANNEX C TEST DATA

Please refer the document “Ti-EE26040641-ATD.pdf”.

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “Ti-EE26040641-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “Ti-EE26040641-AS.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “Ti-EE26040641-AC.pdf”.

ANNEX G TUNE-UP PROCEDURE

Please refer the document “Ti-EE26040641-AT.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--