

TEST REPORT

Applicant: Shenzhen Ziwu Chuangxin Technology Co., Ltd.
Address: Room 225, Office Area, Floor 2, Xing He Ling
Chuang Tianxia Phase II, Nankeng Community,
Bantian Street, Longgang District, Shenzhen
Guangdong, P.R. China
Equipment Type: RESO PILOT PRO
Model Name: KR700 (refer to section 2.3)
Brand Name: Reso
FCC ID: 2BUIA-KR700
Test Standard: 47 CFR Part 15 Subpart C
(refer to section 3.1)
Sample Arrival Date: Apr. 24, 2026
Test Date: Apr. 29, 2026 - May 19, 2026
Date of Issue: Jul 02, 2026

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Li Renyu**Checked by:** Li Ganming**Approved by:** Tolan Tu

(Testing Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jul. 02, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards	7
3.2	Verdict	7
4	GENERAL TEST CONFIGURATIONS	8
4.1	Test Environments	8
4.2	Test Equipment List	8
4.3	Test Software List	8
4.4	Measurement Uncertainty	9
4.5	Description of Test Setup	9
4.6	Measurement Results Explanation Example	12
5	TEST ITEMS	13
5.1	Antenna Requirements	13
5.2	Output Power and E.I.R.P.	14
5.3	Occupied Bandwidth	16
5.4	Conducted Spurious Emission	17
5.5	Band Edge (Authorized-band band-edge)	19

5.6	Conducted Emission.....	21
5.7	Radiated Spurious Emission.....	22
5.8	Band Edge (Restricted-band band-edge).....	27
5.9	Power Spectral density (PSD)	28
ANNEX A	TEST RESULT	29
A.1	Output Power	29
A.2	Occupied Bandwidth.....	30
A.3	Conducted Spurious Emissions	34
A.4	Band Edge (Authorized-band band-edge).....	39
A.5	Conducted Emissions	42
A.6	Radiated Spurious Emission.....	44
A.7	Band Edge (Restricted-band band-edge).....	53
A.8	Power Spectral Density (PSD).....	56
ANNEX B	TEST SETUP PHOTOS	59
ANNEX C	EUT EXTERNAL PHOTOS.....	59
ANNEX D	EUT INTERNAL PHOTOS.....	59

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	601, Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Building 2, Intelligent Connected Vehicle Industrial Park, No.55, Xiangshan Road, Luotian Community, Yanluo Sub-district, Bao'an District, Shenzhen, Guangdong
	☒ 1/F., Building B, Ganghongji High-Tech Intelligent Industrial Park, No.1008, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Ziwu Chuangxin Technology Co., Ltd.
Address	Room 225, Office Area, Floor 2, Xing He Ling Chuang Tianxia Phase II, Nankeng Community, Bantian Street, Longgang District, Shenzhen Guangdong, P.R. China

2.2 Manufacturer Information

Manufacturer	Shenzhen Ziwu Chuangxin Technology Co., Ltd.
Address	Room 225, Office Area, Floor 2, Xing He Ling Chuang Tianxia Phase II, Nankeng Community, Bantian Street, Longgang District, Shenzhen Guangdong, P.R. China

2.3 General Description for Equipment under Test (EUT)

EUT Name	RESO PILOT PRO
Model Name Under Test	KR700
Series Model Name	KR701 (Product Name: RESO SYNC PRO)
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in product name and model name. All other functional, electrical, and environmental characteristics are identical between the two bases. The only differences are the mechanical interface dimensions and alignment features required to physically mate with the two distinct host bottom case designs. (this information provided by the applicant)
Hardware Version	V4
Software Version	0.2.4.84
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g and 802.11n 2.4G ISM Band, GPS, GLONASS, Galileo, BDS
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	O-QPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	250 Kbps, 1 Mbps
Frequency Range	The frequency block is 2400 MHz to 2483.5 MHz.
Number of Channel	15
Tested Channel	1 (2405 MHz), 8 (2440 MHz), 15 (2475 MHz)
Antenna Type	FPC Antenna
Antenna Gain	1.93 dBi
Adaptive or Non-Adaptive	Adaptive
The Max RF Output power	10.38 dBm
Antenna System (MIMO Smart Antenna)	N/A

All Channel List:

Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)	Channel Number	Freq. (MHz)
1	2405	6	2430	11	2455
2	2410	7	2435	12	2460
3	2415	8	2440	13	2465
4	2420	9	2445	14	2470
5	2425	10	2450	15	2475

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2020	American National Standard for Procedures for Compliance Testing of Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	--	Pass ^{Note}
2	Output Power	15.247(b)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	Low/Middle/High	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Low/Middle/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	Low/Middle/High	ANNEX A.8	Pass

Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	41% to 69%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+18.3℃ to +26.9℃
Working Voltage of the EUT	NV (Normal Voltage)	3.85 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420186	2025.05.21	2026.05.20
Power meter	R&S	NRP8S	101498	2025.07.07	2026.07.06
Spectrum Analyzer	KEYSIGHT	N9020A	MY56060127	2025.12.25	2026.12.24
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Test Antenna-Bi-Log	Schwarzbeck	VULB 9163	01414	2023.11.03	2026.11.02
Test Antenna-Horn	Schwarzbeck	BBHA 9120D	02459	2023.10.26	2026.10.25
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Anechoic Chamber	YIHENG	C8-966	N/A	2024.05.12	2027.05.11
EMI Receiver	Keysight	N9038A	MY55330121	2025.12.26	2026.12.25
Filtering unit	balun	SU319F	LW-SZ19D0001F01	N/A	N/A
Switching unit	BALUN	SU319	LW-SZ19D0001S01	N/A	N/A
EMI Receiver	keysight	N9038B	MY61380132	2025.12.26	2026.12.25
LISN	SCHWARZBECK MESS- ELEKTRONIK	NSLK8127	01009	2025.07.15	2026.07.14
Shielded Enclosure	YiHeng Electronic Co., Ltd	4.3m*2.9m*2.4 m	235	2024.11.05	2027.11.04

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V19.8.28.435	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%

4.5 Description of Test Setup

4.5.1. For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2. For AC Power Supply Port Test




(Diagram 2)

4.5.3. For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4. For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5. For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1. Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2. Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3. Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power and E.I.R.P

5.2.1. Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2. Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3. Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the $RBW \geq DTS$ bandwidth.

Set $VBW \geq 3 \times RBW$.

Set span $\geq 3 \times RBW$

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4. Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1. Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2. Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3. Test Procedure

Use the following spectrum analyzer settings:

Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4. Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1. Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2. Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3. Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4. Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1. Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2. Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3. Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4. Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1. Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2. Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3. Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4. Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1. Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V/m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V/m}@3\text{m}$ (PK).

5.7.2. Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3. Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements

for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Ta1.
- b) VBW $\geq 3 \times$ RBW.

- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Ta1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
- 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the

Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4. Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1. Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2. Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3. Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4. Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1. Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2. Test Setup

See section 4.5.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3. Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4. Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	O-QPSK (250Kbps)		dBm	mW	
	dBm	mW			
Low Channel	8.46	7.01	30	1000	Pass
Middle Channel	9.73	9.39			Pass
High Channel	10.38	10.92			Pass

Channel	Measured Output Peak Power		Limit		Verdict
	O-QPSK (1Mbps)		dBm	mW	
	dBm	mW			
Low Channel	8.44	6.99	30	1000	Pass
Middle Channel	9.70	9.33			Pass
High Channel	10.36	10.87			Pass

A.2 Occupied Bandwidth

Test Data

Test Mode	O-QPSK (250Kbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	1462.600	2245.100	≥500
Middle Channel	1530.000	2266.500	≥500
High Channel	1575.000	2277.300	≥500

Test Mode	O-QPSK (1Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	1327.600	2291.600	≥500
Middle Channel	1417.500	2300.200	≥500
High Channel	1439.900	2337.300	≥500

Test Plots

6 dB Bandwidth

O-QPSK (250Kbps) LOW CHANNEL



O-QPSK (250Kbps) MIDDLE CHANNEL



O-QPSK (250Kbps) HIGH CHANNEL




O-QPSK (1Mbps) LOW CHANNEL



O-QPSK (1Mbps) MIDDLE CHANNEL



O-QPSK (1Mbps) HIGH CHANNEL




99% Bandwidth


O-QPSK (250Kbps) LOW CHANNEL




O-QPSK (250Kbps) MIDDLE CHANNEL




O-QPSK (250Kbps) HIGH CHANNEL




O-QPSK (1Mbps) LOW CHANNEL



O-QPSK (1Mbps) MIDDLE CHANNEL



O-QPSK (1Mbps) HIGH CHANNEL



A.3 Conducted Spurious Emissions


Test Data

O-QPSK (250Kbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-36.50	5.79	-14.21	Pass
Middle Channel	-37.53	6.75	-13.25	Pass
High Channel	-39.04	7.49	-12.51	Pass


O-QPSK (1Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-38.60	4.62	-15.38	Pass
Middle Channel	-37.71	5.94	-14.06	Pass
High Channel	-38.26	6.45	-13.55	Pass

Test Plots


O-QPSK (250Kbps) LOW CHANNEL, CARRIER LEVEL




O-QPSK (250Kbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




O-QPSK (250Kbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




O-QPSK (250Kbps) MIDDLE CHANNEL, CARRIER LEVEL




O-QPSK (250Kbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




O-QPSK (250Kbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




O-QPSK (250Kbps) HIGH CHANNEL, CARRIER LEVEL




O-QPSK (250Kbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




O-QPSK (250Kbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




O-QPSK (1Mbps) LOW CHANNEL, CARRIER LEVEL




O-QPSK (1Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




O-QPSK (1Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




O-QPSK (1Mbps) MIDDLE CHANNEL, CARRIER LEVEL




O-QPSK (1Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




O-QPSK (1Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




O-QPSK (1Mbps) HIGH CHANNEL, CARRIER LEVEL



O-QPSK (1Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



O-QPSK (1Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Test Data

O-QPSK (250Kbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-37.63	5.79	-14.21	Pass
High Channel	-41.70	7.49	-12.51	Pass


O-QPSK (1Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-36.41	4.62	-15.38	Pass
High Channel	-42.04	6.45	-13.55	Pass

Test Plots


O-QPSK (250Kbps) LOW CHANNEL, CARRIER LEVEL




O-QPSK (250Kbps) LOW CHANNEL, BAND EDGE




O-QPSK (250Kbps) HIGH CHANNEL, CARRIER LEVEL




O-QPSK (250Kbps) HIGH CHANNEL, BAND EDGE




O-QPSK (1Mbps) LOW CHANNEL, CARRIER LEVEL




O-QPSK (1Mbps) LOW CHANNEL, BAND EDGE



O-QPSK (1Mbps) HIGH CHANNEL, CARRIER
LEVEL

O-QPSK (1Mbps) HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions

Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.


Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.378	36.00	10.70	58.32	22.32	Peak	L	Pass
1**	0.378	25.42	10.70	48.32	22.90	AV	L	Pass
2	0.690	36.67	10.63	56.00	19.33	Peak	L	Pass
2**	0.690	25.18	10.63	46.00	20.82	AV	L	Pass
3	1.314	35.65	10.42	56.00	20.35	Peak	L	Pass
3**	1.314	24.65	10.42	46.00	21.35	AV	L	Pass
4	2.572	35.31	9.94	56.00	20.69	Peak	L	Pass
4**	2.572	24.79	9.94	46.00	21.21	AV	L	Pass
5	6.668	36.29	10.58	60.00	23.71	Peak	L	Pass
5**	6.668	25.07	10.58	50.00	24.93	AV	L	Pass
6	11.232	37.56	10.77	60.00	22.44	Peak	L	Pass
6**	11.232	24.74	10.77	50.00	25.26	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.352	36.71	10.81	58.92	22.21	Peak	N	Pass
1**	0.352	24.99	10.81	48.92	23.93	AV	N	Pass
2	0.724	36.26	10.47	56.00	19.74	Peak	N	Pass
2**	0.724	24.67	10.47	46.00	21.33	AV	N	Pass
3	1.568	35.77	10.10	56.00	20.23	Peak	N	Pass
3**	1.568	24.76	10.10	46.00	21.24	AV	N	Pass
4	3.654	36.02	10.43	56.00	19.98	Peak	N	Pass
4**	3.654	24.87	10.43	46.00	21.13	AV	N	Pass
5	5.980	36.21	10.37	60.00	23.79	Peak	N	Pass
5**	5.980	24.25	10.37	50.00	25.75	AV	N	Pass
6	14.878	36.97	10.80	60.00	23.03	Peak	N	Pass
6**	14.878	23.91	10.80	50.00	26.09	AV	N	Pass

A.6 Radiated Spurious Emission

Note ¹: The symbol of "--" in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note ⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots

30 MHz to 1 GHz, ANT H


RE Test case_FCC Part 15C_FCC Part 15C_30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	36.645	17.90	-30.22	40.0	22.10	Peak	72.00	100	Horizontal	Pass
2	104.399	21.40	-32.62	43.5	22.10	Peak	0.00	200	Horizontal	Pass
3	204.794	20.91	-30.81	43.5	22.59	Peak	162.50	200	Horizontal	Pass
4	324.734	24.32	-25.49	46.0	21.68	Peak	109.20	100	Horizontal	Pass
5	465.190	25.86	-21.09	46.0	20.14	Peak	114.10	100	Horizontal	Pass
6	986.323	29.24	-10.81	54.0	24.76	Peak	309.40	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

RE Test case_FCC Part 15C_FCC Part 15C_30MHz-1GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	68.703	22.43	-30.58	40.0	17.57	Peak	357.70	100	Vertical	Pass
2	104.351	25.60	-32.63	43.5	17.90	Peak	212.60	100	Vertical	Pass
3	225.940	23.13	-30.95	46.0	22.87	Peak	313.60	100	Vertical	Pass
4	330.894	26.50	-25.13	46.0	19.50	Peak	5.20	100	Vertical	Pass
5	549.969	28.32	-18.98	46.0	17.68	Peak	322.90	100	Vertical	Pass
6	923.807	28.80	-10.73	46.0	17.20	Peak	254.80	100	Vertical	Pass

Note¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

O-QPSK (250Kbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

3#_RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1251.530	42.13	74.0	31.87	Peak	331.00	300	Horizontal	Pass
1**	1251.530	36.59	54.0	17.41	AV	331.00	300	Horizontal	Pass
2	2944.980	48.71	74.0	25.29	Peak	60.00	400	Horizontal	Pass
2**	2944.980	39.80	54.0	14.20	AV	60.00	400	Horizontal	Pass
3	4945.072	47.42	74.0	26.58	Peak	5.00	200	Horizontal	Pass
3**	4945.072	39.01	54.0	14.99	AV	5.00	200	Horizontal	Pass
4	6768.583	52.53	74.0	21.47	Peak	190.00	100	Horizontal	Pass
4**	6768.583	43.62	54.0	10.38	AV	190.00	100	Horizontal	Pass
5	12487.282	45.26	74.0	28.74	Peak	209.00	400	Horizontal	Pass
5**	12487.282	40.25	54.0	13.75	AV	209.00	400	Horizontal	Pass
6	16450.646	47.24	74.0	26.76	Peak	36.00	100	Horizontal	Pass
6**	16450.646	40.92	54.0	13.08	AV	36.00	100	Horizontal	Pass

O-QPSK (250Kbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1466.402	45.96	74.0	28.04	Peak	77.00	100	Vertical	Pass
1**	1466.402	32.93	54.0	21.07	AV	77.00	100	Vertical	Pass
2	2994.164	50.70	74.0	23.30	Peak	359.00	100	Vertical	Pass
2**	2994.164	39.97	54.0	14.03	AV	359.00	100	Vertical	Pass
3	4820.987	50.88	74.0	23.12	Peak	158.00	200	Vertical	Pass
3**	4820.987	39.39	54.0	14.61	AV	158.00	200	Vertical	Pass
4	7968.975	59.27	74.0	14.73	Peak	174.00	200	Vertical	Pass
4**	7968.975	42.25	54.0	11.75	AV	174.00	200	Vertical	Pass
5	12439.602	51.06	74.0	22.94	Peak	319.00	100	Vertical	Pass
5**	12439.602	42.53	54.0	11.47	AV	319.00	100	Vertical	Pass
6	17454.162	52.80	74.0	21.20	Peak	21.00	200	Vertical	Pass
6**	17454.162	42.66	54.0	11.34	AV	21.00	200	Vertical	Pass

O-QPSK (250Kbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1247.358	38.46	74.0	35.54	Peak	174.00	100	Horizontal	Pass
1**	1247.358	33.58	54.0	20.42	AV	174.00	100	Horizontal	Pass
2	2940.555	48.99	74.0	25.01	Peak	169.00	100	Horizontal	Pass
2**	2940.555	43.25	54.0	10.75	AV	169.00	100	Horizontal	Pass
3	4944.447	48.44	74.0	25.56	Peak	179.00	200	Horizontal	Pass
3**	4944.447	41.31	54.0	12.69	AV	179.00	200	Horizontal	Pass
4	6768.322	48.79	74.0	25.21	Peak	97.00	400	Horizontal	Pass
4**	6768.322	40.47	54.0	13.53	AV	97.00	400	Horizontal	Pass
5	12486.437	49.02	74.0	24.98	Peak	20.00	200	Horizontal	Pass
5**	12486.437	40.43	54.0	13.57	AV	20.00	200	Horizontal	Pass
6	16446.767	47.15	74.0	26.85	Peak	131.00	300	Horizontal	Pass
6**	16446.767	38.03	54.0	15.97	AV	131.00	300	Horizontal	Pass

O-QPSK (250Kbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1463.250	42.89	74.0	31.11	Peak	256.00	400	Vertical	Pass
1**	1463.250	31.51	54.0	22.49	AV	256.00	400	Vertical	Pass
2	2991.920	51.01	74.0	22.99	Peak	24.00	100	Vertical	Pass
2**	2991.920	38.06	54.0	15.94	AV	24.00	100	Vertical	Pass
3	4820.738	50.65	74.0	23.35	Peak	334.00	200	Vertical	Pass
3**	4820.738	39.40	54.0	14.60	AV	334.00	200	Vertical	Pass
4	7969.327	57.19	74.0	16.81	Peak	204.00	400	Vertical	Pass
4**	7969.327	41.35	54.0	12.65	AV	204.00	400	Vertical	Pass
5	12441.810	49.85	74.0	24.15	Peak	132.00	300	Vertical	Pass
5**	12441.810	41.26	54.0	12.74	AV	132.00	300	Vertical	Pass
6	17454.092	52.95	74.0	21.05	Peak	23.00	300	Vertical	Pass
6**	17454.092	42.81	54.0	11.19	AV	23.00	300	Vertical	Pass

O-QPSK (250Kbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1247.787	41.16	74.0	32.84	Peak	305.00	100	Horizontal	Pass
1**	1247.787	34.70	54.0	19.30	AV	305.00	100	Horizontal	Pass
2	2942.689	50.87	74.0	23.13	Peak	43.00	400	Horizontal	Pass
2**	2942.689	41.21	54.0	12.79	AV	43.00	400	Horizontal	Pass
3	4945.091	49.38	74.0	24.62	Peak	318.00	200	Horizontal	Pass
3**	4945.091	37.00	54.0	17.00	AV	318.00	200	Horizontal	Pass
4	6766.644	52.20	74.0	21.80	Peak	181.00	300	Horizontal	Pass
4**	6766.644	38.64	54.0	15.36	AV	181.00	300	Horizontal	Pass
5	12486.180	45.73	74.0	28.27	Peak	180.00	400	Horizontal	Pass
5**	12486.180	39.74	54.0	14.26	AV	180.00	400	Horizontal	Pass
6	16452.450	48.82	74.0	25.18	Peak	257.00	400	Horizontal	Pass
6**	16452.450	37.80	54.0	16.20	AV	257.00	400	Horizontal	Pass

O-QPSK (250Kbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1469.023	41.38	74.0	32.62	Peak	24.00	400	Vertical	Pass
1**	1469.023	29.49	54.0	24.51	AV	24.00	400	Vertical	Pass
2	2995.110	48.09	74.0	25.91	Peak	66.00	100	Vertical	Pass
2**	2995.110	38.37	54.0	15.63	AV	66.00	100	Vertical	Pass
3	4819.742	53.62	74.0	20.38	Peak	104.00	200	Vertical	Pass
3**	4819.742	39.17	54.0	14.83	AV	104.00	200	Vertical	Pass
4	7964.668	56.18	74.0	17.82	Peak	160.00	200	Vertical	Pass
4**	7964.668	43.26	54.0	10.74	AV	160.00	200	Vertical	Pass
5	12441.720	51.28	74.0	22.72	Peak	172.00	100	Vertical	Pass
5**	12441.720	43.57	54.0	10.43	AV	172.00	100	Vertical	Pass
6	17454.946	53.52	74.0	20.48	Peak	345.00	100	Vertical	Pass
6**	17454.946	42.99	54.0	11.01	AV	345.00	100	Vertical	Pass

O-QPSK (1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1244.905	42.18	74.0	31.82	Peak	56.00	200	Horizontal	Pass
1**	1244.905	36.85	54.0	17.15	AV	56.00	200	Horizontal	Pass
2	2941.254	48.75	74.0	25.25	Peak	235.00	300	Horizontal	Pass
2**	2941.254	39.76	54.0	14.24	AV	235.00	300	Horizontal	Pass
3	4943.503	47.29	74.0	26.71	Peak	133.00	200	Horizontal	Pass
3**	4943.503	39.24	54.0	14.76	AV	133.00	200	Horizontal	Pass
4	6762.994	52.66	74.0	21.35	Peak	69.00	100	Horizontal	Pass
4**	6762.994	44.68	54.0	9.33	AV	69.00	100	Horizontal	Pass
5	12485.744	45.24	74.0	28.76	Peak	260.00	300	Horizontal	Pass
5**	12485.744	40.15	54.0	13.85	AV	260.00	300	Horizontal	Pass
6	16449.333	47.15	74.0	26.85	Peak	156.00	100	Horizontal	Pass
6**	16449.333	38.06	54.0	15.94	AV	156.00	100	Horizontal	Pass

O-QPSK (1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1468.983	41.98	74.0	32.03	Peak	340.00	100	Vertical	Pass
1**	1468.983	36.44	54.0	17.57	AV	340.00	100	Vertical	Pass
2	2993.682	48.93	74.0	25.07	Peak	141.00	300	Vertical	Pass
2**	2993.682	39.69	54.0	14.31	AV	141.00	300	Vertical	Pass
3	4823.124	47.25	74.0	26.75	Peak	316.00	200	Vertical	Pass
3**	4823.124	38.82	54.0	15.18	AV	316.00	200	Vertical	Pass
4	7960.689	52.39	74.0	21.61	Peak	66.00	200	Vertical	Pass
4**	7960.689	43.34	54.0	10.66	AV	66.00	200	Vertical	Pass
5	12438.672	45.33	74.0	28.67	Peak	30.00	200	Vertical	Pass
5**	12438.672	40.53	54.0	13.47	AV	30.00	200	Vertical	Pass
6	17458.767	47.50	74.0	26.50	Peak	117.00	200	Vertical	Pass
6**	17458.767	40.81	54.0	13.20	AV	117.00	200	Vertical	Pass

O-QPSK (1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1247.891	42.14	74.0	31.87	Peak	344.00	300	Horizontal	Pass
1**	1247.891	36.85	54.0	17.15	AV	344.00	300	Horizontal	Pass
2	2939.778	48.75	74.0	25.26	Peak	239.00	300	Horizontal	Pass
2**	2939.778	39.62	54.0	14.38	AV	239.00	300	Horizontal	Pass
3	4943.258	47.13	74.0	26.87	Peak	129.00	200	Horizontal	Pass
3**	4943.258	39.24	54.0	14.77	AV	129.00	200	Horizontal	Pass
4	6766.875	52.69	74.0	21.31	Peak	356.00	400	Horizontal	Pass
4**	6766.875	44.66	54.0	9.35	AV	356.00	400	Horizontal	Pass
5	12484.375	45.25	74.0	28.75	Peak	227.00	400	Horizontal	Pass
5**	12484.375	40.51	54.0	13.49	AV	227.00	400	Horizontal	Pass
6	16453.338	47.24	74.0	26.76	Peak	121.00	400	Horizontal	Pass
6**	16453.338	37.87	54.0	16.13	AV	121.00	400	Horizontal	Pass

O-QPSK (1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1470.986	42.00	74.0	32.00	Peak	224.00	100	Vertical	Pass
1**	1470.986	36.40	54.0	17.60	AV	224.00	100	Vertical	Pass
2	2997.203	48.56	74.0	25.44	Peak	253.00	200	Vertical	Pass
2**	2997.203	39.82	54.0	14.18	AV	253.00	200	Vertical	Pass
3	4822.143	47.58	74.0	26.42	Peak	348.00	200	Vertical	Pass
3**	4822.143	39.15	54.0	14.85	AV	348.00	200	Vertical	Pass
4	7964.866	52.52	74.0	21.48	Peak	252.00	400	Vertical	Pass
4**	7964.866	43.59	54.0	10.41	AV	252.00	400	Vertical	Pass
5	12442.714	45.00	74.0	29.01	Peak	238.00	100	Vertical	Pass
5**	12442.714	40.26	54.0	13.74	AV	238.00	100	Vertical	Pass
6	17454.426	47.22	74.0	26.78	Peak	212.00	100	Vertical	Pass
6**	17454.426	40.78	54.0	13.22	AV	212.00	100	Vertical	Pass

O-QPSK (1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1249.916	42.26	74.0	31.74	Peak	233.00	300	Horizontal	Pass
1**	1249.916	36.89	54.0	17.11	AV	233.00	300	Horizontal	Pass
2	2945.749	48.71	74.0	25.29	Peak	35.00	400	Horizontal	Pass
2**	2945.749	39.96	54.0	14.04	AV	35.00	400	Horizontal	Pass
3	4942.201	47.26	74.0	26.74	Peak	353.00	200	Horizontal	Pass
3**	4942.201	38.91	54.0	15.09	AV	353.00	200	Horizontal	Pass
4	6764.513	52.47	74.0	21.53	Peak	111.00	300	Horizontal	Pass
4**	6764.513	44.36	54.0	9.64	AV	111.00	300	Horizontal	Pass
5	12487.695	45.22	74.0	28.78	Peak	59.00	400	Horizontal	Pass
5**	12487.695	40.06	54.0	13.94	AV	59.00	400	Horizontal	Pass
6	16449.790	47.36	74.0	26.64	Peak	165.00	400	Horizontal	Pass
6**	16449.790	37.57	54.0	16.43	AV	165.00	400	Horizontal	Pass

O-QPSK (1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1465.558	42.07	74.0	31.93	Peak	350.00	300	Vertical	Pass
1**	1465.558	36.77	54.0	17.23	AV	350.00	300	Vertical	Pass
2	2992.503	48.78	74.0	25.22	Peak	49.00	200	Vertical	Pass
2**	2992.503	39.85	54.0	14.15	AV	49.00	200	Vertical	Pass
3	4820.711	47.60	74.0	26.40	Peak	170.00	200	Vertical	Pass
3**	4820.711	39.21	54.0	14.79	AV	170.00	200	Vertical	Pass
4	7963.181	52.38	74.0	21.62	Peak	187.00	300	Vertical	Pass
4**	7963.181	43.73	54.0	10.27	AV	187.00	300	Vertical	Pass
5	12441.905	45.30	74.0	28.70	Peak	147.00	200	Vertical	Pass
5**	12441.905	40.01	54.0	13.99	AV	147.00	200	Vertical	Pass
6	17456.037	47.18	74.0	26.83	Peak	65.00	300	Vertical	Pass
6**	17456.037	40.89	54.0	13.11	AV	65.00	300	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note³: According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note⁴: The Level (dBuV/m) has been corrected by factor.

Note⁵: Both horizontal and vertical directions were pre tested, only the worst configuration has been reported in this report.


Test Data and Plots

O-QPSK (250Kbps) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2372.269	55.7	74.0	18.30	Peak	102.00	100	Horizontal	Pass
1**	2372.269	41.31	54.0	12.69	AV	102.00	100	Horizontal	Pass
2	2390.000	51.59	74.0	22.41	Peak	99.00	200	Horizontal	Pass
2**	2390.000	43.63	54.0	10.37	AV	99.00	200	Horizontal	Pass

O-QPSK (250Kbps) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.52	74.0	19.48	Peak	85.00	200	Horizontal	Pass
1**	2483.500	42.83	54.0	11.17	AV	85.00	200	Horizontal	Pass
2	2493.542	55.78	74.0	18.22	Peak	173.00	100	Horizontal	Pass
2**	2493.542	43.05	54.0	10.95	AV	173.00	100	Horizontal	Pass

O-QPSK (1Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2320.560	58.7	74.0	15.30	Peak	2.00	300	Horizontal	Pass
1**	2320.560	43.64	54.0	10.36	AV	2.00	300	Horizontal	Pass
2	2390.000	52.68	74.0	21.32	Peak	74.00	200	Horizontal	Pass
2**	2390.000	42.10	54.0	11.90	AV	74.00	200	Horizontal	Pass

O-QPSK (1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.42	74.0	19.58	Peak	200.00	200	Horizontal	Pass
1**	2483.500	43.06	54.0	10.94	AV	200.00	200	Horizontal	Pass
2	2494.879	57.5	74.0	16.50	Peak	9.00	100	Horizontal	Pass
2**	2494.879	42.03	54.0	11.97	AV	9.00	100	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

O-QPSK (250Kbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-7.11	8	Pass
Middle Channel	-5.90	8	Pass
High Channel	-5.45	8	Pass


O-QPSK (1Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-4.85	8	Pass
Middle Channel	-3.72	8	Pass
High Channel	-3.12	8	Pass

Test Plots


O-QPSK (250Kbps) LOW CHANNEL




O-QPSK (250Kbps) MIDDLE CHANNEL




O-QPSK (250Kbps) HIGH CHANNEL




O-QPSK (1Mbps) LOW CHANNEL



O-QPSK (1Mbps) MIDDLE CHANNEL



O-QPSK (1Mbps) HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “Ti-EE26040641-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “Ti-EE26040641-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “Ti-EE26040641-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--