

RF EXPOSURE EVALUATION

EUT Specification

EUT	Mechanical Keyboard
Model Number	CORE
Series Model	CORE V1, CORE V2, CORE V3, CORE V4
Model Difference	The difference of the models are product appearance color and the keycaps of the keyboard keys, others are the same.
FCC ID	2BUIS-CORE
Antenna gain (Max)	BT: 2.34dBi BLE: 2.34dBi 2.4G: 2.34dBi
Operation Frequency	BT: 2402 MHz to 2480 MHz BLE: 2402 MHz to 2480 MHz 2.4G: 2405 MHz to 2475 MHz
Power Supply	AC 120V/60Hz DC 5V Battery 3.7V
Classification Per Stipulated Test Standard	§15.247(i), §2.1093
Modulation	BT: GFSK BLE: GFSK 2.4G: GFSK
Max. output power	BT: 0.2dBm (0.0010W) BLE: 2.53dBm (0.0018W) 2.4G: 1.01dBm (0.0013W)

Test Requirement:

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

One antenna is available for the EUT. The minimum separation distance is 5mm.

Measurement Result

BT:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	1-DH5	0.2	0±1	1	0.39	3

BLE:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	BLE 1M	2.53	2±1	3	0.62	3

2.4G:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	2.4G	1.01	1±1	2	0.49	3

Bluetooth & 2.4G can't transmit simultaneously (declared by client). According to KDB 447498, no simultaneous SAR measurement is required.

Signature:



Shawn Wen

Date: 2026-3-11