



RF TEST REPORT

Product Name: GapaSea G1 Pro

Model Number: GapaSea G1

FCC ID: 2BULT-G1PRO

Issued For : Beijing Langren Technology Co., Ltd.
1-2, 1st to 2nd Floor, Building 15, Fanggu Garden Community
No. 1, Fengtai District, Beijing

Issued By : Shenzhen LGT Test Service Co., Ltd.
Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT25K102RF06

Sample Received Date: Jan. 31, 2026

Date of Test: Mar. 05, 2026 ~ Apr. 20, 2026

Date of Issue: Apr. 20, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Beijing Langren Technology Co., Ltd.
Address: 1-2, 1st to 2nd Floor, Building 15, Fanggu Garden Community No. 1, Fengtai District, Beijing
Manufacturer: Beijing Langren Technology Co., Ltd.
Address: 1-2, 1st to 2nd Floor, Building 15, Fanggu Garden Community No. 1, Fengtai District, Beijing
Product Name: GapaSea G1 Pro
Trademark: GapaSea
Model Number: GapaSea G1
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST LABORATORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	9
2.3 TEST SOFTWARE AND POWER LEVEL	9
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	10
2.5 EQUIPMENTS LIST	11
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.2 TEST PROCEDURE	14
3.3 TEST SETUP	14
3.4 EUT OPERATING CONDITIONS	14
3.5 TEST RESULTS	15
4. RADIATED EMISSION MEASUREMENT	17
4.1 RADIATED EMISSION LIMITS	17
4.2 TEST PROCEDURE	19
4.3 TEST SETUP	19
4.4 EUT OPERATING CONDITIONS	20
4.5 FIELD STRENGTH CALCULATION	20
4.6 TEST RESULTS (BAND EDGE REQUIREMENTS)	26
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	28
5.1 LIMIT	28
5.2 TEST PROCEDURE	28
5.3 TEST SETUP	28
5.4 EUT OPERATION CONDITIONS	28
5.5 TEST RESULTS	28
6. POWER SPECTRAL DENSITY TEST	29
6.1 LIMIT	29
6.2 TEST PROCEDURE	29
6.3 TEST SETUP	29
6.4 EUT OPERATION CONDITIONS	29



6.5 TEST RESULTS	29
7. BANDWIDTH TEST	30
7.1 LIMIT	30
7.2 TEST PROCEDURE	30
7.3 TEST SETUP	30
7.4 EUT OPERATION CONDITIONS	30
7.5 TEST RESULTS	30
8. PEAK OUTPUT POWER TEST	31
8.1 LIMIT	31
8.2 TEST PROCEDURE	31
8.3 TEST SETUP	31
8.4 EUT OPERATION CONDITIONS	31
8.5 TEST RESULTS	31
9. ANTENNA REQUIREMENT	32
9.1 STANDARD REQUIREMENT	32
9.2 EUT ANTENNA	32
APPENDIX I - TEST RESULTS	33
DUTY CYCLE	33
MAXIMUM PEAK CONDUCTED OUTPUT POWER	36
-6DB BANDWIDTH	39
OCCUPIED CHANNEL BANDWIDTH	42
MAXIMUM POWER SPECTRAL DENSITY LEVEL	45
BAND EDGE	48
CONDUCTED RF SPURIOUS EMISSION	52
APPENDIX II - MEASUREMENT PHOTOS	57



Revision History

Rev.	Issue Date	Revisions
00	Apr. 20, 2026	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 Part 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.



1.1 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate:	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	Occupied Channel Bandwidth	$\pm 0.46\%$
2	RF Output Power, Conducted	$\pm 0.71\text{dB}$
3	Power Spectral Density, Conducted	$\pm 1.57\text{dB}$
4	Unwanted Emission, Conducted	$\pm 0.63\text{dB}$
5	Conducted emission	$\pm 2.80\text{dB}$
6	All Emissions, Radiated (0.009-30MHz)	$\pm 2.16\text{dB}$
7	All Emissions, Radiated (30MHz-1GHz)	$\pm 4.61\text{dB}$
8	All Emissions, Radiated (1GHz-18GHz)	$\pm 5.49\text{dB}$
9	Temperature	$\pm 0.5^{\circ}\text{C}$
10	Humidity	$\pm 2\%$
11	Duty Cycle	$\pm 2.3\%$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	GapaSea G1 Pro		
Test Model Number:	GapaSea G1		
Series Number:	N/A		
Model Difference:	N/A		
Product Description:			
	Operation Frequency:	2404~2474MHz	
	Modulation Type:	GFSK	
	Number Of Channel:	24CH	
	Antenna Designation:	FPC Antenna	
	Antenna Gain (dBi)	1.5dBi	
Channel List:	Please refer to the Note 3.		
Rating:	Charging Case: Input: DC 5V 1A Output: DC 5V 0.5A		
	Charging Cable: Input: DC 5V 1A Output: DC 5V 0.5A		
Battery:	Capacity: 160mAh Rated Voltage: 3.89V		
Hardware Version:	EVT		
Software Version:	1.0.4.108		
Connecting I/O Port(s):	Please refer to the Note 1.		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.
- 3.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2404	7	2422	13	2440	19	2459
2	2407	8	2425	14	2443	20	2462
3	2410	9	2428	15	2447	21	2465
4	2413	10	2431	16	2450	22	2468
5	2416	11	2434	17	2453	23	2471
6	2419	12	2437	18	2456	24	2474



2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Description	Data/Modulation
Mode 1	TX CH01(2404MHz)	GFSK
Mode 2	TX CH13(2440MHz)	GFSK
Mode 3	TX CH24(2474MHz)	GFSK

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

(2) We have be tested for all avaiable U.S. voltage and frequency (For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report.

(3) The battery is fully-charged during the radited and RF conducted test.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 4: Keeping TX

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test software Version	Test program:2.4G	
	Mode Or Modulation type	Power setting
	1M	Default
	2M	Default



2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Mobile phone	TANK	OB-A93	N/A	N/A
Adapter	Tenpao	S005CAU0500100	N/A	Input: 100-240V ~ 50/60Hz 0.2A Output: 5V, 2A
USB-A to USB-C Cable	N/A	N/A	N/A	0.5m
Laptop	ASUS	UX3407Q	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.5 EQUIPMENTS LIST

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2026-03-02	2027-03-01
LISN	COM-POWER	LI-115	02032	2026-03-03	2027-03-02
LISN	SCHWARZBECK	NNLK 8122	00160	2026-03-03	2027-03-02
Transient Limiter	CYBERTEK	EM5010A	E225010004 9	2026-03-03	2027-03-02
Coaxial cables (9kHz-30MHz)	Juncoax	JMR600-NM NM-2M	N.A	2026-03-03	2027-03-02
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2026-03-05	2027-03-04
Testing Software	EMC-I_V1.5.0.16_SKET				

Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2026-03-02	2027-03-01
Active loop Antenna	ETS	6502	00049544	2025-03-11	2028-03-10
Spectrum Analyzer	Keysight	N9010B	MY60242508	2026-03-03	2027-03-02
Trilog Broadband Antenna (30M-1G)	SCHWARZBECK	VULB 9168	2705	2024-05-17	2027-05-16
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2025-03-10	2028-03-09
Horn Antenna(18-40G)	SCHWARZBECK	BBHA 9170	685	2023-10-23	2026-10-22
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2026-03-02	2027-03-01
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2026-03-02	2027-03-01
Pre-amplifier(18-40G)	SCHWARZBECK	BBV 9721	9721-019	2025-10-20	2026-10-19
Coaxial cables (9kHz-1GHz)	Juncoax	JMR600-NM NM-8M	N.A	2026-03-03	2027-03-02
Coaxial cables (1GHz-18GHz)	TaiHe	UCD460B-N MSM-1M9	N.A	2026-03-03	2027-03-02
Coaxial cables (18GHz-40GHz)	Junkosha Inc.	MWX241-05 000KMSKMS	N.A	2026-03-03	2027-03-02
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2025-07-30	2026-07-29
Antenna Tower	SAEMC	BK-4AT-BS- D	SK20210930 08	N.A	N.A
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2026-03-05	2027-03-04
Testing Software	EMC-I_V1.5.0.16_SKET				

RF Conducted Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
Signal Analyzer	Keysight	N9010B	MY60242508	2026-03-03	2027-03-02
Signal Analyzer	Keysight	N9020A	MY50530994	2026-03-02	2027-03-01
Power Sensor	R&S	NRP8S	104963	2026-03-02	2027-03-01
RF Automatic Test system	MW	MW100-RFC B	MW220324L G-33	2026-03-03	2027-03-02
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2026-03-03	2027-03-02
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2025-07-30	2026-07-29



Attenuator	eastsheep	90db	N.A	2026-03-02	2027-03-01
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2026-03-05	2027-03-04
Digital multimeter	MASTECH	MS8261	MBGBC8305 3	2025-07-30	2026-07-29
DC source	Keysight	E3634A	MY58036468	2026-03-05	2027-03-04
Testing Software	MTS8310_V2.0.0.0_MW				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



3.2 TEST PROCEDURE

- a. The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN is at least 80 cm from the nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.5 TEST RESULTS

Note: Level = Reading + Factor

Margin = Level – Limit


Project: LGT25K102	Test Engineer: LiuH
EUT: GapaSea G1 Pro	Temperature: 24.2°C
M/N: GapaSea G1	Humidity: 46%RH
Test Voltage: AC 120V/60Hz	Test Data: 2026-03-18
Test Mode: TX 2.4G	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.294	31.04	10.77	41.81	60.41	-18.60	QP	L1
2*	0.382	28.86	10.88	39.74	58.24	-18.50	QP	L1
3*	0.726	28.03	10.84	38.87	56.00	-17.13	QP	L1
4*	1.354	24.93	11.08	36.01	56.00	-19.99	QP	L1
5*	3.014	21.25	11.34	32.59	56.00	-23.41	QP	L1
6*	15.874	13.01	11.74	24.75	60.00	-35.25	QP	L1
7*	0.294	20.44	10.77	31.21	50.41	-19.20	AV	L1
8*	0.386	20.03	10.87	30.90	48.15	-17.25	AV	L1
9*	0.518	17.85	10.93	28.78	46.00	-17.22	AV	L1
10*	0.778	16.63	10.87	27.50	46.00	-18.50	AV	L1
11*	1.402	14.03	11.10	25.13	46.00	-20.87	AV	L1
12*	3.022	8.49	11.33	19.82	46.00	-26.18	AV	L1



Project: LGT25K102	Test Engineer: LiuH
EUT: GapaSea G1 Pro	Temperature: 24.2°C
M/N: GapaSea G1	Humidity: 46%RH
Test Voltage: AC 120V/60Hz	Test Data: 2026-03-18
Test Mode: TX 2.4G	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.290	28.02	10.75	38.77	60.52	-21.75	QP	N
2*	0.738	26.09	10.84	36.93	56.00	-19.07	QP	N
3*	0.990	25.33	10.84	36.17	56.00	-19.83	QP	N
4*	1.354	23.06	11.02	34.08	56.00	-21.92	QP	N
5*	3.162	15.02	11.24	26.26	56.00	-29.74	QP	N
6*	9.202	11.05	11.47	22.52	60.00	-37.48	QP	N
7*	0.290	17.89	10.75	28.64	50.52	-21.88	AV	N
8*	0.450	15.82	10.83	26.65	46.88	-20.23	AV	N
9*	0.778	16.99	10.83	27.82	46.00	-18.18	AV	N
10*	1.406	13.09	11.05	24.14	46.00	-21.86	AV	N
11*	4.170	4.79	11.28	16.07	46.00	-29.93	AV	N
12*	14.470	-0.26	11.63	11.37	50.00	-38.63	AV	N



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In case the emission fall within the Restricted band specified on Part15.205 (a)&209(a) limit in the table and according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz (Peak/QP/AV)
Stop Frequency	150KHz/30MHz (Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz (Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz (Peak/AV)
Stop Frequency	10th carrier hamonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.

4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



4.6 TEST RESULTS

Results of Radiated Emissions (9 KHz~30MHz)

No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Remark
1*	-	-	-	-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.




Results of Radiated Emissions (30MHz~1000MHz)

Note:1. All mode has been tested, only shown the worst case data.


2. Note: Level = Reading + Factor

Margin = Level – Limit

Project: LGT25K102	Test Engineer: zhangyangda
EUT: GapaSea G1 Pro	Temperature: 22.8°C
M/N: GapaSea G1	Humidity: 62%RH
Test Voltage: Battery 3.89V	Test Data: 2026-03-18
Test Mode: TX 2.4G-1M 2404	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	42.368	2.55	20.88	23.43	40.00	-16.57	PK	Hor
2*	53.280	4.12	20.86	24.98	40.00	-15.02	PK	Hor
3*	149.553	3.54	21.88	25.42	43.50	-18.08	PK	Hor
4*	282.443	4.39	21.49	25.88	46.00	-20.12	PK	Hor
5*	659.288	5.45	30.51	35.96	46.00	-10.04	PK	Hor
6*	982.055	4.50	35.27	39.77	54.00	-14.23	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	43.095	2.96	21.06	24.02	40.00	-15.98	PK	Ver
2*	49.400	2.89	20.88	23.77	40.00	-16.23	PK	Ver
3*	145.066	4.08	21.56	25.64	43.50	-17.86	PK	Ver
4*	300.873	3.88	22.05	25.93	46.00	-20.07	PK	Ver
5*	607.029	4.79	29.52	34.31	46.00	-11.69	PK	Ver
6*	997.696	4.99	35.16	40.15	54.00	-13.85	PK	Ver




Results of Radiated Emissions (Above 1000MHz)

Project: LGT25K102	Test Engineer: zhangyangda
EUT: GapaSea G1 Pro	Temperature: 25.2°C
M/N: GapaSea G1	Humidity: 59%RH
Test Voltage: Battery 3.89V	Test Data: 2026-04-18
Test Mode: 2.4G-1M 2404	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3336GHz	71.02	-21.81	49.21	74.00	-24.79	PK	Ver
!2*	2.4046GHz	93.36	-11.03	82.33	74.00	8.33	PK	Ver
3*	7.5280GHz	59.72	-7.05	52.67	74.00	-21.33	PK	Ver
4*	17.7641GHz	55.48	1.77	57.25	74.00	-16.75	PK	Ver
5*	1.3336GHz	62.61	-21.81	40.80	54.00	-13.20	AV	Ver
6*	7.5280GHz	48.85	-7.05	41.80	54.00	-12.20	AV	Ver
7*	17.7641GHz	45.23	1.77	47.00	54.00	-7.00	AV	Ver




No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.5950GHz	61.22	-19.58	41.64	74.00	-32.36	PK	Hor
!2*	2.4046GHz	93.23	-11.03	82.20	74.00	8.20	PK	Hor
3*	7.5641GHz	58.94	-7.12	51.82	74.00	-22.18	PK	Hor
4*	17.6260GHz	56.42	1.26	57.68	74.00	-16.32	PK	Hor
5*	1.5950GHz	51.08	-19.58	31.50	54.00	-22.50	AV	Hor
6*	7.5641GHz	48.72	-7.12	41.60	54.00	-12.40	AV	Hor
7*	17.6260GHz	45.54	1.26	46.80	54.00	-7.20	AV	Hor



Project: LGT25K102	Test Engineer: zhangyangda
EUT: GapaSea G1 Pro	Temperature: 25.2°C
M/N: GapaSea G1	Humidity: 59%RH
Test Voltage: Battery 3.89V	Test Data: 2026-04-18
Test Mode: 2.4G-1M 2440	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3315GHz	63.81	-21.83	41.98	74.00	-32.02	PK	Hor
!2*	2.4407GHz	92.15	-10.69	81.46	74.00	7.46	PK	Hor
3*	4.8824GHz	58.38	-5.91	52.47	74.00	-21.53	PK	Hor
4*	7.3941GHz	59.16	-7.01	52.15	74.00	-21.85	PK	Hor
5*	1.3315GHz	55.13	-21.83	33.30	54.00	-20.70	AV	Hor
6*	4.8824GHz	47.21	-5.91	41.30	54.00	-12.70	AV	Hor
7*	7.3941GHz	47.11	-7.01	40.10	54.00	-13.90	AV	Hor




No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.6821GHz	62.00	-18.58	43.42	74.00	-30.58	PK	Ver
!2*	2.4407GHz	92.53	-10.69	81.84	74.00	7.84	PK	Ver
3*	4.8590GHz	57.22	-5.89	51.33	74.00	-22.67	PK	Ver
4*	7.5004GHz	59.86	-6.99	52.87	74.00	-21.13	PK	Ver
5*	1.6821GHz	50.78	-18.58	32.20	54.00	-21.80	AV	Ver
6*	4.8590GHz	46.39	-5.89	40.50	54.00	-13.50	AV	Ver
7*	7.5004GHz	48.99	-6.99	42.00	54.00	-12.00	AV	Ver



Project: LGT25K102	Test Engineer: zhangyangda
EUT: GapaSea G1 Pro	Temperature: 25.2°C
M/N: GapaSea G1	Humidity: 59%RH
Test Voltage: Battery 3.89V	Test Data: 2026-04-18
Test Mode: 2.4G-1M 2474	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
!1*	2.4747GHz	92.87	-10.38	82.49	74.00	8.49	PK	Hor
2*	6.3082GHz	57.44	-7.68	49.76	74.00	-24.24	PK	Hor
3*	11.9947GHz	55.91	-3.34	52.57	74.00	-21.43	PK	Hor
4*	17.9936GHz	55.29	2.61	57.90	74.00	-16.10	PK	Hor
5*	6.3082GHz	47.08	-7.68	39.40	54.00	-14.60	AV	Hor
6*	11.9947GHz	44.94	-3.34	41.60	54.00	-12.40	AV	Hor
7*	17.9936GHz	44.89	2.61	47.50	54.00	-6.50	AV	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3315GHz	70.92	-21.83	49.09	74.00	-24.91	PK	Ver
!2*	2.4747GHz	86.58	-10.38	76.20	74.00	2.20	PK	Ver
3*	8.2101GHz	60.06	-7.77	52.29	74.00	-21.71	PK	Ver
4*	17.9022GHz	55.16	2.27	57.43	74.00	-16.57	PK	Ver
5*	1.3315GHz	61.53	-21.83	39.70	54.00	-14.30	AV	Ver
6*	8.2101GHz	48.97	-7.77	41.20	54.00	-12.80	AV	Ver
7*	17.9022GHz	45.23	2.27	47.50	54.00	-6.50	AV	Ver


Remark:

In frequency ranges 18~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.




4.6 TEST RESULTS (BAND EDGE REQUIREMENTS)

Project: LGT25K102	Test Engineer: zhangyangda
EUT: GapaSea G1 Pro	Temperature: 25.2°C
M/N: GapaSea G1	Humidity: 59%RH
Test Voltage: Battery 3.89V	Test Data: 2026-04-18
Test Mode: 2.4G-2M 2404	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2379.0000	16.75	35.54	52.29	74.00	-21.71	PK	Hor
2*	2390.0000	13.41	35.59	49.00	74.00	-25.00	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2380.6000	16.99	35.55	52.54	74.00	-21.46	PK	Ver
2*	2390.0000	12.91	35.59	48.50	74.00	-25.50	PK	Ver



Project: LGT25K102	Test Engineer: zhangyangda
EUT: GapaSea G1 Pro	Temperature: 25.2°C
M/N: GapaSea G1	Humidity: 59%RH
Test Voltage: Battery 3.89V	Test Data: 2026-04-18
Test Mode: 2.4G-2M 2474	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2483.5000	13.72	35.98	49.70	74.00	-24.30	PK	Hor
2*	2499.9000	17.86	36.05	53.91	74.00	-20.09	PK	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2483.5000	14.92	35.98	50.90	74.00	-23.10	PK	Ver
2*	2499.5000	17.74	36.05	53.79	74.00	-20.21	PK	Ver



5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 – 2407 MHz Upper Band Edge: 2475 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

5.5 TEST RESULTS

For the measurement records, refer to the appendix I.

Note: Not recorded emission from 9 KHz to 30 MHz as emission level at least 20dBc lower than emission limit.



6. POWER SPECTRAL DENSITY TEST


6.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

6.5 TEST RESULTS

For the measurement records, refer to the appendix I.



7. BANDWIDTH TEST


7.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

7.5 TEST RESULTS

For the measurement records, refer to the appendix I.



8. PEAK OUTPUT POWER TEST

8.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

Integrated band power method:

The following procedure can be used when the maximum available RBW of the instrument is less than the


DTS bandwidth:

- Set the RBW = 1 MHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Set the span $\geq [1.5 \times \text{DTS bandwidth}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.

PKPM1 Peak power sensor method:

The maximum peak conducted output power may be measured using a broadband peak RF power sensor. The power sensor shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

8.5 TEST RESULTS

For the measurement records, refer to the appendix I.



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA


The EUT antenna is FPC Antenna. It comply with the standard requirement.




APPENDIX I - TEST RESULTS

Duty Cycle

Condition	Mode	Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	2.4G_1M	2404	1.638	1.874	87.41	0.58	0.61
NVNT	2.4G_1M	2440	1.637	1.873	87.4	0.58	0.61
NVNT	2.4G_1M	2474	1.638	1.875	87.36	0.59	0.61
NVNT	2.4G_2M	2404	0.823	1.249	65.89	1.81	1.21
NVNT	2.4G_2M	2440	0.825	1.25	66	1.8	1.21
NVNT	2.4G_2M	2474	0.824	1.25	65.92	1.81	1.21









Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	2.4G_1M	2404	11.55	30	Pass
NVNT	2.4G_1M	2440	10.61	30	Pass
NVNT	2.4G_1M	2474	9.43	30	Pass
NVNT	2.4G_2M	2404	11.27	30	Pass
NVNT	2.4G_2M	2440	10.33	30	Pass
NVNT	2.4G_2M	2474	9.18	30	Pass








-6dB Bandwidth

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	2.4G_1M	2404	0.6565	0.5	Pass
NVNT	2.4G_1M	2440	0.6507	0.5	Pass
NVNT	2.4G_1M	2474	0.6553	0.5	Pass
NVNT	2.4G_2M	2404	1.121	0.5	Pass
NVNT	2.4G_2M	2440	1.154	0.5	Pass
NVNT	2.4G_2M	2474	1.229	0.5	Pass








Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	2.4G_1M	2404	1.023
NVNT	2.4G_1M	2440	1.022
NVNT	2.4G_1M	2474	1.019
NVNT	2.4G_2M	2404	2.035
NVNT	2.4G_2M	2440	2.037
NVNT	2.4G_2M	2474	2.04








Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	2.4G_1M	2404	-5.07	8	Pass
NVNT	2.4G_1M	2440	-6	8	Pass
NVNT	2.4G_1M	2474	-7.25	8	Pass
NVNT	2.4G_2M	2404	-8.42	8	Pass
NVNT	2.4G_2M	2440	-9.37	8	Pass
NVNT	2.4G_2M	2474	-10.47	8	Pass












Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	2.4G_1M	2404	-58.18	-20	Pass
NVNT	2.4G_1M	2474	-55.03	-20	Pass
NVNT	2.4G_2M	2404	-57.46	-20	Pass
NVNT	2.4G_2M	2474	-54.95	-20	Pass















Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	2.4G_1M	2404	-57.56	-20	Pass
NVNT	2.4G_1M	2440	-57.56	-20	Pass
NVNT	2.4G_1M	2474	-57.02	-20	Pass
NVNT	2.4G_2M	2404	-57.99	-20	Pass
NVNT	2.4G_2M	2440	-56.97	-20	Pass
NVNT	2.4G_2M	2474	-56.11	-20	Pass











APPENDIX II - MEASUREMENT PHOTOS

Note: Please see the attached RF_Test Setup photos for FCC ID & IC.

※※※※※END OF THE REPORT※※※※※