





COMPANY	Shenzhen Stupu Technology Co., Ltd.
DESCRIPTION	PCB-mounted antenna
OUR MODEL NO	ST003
Dimension (mm)L*W*T	2.6*1.5*0.8


Central Frequency	2450	MHz
Bandwidth	120 (Min.)	MHz
Peak Gain	1.2	dBi
Impedance	50	Ohm
Operating Temperature	-40~+85	°C

二 .Return Loss



Address: Side A, 4th Floor, Building A3, Huafeng Century Technology Park, Xixiang Subdistrict,
Bao'an District, Shenzhen

三. 2D Radiation Patterns



	XZ-Plane		YZ-Plane		XY-Plane	
Frequency [MHz]	Max. Value (dB)	Ave. Value (dB)	Max. Value (dB)	Ave. Value (dB)	Max. Value (dB)	Ave. Value (dB)
2400 MHz	-3.3	-9.21	-5.95	-9.87	-3.11	-9.52
2450 MHz	-1.79	-6.72	-5.68	-8.42	-1.77	-8.19
2500 MHz	-2.17	-6.63	-3.32	-8.02	-1.2	-7.83

Address: Side A, 4th Floor, Building A3, Huafeng Century Technology Park, Xixiang Subdistrict, Bao'an District, Shenzhen