

MPE REPORT

Charging Station

MODEL No.: M1

FCC ID: 2BUNJ-M1

REPORT NO.: SZNTT26029432E1-2

ISSUE DATE: Aug. 11, 2026

Prepared for

Shenzhen Xianyang Innovation Technology Co., Ltd.

Rm 302, Bldg. 8, Yunli intelligent park, No. 7, Changfa Middle Rd,
Bantian st., Longgang Dist., Shenzhen, China

Prepared by

Shenzhen NTT Testing Technology Co.,Ltd.

1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang
Industrial Park, No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district,
Bao 'an District, Shenzhen City, Guangdong, China

TABLE OF CONTENT

Test Report Description	Page
1. SUMMARY OF TEST RESULT	4
2. GENERAL INFORMATION	5
2.1. DESCRIPTION OF DEVICE (EUT)	5
2.2. TEST SETUP	6
2.3. DESCRIPTION OF TEST FACILITY	7
2.4. MEASUREMENT UNCERTAINTY	7
3. MEASURING DEVICE AND TEST EQUIPMENT	8
3.1. FOR MPE MEASUREMENT	8
4. RF EXPOSURE	9
4.1. MEASURING STANDARD	9
4.2. REQUIMENTS	9
4.3. TEST CONFIGURATIO	10
4.4. LIMITS	11
4.5. MEASURING RESULTS	13
5. PHOTOGRAPHS OF TEST SETUP	15



TEST REPORT DESCRIPTION

Applicant : Shenzhen Xianyang Innovation Technology Co., Ltd.
Address : Rm 302, Bldg. 8, Yunli intelligent park, No. 7, Changfa Middle Rd,
Bantian st., Longgang Dist., Shenzhen, China
Manufacturer : Shenzhen Xianyang Innovation Technology Co., Ltd.
Address : Rm 302, Bldg. 8, Yunli intelligent park, No. 7, Changfa Middle Rd,
Bantian st., Longgang Dist., Shenzhen, China
EUT : Charging Station
Model Name : M1
Trademark : RORRY

Measurement Procedure Used:

FCC Part 1(1.1310) and Part 2(2.1091)
KDB 680106 D01 Wireless Power Transfer v04

The device described above is tested by Shenzhen NTT Testing Technology Co.,Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen NTT Testing Technology Co.,Ltd. is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen NTT Testing Technology Co.,Ltd.

Prepared by(Test Engineer):
Cindy Qin

Reviewer(Supervisor):
Ken Wu

Approved(Manager):
Abel Yu

1. SUMMARY OF TEST RESULT

EMISSION		
Description of Test Item	Standard & Limits	Results
MPE	FCC Part 1(1.1310) and Part 2(2.1091) KDB 680106 D01 Wireless Power Transfer v04	Pass
Note: N/A is an abbreviation for Not Applicable.		



2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT : Charging Station

Model Number : M1

Model different : /

Power Rating : USB-C1 Input: 9V $\overline{=}$ 3A
Pogo pin Output: 5V $\overline{=}$ 3A, 9V $\overline{=}$ 2A
Charger for iWatch: 5W Max
Charger for Earbuds/Phone: 15W Max

Operation : 111-205kHz for Phone and Earbuds

Frequency for WPT : 300-350kHz, 1778kHz for iWatch

Modulation : MSK


Antenna Type: : Coil Antenna

Date of Received : Jul. 15, 2026

Date of Test : Jul. 15, 2026 to Aug. 11, 2026



2.2. Test Setup



2.3. Description of Test Facility

Site Description

EMC Lab. : Designation Number: CN3446
Test Firm Registration Number: 129414
Accredited by ANAB, Dec. 19, 2025
The Certificate Registration Number is AT-3446
Name of Firm : Shenzhen NTT Testing Technology Co.,Ltd.
Site Location : 1B, Building 2, Factory Building & 103, Building 3, Factory Building,
Dayang Industrial Park, No.4, Industrial Avenue, Tangwei Community,
Fuhai Sub-district, Bao 'an District, Shenzhen City, Guangdong, China

2.4. Measurement Uncertainty

Parameter	Uncertainty
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Electric Field Emissions(0.3-3.0MHz)	$\pm 0.08\text{V/m}$
Magnetic Field Emissions(0.3-3.0MHz)	$\pm 0.02\text{A/m}$
uT	± 0.01



3. MEASURING DEVICE AND TEST EQUIPMENT

3.1. For MPE Measurement

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	Exposure Level Tester(9kHz-30MHz)	Narda	EHP-200A	180ZX00634	2027/6/10	2028/6/09

4. RF EXPOSURE

4.1.Measuring Standard

FCC Part 1(1.1310) and Part 2(2.1091)

4.2.Requiments

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- o Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- o Mobile Devices: a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- o Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

Occupational/Controlled Exposure: In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.

General Population/Uncontrolled Exposure: The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.



4.3. Test configuratio

1. The RF exposure test was performed in anechoic chamber.
2. E and H-field measurements should be made with these devices considered to meet the § 2.1091-Mobile conditions ("generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and [the nearest person]").
3. The highest emission level was recorded and compared with limit.
4. The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

4.4. Limits

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500	/	/	f/300	6
1,500-100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500	/	/	f/1500	30
1,500-100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

According to FCC 680106 D01 RF Exposure Charging Station Apps v04 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 - Section 1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):

	E-Field	*/*	B-Field
Frequency	V/m	A/m	uT
0.3 MHz – 3.0 MHz	614	1.613	2.0
3.0 MHz – 30 MHz	824/f (=27.5 _{30MHz})	2.19/f (=0.073 _{30MHz})	--

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.

Description of Support Unit

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Charging Station	N/A	M1	N/A	EUT
E-2	Mobile phone	N/A	Iqoo z9turbo	N/A	Auxiliary
E-3	Adapter	N/A	X2903	N/A	Auxiliary
E-4	iWatch	N/A	iWatch 5	N/A	Auxiliary

Test Mode:

Mode	Description
1	Wireless Output (Phone: 5W + iWatch: 2.5W)
2	Wireless Output (Phone: 7.5W + iWatch: 2.5W)
3	Wireless Output (Phone: 10W + iWatch: 2.5W)
4	Wireless Output (Phone: 15W + iWatch: 2.5W)
5	Wireless Output (Phone: 5W + iWatch: 5W)
6	Wireless Output (Phone: 7.5W + iWatch: 5W)
7	Wireless Output (Phone: 10W + iWatch: 5W)
8	Wireless Output (Phone: 15W + iWatch: 5W)
Remark: All the modes have tested and recorded the worst mode in the report.	

4.5. Measuring Results

For Mobile exposure conditions

Test Mode: Mode 1

Electric Field Emissions				
Test Position	Measure Value (V/m)	Limit(V/m)	50%Limit(V/m)	Distance(cm)
Top	1.4253	614	307	20
Left	1.2369	614	307	20
Right	1.2263	614	307	20
Rear	2.0121	614	307	20
Front	0.5023	614	307	20
Magnetic Field Emissions				
Test Position	Measure Value (A/m)	Limit(A/m)	50%Limit(A/m)	Distance(cm)
Top	0.0403	1.63	0.815	20
Left	0.0323	1.63	0.815	20
Right	0.0311	1.63	0.815	20
Rear	0.0453	1.63	0.815	20
Front	0.0278	1.63	0.815	20

Test Mode: Mode 4

Electric Field Emissions				
Test Position	Measure Value (V/m)	Limit(V/m)	50%Limit(V/m)	Distance(cm)
Top	1.4963	614	307	20
Left	1.3323	614	307	20
Right	1.3152	614	307	20
Rear	2.1236	614	307	20
Front	0.6023	614	307	20
Magnetic Field Emissions				
Test Position	Measure Value (A/m)	Limit(A/m)	50%Limit(A/m)	Distance(cm)
Top	0.0436	1.63	0.815	20
Left	0.0352	1.63	0.815	20
Right	0.0301	1.63	0.815	20
Rear	0.0526	1.63	0.815	20
Front	0.0280	1.63	0.815	20

Test Mode: Mode 8

Electric Field Emissions				
Test Position	Measure Value (V/m)	Limit(V/m)	50%Limit(V/m)	Distance(cm)
Top	1.5686	614	307	20
Left	1.3563	614	307	20
Right	1.3486	614	307	20
Rear	2.2960	614	307	20
Front	0.6690	614	307	20
Magnetic Field Emissions				



Test Position	Measure Value (A/m)	Limit(A/m)	50%Limit(A/m)	Distance(cm)
Top	0.0486	1.63	0.815	20
Left	0.0396	1.63	0.815	20
Right	0.0383	1.63	0.815	20
Rear	0.0675	1.63	0.815	20
Front	0.0363	1.63	0.815	20

Note:According to KDB 680106 D01, the 50% MPE limit is the threshold for RF-exposure evaluation exemption, not statutory absolute limit.

All measured E- field and H- field values at 20 cm are below 50% of MPE limit, so the WPT device qualifies for RF-exposure evaluation exemption under Mobile exposure condition § 2.1091.



5. PHOTOGRAPHS OF TEST SETUP

Please see the attachment for details.

-----End of Report-----