

TEST REPORT

FCC ID. :	2BUOD-KEMIT1	
Test Report No..... :	TCT260116E028	
Date of issue..... :	Jan. 30, 2026	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	SHENZHEN NEWLINK SOFTWARE CO., LTD	
Address..... :	504, Unit 4, Bldg 2, Runzhi R&D Center, No.5, Runfang Road, Xingdong Community, Bao'an District, Shenzhen, China	
Manufacturer's name	SHENZHEN NEWLINK SOFTWARE CO., LTD	
Address..... :	504, Unit 4, Bldg 2, Runzhi R&D Center, No.5, Runfang Road, Xingdong Community, Bao'an District, Shenzhen, China	
Standard(s)	FCC CFR Title 47 Part 1.1307 FCC CFR Title 47 Part 2.1091 447498 D01 General RF Exposure Guidance v06	
Product Name..... :	Kemi AI Smart Dual Screen	
Trade Mark	N/A	
Model/Type reference..... :	Refer to model list of page 3	
Rating(s)..... :	Adapter information: Model: KZ1902200 Input: AC 100-240V, 50/60Hz, 1.0A MAX Output: DC 19V, 2.2A, 41.8W Or DC 14.8V, 2600mAh Li-ion battery	
Date of receipt of test item	Dec. 17, 2025	
Date (s) of performance of test..... :	Dec. 17, 2025 ~ Jan. 30, 2026	
Tested by (+signature) ... :	Yannie ZHONG	
Check by (+signature).... :	Beryl ZHAO	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	4
2. General Information.....	4
2.1. Test environment and mode.....	5
2.2. Description of Support Units.....	5
3. Facilities and Accreditations	6
3.1. Facilities	6
3.2. Location	6
4. Limit.....	7
5. Test Results and Measurement Data	8

1. General Product Information

1.1. EUT description

Product Name	Kemi AI Smart Dual Screen
Model/Type reference	KEMI T1
Sample Number.....	TCT260116E012-0101
Operation Frequency.....	For BT/BLE: 2402MHz~2480MHz For 2.4G WIFI: 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)/802.11ax(HE20)) 2422MHz~2452MHz (802.11n(HT40)/802.11ax(HE40)) For 5G WIFI: Band 1: 5180 MHz~5240 MHz Band 2A: 5260 MHz~5320 MHz Band 2C: 5500 MHz~5700 MHz Band 3: 5745 MHz~5825 MHz
Modulation Type.....	For BT: GFSK, $\pi/4$ -DQPSK, 8DPSK For BLE: GFSK For 2.4G WIFI: 802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n: Orthogonal Frequency Division Multiplexing (OFDM) 802.11ax: Orthogonal Frequency-Division Multiple Access (OFDMA) For 5G WIFI: 802.11a/n: 64QAM, 16QAM, QPSK, BPSK 802.11ac: 256QAM, 64QAM, 16QAM, QPSK, BPSK 802.11ax: 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK
Antenna Type	FPC Antenna
Antenna Gain	For BT/BLE/2.4G WIFI: 2.73dBi For 5G WIFI: 3.27dBi
Rating(s)	Adapter information: Model: KZ1902200 Input: AC 100-240V, 50/60Hz, 1.0A MAX Output: DC 19V, 2.2A, 41.8W Or DC 14.8V, 2600mAh Li-ion battery

Note: 1. The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

2. 802.11ax not support partial RU mode, all test configurations are solely applicable to Full RU.

1.2. Model(s) list

No.	Model No.	Tested with
1	KEMI T1	☒
Other models	KEMI T*, KEMI T**, KEMI T***, KEMI S*, KEMI S**, KEMI S***, KEMI Q*, KEMI Q**, KEMI Q***, KEMI V*, KEMI V**, KEMI V***, KEMI W*, KEMI W**, KEMI W***("*" stands for numbers "1-9", letters "A-Z", "a-z", for different customers or shell colors, which do not affect safety or electromagnetic compatibility performance)	☐

Note: KEMI T1 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, schematics, and BOM lists. The different are the model names and enclosure colour for commercial purpose. So the test data of KEMI T1 can represent the remaining models.

2. General Information

2.1. Test environment and mode

Item	Normal condition
Temperature	+25°C
Voltage	AC 120V
Humidity	56%
Atmospheric Pressure:	1008 mbar
Test Mode:	
Transmitting Mode:	Keep the EUT in continuous transmitting by select channel

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4. Limit

According to §1.1310, the limit is as follow,

TABLE 1 TO § 1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
-----------------------	-------------------------------	-------------------------------	-------------------------------------	--------------------------

(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE

0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6

(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

5. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) **For BT:** The maximum output power for antenna is 6.74dBm (4.72mW) at 2480MHz, 2.73dBi antenna gain(with 1.87 numeric antenna gain.)

For BLE: The maximum output power for antenna is 6.76dBm (4.74mW) at 2480MHz, 2.73dBi antenna gain(with 1.87 numeric antenna gain.)

For 2.4G WIFI: The maximum output power for antenna is 18.66dBm (73.45mW) at 2437MHz, 2.73dBi antenna gain(with 1.87 numeric antenna gain.)

For 5G WIFI: The maximum output power for antenna is 13.54dBm (22.59mW) at 5700MHz, 3.27dBi antenna gain(with 2.12 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field Strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using $d=20\text{cm}$ into above equation.

Yields: $S=0.000199 \times P \times G$

Mode	Power(mW)	numeric antenna gain	Power density (mW/cm ²)	Limit (mW/cm ²)	Result
BT	4.72	1.87	0.001761	1.0	PASS
BLE	4.74	1.87	0.001769		
2.4G WIFI	73.45	1.87	0.027398		
5G WIFI	22.59	2.12	0.009544		

BT and WiFi transmission synchronization: $0.029167 < 1$

*******END OF REPORT*******