

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

| Modulation | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| GFSK       | 2.402               | -0.91                  | 0.81                  | 0±1                 | 1                       | 1.26                   | <5            | 0.39023            | 3.00                    | YES                |
|            | 2.441               | -0.13                  | 0.97                  | 0±1                 | 1                       | 1.26                   | <5            | 0.39338            | 3.00                    | YES                |
|            | 2.480               | 0.7                    | 1.17                  | 0±1                 | 1                       | 1.26                   | <5            | 0.39651            | 3.00                    | YES                |
| π/4-DQPSK  | 2.402               | -0.11                  | 0.97                  | 0±1                 | 1                       | 1.26                   | <5            | 0.39023            | 3.00                    | YES                |
|            | 2.441               | 0.64                   | 1.16                  | 0±1                 | 1                       | 1.26                   | <5            | 0.39338            | 3.00                    | YES                |
|            | 2.480               | 1.47                   | 1.40                  | 1±1                 | 2                       | 1.58                   | <5            | 0.49918            | 3.00                    | YES                |
| 8-DPSK     | 2.402               | 0.3                    | 1.07                  | 0±1                 | 1                       | 1.26                   | <5            | 0.39023            | 3.00                    | YES                |
|            | 2.441               | 1.05                   | 1.27                  | 1±1                 | 2                       | 1.58                   | <5            | 0.49524            | 3.00                    | YES                |
|            | 2.480               | 1.86                   | 1.53                  | 1±1                 | 2                       | 1.58                   | <5            | 0.49918            | 3.00                    | YES                |

**Conclusion:**

For the max result:  $0.50 \leq 3$  for 1g SAR, SAR is not required.

**Signature:**

*Alex Li*

**Date:** 2026-02-06

**NAME AND TITLE** (Please print or type): Alex Li/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China