



F2 Labs
16740 Peters Road
Middlefield, Ohio 44062
United States of America
www.f2labs.com

RF EXPOSURE REPORT

Manufacturer: Hum Industrial Technology Inc.
4220 Duncan Avenue, Suite 201
St. Louis, Missouri 63110 USA

Applicant: Same as Above

Product Name: ValveSense

Product Description: Sensor for monitoring the position of valves open/close

**Operating Voltage/Freq.
of EUT During Testing:** Battery-Operated (3.3V)

Model: HI24030101

FCC ID: 2BUPV-VS01

IC: 35176-VS01

Testing Commenced: 2026-05-26

Testing Ended: 2026-05-27

Test Results: In Compliance

The EUT complies with the EMC requirements when manufactured identically as the unit tested in this report, including any required modifications. Any changes to the design or build of this unit subsequent to this testing may deem it non-compliant.

Standards:

- KDB447498
- FCC 1.1310
- FCC 1.1307(b)(3)(i)(A)
- Safety Code 6
- RSS-102, Issue 6



Order No(s): F2P28727A-1-C1

Applicant: Hum Industrial Technology Inc.
Model: HI24030101

Evaluation Conducted by:

Erik Tobin, EMC Engineer

Report Reviewed by:

Ken Littell, Vice President of Operations

F2 Labs
26501 Ridge Road
Damascus, MD 20872
Ph 301.253.4500

F2 Labs
16740 Peters Road
Middlefield, OH 44062
Ph 440.632.5541

F2 Labs
8583 Zionsville Road
Indianapolis, IN 46268
Ph 317.610.0611

This test report may be reproduced in full; partial reproduction only may be made with the written consent of F2 Labs. The results in this report apply only to the equipment tested.



TABLE OF CONTENTS

1	<u>ADMINISTRATIVE INFORMATION</u>
2	<u>SUMMARY OF TEST RESULTS/MODIFICATIONS</u>
3	<u>ENGINEERING STATEMENT</u>
4	<u>EUT INFORMATION AND DATA</u>
5	<u>RF EXPOSURE FOR DEVICE <5mm FROM HUMAN</u>
	➤ <u>FCC</u>
	➤ <u>IC</u>



1 ADMINISTRATIVE INFORMATION

1.1 Measurement Location:

F2 Labs in Middlefield, Ohio.

Site description and attenuation data are on file with the FCC's Sampling and Measurement Branch at the FCC Laboratory in Columbia, MD.

Site description and attenuation data are on file with the Certification and Engineering Bureau, Industry Canada, Site Number 4730B.

1.2 Measurement Procedure:

All measurements were performed according to:

- KDB558074
- FCC 15.249
- RSS-210

1.4 Document History

Document Number	Description	Issue Date	Approved By
F2P28727A-1-C1-02E	First Issue	2026-05-27	K. Littell



2 SUMMARY OF TEST RESULTS

Test Name	Standard(s)	Results
RF Exposure for Device 5mm from Human	KDB447498 FCC 1.1310 FCC 1.1307(b)(3)(i)(A) Safety Code 6 RSS-102, Issue 6	Complies

Modifications Made to the Equipment
None



3 **ENGINEERING STATEMENT**

This report has been prepared on behalf of Hum Industrial Technology Inc. to provide documentation for the calculations described herein, based on the measurements taken in supporting Test Reports. This equipment has been tested, and calculations were found to comply with KDB447498, FCC 1.1310, FCC 1.1307(b)(3)(i)(A), Safety Code 6 and RSS-102 Issue 6. The test results found in this test report relate only to the item(s) tested.



4 EUT INFORMATION AND DATA

4.1 Equipment Under Test:

Product: ValveSense

Model: HI24030101


Serial No.: 1216930828

Firmware Version: 2.4.1

Hardware Version: V5R2

FCC ID: 2BUPV-VS01

IC: 35176-VS01



4.2 Trade Name:

Hum Industrial Technology Inc.

4.3 Power Supply:

Battery-Operated (3.3V)

4.4 Applicable Rules:

- KDB447498
- FCC 1.1310
- FCC 1.1307(b)(3)(i)(A)
- Safety Code 6
- RSS-102, Issue 6

4.5 Antenna:

Chip Antenna, -1.0dBi Gain

4.6 Accessories:

None

4.7 Test Item Condition:

The equipment to be tested was received in good condition.

**5. RF EXPOSURE FOR DEVICE <5mm FROM HUMAN****5.1 Requirements: Distance used is 5mm**

FCC	
Limit:	FCC 1.1307(b)(3)(i)(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.
Formula Used for Result:	$P(dBm) = E(dBuVm) + 20\log(d) - G - 104.77$
Results:	903 MHz was the highest $91.5 + 9.542425 + 1.0 - 104.77 = -2.73\text{dBm}$ $P(dBm) = -2.73$ which is 0.5333mW

IC	
Limit:	20mW per Table 11 in Section 6.3 of RSS-102 Issue 6
Formula Used for Result:	$P(dBm) = E(dBuVm) + 20\log(d) - G - 104.77$
Results:	903 MHz was the highest $91.5 + 9.542425 + 1.0 - 104.77 = -2.73\text{dBm}$ $P(dBm) = -2.73$ which is 0.5333mW