

SPECIFIC ABSORPTION RATE (SAR) EVALUATION REPORT

Report No.: 26020370HKG-001

For 2.4GHz and 13.56MHz Transceiver

Brand Name: **dyson**

FCC ID: 2BUQBOC01001

Prepared for

Dyson Operations Pte Ltd.

3 Sentosa Gateway,

098544, Singapore.

PREPARED AND CHECKED BY:

APPROVED BY:

Signed On File

Leung Pak To

Assistant Engineer

Date: 27 March, 2026

Digitally signed
by Herbert Wong
Location: Intertek
Testing Services
Hong Kong
Limited

Wong Cheuk Ho, Herbert

Assistant Manager

Date: 27 March, 2026

Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

© 2017 Intertek

TEST REPORT

TL-964

TABLE OF CONTENTS

1 Test Result Summary	3
2 General Information	5
3 SAR Measurement System Description	8
4 Tissue Verificaiton.....	16
5 SAR Measurement System Verification	19
6 SAR Evaluation.....	21
7 SAR Test Exclusion and Simultaneous Anlaysis.....	42
8 Test Equipment List.....	43
9 Measurement Uncertainty	44
10 E-Field Probe and Dipole Antenna Calibration.....	45
APPENDIX A – System Check Data	46
APPENDIX B – SAR Evaluation Data.....	47
APPENDIX C – E-Field Probe and Dipole Antenna Calibration.....	51
APPENDIX D – SAR System Validation.....	52

TEST REPORT

1. TEST RESULT SUMMARY

Applicant:	Dyson Operations Pte Ltd.
Applicant Address:	3 Sentosa Gateway, 098544, Singapore.
Brand Name:	dyson
Description of EUT:	2.4GHz and 13.56MHz Transceiver
FCC ID:	2BUQBOC01001
Serial Number:	4WZ-US-FKN0143X
Test Device:	Production Unit
EUT Exercising Software:	AmebaDPlus_mptool 1V13 Bluetooth RF test Tool (RtlBluetoothMP.dll Version:5.5.0.21 RTLBTAPP Version: 5.2.4.27) Tera Term 5
Exposure Category:	General Population/Uncontrolled Exposure
Sample Receive Date:	January 13, 2026
Date of Test:	February 24, 2026 to February 26, 2026
Test Location:	Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China.
Environmental Conditions:	Temperature: +18 to 25°C Humidity 25 to 75%
Test Specification:	ANSI/IEEE C95.1 IEEE Std 1528: 2013 FCC KDB Publication 447498 D01 v06 FCC KDB Publication 865664 D01 v01r04 FCC KDB Publication 865664 D02 v01r02 FCC KDB Publication 248227 D01 802 11 Wi-Fi SAR v02r02

TEST REPORT

TL-964

The maximum spatial peak SAR value for the sample device averaged over 1g was found to be:

Frequency Band	Operating Mode	TX Frequency (MHz)	Highest Reported SAR Body Exposure (W/kg)	SAR _{1g} Limit (W/kg)
2.4GHz WiFi	Data	2412 – 2472	1.330	1.6
2.4GHz Bluetooth 5.4 LE	Data	2402 – 2480	0.014	1.6
13.56MHz	Data	13.56	N/A	N/A
Highest Simultaneous Transmission SAR				
2.4GHz WiFi + 2.4GHz Bluetooth 5.4 LE + 13.56MHz			1.468	1.6

The maximum spatial peak SAR value for the sample device averaged over 10g was found to be:

Frequency Band	Operating Mode	TX Frequency (MHz)	Highest Reported SAR Limb Exposure (W/kg)	SAR _{10g} Limit (W/kg)
2.4GHz WiFi	Data	2412 – 2472	0.475	4.0
2.4GHz Bluetooth 5.4 LE	Data	2402 – 2480	0.004	4.0
13.56MHz	Data	13.56	N/A	N/A
Highest Simultaneous Transmission SAR				
2.4GHz WiFi + 2.4GHz Bluetooth 5.4 LE + 13.56MHz			0.5864	4.0

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment / general population exposure limits specified in ANSI/IEEE C95.1.

TEST REPORT

2. GENERAL INFORMATION


2.1. Description of Equipment Under Test (EUT)

Manufacturer:	Dyson Operations Pte Ltd.
Manufacturer Address:	3 Sentosa Gateway, 098544, Singapore.
Device Dimension (L x W):	260 (mm) x 45 (mm)
Device Thickness:	45mm (knob diameter) 30mm (handle diameter)
Antenna Type: (WiFi and Bluetooth)	Internal PCB Antenna, 1pc only (WiFi and Bluetooth Transmission use the same antenna)
Antenna Gain: (WiFi and Bluetooth)	1.78dBi
Antenna Type: (RFID)	Internal PCB Antenna
Antenna Gain: (RFID)	-57.90 dBi
EUT received condition:	Final Product with good operating condition
Operating Configuration(s) / Mode:	Body (Data), Limb (Data)
WiFi TX Frequency (MHz):	2412 MHz to 2472 MHz (802.11b, g, n20)
Duty Cycle*:	100%
Bluetooth TX Frequency (MHz):	2402 MHz to 2480 MHz (Bluetooth v5.4 LE)
Duty Cycle*:	100%
RFID TX Frequency (MHz):	13.56 MHz
Duty Cycle:	11.6%
H/W Version:	N/A
S/W Version:	N/A
Battery Type:	3.7V (1X 3.7VDC 1200mAh Li-ion rechargeable Battery)
Body-worn Accessories:	N/A

Note:

- *The SAR test of WiFi and Bluetooth were conducted in test mode with 100% to represent the worst case respectively.
- The production units are required to conform to the initial sample as received when the units are placed on the market.
- No SAR test of RFID was conducted.
- The test sample was provided by the client.

2.2. EUT Antenna Locations



EUT Front View

Exposure Position	Separation Distance from the Antenna to the Outer Surface (mm)
Front	20
Top	166
Left	2
Right	21
Back	5
Bottom	81

Details of antenna specification are shown in separate antenna dimension document.

TEST REPORT

TL-964

2.3 Nominal and Maximum Output Power Specifications

The EUT operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498.

Band	Operating Mode	TX Frequency (MHz)	Output Power	
			Nominal (dBm)	Maximum (dBm)
2.4GHz Wifi	802.11b 1Mbps	2412-2472	15.2	17
2.4GHz Wifi	802.11g 6Mbps	2412-2472	14.5	15.2
2.4GHz Wifi	802.11n20 MCS0	2412-2472	14.4	16
Bluetooth 5.4 LE	Data	2402-2480	3.1	4

TEST REPORT

TL-964

3. SAR MEASUREMENT SYSTEM DESCRIPTION

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of given mass density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/Kg)

SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

Where

- SAR is the specific absorption rate in watts per kilogram;
 - E is the r.m.s. value of the electric field strength in the tissue in volts per meter;
 - σ is the conductivity of the tissue in siemens per metre;
 - ρ is the density of the tissue in kilograms per cubic metre;
 - c_h is the heat capacity of the tissue in joules per kilogram and Kelvin;
- is the initial time derivative of temperature in the tissue in kelvins per second.

TEST REPORT

An SAR measurement system usually consists of a small diameter isotropic electric field probe, a multiple axis probe positioning system, a test device holder, one or more phantom models, the field probe instrumentation, a computer and other electronic equipment for controlling the probe and making the measurements. Other supporting equipment, such as a network analyzer, power meters and RF signal generators, are also required to measure the dielectric parameters of the simulated tissue media and to verify the measurement accuracy of the SAR system.

The SAR measurement system being used is COMOSAR system, which consists following items for performing compliance tests.




Figure 1: Schematic diagram of the SAR measurement system

- The PC. It controls most of the bench devices and stores measurement data. A computer running WinXP and the Opensar software.
- The E-Field probe. The probe is a 3-axis system made of 3 distinct dipoles. Each dipole returns a voltage in function of the ambient electric field.
- The Keithley multimeter measures each probe dipole voltages.
- The SAM phantom simulates a human head. The measurement of the electric field is made inside the phantom.
- The liquids simulate the dielectric properties of the human head tissues.
- The network emulator controls the mobile phone under test.
- The validation dipoles are used to measure a reference SAR. They are used to periodically check the bench to make sure that there is no drift of the system characteristics over time.
- The phantom, the device holder and other accessories according to the targeted measurement.

TEST REPORT

ROBOT

The COMOSAR system uses the KUKA robot from SATIMO SA (France). For the 6-axis controller COMOSAR system, the KUKA robot controller version from SATIMO is used.

The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller



TEST REPORT

COMOSAR E-FIELD PROBE

The SAR measurement is conducted with the dissymmetric probe manufactured by SATIMO. The probe is specially designed and calibrated for use in liquid with high permittivity. The dissymmetric probe has special calibration in liquid at different frequency. SATIMO conducts the probe calibration in compliance with international and national standards (e.g. IEC/IEEE 62209-1528:2020 and relevant KDB files). The calibration data are in Appendix C.

Model	SSE2
Manufacturer	MVG
Frequency	0.45GHz-6GHz Linearity: $\pm 0.08\text{dB}$
Dynamic Range	0.01W/Kg-100W/Kg Linearity: $\pm 0.08\text{dB}$
Dimensions	Overall length:330mm Length of individual dipoles:2mm Maximum external diameter:8mm Probe Tip external diameter:2.5mm Distance between dipoles/ probe extremity:1mm




TEST REPORT

VIDEO POSITIONING SYSTEM

The video positioning system is used in OpenSAR to check the probe. Which is composed of a camera, LED, mirror and mechanical parts. The camera is piloted by the main computer with firewire link.

During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



TEST REPORT

SAM TWIN PHANTOM

The SAM twin phantom is a fiberglass shell phantom with $2\text{mm} \pm 0.2\text{ mm}$ shell thickness (except the ear region where shell thickness increases to $6\text{mm} \pm 0.2\text{ mm}$), relative permittivity $\epsilon_r = 3.4$ and loss tangent $\delta = 0.02$. It has three measurement areas:

- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

TEST REPORT

ELLIPTICAL PHANTOM

The elliptical phantom is a fiberglass shell phantom with

- $2\text{mm} \pm 0.2\text{ mm}$ shell thickness
- relative permittivity $\epsilon_r = 3.4$
- loss tangent $\delta = 0.02$




DEVICE HOLDER

The COMOSAR device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The COMOSAR device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r = 3.7$ and loss tangent $\delta = 0.005$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



TEST REPORT

TL-964

During measurement, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom scanning area is greater than the projection of EUT and antenna.

Area Scan Parameters extracted from KDB 865664

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm $\pm$ 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm $\pm$ 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° $\pm$ 1°	20° $\pm$ 1°
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

When the maximum SAR point has been found, the system will then carry out a zoom (3D) scan centered at that point to determine volume averaged SAR level.

Zoom Scan Parameters extracted from KDB 865664

Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1) \text{ mm}$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB Publication 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

TEST REPORT

4. TISSUE VERIFICATION

For SAR measurement of field distribution inside phantom, homogeneous tissue simulating liquid as below liquid recipes were filled to a depth of 15cm $\pm$ 0.5cm for below 3GHz measurement and of 10cm $\pm$ 0.5cm for above 3GHz.

HEAD TISSUE RECIPES

Frequency	De-ionized Water	Salt	Ingredients			
			1,2 propanediol	DGBE	DGMH	Triton X100
450 MHz	33.5%	3.4%	63.1%			
750 MHz	34.2%	1.4%	64.4%			
900 MHz	35.3%	1.0%	63.7%			
1800 MHz	55.2%	0.6%		13.8%		30.4%
1900 MHz	55.3%	0.5%		13.8%		30.4%
2000 MHz	55.3%	0.4%		13.8%		30.5%
2450 MHz	55.7%	0.3%		18.7%		25.3%
5000 MHz	65.3%				17.2%	17.5%

BODY TISSUE RECIPES

Frequency	De-ionized Water	Salt	Ingredients			
			1,2 propanediol	DGBE	DGMH	Triton X100
450 MHz	52.4%	1.9%	45.7%			
750 MHz	55.4%	1.3%	43.3%			
900 MHz	52.9%	1.0%	46.1%			
1800 MHz	70.8%	0.5%		8.7%		20.0%
1900 MHz	70.1%	0.4%		8.9%		20.6%
2000 MHz	70.2%	0.3%		8.6%		20.9%
2450 MHz	70.8%	0.3%		8.7%		20.2%
5000 MHz	77.8%				11.7%	11.5%

TEST REPORT

The head tissue dielectric parameters recommended by the IEC/IEEE 62209-1528:2020 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. For other head and body tissue parameters, they are recommended by KDB 865664.

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	1.01	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and ρ = 1000 kg/m³)

When a transmission band overlaps with one of the target frequencies, the tissue dielectric parameters of the tissue medium at the middle of a device transmission band should be within $\pm 5\%$ of the parameters specified at that target frequency.

TEST REPORT

TL-964

The dielectric parameters of the liquids were verified prior to the SAR evaluation using SATIMO Dielectric Probe Kit and R&S Network Analyzer ZVL6.

The dielectric parameters were:

Head Liquid

Freq. (MHz)	Temp. (°C)	ϵ_r / Relative Permittivity			σ / Conductivity			ρ **(kg/m ³)
		Measured	Target*	Δ ($\pm 5\%$)	Measured	Target*	Δ ($\pm 5\%$)	
2450	24.6	38.3	39.2	-2.30	1.81	1.8	0.56	1000

* Target values refer to KDB 865664

** Worst-case assumption

Note:


1. Date of tissue verification measurement: 24 Feb 2026.
2. Ambient temperature: 25.0 deg C.
3. The temperature condition is within +/- 2 deg. C during the SAR measurements.

TEST REPORT

5. SAR MEASUREMENT SYSTEM VERIFICATION

Each SATIMO system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the SATIMO software, enable user to conduct the system check. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.



TEST REPORT

VALIDATION DIPOLE



The dipoles used is based on the IEC/IEEE 62209-1528:2020, and is complied with mechanical and electrical specifications in line with the requirements of both FCC and KDB requirement.

SYSTEM CHECK RESULTS

Date	Freq. (MHz)	Liquid Type	System Dipole	System Verification				
				Serial No.	Target SAR _{1g} (W/kg)	Measured SAR _{1g} (W/kg)	Normalized SAR _{1g} (W/kg)	Deviation (±10%)
24 Feb 2026	2450	Head	2450MHz	SN 22/16				
				DIP	50.04	5.031	50.31	0.54
				2G450-411				

Date	Freq. (MHz)	Liquid Type	System Dipole	System Verification				
				Serial No.	Target SAR _{10g} (W/kg)	Measured SAR _{10g} (W/kg)	Normalized SAR _{10g} (W/kg)	Deviation (±10%)
24 Feb 2026	2450	Head	2450MHz	SN 22/16				
				DIP	23.05	2.271	22.71	-1.48
				2G450-411				

* The target was quoted from dipole calibration report

* Input power level = 20dBm (0.1W)

SAR_{1g} and SAR_{10g} ambient measured value < 12 mW/kg

Details of System Verification plot is shown in the Appendix A - plot 1.

TEST REPORT

6. SAR EVALUATION

6.1. Device Test Positions Relative to the Head


This practice specifies two handset test positions against the head phantom—the “cheek” position and the “tilt” position. These two test positions are defined in the following subclauses. The handset should be tested in both positions on left and right sides of the SAM phantom. If handset construction is such that the handset positioning procedures described below to represent normal use conditions cannot be used, e.g., some asymmetric handsets, alternative alignment procedures should be adapted with all details provided in the test report. These alternative procedures should replicate intended use conditions as closely as possible according to the intent of the procedures described in this subclause.

TEST REPORT

DEFINITION OF THE CHEEK POSITION

The cheek position is established as follows:



1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in below figure), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see below left figure). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see right figure), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see the figure as next page), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.



TEST REPORT

TL-964

5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek.




TEST REPORT

DEFINITION OF THE TILT POSITION

The tilt position is established as follows:

1. Repeat steps to place the device in the cheek position.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See the figure below. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced.
5. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point on the handset is in contact with the phantom, e.g., the antenna with the back of the head.



TEST REPORT

6.2. Device test positions relative to body-worn accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $>1.2\text{W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be reported for that body-worn accessory with a headset attached to the handset.

SAR evaluation is required for body-worn accessories supplied with the host device. The test configurations must be conservative for supporting the body-worn accessory use conditions expected by users. Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components, either supplied with the product or available as an option from the device manufacturer, must be tested in conjunction with the host device to demonstrate compliance.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid.

TEST REPORT

6.3. Device test positions relative to Body-supported device

Per IEC/IEEE 62209-1528: 2020, a typical example of a body supported device is a wireless enabled laptop device that among other orientations may be supported on the thighs of a sitting user. To represent this orientation, the device shall be positioned with its base against the flat phantom. Other orientations may be specified by the manufacturer in the user instructions. If the intended use is not specified, the device shall be tested directly against the flat phantom in all usable orientations.

Devices that fall into this category include tablet type portable computers and credit card transaction authorization terminals, point-of-sale and/or inventory terminals. Where these devices may be torso or limb-supported, the same principles for body-supported devices are applied.

The example in Figure a) shows a tablet form factor portable computer for which SAR should be separately assessed with each surface and the separation distances positioned against the flat phantom that correspond to the intended use as specified by the manufacturer. If the intended use is not specified in the user instructions, the device shall be tested directly against the flat phantom in all usable orientations.





Figure a) – Tablet form factor portable computer

TEST REPORT

TL-964

A block diagram of testing procedure is shown as below figure.



IEC


TEST REPORT

6.4. General Device Setup

The device was first charged on a charger over a duration defined by the applicant to make sure the installed battery was fully charged.

The device was then placed into test mode to simulate the worst case configuration through the highest power channel, where the operating parameters established in this test mode is identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequency is corresponded to actual channel frequencies defined for domestic use.

During testing, the device was evaluated with a fully charged battery, power saving function disabled and was configured to operate at maximum output power. A receive antenna and a spectrum analyzer were placed with a distance > 50cm away from the device to monitor the transmission states.



TEST REPORT

TL-964

6.5. RF Output Power Measurements

WiFi 2.4GHzF

Mode	Frequency (MHz)	Channel	Duty Cycle	Measured Conducted Power (Peak) (dBm)	Maximum Tune-up Conducted Power (dBm)	Maximum Tune-up Conducted Power (Time Average) (dBm)
802.11b 1Mbps	2412	1	100%	14.9	15.5	15.5
	2442	7		13.6	15.5	15.5
	2467	12		15.2	15.5	15.5
	2472	13		16.5	17	17
802.11g 6Mbps	2412	1	100%	14.5	15.2	15.2
	2442	7		14.9	15.2	15.2
	2467	12		13.3	15.2	15.2
	2472	13		4.4	6	6
802.11n20 MSCO	2412	1	100%	14.4	16	16
	2442	7		15.3	16	16
	2467	12		14.2	16	16
	2472	13		1.1	2	2

Bluetooth 5.4 LE

Mode	Frequency (MHz)	Channel	Duty Cycle	Measured Conducted Power (Peak) (dBm)	Maximum Tune-up Conducted Power (dBm)	Maximum Tune-up Conducted Power (Time Average) (dBm)
Bluetooth 5.4 LE	2402	1	100%	3.4	4	4
	2440	20		3.1	4	4
	2480	40		2.6	4	4

TEST REPORT

TL-964

Note:

1. Time Average power (dBm) = Power (dBm) + Time Average factor.
2. Time Average factor = $10 \cdot \log(\text{duty cycle})$
3. Per KDB 447498, the tested device was within the specified tune-up tolerances range, but not more than 2dB lower than the maximum tune-up tolerance limit.
4. Per KDB 447498, when antenna port was not available on the device to support conducted power measurement and test software was used to establish transmitter power levels, the power level was verified separately according to design and component specifications and product development information specified by the manufacturer.

TEST REPORT

TL-964

6.6. SAR Test Exclusion Consideration for Adjacent Edges

The Exemption limits for Routine Evaluation – SAR Evaluation in KDB 447498 can be applied to determine SAR test exclusion for adjacent edge configurations.

The test separation distance for SAR test exclusion of adjacent edges is determined by the closest distance between the antenna and outer housing on the adjacent edge of the device.

According to the antenna to outer housing separation distance and maximum time-averaged output power as below, SAR evaluation of all edges are not required for BLE while SAR evaluation of top and bottom are not required for WiFi.

However, client optional decided to keep left position for data evaluation for BLE.

WiFi 2.4G

Exposure Position	Antenna to Outer Housing Separation Distance	SAR Exemption Limit	Maximum Tune-up Time-Averaged Conducted Power	SAR Exclusion Result
Front	20mm	38mW	50.1mW	Test required
Top	166mm	>96mW		Excluded
Left	2mm	10mW		Test required
Right	21mm	40mW		Test required
Back	5mm	10mW		Test required
Bottom	81mm	>96mW		Excluded

Bluetooth

Exposure Position	Antenna to Outer Housing Separation Distance	SAR Exemption Limit	Maximum Tune-up Time-Averaged Conducted Power	SAR Exclusion Result
Front	20mm	38mW	2.5mW	Excluded
Top	166mm	>96mW		Excluded
Left	2mm	10mW		Test required ¹
Right	21mm	40mW		Excluded
Back	5mm	10mW		Excluded
Bottom	81mm	>96mW		Excluded

Note:

- Client optional decided to keep left for data evaluation.

TEST REPORT

TL-964

6.7. Exposure Conditions

Body Exposure Conditions

Test Configurations	Band	Operation Mode	SAR Required	Note
Front 0mm Separation	WiFi 2.4GHz	Data	Yes	
Top 0mm Separation	WiFi 2.4GHz	Data	No	SAR test exclusion applied
Left 0mm Separation	WiFi 2.4GHz	Data	Yes	
Right 0mm Separation	WiFi 2.4GHz	Data	Yes	
Back 0mm Separation	WiFi 2.4GHz	Data	Yes	
Bottom 0mm Separation	WiFi 2.4GHz	Data	No	SAR test exclusion applied
Front 0mm Separation	Bluetooth	Data	No	SAR test exclusion applied
Top 0mm Separation	Bluetooth	Data	No	SAR test exclusion applied
Left 0mm Separation	Bluetooth	Data	Yes ²	
Right 0mm Separation	Bluetooth	Data	No	SAR test exclusion applied
Back 0mm Separation	Bluetooth	Data	No	SAR test exclusion applied
Bottom 0mm Separation	Bluetooth	Data	No	SAR test exclusion applied

Note:

1. Per KDB 447498 D01, SAR Evaluation can be applied to determine SAR test exclusion for adjacent edge configuration.
2. Client optional decided to keep left position for data evaluation for Bluetooth.
3. For front, back, right and left, the EUT is positioned inclined.

TEST REPORT

6.8. Test Result

The results on the following page(s) were obtained when the device was tested in the condition described in this report. Detailed measurement data and plots, which reveal information about the location of the maximum SAR with respect to the device, are reported in Appendix B.

Body Exposure SAR – 802.11b 1Mbps

					Measurement Result						
					Maximum					Reported	Plot
Chan	Freq. (MHz)	Battery	Mode	Test Position	Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{1g} (W/kg)	Scaling factor	SAR _{1g} (W/kg)	
13	2472	3.7V	Data	Left 0mm	17	16.5	-1.56	1.097	1.12	1.231	1
13	2472	3.7V	Data	Left 0mm	17	16.5	-0.52	1.185	1.12	1.330	
13	2472	3.7V	Data	Front 0mm	17	16.5	-1.31	0.195	1.12	0.219	
13	2472	3.7V	Data	Back 0mm	17	16.5	-2.22	0.505	1.12	0.567	
13	2472	3.7V	Data	Right 0mm	17	16.5	-4.13	0.382	1.12	0.429	
1	2412	3.7V	Data	Left 0mm	15.5	14.9	-4.5	0.204	1.15	0.234	
7	2442	3.7V	Data	Left 0mm	15.5	13.6	-4.67	0.375	1.55	0.581	
12	2467	3.7V	Data	Left 0mm	15.5	15.2	-4.34	0.499	1.07	0.535	

Limb Exposure SAR – 802.11b 1Mbps

					Measurement Result						
					Maximum					Reported	Plot
Chan	Freq. (MHz)	Battery	Mode	Test Position	Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{10g} (W/kg)	Scaling factor	SAR _{10g} (W/kg)	
13	2472	3.7V	Data	Left 0mm	17	16.5	-0.52	0.475	1.12	0.533	1
13	2472	3.7V	Data	Front 0mm	17	16.5	-1.31	0.071	1.12	0.080	
13	2472	3.7V	Data	Back 0mm	17	16.5	-2.22	0.224	1.12	0.251	
13	2472	3.7V	Data	Right 0mm	17	16.5	-4.13	0.155	1.12	0.174	
1	2412	3.7V	Data	Left 0mm	15.5	14.9	-4.5	0.08	1.15	0.092	
7	2442	3.7V	Data	Left 0mm	15.5	13.6	-4.67	0.146	1.55	0.226	
12	2467	3.7V	Data	Left 0mm	15.5	15.2	-4.34	0.197	1.07	0.211	

TEST REPORT

Note:

1. Fully charged batteries were used at the beginning of each SAR measurement.
2. There was no power reduction used for any band/mode implemented in this device.
3. Reported SAR results were scaled to the maximum allowed power with the scaling factor equation $-10^{[(\text{Maximum power} - \text{measured power}) / 10]}$.
4. Per KDB 447498 D01 for Body exposure, if the reported SAR value was ≤ 0.8 W/kg and the transmission band was ≤ 100 MHz, SAR testing was not required for the other test channels in the band.
5. Per KDB 447498 D01 for Limb exposure, if the reported SAR value was ≤ 2.0 W/kg and the transmission band was ≤ 100 MHz, SAR testing was not required for the other test channels in the band.
6. Per KDB 865664 D01 for Body exposure, repeated measurement was required when the original highest measured SAR was > 0.8 W/kg and analysis details were shown as below.
7. Per KDB 865664 D01 for Limb exposure, repeated measurement was not required when the original highest measured SAR was < 2.0 W/kg.
8. Per KDB 865664 D02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode, and frequency band combination.
9. Per KDB 865664 D01, when the maximum output power variation across the required test channels was < 0.5 dB, measurement on the middle channel was required.
10. The EUT is positioned inclined during testing.

TEST REPORT

Per KDB 865664 D01, measurement variability was assessed using the following procedures,

1. When the original highest measured SAR is $\geq 0.80\text{W/kg}$, repeat that measurement once.
2. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurement is ≥ 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/kg}$ (~ 10% from the 1-g SAR limit).
3. Perform a third repeated measurement only if the ratio of largest to smallest SAR for the original, first and second repeated measurement is $\geq 1.5\text{ W/kg}$ and the ratio of largest to smallest SAR for the original, first and second repeated measurement is > 1.20 .

Body Exposure SAR – 802.11b 1Mbps

Measurement Variability Result								
Chan	Freq. (MHz)	Band	Test Position	Measured SAR _{1g} (W/kg)	1 st repeated SAR _{1g} (W/kg)	Ratio	2 nd repeated SAR _{1g} (W/kg)	Ratio
13	2472	802.11b 1Mbps	Left 0mm	1.097	1.185	1.080	--	--

TEST REPORT

Body Exposure SAR – 802.11g 6Mbps

					Measurement Result						
					Maximum					Reported	
Chan	Freq. (MHz)	Battery	Mode	Test Position	Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{1g} (W/kg)	Scaling factor	SAR _{1g} (W/kg)	Plot
7	2442	3.7V	Data	Left 0mm	15.2	14.9	-4.38	0.376	1.07	0.403	2
7	2442	3.7V	Data	Front 0mm	15.2	14.9	-4.34	0.181	1.07	0.194	
7	2442	3.7V	Data	Back 0mm	15.2	14.9	-4.34	0.117	1.07	0.125	
7	2442	3.7V	Data	Right 0mm	15.2	14.9	-3.45	0.072	1.07	0.077	
1	2412	3.7V	Data	Left 0mm	15.2	14.5	-4.9	0.218	1.17	0.256	
12	2467	3.7V	Data	Left 0mm	15.2	13.3	-4.67	0.183	1.55	0.283	
13	2472	3.7V	Data	Left 0mm	6	4.4	-2.56	0.024	1.45	0.035	

Limb Exposure SAR – 802.11g 6Mbps

					Measurement Result						
					Maximum					Reported	
Chan	Freq. (MHz)	Battery	Mode	Test Position	Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{10g} (W/kg)	Scaling factor	SAR _{10g} (W/kg)	Plot
7	2442	3.7V	Data	Left 0mm	15.2	14.9	-4.38	0.151	1.07	0.162	2
7	2442	3.7V	Data	Front 0mm	15.2	14.9	-4.34	0.068	1.07	0.073	
7	2442	3.7V	Data	Back 0mm	15.2	14.9	-4.34	0.049	1.07	0.053	
7	2442	3.7V	Data	Right 0mm	15.2	14.9	-3.45	0.028	1.07	0.030	
1	2412	3.7V	Data	Left 0mm	15.2	14.5	-4.9	0.084	1.17	0.099	
12	2467	3.7V	Data	Left 0mm	15.2	13.3	-4.67	0.069	1.55	0.107	
13	2472	3.7V	Data	Left 0mm	6	4.4	-2.56	0.008	1.45	0.012	

TEST REPORT

Note:

1. Fully charged batteries were used at the beginning of each SAR measurement.
2. There was no power reduction used for any band/mode implemented in this device.
3. Reported SAR results were scaled to the maximum allowed power with the scaling factor equation $-10^{[(\text{Maximum power} - \text{measured power}) / 10]}$.
4. Per KDB 447498 D01 for Body exposure, if the reported SAR value was $\leq 0.8 \text{ W/kg}$ and the transmission band was $\leq 100\text{MHz}$, SAR testing was not required for the other test channels in the band.
5. Per KDB 447498 D01 for Limb exposure, if the reported SAR value was $\leq 2.0 \text{ W/kg}$ and the transmission band was $\leq 100\text{MHz}$, SAR testing was not required for the other test channels in the band.
6. Per KDB 865664 D01 for Body exposure, repeated measurement was not required when the original highest measured SAR was $< 0.8\text{W/kg}$.
7. Per KDB 865664 D01 for Limb exposure, repeated measurement was not required when the original highest measured SAR was $< 2.0\text{W/kg}$.
8. Per KDB 865664 D02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode, and frequency band combination.
9. Per KDB 865664 D01, when the maximum output power variation across the required test channels was $< 0.5\text{dB}$, measurement on the middle channel was required.
10. The EUT is positioned inclined during testing.

TEST REPORT

TL-964

Body Exposure SAR – 802.11n20 MSC0

Measurement Result											
Chan	Freq. (MHz)	Battery	Mode	Test Position	Maximum Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{1g} (W/kg)	Scaling factor	Reported SAR _{1g} (W/kg)	Plot
7	2442	3.7V	Data	Left 0mm	16	15.3	0.61	0.193	1.17	0.227	3
7	2442	3.7V	Data	Front 0mm	16	15.3	0.85	0.012	1.17	0.014	
7	2442	3.7V	Data	Back 0mm	16	15.3	-1.06	0.136	1.17	0.160	
7	2442	3.7V	Data	Right 0mm	16	15.3	-1.31	0.086	1.17	0.101	
1	2412	3.7V	Data	Left 0mm	16	14.4	-2.75	0.147	1.45	0.212	
12	2467	3.7V	Data	Left 0mm	16	14.2	-4.16	0.149	1.51	0.226	
13	2472	3.7V	Data	Left 0mm	2	1.1	1.90	0.009	1.23	0.011	

Limb Exposure SAR – 802.11n20 MSC0

Measurement Result											
Chan	Freq. (MHz)	Battery	Mode	Test Position	Maximum Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{10g} (W/kg)	Scaling factor	Reported SAR _{10g} (W/kg)	Plot
7	2442	3.7V	Data	Left 0mm	16	15.3	0.61	0.075	1.17	0.088	3
7	2442	3.7V	Data	Front 0mm	16	15.3	0.85	0.004	1.17	0.005	
7	2442	3.7V	Data	Back 0mm	16	15.3	-1.06	0.06	1.17	0.070	
7	2442	3.7V	Data	Right 0mm	16	15.3	-1.31	0.034	1.17	0.040	
1	2412	3.7V	Data	Left 0mm	16	14.4	-2.75	0.055	1.45	0.079	
12	2467	3.7V	Data	Left 0mm	16	14.2	-4.16	0.055	1.51	0.083	
13	2472	3.7V	Data	Left 0mm	2	1.1	1.90	0.003	1.23	0.004	

TEST REPORT

Note:

1. Fully charged batteries were used at the beginning of each SAR measurement.
2. There was no power reduction used for any band/mode implemented in this device.
3. Reported SAR results were scaled to the maximum allowed power with the scaling factor equation $-10^{[(\text{Maximum power} - \text{measured power}) / 10]}$.
4. Per KDB 447498 D01 for Body exposure, if the reported SAR value was $\leq 0.8 \text{ W/kg}$ and the transmission band was $\leq 100\text{MHz}$, SAR testing was not required for the other test channels in the band.
5. Per KDB 447498 D01 for Limb exposure, if the reported SAR value was $\leq 2.0 \text{ W/kg}$ and the transmission band was $\leq 100\text{MHz}$, SAR testing was not required for the other test channels in the band.
6. Per KDB 865664 D01 for Body exposure, repeated measurement was not required when the original highest measured SAR was $< 0.8\text{W/kg}$.
7. Per KDB 865664 D01 for Limb exposure, repeated measurement was not required when the original highest measured SAR was $< 2.0\text{W/kg}$.
8. Per KDB 865664 D02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode, and frequency band combination.
9. Per KDB 865664 D01, when the maximum output power variation across the required test channels was $< 0.5\text{dB}$, measurement on the middle channel was required.
10. The EUT is positioned inclined during testing.

TEST REPORT

TL-964

Body Exposure SAR – Bluetooth 5.4 LE

					Measurement Result						
Chan	Freq. (MHz)	Battery	Mode	Test Position	Maximum Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{1g} (W/kg)	Scaling factor	Reported SAR _{1g} (W/kg)	Plot
1	2402	3.7V	Data	Left 0mm	4	3.4	2.46	0.009	1.15	0.010	
20	2440	3.7V	Data	Left 0mm	4	3.1	2.97	0.007	1.23	0.009	
40	2480	3.7V	Data	Left 0mm	4	2.6	-2.18	0.010	1.38	0.014	4

Limb Exposure SAR – Bluetooth 5.4 LE

					Measurement Result						
Chan	Freq. (MHz)	Battery	Mode	Test Position	Maximum Allowed Power (dBm)	Measured Power (dBm)	SAR Drift (%)	Measured SAR _{1g} (W/kg)	Scaling factor	Reported SAR _{1g} (W/kg)	Plot
1	2402	3.7V	Data	Left 0mm	4	3.4	2.46	0.002	1.15	0.002	
20	2440	3.7V	Data	Left 0mm	4	3.1	2.97	0.002	1.23	0.002	
40	2480	3.7V	Data	Left 0mm	4	2.6	-2.18	0.003	1.38	0.004	4

Note:

- Fully charged batteries were used at the beginning of each SAR measurement.
- There was no power reduction used for any band/mode implemented in this device.
- Reported SAR results were scaled to the maximum allowed power with the scaling factor equation $-10^{[(\text{Maximum power} - \text{measured power}) / 10]}$.
- Per KDB 447498 D01 for Body exposure, if the reported SAR value was ≤ 0.8 W/kg and the transmission band was ≤ 100 MHz, SAR testing was not required for the other test channels in the band.
- Per KDB 447498 D01 for Limb exposure, if the reported SAR value was ≤ 2.0 W/kg and the transmission band was ≤ 100 MHz, SAR testing was not required for the other test channels in the band.
- Per KDB 865664 D01 for Body exposure, repeated measurement was not required when the original highest measured SAR was < 0.8 W/kg.
- Per KDB 865664 D01 for Limb exposure, repeated measurement was not required when the original highest measured SAR was < 2.0 W/kg.
- Per KDB 865664 D02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode, and frequency band combination.
- Per KDB 865664 D01, when the maximum output power variation across the required test channels was < 0.5 dB, measurement on the middle channel was required.
- The EUT is positioned inclined during testing.

TEST REPORT

SAR Limits

The following FCC limits (Std. C95.1-1992) for SAR apply to devices operate in General Population/Uncontrolled Exposure and Controlled environment:

GENERAL POPULATION / UNCONTROLLED ENVIRONMENTS:

Defined as location where there is the exposure of individuals who have no knowledge or control of their exposure.

EXPOSURE (General Population/Uncontrolled Exposure environment)	SAR (W/kg)
Spatial Peak SAR (Head)*	1.60
Spatial Peak SAR (Partial Body)*	1.60
Spatial Peak SAR (Whole Body)*	0.08
Spatial Peak SAR (Hands / Wrists / Feet / Ankles)**	4.00

OCCUPATIONAL / CONTROLLED ENVIRONMENTS:

Defined as location where there is the exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation)

EXPOSURE (Occupational/Controlled Exposure environment)	SAR (W/kg)
Spatial Peak SAR (Head)*	8.00
Spatial Peak SAR (Partial Body)*	8.00
Spatial Peak SAR (Whole Body)*	0.40
Spatial Peak SAR (Hands / Wrists / Feet / Ankles)**	20.00

Notes:

- * The Spatial Peak value of the SAR averaged over any 1 gram of tissue.
(defined as a tissue volume in the shape of a cube) and over the appropriate averaging time
- ** The Spatial Peak value of the SAR averaged over any 10 gram of tissue.
(defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

TEST REPORT

7. SAR TEST EXCLUSION AND SIMULTANEOUS ANALYSIS

7.1 SAR Test Exclusion RFID

The SAR test exclusion threshold for the RFID transmitter as per FCC KDB 447498 D01 clause 4.3.1 is as follows:

Conducted Power in Peak (maximum)
= 16 dBm (39.81 mW)

The SAR Exclusion Threshold Level 13.56MHz when the minimum test separation distance is < 50mm:
= $[474 * (1 + \log_{10}(f(\text{MHz})))]/2$
= $[474 * (1 + \log_{10}(13.56))]/2$ mW
= 442.65 mW

The RFID transmitter meets the SAR test exclusion threshold

7.2 Simultaneous SAR Evaluation

Since the 2.4GHz Wi-Fi, Bluetooth BLE and RFID transmitters of this device may operate simultaneously, simultaneous transmission analysis is required. Per KDB447498 D01 v06, simultaneous transmission SAR test exclusion can be applied when the sum of 1-g SAR and the sum of 10-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR_{1g} limit ($\leq 1.6\text{W/kg}$) and the SAR_{10g} limit ($\leq 4\text{W/kg}$). When the standalone SAR test exclusion is applied, the standalone 1-g SAR and 10-g SAR must be estimated according to the following equation,

$$\text{Estimated SAR} = (\sqrt{F(\text{GHz}/x)} \times (P_{\text{max}}/TD))$$

where

$F(\text{GHz})$ is the RF channel transmit frequency in GHz

P_{max} is the max. power of channel, including tune-up tolerance, mW

TD is the min. test separation distance, mm

$x=7.5$ for 1g SAR and $x = 18.75$ for 10g SAR

For RFID operation,

Maximum Time-averaged Conducted Power of this device = 39.81 mW (16dBm)

Therefore, the Estimated SAR will be determined as follow,

Estimated SAR = 0.123621 W/kg for 1g

Estimated SAR = 0.0494482 W/kg for 10g

where $P_{\text{max}} = 39.81$ mW, $TD = 5$ mm and $F(\text{GHz}) = 0.01356$ GHz

Simultaneous Transmission Analysis

Body Exposure SAR

2.4GHz Wi-Fi Measured SAR (W/kg)	Bluetooth BLE Measured SAR (W/kg)	RFID Estimated SAR (W/kg)	Σ SAR (W/kg)	Simultaneous SAR Required
1.33	0.014	0.1236	1.468	No

Limb Exposure SAR

2.4GHz Wi-Fi Measured SAR (W/kg)	Bluetooth BLE Measured SAR (W/kg)	RFID Estimated SAR (W/kg)	Σ SAR (W/kg)	Simultaneous SAR Required
0.533	0.004	0.0494	0.5864	No

Conclusion

Since the above summed SAR result for all simultaneous transmission conditions were below the 1g SAR limit (1.6 W/kg) and below the 10g SAR limit (4W/kg), SAR evaluation for simultaneous transmission configuration is not required.

TEST REPORT

8. TEST EQUIPMENT LIST

Equipment	Registration No.	Manufacturer	Model No.	Calibration Date	Calibration Due Date
SAR System	EW-3211	MVG	SATIMO System (OpenSAR Software V5)	N/A	N/A
Phantom	EW-3211	SATIMO	COMOSAR SAM PHANTOM	N/A	N/A
SAR Probe	EW-3210	MVG	SSE2 (SN 36/20 EPGO347)	05 Jun 2025	05 Jun 2026
SAR Dipole	EW-3212	MVG	SN 22/16 DIP2G450-411	13 Jun 2025	13 Jun 2026
Dielectric Probe for SAR Test	EW-3213	MVG	Liquid Measurement Kit (SN 24/16 OCPG 76)	13 Jun 2025	13 Jun 2026
Digital Multimeter	EW-3206	KEITHLEY	2000	23 Jun 2025	23 Jun 2026
Network Analyzer	EW-3192	Rhode & Schwarz	ZVL6	18 Jul 2025	18 Jul 2026
Plastic Ruler	EW-3084	MUJI	30cm	23 Jan 2024	23 Jan 2027
Signal and Spectrum Analyzer (9kHz to 13.6GHz)	EW-2839	Rhode & Schwarz	FSP13	18-Dec-2024	18-Mar-2026
Precision Dual Coupler (0.8-3GHz 20dB)	EW-3184	VectaWave USA	VDC0830-20	04 Sep 2025	04 Sep 2026
SAR Amplifier	EW-3275	SATIMO	SAR Amplifier	18 Jul 2025	18 Jul 2026
Digital Thermo-Meter for SAR test	EW-2901	TES	1306	26 Jun 2025	26 Jun 2026
Signal Generator (100kHz to 40GHz)	EW-1983	AGILENTTECH	E8247C	24 Dec 2025	24 Dec 2027
Wideband power sensor 2 pcs 50MHz to 18GHz	EW-3309	Rhode & Schwarz	NRP-Z81	29 Jul 2025	29 Jul 2026
Thermohydrometer	EW- 3043	OREGON	THG312	18-Sep-2025	18-Sep-2026

TEST REPORT

TL-964

9. MEASUREMENT UNCERTAINTY

Per FCC KDB 865884, the extensive SAR measurement uncertainty analysis was not required when the highest measured SAR was $< 1.5\text{W/kg}$ for all frequency band.

Decision Rule for compliance: For FCC/IC standard, the measured value must be within the limits of applicable standard without accounting for the measurement uncertainty. For EN/IEC/HKTA/HKTC standard, conformity rules will be used as per standard directly excepted EN/IEC 61000-3-2, EN/IEC 61000-3-3, HKTA1004, HKCA1008, HKTA1019, HKTA1020, HKTA1041 and HKTA1044.

TEST REPORT

10. E-FIELD PROBE AND DIPOLE ANTENNA CALIBRATION

Probe calibration factors and dipole antenna calibration are included in Appendix C.

TEST REPORT

TL-964

APPENDIX A – SYSTEM CHECK DATA

Plot #1

Operating Frequency: 2450MHz
Medium (Liquid Type): 2450 Head
Test Date: 24 Feb 2026


A. Experimental conditions.

Probe	SN 36/20 EPG0347
ConvF	2.26
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels/Frequency	2450MHz
Signal	CW

B. Permittivity

Middle TX Frequency (MHz)	2450.000
Relative permittivity (real part)	38.300
Relative permittivity (imaginary part)	13.579
Conductivity (S/m)	1.810

C. SAR Surface and Volume



Maximum location: X=-1.00, Y=2.00 ; SAR Peak: 9.37 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.271
SAR 1g (W/Kg)	5.031
Variation (%)	-0.780
Horizontal validation criteria: minimum distance (mm)	11.180340
Vertical validation criteria: SAR ratio M2/M1 (%)	47.460858

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	9.449	5.480	2.601	1.283	0.637	0.318	0.166

TEST REPORT

TL-964

APPENDIX B – SAR EVALUATION DATA

Plot #1

Operating Frequency: 2472MHz

Medium (Liquid Type): 2450 Head

Product Description: 2.4GHz and 13.56MHz Transceiver

Serial Number: 4WZ-US-FKN0143X (3.7VDC 1200mAh Li-ion rechargeable Battery)

Duty Cycle: 1:1

Test Date: 24 Feb 2026


A. Experimental conditions.

Probe	SN 36/20 EPG0347
ConvF	2.26
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Left 0mm separation
Band	(2412 – 2472) MHz
Channels/Frequency	(13)/ frequency 2472.000 MHz
Signal	IEEE 802.11 b

B. Permittivity

Middle TX Frequency (MHz)	2472.000
Relative permittivity (real part)	38.300
Relative permittivity (imaginary part)	13.579
Conductivity (S/m)	1.810

C. SAR Surface and Volume



Maximum location: X=0.00, Y=-2.00 ; SAR Peak: 2.42 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.475
SAR 1g (W/Kg)	1.185
Variation (%)	-0.52
Horizontal validation criteria: minimum distance (mm)	10.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	41.651954

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.441	1.329	0.554	0.224	0.092	0.032	0.015

TEST REPORT

TL-964

APPENDIX B – SAR EVALUATION DATA

Plot #2

Operating Frequency: 2442MHz

Medium (Liquid Type): 2450 Head

Product Description: 2.4GHz and 13.56MHz Transceiver

Serial Number: 4WZ-US-FKN0143X (3.7VDC 1200mAh Li-ion rechargeable Battery)

Duty Cycle: 1:1

Test Date: 24 Feb 2026


A. Experimental conditions.

Probe	SN 36/20 EPG0347
ConvF	2.26
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Left 0mm separation
Band	(2412 – 2472) MHz
Channels/Frequency	(7)/ frequency 2442.000 MHz
Signal	IEEE 802.11 g

B. Permittivity

Middle TX Frequency (MHz)	2442.000
Relative permittivity (real part)	38.300
Relative permittivity (imaginary part)	13.579
Conductivity (S/m)	1.810

C. SAR Surface and Volume



Maximum location: X=-16.00, Y=-8.00 ; SAR Peak: 0.78 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.151
SAR 1g (W/Kg)	0.376
Variation (%)	-4.380
Horizontal validation criteria: minimum distance (mm)	10.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	40.053503

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.833	0.414	0.144	0.064	0.027	0.014	0.006

TEST REPORT

TL-964

APPENDIX B – SAR EVALUATION DATA

Plot #3

Operating Frequency: 2442MHz

Medium (Liquid Type): 2450 Head

Product Description: 2.4GHz and 13.56MHz Transceiver

Serial Number: 4WZ-US-FKN0143X (3.7VDC 1200mAh Li-ion rechargeable Battery)

Duty Cycle: 1:1

Test Date: 25 Feb 2026


A. Experimental conditions.

Probe	SN 36/20 EPG0347
ConvF	2.26
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x7, dx=5mm dy=5mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Left 0mm separation
Band	(2412 – 2472) MHz
Channels/Frequency	(7)/ frequency 2442.000 MHz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	2442.000
Relative permittivity (real part)	38.300
Relative permittivity (imaginary part)	13.579
Conductivity (S/m)	1.810

C. SAR Surface and Volume



Maximum location: X=-8.00, Y=-1.00 ; SAR Peak: 0.40 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.075
SAR 1g (W/Kg)	0.193
Variation (%)	0.610
Horizontal validation criteria: minimum distance (mm)	10.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	39.384929

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.398	0.214	0.084	0.027	0.006	0.001	0.001

TEST REPORT

TL-964

APPENDIX B – SAR EVALUATION DATA

Plot #4

Operating Frequency: 2480MHz

Medium (Liquid Type): 2450 Head

Product Description: 2.4GHz and 13.56MHz Transceiver

Serial Number: 4WZ-US-FKN0143X (3.7VDC 1200mAh Li-ion rechargeable Battery)

Duty Cycle: 1:1

Test Date: 25 Feb 2026


A. Experimental conditions.

Probe	SN 36/20 EPG0347
ConvF	2.26
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	12x12x12,dx=2mm dy=2mm dz=2.5mm,Complete
Phantom	Validation plane
Device Position	Left 0mm separation
Band	(2402 – 2480) MHz
Channels/Frequency	(40)/ frequency 2480.000 MHz
Signal	Bluetooth 5.4 LE

B. Permittivity

Middle TX Frequency (MHz)	2480.000
Relative permittivity (real part)	38.300
Relative permittivity (imaginary part)	13.579
Conductivity (S/m)	1.810

C. SAR Surface and Volume



Maximum location: X=0.00, Y=8.00 ; SAR Peak: 0.04 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.003
SAR 1g (W/Kg)	0.010
Variation (%)	-2.180
Horizontal validation criteria: minimum distance (mm)	3.538361
Vertical validation criteria: SAR ratio M2/M1 (%)	34.616003

E. Z Axis Scan

Z (mm)	0.00	4.00	6.50	9.00	11.50	14.00	16.50	19.00	21.50	24.00	26.50	29.00
SAR (W/Kg)	0.042	0.015	0.003	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001

TEST REPORT

TL-964

APPENDIX C – E-FIELD PROBE AND DIPOLE ANTENNA CALIBRATION



COMOSAR E-Field Probe Calibration Report

Ref : ACR.168.7.25.BES.A

INTERTEK TESTING SERVICES HONG KONG LIMITED

WORKSHOP NO. 3 G/F, WORLD-WIDE INDUSTRIAL
CENTRE, 43-47 SHAN MEI STREET,
FO TAN, SHA TIN, N.T. HONG KONG
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 36/20 EPG0347

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 06/05/2025



Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.168.7.25.BES.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Pedro Ruiz	Technical Manager	6/17/2025	
<i>Checked & approved by:</i>	Pedro Ruiz	Technical Manager	6/17/2025	
<i>Authorized by:</i>	Kim Rutkowski	Quality Manager	6/23/2025	Signed by: Kimberley RUTKOWSKI 2B689547AD17461...

	<i>Customer Name</i>
<i>Distribution :</i>	Intertek Testing Services Hong Kong Limited

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Pedro Ruiz	6/17/2025	Initial release



TABLE OF CONTENTS

1 Device Under Test4

2 Product Description4

2.1 General Information4

3 Measurement Method4

3.1 Sensitivity4

3.2 Linearity5

3.3 Isotropy5

3.4 Boundary Effect5

3.5 Probe Modulation Response6

4 Measurement Uncertainty6

5 Calibration Results.....6

5.1 Calibration in air6

5.2 Calibration in liquid7

6 Verification Results8

7 List of Equipment9



1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 36/20 EPGO347
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-7.5GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.220 MΩ Dipole 2: R2=0.224 MΩ Dipole 3: R3=0.205 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Probe

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their effect. All calibrations / measurements performed meet the fore-mentioned standards.

3.1 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards for frequency range 600-7500MHz and using the calorimeter cell method (transfer method) as outlined in the standards for frequency 150-450 MHz.



3.2 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

3.3 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.4 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta} - e^{-(d_{be} + d_{step})/\delta})}{\delta/2} \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

The measured worst case boundary effect $SAR_{uncertainty}[\%]$ for scanning distances larger than 4mm is 1.0% Limit ,2%).



3.5 PROBE MODULATION RESPONSE

MVG's probe were evaluated experimentally with various modulated signal and the deviation from CW response were found neglectable in the used power range of the probe. So the correction to taking into account the linearization parameters for different modulation is null, therefore the CW factor given in this report can be used whatever the measured modulation

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty associated with a SAR probe calibration using the waveguide or calorimetric cell technique depending on the frequency.

The estimated expanded uncertainty (k=2) in calibration for SAR (W/kg) is +/-11% for the frequency range 150-450MHz.


The estimated expanded uncertainty (k=2) in calibration for SAR (W/kg) is +/-14% for the frequency range 600-7500MHz.

5 CALIBRATION RESULTS

Ambient condition	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 CALIBRATION IN AIR

The following curve represents the measurement in waveguide of the voltage picked up by the probe toward the E-field generated inside the waveguide.



From this curve, the sensitivity in air is calculated using the below formula.

$$E^2 = \sum_{i=1}^3 \frac{V_i (1 + V_i / DCP_i)}{Norm_i}$$



where

V_i =voltage readings on the 3 channels of the probe

DCPi=diode compression point given below for the 3 channels of the probe

Normi=dipole sensitivity given below for the 3 channels of the probe

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.76	0.70	0.72

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
101	102	105

5.2 CALIBRATION IN LIQUID

The calorimeter cell or the waveguide is used to determine the calibration in liquid using the formula below.

$$\text{ConvF} = \frac{E_{\text{liquid}}^2}{E_{\text{air}}^2}$$

The E-field in the liquid is determined from the SAR measurement according to the below formula.

$$E_{\text{liquid}}^2 = \frac{\rho \text{ SAR}}{\sigma}$$

where

σ =the conductivity of the liquid

ρ =the volumetric density of the liquid

SAR=the SAR measured from the formula that depends on the setup used. The SAR formulas are given below

For the calorimeter cell (150-450 MHz), the formula is:

$$\text{SAR} = c \frac{dT}{dt}$$

where

c =the specific heat for the liquid

dT/dt =the temperature rises over the time

For the waveguide setup (600-75000 MHz), the formula is:

$$\text{SAR} = \frac{4P_W}{ab\delta} e^{-\frac{2z}{\delta}}$$



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.168.7.25.BES.A

where

a=the larger cross-sectional of the waveguide

b=the smaller cross-sectional of the waveguide



δ =the skin depth for the liquid in the waveguide

Pw=the power delivered to the liquid

The below table summarize the ConvF for the calibrated liquid. The curves give examples for the measured SAR depending on the voltage in some liquid.


Liquid	Frequency (MHz*)	ConvF
HL1900	1900	2.04
BL1900	1900	2.02
HL2450	2450	2.26
BL2450	2450	2.27
HL5250	5250	2.32
BL5250	5250	2.05
HL5600	5600	2.32
BL5600	5600	1.85
HL5750	5750	2.23
BL5750	5750	1.93

(*) Frequency validity is +/-50MHz below 600MHz, +/-100MHz from 600MHz to 6GHz and +/-700MHz above 6GHz




6 VERIFICATION RESULTS

The figures below represent the measured linearity and axial isotropy for this probe. The probe specification is +/-0.2 dB for linearity and +/-0.15 dB for axial isotropy.



Linearity: +/-1.56% (+/-0.07dB)



Isotropy: +/-0.27% (+/-0.01dB)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.168.7.25.BES.A

7 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
CALIPROBE Test Bench	Version 2	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	08/2021	08/2026
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	07/2022	07/2027
Multimeter	Keithley 2000	4013982	02/2023	02/2026
Signal Generator	Rohde & Schwarz SMB	183277	05/2022	05/2026
Amplifier	MVG	MODU-023-C-0002	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	06/2021	06/2026
USB Sensor	Keysight U2000A	SN: MY62340002	10/2024	10/2027
Directional Coupler	Krytar 158020	131467	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Fluoroptic Thermometer	LumaSense Luxtron 812	94264	09/2022	09/2025
Coaxial cell	MVG	SN 32/16 COAXCELL_1	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG2_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_0G600_1	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG4_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_0G900_1	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG6_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_1G500_1	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG8_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_1G800B_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_1G800H_1	Validated. No cal required.	Validated. No cal required.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.168.7.25.BES.A

Waveguide	MVG	SN 32/16 WG10_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_3G500_1	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG12_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_5G000_1	Validated. No cal required.	Validated. No cal required.
Waveguide	MVG	SN 32/16 WG14_1	Validated. No cal required.	Validated. No cal required.
Liquid transition	MVG	SN 32/16 WGLIQ_7G000_1	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44235403	02/2024	02/2027



SAR Reference Dipole Calibration Report

Ref : ACR.168.9.25.BES.A

INTERTEK TESTING SERVICES HONG KONG LIMITED

**WORKSHOP NO. 3 G/F, WORLD-WIDE INDUSTRIAL
CENTRE, 43-47 SHAN MEI STREET,
FO TAN, SHA TIN, N.T. HONG KONG**

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 2450 MHZ

SERIAL NO.: SN 22/16 DIP2G450-411

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 06/13/2025



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.168.9.25.BES.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Pedro Ruiz	Technical Manager	6/17/2025	
<i>Checked & approved by:</i>	Pedro Ruiz	Technical Manager	6/17/2025	
<i>Authorized by:</i>	Kim Rutkowski	Quality Manager	6/23/2025	Signed by:  2B689547AD17461...

	<i>Customer Name</i>
<i>Distribution :</i>	Intertek Testing Services Hong Kong Limited

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Pedro Ruiz	6/17/2025	Initial release



TABLE OF CONTENTS

1 Introduction..... 4

2 Device Under Test 4

3 Product Description 4

 3.1 General Information 4

4 Measurement Method 5

 4.1 Mechanical Requirements..... 5

 4.2 S11 parameter Requirements 5

 4.3 SAR Requirements 5

5 Measurement Uncertainty 5

 5.1 Mechanical dimensions..... 5

 5.2 S11 Parameter 5

 5.3 SAR..... 5

6 Calibration Results..... 6

 6.1 Mechanical Dimensions 6

 6.2 S11 parameter 6

 6.3 SAR..... 7

7 List of Equipment 9



1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 2450 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID2450
Serial Number	SN 22/16 DIP2G450-411
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards. The product is designed for use with the COMOSAR test bench only, however, being built in accordance to relevant standards, it can be used in others SAR test benches as long as the final user take care that the prescribed S11 and SAR target value are met.



Figure 1 – MVG COMOSAR Validation Dipole



4 MEASUREMENT METHOD

4.1 MECHANICAL REQUIREMENTS

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

4.2 S11 PARAMETER REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a S11 of -20 dB or better. The S11 measurement shall be performed against a liquid filled flat phantom and using a prescribed spacer, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.3 SAR REQUIREMENTS

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore-mentioned standards.

5 MEASUREMENT UNCERTAINTY

5.1 MECHANICAL DIMENSIONS

For the measurement in the range 0-300mm, the estimated expanded uncertainty (k=2) in calibration for the dimension measurement in mm is +/-0.20 mm with respect to measurement conditions.

For the measurement in the range 300-450mm, the estimated expanded uncertainty (k=2) in calibration for the dimension measurement in mm is +/-0.44 mm with respect to measurement conditions.

5.2 S11 PARAMETER

The estimated expanded uncertainty (k=2) in calibration for the S11 parameter in linear is +/-0.08 with respect to measurement conditions.

5.3 SAR

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty for validation measurements.



The estimated expanded uncertainty (k=2) in calibration for the 1g and 10g SAR measurement in W/kg is +/-19% with respect to measurement conditions.


6 CALIBRATION RESULTS

6.1 MECHANICAL DIMENSIONS

L mm		h mm		d mm	
Measured	Required	Measured	Required	Measured	Required
-	51.50 +/- 2%	-	30.40 +/- 2%	-	3.60 +/- 2%


6.2 S11 PARAMETER

6.2.1 S11 parameter in Head Liquid



Frequency (MHz)	S11 parameter (dB)	Requirement (dB)	Impedance
2450	-22.93	-20	53.5Ω - 6.1jΩ

6.2.2 S11 parameter in Body Liquid



Frequency (MHz)	S11 parameter (dB)	Requirement (dB)	Impedance
2450	-20.53	-20	57.7Ω - 5.8jΩ



6.3 SAR


The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom by using a prescribed spacer.

6.3.1 SAR with Head Liquid

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	4424-EPGO-443
Liquid	Head Liquid Values: eps' : 41.6 sigma : 1.88
Distance between dipole center and liquid	10.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=5mm/dy=5mm/dz=5mm
Frequency	2450 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

Frequency	1g SAR (W/kg)			10g SAR (W/kg)		
	Measured	Measured normalized to 1W	Target normalized to 1W	Measured	Measured normalized to 1W	Target normalized to 1W
2450 MHz	5.00	50.04	52.40	2.30	23.05	24.00






6.3.2 SAR with Body Liquid

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 4424-EPGO-443
Liquid	Body Liquid Values: eps' : 53.4 sigma : 2.08
Distance between dipole center and liquid	10.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=5mm/dy=5mm/dz=5mm
Frequency	2450
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

Frequency	1g SAR (W/kg)			10g SAR (W/kg)		
	Measured	Measured normalized to 1W	Target normalized to 1W	Measured	Measured normalized to 1W	Target normalized to 1W
2450 MHz	5.09	50.86	51.20	2.34	23.40	23.70





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.168.9.25.BES.A

7 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN 13/09 SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	08/2021	08/2026
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	07/2022	07/2027
Calipers	Mitutoyo	SN 0009732	11/2022	11/2025
Reference Probe	MVG	4424-EPGO-443	05/2025	05/2026
Multimeter	Keithley 2000	4013982	02/2023	02/2026
Signal Generator	Rohde & Schwarz SMB	183277	05/2022	05/2026
Amplifier	MVG	MODU-023-C-0002	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	06/2021	06/2026
Power Meter	Keysight U2000A	SN: MY62340002	10/2024	10/2027
Directional Coupler	Krytar 158020	131467	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44235403	10/2024	10/2027

TEST REPORT

TL-964

APPENDIX D – SAR SYSTEM VALIDATION

Per KDB 865664, SAR system validation status should be documented to confirm measurement accuracy. SAR measurement systems are validated according to procedures in KDB 865664. The validation status is documented according to the validation date(s), measurement frequencies, SAR probe and tissue dielectric parameters. When multiple SAR system is used, the validation status of each SAR system is needed to be documented separately according to the associated system components.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probe and tissue dielectric parameters are shown as below.

Date	Probe S/N	Tested Freq. (MHz)	Tissue Type	CW Validation					Mod. Validation			Peak to average power ratio
				Perm	Cond	Sensitivity	Probe Linearity	Probe Isotropy	Mod. Type	Duty Factor		
05/11/2025	EPGO 347	2450	Head	38.40	1.74	PASS	PASS	PASS	FHSS	PASS	PASS	
05/11/2025	EPGO 347	2450	Head	38.40	1.74	PASS	PASS	PASS	OFDM	N/A	PASS	
05/11/2025	EPGO 347	2450	Head	38.40	1.74	PASS	PASS	PASS	DSSS	PASS	N/A	