



FCC Part 15C Test Report

FCC ID:2BURK-CD8S341F2

Applicant: Cozyla US Corp.
Address: 2025 Production Drive Apex, Wake County, North Carolina, 27539, US
Manufacturer: Cozyla US Corp.
Address: 2025 Production Drive Apex, Wake County, North Carolina, 27539, US
EUT: Cozyla Calendar 3
Trade Mark: Cozyla
Model Number: Cozyla CD-8S341F2
Cozyla CD-8S341FX(X=0,1-9)
Date of Receipt: Apr. 10, 2026
Test Date: Apr. 10, 2026 to Apr. 30, 2026
Date of Report: Apr. 30, 2026
Prepared By: Shenzhen DL Testing Technology Co., Ltd.
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China.
Applicable Standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
ANSI C63.10:2020
KDB 789033 D02 v02r01
Test Result: Pass
Report Number: DLE-260417007R

Prepared (Test Engineer):

Dimon Tan

Reviewer (Supervisor):

Jack Bu

Approved (Manager):

Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents

Page

1. VERSION.....	4
2.SUMMARY OF TEST RESULTS.....	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY.....	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4.EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS.....	12
4.1.2 TEST PROCEDURE.....	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULT	14
4.2 RADIATED EMISSION MEASUREMENT	18
4.2.1 APPLICABLE STANDARD	18
4.2.2 CONFORMANCE LIMIT.....	18
4.2.3 MEASURING INSTRUMENTS	18
4.2.4 TEST CONFIGURATION.....	19
4.2.5 TEST PROCEDURE.....	20
4.2.6 TEST RESULT	21
5.POWER SPECTRAL DENSITY TEST	37
5.1 APPLIED PROCEDURES / LIMIT	37
5.2 TEST PROCEDURE.....	38
5.3 DEVIATION FROM STANDARD	38
5.4 TEST SETUP	38
5.5 EUT OPERATION CONDITIONS	38
5.6 TEST RESULTS	39
6. 26DB EMISSION BANDWIDTH & 6DB OCCUPIED BANDWIDTH	47
6.1 APPLIED PROCEDURES / LIMIT	47
6.2 TEST PROCEDURE.....	47
6.3 EUT OPERATION CONDITIONS	47
6.4 TEST RESULTS	48
7.MAXIMUM CONDUCTED OUTPUT POWER	56
7.1 PPLIED PROCEDURES / LIMIT	56
7.2 TEST PROCEDURE.....	56
7.3 DEVIATION FROM STANDARD	56
7.4 TEST SETUP	56
7.5 EUT OPERATION CONDITIONS	56
7.6 TEST RESULTS	57



Table of Contents

Page

8.OUT OF BAND EMISSIONS	59
8.1 APPLICABLE STANDARD	59
8.2 TEST PROCEDURE.....	59
8.3 DEVIATION FROM STANDARD	59
8.4 TEST SETUP	59
8.5 EUT OPERATION CONDITIONS	59
8.6 TEST RESULTS	59
9.FREQUENCY STABILITY MEASUREMENT	64
9.1 LIMIT	64
9.2 TEST PROCEDURES	64
9.3 TEST SETUP LAYOUT	64
9.4 EUT OPERATION DURING TEST.....	64
9.5 TEST RESULTS	64
10. DUTY CYCLE	75
10.1 APPLIED PROCEDURES / LIMIT	75
10.2 DEVIATION FROM STANDARD	75
10.3 TEST SETUP	75
11.ANTENNA REQUIREMENT	84
12. TEST SETUP PHOTO	85
13. EUT CONSTRUCTIONAL DETAILS	85

**1. VERSION**

Report No.	Version	Description	Approved
DLE-260417007R	Rev.01	Initial issue of report	Apr. 30, 2026

**2.SUMMARY OF TEST RESULTS**

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emission	PASS	
789033 D02 General U-NII	Duty Cycle	PASS	
15.209(a) 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(8)	Spurious Radiated Emissions	PASS	
15.407 (a) 15.1049 15.407(e)	26dB Emission Bandwidth & 6dB Occupied Bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
2.1051, 15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
2.1051, 15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add. : 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China.

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8MHz
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Cozyla Calendar 3	
Model No.:	Cozyla CD-8S341F2	
Serial Model:	Cozyla CD-8S341FX(X=0,1-9)	
Model Different.:	All the model are the same circuit and RF module, except model names and appearance color.	
Sample(s) Status:	Engineer sample	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/n/ac (20MHz channel bandwidth) ☒ 802.11ac/n (40MHz channel bandwidth) ☒ 802.11ac (80MHz channel bandwidth)
	Data Rate	802.11a 802.11n(HT20/HT40):MCS0-MCS7; 802.11ac(VHT20/VHT40/VHT80):MCS0-MCS9
	Modulation	OFDM with BPSK / QPSK / 16-QAM / 64-QAM for 802.11a/n; OFDM with BPSK / QPSK / 16-QAM / 64-QAM / 256-QAM for 802.11ac;
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/n20/ac20; ☒ 5190-5230MHz for 802.11ac40/n40; ☒ 5210MHz for 802.11 ac80. ☒ 5745-5825 MHz for 802.11a/n20/ac20; ☒ 5755-5795 MHz for 802.11ac40/n40; ☒ 5775MHz for 802.11 ac80.
	Number of Channels	☒ 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ; ☒ 2 channels for 802.11 ac40/n40 in the 5190-5230 MHz band ; ☒ 1 channels for 802.11 ac80 in the 5210MHz band. ☒ 5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ; ☒ 2 channels for 802.11 ac40/n40 in the 5755-5795 MHz band ; ☒ 1 channels for 802.11 ac80 in the 5775MHz band
Channel List	Please refer to the Note 2.	
Antenna Type:	FPC antenna	
Antenna gain:	5.2G: 2.23dBi 5.8G: 2.06dBi	
Power Supply:	Input: 12V=== 5A From Adapter	
Adapter:	Model: NO.: SOY-1200300US-540 Input: 100-240V~ 50/60Hz 0.9A Max Output: 12V=== 3A 36.0W	

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



802.11a/n/ac(20MHz) Frequency Channel for 5.2G							
Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)
36	5180	44	5200	40	5220	48	5240

802.11n/ac(40MHz) Frequency Channel for 5.2G							
Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)
38	5190	46	5230	-	-	-	-

802.11ac (80MHz) Frequency Channel for 5.2G	
Channel	Frequency (MHz)
42	5210

802.11a/n/ac(20 MHz) Frequency Channel for 5.8G							
Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)	Channel	Frequenc y (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

802.11n/ac(40MHz) Frequency Channel for 5.8G					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

802.11ac (80MHz) Frequency Channel for 5.8G	
Channel	Frequency (MHz)
155	5775



3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	CMD
Power level setup	Default

Pretest Mode	Description
Mode 1	802.11a/n20/ac20 CH 36/ CH 40/ CH 48 for 5.2G 802.11a/n20/ac20 CH149/ CH157/ CH 165 for 5.8G
Mode 2	802.11n 40/ac 40 CH38/ CH 46 for 5.2G 802.11n 40/ac 40 CH 151 / CH 159 for 5.8G
Mode 3	802.11 ac80 CH 42 for 5.2G 802.11 ac80 CH 155 for 5.8G

For Conducted Emission	
Final Test Mode	Description
Mode 1	802.11a/n20/ac20 CH 36/ CH 40/ CH 48 for 5.2G 802.11a/n20/ac20 CH149/ CH157/ CH 165 for 5.8G
Mode 2	802.11n 40/ac 40 CH38/ CH 46 for 5.2G 802.11n 40/ac 40 CH 151 / CH 159 for 5.8G
Mode 3	802.11 ac80 CH 42 for 5.2G 802.11 ac80 CH 155 for 5.8G

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a/n20/ac20 CH 36/ CH 40/ CH 48 for 5.2G 802.11a/n20/ac20 CH149/ CH157/ CH 165 for 5.8G
Mode 2	802.11n 40/ac 40 CH38/ CH 46 for 5.2G 802.11n 40/ac 40 CH 151 / CH 159 for 5.8G
Mode 3	802.11 ac80 CH 42 for 5.2G 802.11 ac80 CH 155 for 5.8G

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Cozyla Calendar 3	Cozyla	Cozyla CD-8S341F2	N/A	EUT
A1	AC/DC Adapter	N/A	SOY-1200300US-540	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Oct. 25, 2025	Oct. 24, 2026
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Oct. 25, 2025	Oct. 24, 2026
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Oct. 27, 2025	Oct. 24, 2026
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Oct. 27, 2025	Oct. 24, 2026
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Oct. 25, 2025	Oct. 24, 2026
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Oct. 25, 2025	Oct. 24, 2026
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Oct. 25, 2025	Oct. 24, 2026
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Oct. 25, 2025	Oct. 24, 2026
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Oct. 25, 2025	Oct. 24, 2026
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Oct. 25, 2025	Oct. 24, 2026
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Oct. 25, 2025	Oct. 24, 2026
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Oct. 25, 2025	Oct. 24, 2026
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Oct. 25, 2025	Oct. 24, 2026
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Oct. 25, 2025	Oct. 24, 2026
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Oct. 25, 2025	Oct. 24, 2026
16	D.C. Power Supply	LongWei	PS-305D	010964729	Oct. 25, 2025	Oct. 24, 2026
17	Power meter	KEYSIGHT	N1912AP	926431	Oct. 25, 2025	Oct. 24, 2026

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	YIHENG	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Oct. 25, 2025	Oct. 24, 2026
3	LISN	R&S	ENV216	102417	Oct. 25, 2025	Oct. 24, 2026
4	843 Cable 1#	ChengYu	CE Cable	001	Oct. 25, 2025	Oct. 24, 2026

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMG	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMG	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2020
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 TEST RESULT

5.2G:


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	802.11a - 5200MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	41.76	9.65	51.41	65.36	-13.95	QP	P
2	0.1620	26.78	9.65	36.43	55.36	-18.93	AVG	P
3	0.2819	32.57	9.65	42.22	60.76	-18.54	QP	P
4	0.2819	24.79	9.65	34.44	50.76	-16.32	AVG	P
5	0.3660	33.08	9.65	42.73	58.59	-15.86	QP	P
6 *	0.3660	26.17	9.65	35.82	48.59	-12.77	AVG	P
7	0.8860	21.16	9.67	30.83	56.00	-25.17	QP	P
8	0.8860	10.67	9.67	20.34	46.00	-25.66	AVG	P
9	1.2780	19.45	9.68	29.13	56.00	-26.87	QP	P
10	1.2780	7.88	9.68	17.56	46.00	-28.44	AVG	P
11	3.2860	17.94	9.72	27.66	56.00	-28.34	QP	P
12	3.2860	5.12	9.72	14.84	46.00	-31.16	AVG	P



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	802.11a - 5200MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	41.33	9.68	51.01	66.00	-14.99	QP	P
2	0.1500	24.73	9.68	34.41	56.00	-21.59	AVG	P
3	0.2940	33.56	9.68	43.24	60.41	-17.17	QP	P
4	0.2940	23.01	9.68	32.69	50.41	-17.72	AVG	P
5	0.3620	35.17	9.68	44.85	58.68	-13.83	QP	P
6 *	0.3620	27.93	9.68	37.61	48.68	-11.07	AVG	P
7	0.6900	19.87	9.69	29.56	56.00	-26.44	QP	P
8	0.6900	8.58	9.69	18.27	46.00	-27.73	AVG	P
9	1.4860	17.25	9.71	26.96	56.00	-29.04	QP	P
10	1.4860	4.94	9.71	14.65	46.00	-31.35	AVG	P
11	3.2980	18.36	9.76	28.12	56.00	-27.88	QP	P
12	3.2980	2.13	9.76	11.89	46.00	-34.11	AVG	P


Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor
- 4.The test data shows only the worst case 802.11a - 5200MHz.



5.8G:


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	802.11ac40 - 5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1700	41.76	9.65	51.41	64.96	-13.55	QP	P
2	0.1700	25.12	9.65	34.77	54.96	-20.19	AVG	P
3	0.2980	32.18	9.65	41.83	60.30	-18.47	QP	P
4	0.2980	23.41	9.65	33.06	50.30	-17.24	AVG	P
5	0.3700	32.64	9.65	42.29	58.50	-16.21	QP	P
6 *	0.3700	27.51	9.65	37.16	48.50	-11.34	AVG	P
7	0.7340	22.05	9.66	31.71	56.00	-24.29	QP	P
8	0.7340	10.92	9.66	20.58	46.00	-25.42	AVG	P
9	1.4340	20.09	9.68	29.77	56.00	-26.23	QP	P
10	1.4340	7.52	9.68	17.20	46.00	-28.80	AVG	P
11	3.3100	18.43	9.72	28.15	56.00	-27.85	QP	P
12	3.3100	4.79	9.72	14.51	46.00	-31.49	AVG	P



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	802.11ac40 - 5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	40.52	9.68	50.20	66.00	-15.80	QP	P
2	0.1500	21.88	9.68	31.56	56.00	-24.44	AVG	P
3	0.2100	35.77	9.67	45.44	63.21	-17.77	QP	P
4	0.2100	19.44	9.67	29.11	53.21	-24.10	AVG	P
5	0.3060	32.94	9.68	42.62	60.08	-17.46	QP	P
6	0.3060	22.90	9.68	32.58	50.08	-17.50	AVG	P
7	0.3740	34.38	9.68	44.06	58.41	-14.35	QP	P
8 *	0.3740	27.70	9.68	37.38	48.41	-11.03	AVG	P
9	0.6940	19.76	9.69	29.45	56.00	-26.55	QP	P
10	0.6940	9.89	9.69	19.58	46.00	-26.42	AVG	P
11	1.0339	16.93	9.70	26.63	56.00	-29.37	QP	P
12	1.0339	6.36	9.70	16.06	46.00	-29.94	AVG	P

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 802.11ac40 - 5795MHz.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(d) and 15.209

4.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.


4.2.3 MEASURING INSTRUMENTS

The Measuring equipment is listed in the section 6.3 of this test report.




4.2.4 TEST CONFIGURATION


1. For radiated emissions below 30MHz



2. For radiated emissions from 30MHz to 1000MHz



3. Radiated Emission Test-Up Frequency Above 1GHz





4.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205.

It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item – EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.



4.2.6 TEST RESULT


Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

5.2G:


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode :	TX 802.11a - 5200MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.1054	32.69	-11.45	21.24	40.00	-18.76	QP
2	45.8553	29.68	-11.17	18.51	40.00	-21.49	QP
3	105.2718	42.36	-12.70	29.66	43.50	-13.84	QP
4	215.2678	41.72	-10.55	31.17	43.50	-12.33	QP
5	369.4047	39.18	-7.02	32.16	46.00	-13.84	QP
6 *	701.7610	39.18	0.23	39.41	46.00	-6.59	QP



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode :	TX 802.11a - 5200MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	30.2111	45.40	-11.45	33.95	40.00	-6.05	QP
2	47.6586	36.63	-11.29	25.34	40.00	-14.66	QP
3	85.8984	35.73	-13.99	21.74	40.00	-18.26	QP
4	180.0165	43.48	-11.60	31.88	43.50	-11.62	QP
5	356.6758	40.97	-7.15	33.82	46.00	-12.18	QP
6	605.6592	35.35	-1.64	33.71	46.00	-12.29	QP


Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.All modes were tested, and only the worst test data was recorded is 802.11a - 5200MHz.




5.8G:

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode :	TX 802.11ac40 - 5795MHz





Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode :	TX 802.11ac40 - 5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	30.0000	44.84	-11.46	33.38	40.00	-6.62	QP
2	35.8746	39.54	-11.06	28.48	40.00	-11.52	QP
3	108.2667	38.59	-12.61	25.98	43.50	-17.52	QP
4	178.7584	41.50	-11.48	30.02	43.50	-13.48	QP
5	365.5391	32.87	-7.06	25.81	46.00	-20.19	QP
6	605.6592	37.46	-1.64	35.82	46.00	-10.18	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.All modes were tested, and only the worst test data was recorded is 802.11ac40 - 5795MHz.



Between 1GHz – 40GHz

Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	5.2G TX - 802.11a/ n20/ ac20/ n40/ ac40/ac80		
Note: All patterns have been tested, and only the worst test data recorded in this report is 802.11a/n20/ac20.			

802.11a

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:5180MHz									
V	5150.00	41.34	30.45	8.77	38.66	58.32	74.00	-15.68	PK
V	5150.00	29.64	30.45	8.77	38.66	46.62	54.00	-7.38	AV
V	10360.00	51.77	30.55	5.77	24.66	51.65	74.00	-22.35	PK
V	10360.00	42.81	30.55	5.77	24.66	42.69	54.00	-11.31	AV
V	15540.00	54.39	30.33	6.32	24.55	54.93	74.00	-19.07	PK
V	15540.00	43.10	30.33	6.32	24.55	43.64	54.00	-10.36	AV
V	20720.00	49.38	30.85	7.45	24.69	50.67	74.00	-23.33	PK
V	20720.00	43.13	30.85	7.45	24.69	44.42	54.00	-9.58	AV
V	25900.00	51.27	31.02	8.99	25.57	54.81	74.00	-19.19	PK
V	25900.00	43.26	31.02	8.99	25.57	46.80	54.00	-7.20	AV
H	5150.00	41.51	30.45	8.77	38.66	58.49	74.00	-15.51	PK
H	5150.00	29.34	30.45	8.77	38.66	46.32	54.00	-7.68	AV
H	10360.00	50.76	30.55	5.77	24.66	50.64	74.00	-23.36	PK
H	10360.00	42.97	30.55	5.77	24.66	42.85	54.00	-11.15	AV
H	15540.00	52.78	30.33	6.32	24.55	53.32	74.00	-20.68	PK
H	15540.00	43.61	30.33	6.32	24.55	44.15	54.00	-9.85	AV
H	20720.00	51.82	30.85	7.45	24.69	53.11	74.00	-20.89	PK
H	20720.00	42.88	30.85	7.45	24.69	44.17	54.00	-9.83	AV
H	25900.00	49.84	31.02	8.99	25.57	53.38	74.00	-20.62	PK
H	25900.00	42.65	31.02	8.99	25.57	46.19	54.00	-7.81	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:5200MHz									
V	5150.00	42.02	30.45	8.77	38.66	59.00	74.00	-15.00	PK
V	5150.00	29.58	30.45	8.77	38.66	46.56	54.00	-7.44	AV
V	10400.00	52.32	30.55	5.77	24.66	52.20	74.00	-21.80	PK
V	10400.00	42.19	30.55	5.77	24.66	42.07	54.00	-11.93	AV
V	15600.00	53.25	30.33	6.32	24.55	53.79	74.00	-20.21	PK
V	15600.00	42.87	30.33	6.32	24.55	43.41	54.00	-10.59	AV
V	20800.00	49.40	30.85	7.45	24.69	50.69	74.00	-23.31	PK
V	20800.00	43.06	30.85	7.45	24.69	44.35	54.00	-9.65	AV
V	26000.00	51.62	31.02	8.99	25.57	55.16	74.00	-18.84	PK
V	26000.00	41.55	31.02	8.99	25.57	45.09	54.00	-8.91	AV
H	5150.00	41.83	30.45	8.77	38.66	58.81	74.00	-15.19	PK
H	5150.00	28.55	30.45	8.77	38.66	45.53	54.00	-8.47	AV



Shenzhen DL Testing Technology Co., Ltd.

Report No.: DLE-260417007R

H	10400.00	48.88	30.55	5.77	24.66	48.76	74.00	-25.24	PK
H	10400.00	41.74	30.55	5.77	24.66	41.62	54.00	-12.38	AV
H	15600.00	52.11	30.33	6.32	24.55	52.65	74.00	-21.35	PK
H	15600.00	42.08	30.33	6.32	24.55	42.62	54.00	-11.38	AV
H	20800.00	50.36	30.85	7.45	24.69	51.65	74.00	-22.35	PK
H	20800.00	43.38	30.85	7.45	24.69	44.67	54.00	-9.33	AV
H	26000.00	50.55	31.02	8.99	25.57	54.09	74.00	-19.91	PK
H	26000.00	42.53	31.02	8.99	25.57	46.07	54.00	-7.93	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:5240MHz									
V	5350.00	41.68	30.45	8.77	38.66	58.66	74.00	-15.34	PK
V	5350.00	30.29	30.45	8.77	38.66	47.27	54.00	-6.73	AV
V	10480.00	51.42	30.55	5.77	24.66	51.30	74.00	-22.70	PK
V	10480.00	42.34	30.55	5.77	24.66	42.22	54.00	-11.78	AV
V	15720.00	53.70	30.33	6.32	24.55	54.24	74.00	-19.76	PK
V	15720.00	41.81	30.33	6.32	24.55	42.35	54.00	-11.65	AV
V	20960.00	49.19	30.85	7.45	24.69	50.48	74.00	-23.52	PK
V	20960.00	42.34	30.85	7.45	24.69	43.63	54.00	-10.37	AV
V	26200.00	51.42	31.02	8.99	25.57	54.96	74.00	-19.04	PK
V	26200.00	43.28	31.02	8.99	25.57	46.82	54.00	-7.18	AV
H	5350.00	41.79	30.45	8.77	38.66	58.77	74.00	-15.23	PK
H	5350.00	29.54	30.45	8.77	38.66	46.52	54.00	-7.48	AV
H	10480.00	49.73	30.55	5.77	24.66	49.61	74.00	-24.39	PK
H	10480.00	42.90	30.55	5.77	24.66	42.78	54.00	-11.22	AV
H	15720.00	52.61	30.33	6.32	24.55	53.15	74.00	-20.85	PK
H	15720.00	41.87	30.33	6.32	24.55	42.41	54.00	-11.59	AV
H	20960.00	50.56	30.85	7.45	24.69	51.85	74.00	-22.15	PK
H	20960.00	42.04	30.85	7.45	24.69	43.33	54.00	-10.67	AV
H	26200.00	50.01	31.02	8.99	25.57	53.55	74.00	-20.45	PK
H	26200.00	43.30	31.02	8.99	25.57	46.84	54.00	-7.16	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n20

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:5180MHz									
V	5150.00	42.20	30.45	8.77	38.66	59.18	74.00	-14.82	PK
V	5150.00	29.57	30.45	8.77	38.66	46.55	54.00	-7.45	AV
V	10360.00	52.06	30.55	5.77	24.66	51.94	74.00	-22.06	PK
V	10360.00	43.08	30.55	5.77	24.66	42.96	54.00	-11.04	AV
V	15540.00	53.98	30.33	6.32	24.55	54.52	74.00	-19.48	PK
V	15540.00	42.82	30.33	6.32	24.55	43.36	54.00	-10.64	AV
V	20720.00	50.16	30.85	7.45	24.69	51.45	74.00	-22.55	PK
V	20720.00	42.39	30.85	7.45	24.69	43.68	54.00	-10.32	AV
V	25900.00	51.61	31.02	8.99	25.57	55.15	74.00	-18.85	PK
V	25900.00	42.57	31.02	8.99	25.57	46.11	54.00	-7.89	AV
H	5150.00	41.73	30.45	8.77	38.66	58.71	74.00	-15.29	PK
H	5150.00	29.21	30.45	8.77	38.66	46.19	54.00	-7.81	AV
H	10360.00	49.77	30.55	5.77	24.66	49.65	74.00	-24.35	PK
H	10360.00	42.38	30.55	5.77	24.66	42.26	54.00	-11.74	AV
H	15540.00	52.88	30.33	6.32	24.55	53.42	74.00	-20.58	PK
H	15540.00	43.11	30.33	6.32	24.55	43.65	54.00	-10.35	AV
H	20720.00	51.15	30.85	7.45	24.69	52.44	74.00	-21.56	PK
H	20720.00	42.52	30.85	7.45	24.69	43.81	54.00	-10.19	AV
H	25900.00	49.92	31.02	8.99	25.57	53.46	74.00	-20.54	PK
H	25900.00	42.32	31.02	8.99	25.57	45.86	54.00	-8.14	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:5200MHz									
V	5150.00	42.06	30.45	8.77	38.66	59.04	74.00	-14.96	PK
V	5150.00	28.76	30.45	8.77	38.66	45.74	54.00	-8.26	AV
V	10400.00	52.76	30.55	5.77	24.66	52.64	74.00	-21.36	PK
V	10400.00	41.87	30.55	5.77	24.66	41.75	54.00	-12.25	AV
V	15600.00	53.95	30.33	6.32	24.55	54.49	74.00	-19.51	PK
V	15600.00	43.10	30.33	6.32	24.55	43.64	54.00	-10.36	AV
V	20800.00	49.71	30.85	7.45	24.69	51.00	74.00	-23.00	PK
V	20800.00	42.18	30.85	7.45	24.69	43.47	54.00	-10.53	AV
V	26000.00	50.72	31.02	8.99	25.57	54.26	74.00	-19.74	PK
V	26000.00	42.12	31.02	8.99	25.57	45.66	54.00	-8.34	AV
H	5150.00	40.79	30.45	8.77	38.66	57.77	74.00	-16.23	PK
H	5150.00	29.17	30.45	8.77	38.66	46.15	54.00	-7.85	AV
H	10400.00	49.83	30.55	5.77	24.66	49.71	74.00	-24.29	PK
H	10400.00	41.44	30.55	5.77	24.66	41.32	54.00	-12.68	AV
H	15600.00	52.70	30.33	6.32	24.55	53.24	74.00	-20.76	PK
H	15600.00	43.39	30.33	6.32	24.55	43.93	54.00	-10.07	AV
H	20800.00	51.27	30.85	7.45	24.69	52.56	74.00	-21.44	PK
H	20800.00	42.26	30.85	7.45	24.69	43.55	54.00	-10.45	AV
H	26000.00	50.35	31.02	8.99	25.57	53.89	74.00	-20.11	PK
H	26000.00	42.90	31.02	8.99	25.57	46.44	54.00	-7.56	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:5240MHz									
V	5350.00	42.16	30.45	8.77	38.66	59.14	74.00	-14.86	PK
V	5350.00	29.67	30.45	8.77	38.66	46.65	54.00	-7.35	AV
V	10480.00	50.62	30.55	5.77	24.66	50.50	74.00	-23.50	PK
V	10480.00	41.43	30.55	5.77	24.66	41.31	54.00	-12.69	AV
V	15720.00	52.84	30.33	6.32	24.55	53.38	74.00	-20.62	PK
V	15720.00	41.91	30.33	6.32	24.55	42.45	54.00	-11.55	AV
V	20960.00	49.38	30.85	7.45	24.69	50.67	74.00	-23.33	PK
V	20960.00	41.58	30.85	7.45	24.69	42.87	54.00	-11.13	AV
V	26200.00	50.65	31.02	8.99	25.57	54.19	74.00	-19.81	PK
V	26200.00	41.68	31.02	8.99	25.57	45.22	54.00	-8.78	AV
H	5350.00	41.16	30.45	8.77	38.66	58.14	74.00	-15.86	PK
H	5350.00	29.52	30.45	8.77	38.66	46.50	54.00	-7.50	AV
H	10480.00	49.70	30.55	5.77	24.66	49.58	74.00	-24.42	PK
H	10480.00	42.62	30.55	5.77	24.66	42.50	54.00	-11.50	AV
H	15720.00	52.92	30.33	6.32	24.55	53.46	74.00	-20.54	PK
H	15720.00	42.35	30.33	6.32	24.55	42.89	54.00	-11.11	AV
H	20960.00	50.43	30.85	7.45	24.69	51.72	74.00	-22.28	PK
H	20960.00	42.50	30.85	7.45	24.69	43.79	54.00	-10.21	AV
H	26200.00	49.12	31.02	8.99	25.57	52.66	74.00	-21.34	PK
H	26200.00	43.34	31.02	8.99	25.57	46.88	54.00	-7.12	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac20

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:5180MHz									
V	5150.00	42.03	30.45	8.77	38.66	59.01	74.00	-14.99	PK
V	5150.00	29.62	30.45	8.77	38.66	46.60	54.00	-7.40	AV
V	10360.00	51.96	30.55	5.77	24.66	51.84	74.00	-22.16	PK
V	10360.00	42.74	30.55	5.77	24.66	42.62	54.00	-11.38	AV
V	15540.00	53.69	30.33	6.32	24.55	54.23	74.00	-19.77	PK
V	15540.00	42.79	30.33	6.32	24.55	43.33	54.00	-10.67	AV
V	20720.00	49.23	30.85	7.45	24.69	50.52	74.00	-23.48	PK
V	20720.00	42.83	30.85	7.45	24.69	44.12	54.00	-9.88	AV
V	25900.00	51.80	31.02	8.99	25.57	55.34	74.00	-18.66	PK
V	25900.00	42.86	31.02	8.99	25.57	46.40	54.00	-7.60	AV
H	5150.00	41.57	30.45	8.77	38.66	58.55	74.00	-15.45	PK
H	5150.00	29.15	30.45	8.77	38.66	46.13	54.00	-7.87	AV
H	10360.00	50.23	30.55	5.77	24.66	50.11	74.00	-23.89	PK
H	10360.00	42.46	30.55	5.77	24.66	42.34	54.00	-11.66	AV
H	15540.00	52.80	30.33	6.32	24.55	53.34	74.00	-20.66	PK
H	15540.00	42.60	30.33	6.32	24.55	43.14	54.00	-10.86	AV
H	20720.00	51.66	30.85	7.45	24.69	52.95	74.00	-21.05	PK
H	20720.00	42.84	30.85	7.45	24.69	44.13	54.00	-9.87	AV
H	25900.00	50.34	31.02	8.99	25.57	53.88	74.00	-20.12	PK
H	25900.00	42.83	31.02	8.99	25.57	46.37	54.00	-7.63	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:5200MHz									
V	5150.00	42.33	30.45	8.77	38.66	59.31	74.00	-14.69	PK
V	5150.00	30.37	30.45	8.77	38.66	47.35	54.00	-6.65	AV
V	10400.00	51.08	30.55	5.77	24.66	50.96	74.00	-23.04	PK
V	10400.00	42.95	30.55	5.77	24.66	42.83	54.00	-11.17	AV
V	15600.00	53.97	30.33	6.32	24.55	54.51	74.00	-19.49	PK
V	15600.00	42.48	30.33	6.32	24.55	43.02	54.00	-10.98	AV
V	20800.00	50.09	30.85	7.45	24.69	51.38	74.00	-22.62	PK
V	20800.00	42.24	30.85	7.45	24.69	43.53	54.00	-10.47	AV
V	26000.00	51.84	31.02	8.99	25.57	55.38	74.00	-18.62	PK
V	26000.00	41.48	31.02	8.99	25.57	45.02	54.00	-8.98	AV
H	5150.00	40.53	30.45	8.77	38.66	57.51	74.00	-16.49	PK
H	5150.00	28.94	30.45	8.77	38.66	45.92	54.00	-8.08	AV
H	10400.00	49.38	30.55	5.77	24.66	49.26	74.00	-24.74	PK
H	10400.00	42.27	30.55	5.77	24.66	42.15	54.00	-11.85	AV
H	15600.00	52.94	30.33	6.32	24.55	53.48	74.00	-20.52	PK
H	15600.00	42.85	30.33	6.32	24.55	43.39	54.00	-10.61	AV
H	20800.00	51.02	30.85	7.45	24.69	52.31	74.00	-21.69	PK
H	20800.00	42.47	30.85	7.45	24.69	43.76	54.00	-10.24	AV
H	26000.00	49.17	31.02	8.99	25.57	52.71	74.00	-21.29	PK
H	26000.00	42.64	31.02	8.99	25.57	46.18	54.00	-7.82	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:5240MHz									
V	5350.00	42.18	30.45	8.77	38.66	59.16	74.00	-14.84	PK
V	5350.00	29.54	30.45	8.77	38.66	46.52	54.00	-7.48	AV
V	10480.00	52.62	30.55	5.77	24.66	52.50	74.00	-21.50	PK
V	10480.00	42.64	30.55	5.77	24.66	42.52	54.00	-11.48	AV
V	15720.00	53.86	30.33	6.32	24.55	54.40	74.00	-19.60	PK
V	15720.00	42.45	30.33	6.32	24.55	42.99	54.00	-11.01	AV
V	20960.00	49.63	30.85	7.45	24.69	50.92	74.00	-23.08	PK
V	20960.00	41.33	30.85	7.45	24.69	42.62	54.00	-11.38	AV
V	26200.00	51.48	31.02	8.99	25.57	55.02	74.00	-18.98	PK
V	26200.00	41.34	31.02	8.99	25.57	44.88	54.00	-9.12	AV
H	5350.00	40.63	30.45	8.77	38.66	57.61	74.00	-16.39	PK
H	5350.00	28.88	30.45	8.77	38.66	45.86	54.00	-8.14	AV
H	10480.00	48.71	30.55	5.77	24.66	48.59	74.00	-25.41	PK
H	10480.00	42.10	30.55	5.77	24.66	41.98	54.00	-12.02	AV
H	15720.00	51.72	30.33	6.32	24.55	52.26	74.00	-21.74	PK
H	15720.00	42.36	30.33	6.32	24.55	42.90	54.00	-11.10	AV
H	20960.00	50.77	30.85	7.45	24.69	52.06	74.00	-21.94	PK
H	20960.00	42.61	30.85	7.45	24.69	43.90	54.00	-10.10	AV
H	26200.00	50.37	31.02	8.99	25.57	53.91	74.00	-20.09	PK
H	26200.00	42.49	31.02	8.99	25.57	46.03	54.00	-7.97	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	5.8G TX - 802.11a/ n20/ ac20/ n40/ ac40/ac80		
Note: All patterns have been tested, and only the worst test data recorded in this report is 802.11a/n20/ac20.			

802.11a

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Low Channel:5745MHz									
V	11490.00	51.11	30.55	5.77	24.66	50.99	74.00	-23.01	PK
V	11490.00	42.98	30.55	5.77	24.66	42.86	54.00	-11.14	AV
V	17235.00	51.15	30.33	6.32	24.55	51.69	74.00	-22.31	PK
V	17235.00	42.50	30.33	6.32	24.55	43.04	54.00	-10.96	AV
V	22980.00	49.27	30.85	7.45	24.69	50.56	74.00	-23.44	PK
V	22980.00	42.03	30.85	7.45	24.69	43.32	54.00	-10.68	AV
V	28725.00	53.72	31.02	8.99	25.57	57.26	74.00	-16.74	PK
V	28725.00	42.70	31.02	8.99	25.57	46.24	54.00	-7.76	AV
H	11490.00	50.77	30.55	5.77	24.66	50.65	74.00	-23.35	PK
H	11490.00	43.27	30.55	5.77	24.66	43.15	54.00	-10.85	AV
H	17235.00	53.55	30.33	6.32	24.55	54.09	74.00	-19.91	PK
H	17235.00	43.13	30.33	6.32	24.55	43.67	54.00	-10.33	AV
H	22980.00	51.03	30.85	7.45	24.69	52.32	74.00	-21.68	PK
H	22980.00	42.97	30.85	7.45	24.69	44.26	54.00	-9.74	AV
H	28725.00	52.40	31.02	8.99	25.57	55.94	74.00	-18.06	PK
H	28725.00	42.34	31.02	8.99	25.57	45.88	54.00	-8.12	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Middle Channel:5785MHz									
V	11570.00	49.47	30.55	5.77	24.66	49.35	74.00	-24.65	PK
V	11570.00	41.54	30.55	5.77	24.66	41.42	54.00	-12.58	AV
V	17355.00	48.57	30.33	6.32	24.55	49.11	74.00	-24.89	PK
V	17355.00	41.40	30.33	6.32	24.55	41.94	54.00	-12.06	AV
V	23140.00	50.68	30.85	7.45	24.69	51.97	74.00	-22.03	PK
V	23140.00	41.24	30.85	7.45	24.69	42.53	54.00	-11.47	AV
V	28925.00	48.50	31.02	8.99	25.57	52.04	74.00	-21.96	PK
V	28925.00	41.73	31.02	8.99	25.57	45.27	54.00	-8.73	AV
H	11570.00	48.63	30.55	5.77	24.66	48.51	74.00	-25.49	PK
H	11570.00	41.54	30.55	5.77	24.66	41.42	54.00	-12.58	AV
H	17355.00	52.98	30.33	6.32	24.55	53.52	74.00	-20.48	PK
H	17355.00	41.25	30.33	6.32	24.55	41.79	54.00	-12.21	AV
H	23140.00	50.68	30.85	7.45	24.69	51.97	74.00	-22.03	PK
H	23140.00	41.71	30.85	7.45	24.69	43.00	54.00	-11.00	AV
H	28925.00	48.49	31.02	8.99	25.57	52.03	74.00	-21.97	PK
H	28925.00	42.02	31.02	8.99	25.57	45.56	54.00	-8.44	AV



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:5825MHz									
V	11650.00	49.88	30.55	5.77	24.66	49.76	74.00	-24.24	PK
V	11650.00	41.78	30.55	5.77	24.66	41.66	54.00	-12.34	AV
V	17475.00	48.10	30.33	6.32	24.55	48.64	74.00	-25.36	PK
V	17475.00	40.99	30.33	6.32	24.55	41.53	54.00	-12.47	AV
V	23300.00	49.18	30.85	7.45	24.69	50.47	74.00	-23.53	PK
V	23300.00	41.46	30.85	7.45	24.69	42.75	54.00	-11.25	AV
V	29125.00	51.70	31.02	8.99	25.57	55.24	74.00	-18.76	PK
V	29125.00	41.09	31.02	8.99	25.57	44.63	54.00	-9.37	AV
H	11650.00	50.38	30.55	5.77	24.66	50.26	74.00	-23.74	PK
H	11650.00	41.01	30.55	5.77	24.66	40.89	54.00	-13.11	AV
H	17475.00	51.05	30.33	6.32	24.55	51.59	74.00	-22.41	PK
H	17475.00	41.33	30.33	6.32	24.55	41.87	54.00	-12.13	AV
H	23300.00	52.18	30.85	7.45	24.69	53.47	74.00	-20.53	PK
H	23300.00	41.22	30.85	7.45	24.69	42.51	54.00	-11.49	AV
H	29125.00	47.92	31.02	8.99	25.57	51.46	74.00	-22.54	PK
H	29125.00	41.32	31.02	8.99	25.57	44.86	54.00	-9.14	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n20

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:5745MHz									
V	11490.00	51.36	30.55	5.77	24.66	51.24	74.00	-22.76	PK
V	11490.00	43.25	30.55	5.77	24.66	43.13	54.00	-10.87	AV
V	17235.00	52.79	30.33	6.32	24.55	53.33	74.00	-20.67	PK
V	17235.00	42.92	30.33	6.32	24.55	43.46	54.00	-10.54	AV
V	22980.00	49.30	30.85	7.45	24.69	50.59	74.00	-23.41	PK
V	22980.00	42.01	30.85	7.45	24.69	43.30	54.00	-10.70	AV
V	28725.00	53.31	31.02	8.99	25.57	56.85	74.00	-17.15	PK
V	28725.00	42.33	31.02	8.99	25.57	45.87	54.00	-8.13	AV
H	11490.00	51.78	30.55	5.77	24.66	51.66	74.00	-22.34	PK
H	11490.00	43.22	30.55	5.77	24.66	43.10	54.00	-10.90	AV
H	17235.00	54.08	30.33	6.32	24.55	54.62	74.00	-19.38	PK
H	17235.00	42.54	30.33	6.32	24.55	43.08	54.00	-10.92	AV
H	22980.00	50.62	30.85	7.45	24.69	51.91	74.00	-22.09	PK
H	22980.00	42.32	30.85	7.45	24.69	43.61	54.00	-10.39	AV
H	28725.00	51.49	31.02	8.99	25.57	55.03	74.00	-18.97	PK
H	28725.00	42.49	31.02	8.99	25.57	46.03	54.00	-7.97	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:5785MHz									
V	11570.00	49.38	30.55	5.77	24.66	49.26	74.00	-24.74	PK
V	11570.00	41.61	30.55	5.77	24.66	41.49	54.00	-12.51	AV
V	17355.00	48.59	30.33	6.32	24.55	49.13	74.00	-24.87	PK
V	17355.00	41.36	30.33	6.32	24.55	41.90	54.00	-12.10	AV
V	23140.00	50.79	30.85	7.45	24.69	52.08	74.00	-21.92	PK
V	23140.00	41.09	30.85	7.45	24.69	42.38	54.00	-11.62	AV
V	28925.00	48.40	31.02	8.99	25.57	51.94	74.00	-22.06	PK
V	28925.00	41.50	31.02	8.99	25.57	45.04	54.00	-8.96	AV
H	11570.00	48.90	30.55	5.77	24.66	48.78	74.00	-25.22	PK
H	11570.00	41.83	30.55	5.77	24.66	41.71	54.00	-12.29	AV
H	17355.00	53.04	30.33	6.32	24.55	53.58	74.00	-20.42	PK
H	17355.00	41.18	30.33	6.32	24.55	41.72	54.00	-12.28	AV
H	23140.00	50.27	30.85	7.45	24.69	51.56	74.00	-22.44	PK
H	23140.00	41.88	30.85	7.45	24.69	43.17	54.00	-10.83	AV
H	28925.00	48.11	31.02	8.99	25.57	51.65	74.00	-22.35	PK
H	28925.00	41.74	31.02	8.99	25.57	45.28	54.00	-8.72	AV



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:5825MHz									
V	11650.00	49.95	30.55	5.77	24.66	49.83	74.00	-24.17	PK
V	11650.00	41.40	30.55	5.77	24.66	41.28	54.00	-12.72	AV
V	17475.00	48.51	30.33	6.32	24.55	49.05	74.00	-24.95	PK
V	17475.00	41.26	30.33	6.32	24.55	41.80	54.00	-12.20	AV
V	23300.00	49.55	30.85	7.45	24.69	50.84	74.00	-23.16	PK
V	23300.00	41.25	30.85	7.45	24.69	42.54	54.00	-11.46	AV
V	29125.00	52.18	31.02	8.99	25.57	55.72	74.00	-18.28	PK
V	29125.00	41.26	31.02	8.99	25.57	44.80	54.00	-9.20	AV
H	11650.00	50.58	30.55	5.77	24.66	50.46	74.00	-23.54	PK
H	11650.00	40.92	30.55	5.77	24.66	40.80	54.00	-13.20	AV
H	17475.00	51.54	30.33	6.32	24.55	52.08	74.00	-21.92	PK
H	17475.00	41.21	30.33	6.32	24.55	41.75	54.00	-12.25	AV
H	23300.00	52.24	30.85	7.45	24.69	53.53	74.00	-20.47	PK
H	23300.00	41.02	30.85	7.45	24.69	42.31	54.00	-11.69	AV
H	29125.00	47.80	31.02	8.99	25.57	51.34	74.00	-22.66	PK
H	29125.00	41.81	31.02	8.99	25.57	45.35	54.00	-8.65	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11ac20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Low Channel:5745MHz									
V	11490.00	50.77	30.55	5.77	24.66	50.65	74.00	-23.35	PK
V	11490.00	43.07	30.55	5.77	24.66	42.95	54.00	-11.05	AV
V	17235.00	51.82	30.33	6.32	24.55	52.36	74.00	-21.64	PK
V	17235.00	43.14	30.33	6.32	24.55	43.68	54.00	-10.32	AV
V	22980.00	48.78	30.85	7.45	24.69	50.07	74.00	-23.93	PK
V	22980.00	42.25	30.85	7.45	24.69	43.54	54.00	-10.46	AV
V	28725.00	52.04	31.02	8.99	25.57	55.58	74.00	-18.42	PK
V	28725.00	42.62	31.02	8.99	25.57	46.16	54.00	-7.84	AV
H	11490.00	52.18	30.55	5.77	24.66	52.06	74.00	-21.94	PK
H	11490.00	43.10	30.55	5.77	24.66	42.98	54.00	-11.02	AV
H	17235.00	53.56	30.33	6.32	24.55	54.10	74.00	-19.90	PK
H	17235.00	42.09	30.33	6.32	24.55	42.63	54.00	-11.37	AV
H	22980.00	52.11	30.85	7.45	24.69	53.40	74.00	-20.60	PK
H	22980.00	43.33	30.85	7.45	24.69	44.62	54.00	-9.38	AV
H	28725.00	52.22	31.02	8.99	25.57	55.76	74.00	-18.24	PK
H	28725.00	43.03	31.02	8.99	25.57	46.57	54.00	-7.43	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampl ifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Middle Channel:5785MHz									
V	11570.00	49.33	30.55	5.77	24.66	49.21	74.00	-24.79	PK
V	11570.00	41.71	30.55	5.77	24.66	41.59	54.00	-12.41	AV
V	17355.00	48.72	30.33	6.32	24.55	49.26	74.00	-24.74	PK
V	17355.00	41.55	30.33	6.32	24.55	42.09	54.00	-11.91	AV
V	23140.00	50.80	30.85	7.45	24.69	52.09	74.00	-21.91	PK
V	23140.00	41.32	30.85	7.45	24.69	42.61	54.00	-11.39	AV
V	28925.00	48.28	31.02	8.99	25.57	51.82	74.00	-22.18	PK
V	28925.00	41.32	31.02	8.99	25.57	44.86	54.00	-9.14	AV
H	11570.00	48.66	30.55	5.77	24.66	48.54	74.00	-25.46	PK
H	11570.00	41.70	30.55	5.77	24.66	41.58	54.00	-12.42	AV
H	17355.00	52.93	30.33	6.32	24.55	53.47	74.00	-20.53	PK
H	17355.00	41.33	30.33	6.32	24.55	41.87	54.00	-12.13	AV
H	23140.00	50.58	30.85	7.45	24.69	51.87	74.00	-22.13	PK
H	23140.00	41.99	30.85	7.45	24.69	43.28	54.00	-10.72	AV
H	28925.00	48.53	31.02	8.99	25.57	52.07	74.00	-21.93	PK
H	28925.00	41.66	31.02	8.99	25.57	45.20	54.00	-8.80	AV



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:5825MHz									
V	11650.00	50.29	30.55	5.77	24.66	50.17	74.00	-23.83	PK
V	11650.00	41.55	30.55	5.77	24.66	41.43	54.00	-12.57	AV
V	17475.00	48.06	30.33	6.32	24.55	48.60	74.00	-25.40	PK
V	17475.00	41.45	30.33	6.32	24.55	41.99	54.00	-12.01	AV
V	23300.00	49.50	30.85	7.45	24.69	50.79	74.00	-23.21	PK
V	23300.00	41.28	30.85	7.45	24.69	42.57	54.00	-11.43	AV
V	29125.00	52.15	31.02	8.99	25.57	55.69	74.00	-18.31	PK
V	29125.00	41.41	31.02	8.99	25.57	44.95	54.00	-9.05	AV
H	11650.00	50.62	30.55	5.77	24.66	50.50	74.00	-23.50	PK
H	11650.00	40.76	30.55	5.77	24.66	40.64	54.00	-13.36	AV
H	17475.00	51.29	30.33	6.32	24.55	51.83	74.00	-22.17	PK
H	17475.00	41.23	30.33	6.32	24.55	41.77	54.00	-12.23	AV
H	23300.00	52.00	30.85	7.45	24.69	53.29	74.00	-20.71	PK
H	23300.00	40.95	30.85	7.45	24.69	42.24	54.00	-11.76	AV
H	29125.00	48.10	31.02	8.99	25.57	51.64	74.00	-22.36	PK
H	29125.00	41.84	31.02	8.99	25.57	45.38	54.00	-8.62	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(3)

Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.



5.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- Set $VBW \geq 3$ RBW.
- If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.6 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Band :	5.2G		


5.2G						
Test mode	Test Channel (MHz)	PSD (dBm)	duty cycle Factor (dB)	Total PSD (dBm)	Limit (dBm/MHz)	Result
802.11a	5180	4.62	0.19	4.81	11	Pass
	5200	4.93	0.19	5.12	11	Pass
	5240	4.4	0.19	4.59	11	Pass
802.11n20	5180	2.2	0.20	2.40	11	Pass
	5200	2.42	0.20	2.62	11	Pass
	5240	1.96	0.20	2.16	11	Pass
802.11n40	5190	-1.95	0.33	-1.62	11	Pass
	5230	-1.91	0.33	-1.58	11	Pass
802.11ac20	5180	0.17	0.17	0.34	11	Pass
	5200	0.41	0.17	0.58	11	Pass
	5240	0.03	0.17	0.20	11	Pass
802.11ac40	5190	-3.48	0.33	-3.15	11	Pass
	5230	-3.28	0.33	-2.95	11	Pass
802.11ac80	5210	-6.97	0.63	-6.34	11	Pass
Note: duty cycle Factor see page 83						




(802.11a) PSD plot on channel 36



(802.11a) PSD plot on channel 40




(802.11a) PSD plot on channel 48







(802.11n20) PSD plot on channel 36




(802.11n40) PSD plot on channel 38




(802.11n20) PSD plot on channel 40



(802.11n40) PSD plot on channel 46




(802.11n20) PSD plot on channel 48







(802.11ac20) PSD plot on channel 36




(802.11ac40) PSD plot on channel 38




(802.11ac20) PSD plot on channel 40




(802.11ac40) PSD plot on channel 46



(802.11ac20) PSD plot on channel 48



(802.11ac80) PSD plot on channel 42






Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Band :	5.8G		


5.8G						
Test mode	Test Channel (MHz)	PSD (dBm/510kHz)	duty cycle Factor (dB)	Total PSD (dBm)	Limit (dBm/500kHz)	Result
802.11a	5745	-2.26	0.45	-1.81	30	Pass
	5785	-0.99	0.45	-0.54	30	Pass
	5825	-1.13	0.45	-0.68	30	Pass
802.11n20	5745	-2.51	0.50	-2.01	30	Pass
	5785	-1.46	0.50	-0.96	30	Pass
	5825	-1.12	0.50	-0.62	30	Pass
802.11n40	5755	-5.4	1.00	-4.40	30	Pass
	5795	-4.41	1.00	-3.41	30	Pass
802.11ac20	5745	-2.45	0.49	-1.96	30	Pass
	5785	-1.15	0.49	-0.66	30	Pass
	5825	-1.28	0.49	-0.79	30	Pass
802.11ac40	5755	-5.02	0.94	-4.08	30	Pass
	5795	-4.02	0.94	-3.08	30	Pass
802.11ac80	5775	-7.92	1.81	-6.11	30	Pass
Note: duty cycle Factor see page 87						




(802.11a) PSD plot on channel 149



(802.11a) PSD plot on channel 157




(802.11a) PSD plot on channel 165







(802.11n20) PSD plot on channel 149




(802.11n40) PSD plot on channel 151




(802.11n20) PSD plot on channel 157



(802.11n40) PSD plot on channel 159




(802.11n20) PSD plot on channel 165







(802.11ac20) PSD plot on channel 149



(802.11ac40) PSD plot on channel 151




(802.11ac20) PSD plot on channel 157




(802.11ac40) PSD plot on channel 159



(802.11ac20) PSD plot on channel 165



(802.11ac80) PSD plot on channel 155





6. 26DB EMISSION BANDWIDTH & 6DB OCCUPIED BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

6.2 TEST PROCEDURE

The following procedure shall be used for measuring 6dB Occupied Bandwidth:

The procedure for this method is as follows:


- Set RBW = 100KHz.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The following procedure shall be used for measuring 26dB Emission bandwidth:

The procedure for this method is as follows:

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission.

Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.



6.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 6.2 Unless otherwise a special operating condition is specified in the follows during the testing.



6.4 TEST RESULTS


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Band :	5.2G		

5.2G				
Test Mode	Test Channel (MHz)	26dB Emission Bandwidth (MHz)	Limit(KHz)	Result
802.11a	5180	32.68	N/A	Pass
	5200	32.78		
	5240	29.59		
802.11n20	5180	29.67	N/A	Pass
	5200	29.9		
	5240	23.06		
802.11n40	5190	67.66	N/A	Pass
	5230	43.76		
802.11ac20	5180	23.14	N/A	Pass
	5200	21.31		
	5240	21.69		
802.11ac40	5190	44.7	N/A	Pass
	5230	44.65		
802.11ac80	5210	82.24	N/A	Pass




5.2G Test plot


(802.11 a) 26dB Bandwidth plot on channel 36



(802.11 a) 26dB Bandwidth plot on channel 48




(802.11 a) 26dB Bandwidth plot on channel 48






5.2G Test plot


(802.11 n20) 26dB Bandwidth plot on channel 36




(802.11 n40) 26dB Bandwidth plot on channel 38



(802.11 n20) 26dB Bandwidth plot on channel 40



(802.11 n40) 26dB Bandwidth plot on channel 46



(802.11 n20) 26dB Bandwidth plot on channel 48

