

TEST REPORT

Reference No...... : WTX25X10284450W002
FCC ID..... : 2BUSG-WP1
Applicant..... : Firia Inc
Address..... : 1038 Research Blvd. Ste 240, Madison, AL, 35758
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Firia Waypoint WP-1
Model No...... : WP1
Standards..... : FCC Part 15.247
Date of Receipt sample..... : 2025-10-29
Date of Test..... : 2025-11-05 to 2025-11-20
Date of Issue..... : 2025-12-01
Test Report Form No...... : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,

Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	12
3. ANTENNA REQUIREMENT	13
3.1 STANDARD APPLICABLE	13
3.2 EVALUATION INFORMATION	13
4. POWER SPECTRAL DENSITY	14
4.1 STANDARD APPLICABLE	14
4.2 TEST SETUP BLOCK DIAGRAM	14
4.3 TEST PROCEDURE	14
5.4 SUMMARY OF TEST RESULTS/PLOTS	14
5. 6DB BANDWIDTH	15
5.1 STANDARD APPLICABLE	15
5.2 TEST SETUP BLOCK DIAGRAM	15
5.3 TEST PROCEDURE	15
5.4 SUMMARY OF TEST RESULTS/PLOTS	15
6. RF OUTPUT POWER	16
6.1 STANDARD APPLICABLE	16
6.2 TEST SETUP BLOCK DIAGRAM	16
6.3 TEST PROCEDURE	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	17
7.1 STANDARD APPLICABLE	17
7.2 TEST PROCEDURE	17
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	19
7.4 SUMMARY OF TEST RESULTS/PLOTS	19
8. OUT OF BAND EMISSIONS	26
8.1 STANDARD APPLICABLE	26
8.2 TEST PROCEDURE	26
8.3 SUMMARY OF TEST RESULTS/PLOTS	27
9. CONDUCTED EMISSIONS	31
9.1 TEST PROCEDURE	31
9.2 BASIC TEST SETUP BLOCK DIAGRAM	31
9.3 TEST RECEIVER SETUP	31
9.4 SUMMARY OF TEST RESULTS/PLOTS	31
APPENDIX SUMMARY	34
APPENDIX A	35
APPENDIX B	38
APPENDIX C	41
APPENDIX D	44
APPENDIX PHOTOGRAPHS	48

Report version

Version No.	Date of issue	Description
Rev.00	2025-12-01	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Firia Waypoint WP-1
Trade Name:	/
Model No.:	WP1
Adding Model(s):	/
Rated Voltage:	DC12V
Battery Capacity:	/
Power Adapter:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2405-2475MHz
RF Output Power:	Antenna 1: 10.02dBm (Conducted) Antenna 2: 9.44dBm (Conducted)
Modulation:	OQPSK
Quantity of Channels:	15
Channel Separation:	5MHz
Type of Antenna:	Antenna 1: External antenna Antenna 2: PCB antenna
Antenna Gain:	Antenna 1: 5.3dBi Antenna 2: -9.32dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 DTS Meas Guidance v05r02: Guidance for performing Compliance Measurement on Digital Transmission Systems operating under section 15.247.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB 558074 D01 DTS Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The RF sample was used for the purpose of the measurements. All testing was performed under the maximum output power condition, with a duty cycle equal to 100%, and measured its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2405MHz
TM2	Middle	2440MHz
TM3	High	2475MHz
Note: By controlling the chip U13 (SKY13348-374LF) through software, the internal switch of the chip switches between J1 or J2 to use J1's ANT1 (PCB Antenna) or J2's ANT 2 (External Antenna). ANT 1 and ANT 2 cannot be launched simultaneously.		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	/	ADP-36K12	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	0.57dB
Occupied Bandwidth	Conducted	0.015MHz
Power Spectral Density	Conducted	1.8dB
Conducted Spurious Emission	Conducted	2.17dB
Conducted Emissions	Conducted	9-150kHz, 3.74dB
		0.15-30MHz, 3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz, 4.52dB
		0.2-1GHz 5.56dB
		1-6GHz, 3.84dB
		6-18GHz, 3.92dB

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
WTXE1022A 1002	GSM Tester	Rohde & Schwarz	CMU200	114403	2025-02-23	2026-02-22
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2025-02-23	2026-02-22
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2025-02-23	2026-02-22
WTXE1044A 1001	Signal Generator	Agilent	83752A	3610A014 53	2025-02-23	2026-02-22
WTXE1045A 1001	Vector Signal Generator	Agilent	N5182A	MY470702 02	2025-02-23	2026-02-22
WTXE1018A 1001	Power Divider	Weinschel	1506A	PM204	2025-02-23	2026-02-22
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2025-02-23	2026-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2025-02-23	2026-02-22
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2025-02-23	2026-02-22
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22

WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2025-02-23	2026-02-22
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2025-02-23	2026-02-22
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2025-02-23	2026-02-22
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2025-02-23	2026-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2025-02-23	2026-02-22
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22

WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2025-02-23	2026-02-22
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2025-02-23	2026-02-22
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2025-02-23	2026-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2025-02-23	2026-02-22
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2025-02-23	2026-02-22
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6 dB Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has a PCB antenna and an External antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.4 Summary of Test Results/Plots


Please refer to Appendix A

5. 6dB Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

- Set RBW = 100kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

5.4 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq$ 3RBW.
- c) Set span $\geq$ 3RBW.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz
RBW=10kHz,
VBW =30kHz
Sweep time= Auto
Trace = max hold
Detector function = peak

Frequency :30MHz-1GHz
RBW=120kHz,
VBW=300kHz
Sweep time= Auto
Trace = max hold
Detector function = peak, QP

Frequency :Above 1GHz
RBW=1MHz,
VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto
Trace = max hold
Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

7.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emissions Below 1GHz
- External antenna

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	34.0451	28.93	-10.32	18.61	40.00	-21.39	-	-	peak
2	63.1857	32.18	-9.97	22.21	40.00	-17.79	-	-	peak
3	122.3189	27.77	-10.66	17.11	43.50	-26.39	-	-	peak
4	217.6437	32.72	-11.64	21.08	46.00	-24.92	-	-	peak
5	409.6506	29.07	-5.97	23.10	46.00	-22.90	-	-	peak
6	615.7743	30.25	-2.11	28.14	46.00	-17.86	-	-	peak


Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	62.7432	34.96	-9.92	25.04	40.00	-14.96	-	-	peak
2	74.2696	34.67	-11.92	22.75	40.00	-17.25	-	-	peak
3	79.6764	27.72	-12.96	14.76	40.00	-25.24	-	-	peak
4	156.4259	28.50	-8.58	19.92	43.50	-23.58	-	-	peak
5	461.6313	29.39	-4.92	24.47	46.00	-21.53	-	-	peak
6	708.6941	29.75	-0.77	28.98	46.00	-17.02	-	-	peak


➤ PCB antenna

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.8452	30.49	-9.16	21.33	40.00	-18.67	-	-	peak
2	63.1857	35.96	-9.97	25.99	40.00	-14.01	-	-	peak
3	146.8392	29.19	-9.04	20.15	43.50	-23.35	-	-	peak
4	217.6437	36.25	-11.64	24.61	46.00	-21.39	-	-	peak
5	363.5231	31.03	-6.79	24.24	46.00	-21.76	-	-	peak
6	655.9766	30.29	-1.30	28.99	46.00	-17.01	-	-	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	35.0157	29.47	-10.25	19.22	40.00	-20.78	-	-	peak
2	62.3038	34.92	-9.86	25.06	40.00	-14.94	-	-	peak
3	74.2696	35.31	-11.92	23.39	40.00	-16.61	-	-	peak
4	186.4684	32.77	-10.66	22.11	43.50	-21.39	-	-	peak
5	628.8936	29.77	-2.01	27.76	46.00	-18.24	-	-	peak
6	972.2827	32.29	2.98	35.27	54.00	-18.73	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz

External antenna

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2405MHz							
4810.000	58.91	-13.22	45.69	74	-28.31	H	PK
4810.000	55.80	-13.22	42.58	54	-11.42	H	AV
7215.000	55.85	-6.87	48.98	74	-25.02	H	PK
7215.000	51.35	-6.87	44.48	54	-9.52	H	AV
4810.000	60.78	-13.22	47.56	74	-26.44	V	PK
4810.000	57.03	-13.22	43.81	54	-10.19	V	AV
7215.000	56.63	-6.87	49.76	74	-24.24	V	PK
7215.000	53.84	-6.87	46.97	54	-7.03	V	AV
Middle Channel-2440MHz							
4880.000	58.35	-13.10	45.25	74	-28.75	H	PK
4880.000	56.19	-13.10	43.09	54	-10.91	H	AV
7320.000	56.19	-7.12	49.07	74	-24.93	H	PK
7320.000	51.94	-7.12	44.82	54	-9.18	H	AV
4880.000	60.39	-13.10	47.29	74	-26.71	V	PK
4880.000	57.37	-13.10	44.27	54	-9.73	V	AV
7320.000	56.09	-7.12	48.97	74	-25.03	V	PK
7320.000	53.22	-7.12	46.10	54	-7.90	V	AV
High Channel-2475MHz							
4950.000	58.54	-13.06	45.48	74	-28.52	H	PK
4950.000	54.93	-13.06	41.87	54	-12.13	H	AV
7425.000	55.16	-7.48	47.68	74	-26.32	H	PK
7425.000	52.12	-7.48	44.64	54	-9.36	H	AV
4950.000	60.71	-13.06	47.65	74	-26.35	V	PK
4950.000	57.30	-13.06	44.24	54	-9.76	V	AV
7425.000	56.06	-7.48	48.58	74	-25.42	V	PK
7425.000	52.95	-7.48	45.47	54	-8.53	V	AV

PCB antenna

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2405MHz							
4810.000	58.71	-13.22	45.49	74	-28.51	H	PK
4810.000	56.32	-13.22	43.10	54	-10.90	H	AV
7215.000	56.61	-6.87	49.74	74	-24.26	H	PK
7215.000	52.85	-6.87	45.98	54	-8.02	H	AV
4810.000	58.57	-13.22	45.35	74	-28.65	V	PK
4810.000	55.52	-13.22	42.30	54	-11.70	V	AV
7215.000	57.12	-6.87	50.25	74	-23.75	V	PK
7215.000	54.57	-6.87	47.70	54	-6.30	V	AV
Middle Channel-2440MHz							
4880.000	59.78	-13.10	46.68	74	-27.32	H	PK
4880.000	56.29	-13.10	43.19	54	-10.81	H	AV
7320.000	56.07	-7.12	48.95	74	-25.05	H	PK
7320.000	52.52	-7.12	45.40	54	-8.60	H	AV
4880.000	59.27	-13.10	46.17	74	-27.83	V	PK
4880.000	56.01	-13.10	42.91	54	-11.09	V	AV
7320.000	57.07	-7.12	49.95	74	-24.05	V	PK
7320.000	53.73	-7.12	46.61	54	-7.39	V	AV
High Channel-2475MHz							
4950.000	60.19	-13.06	47.13	74	-26.87	H	PK
4950.000	56.18	-13.06	43.12	54	-10.88	H	AV
7425.000	56.66	-7.48	49.18	74	-24.82	H	PK
7425.000	53.53	-7.48	46.05	54	-7.95	H	AV
4950.000	58.87	-13.06	45.81	74	-28.19	V	PK
4950.000	54.81	-13.06	41.75	54	-12.25	V	AV
7425.000	57.29	-7.48	49.81	74	-24.19	V	PK
7425.000	54.18	-7.48	46.70	54	-7.30	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247 (d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100kHz.
4. Set VBW $\geq$ 300kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots

External antenna

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.71	-19.50	22.21	54.00	-31.79	Average Detector
	2310.000	54.52	-19.50	35.02	74.00	-38.98	Peak Detector
2	2390.000	45.48	-19.31	26.17	54.00	-27.83	Average Detector
	2390.000	57.89	-19.31	38.58	74.00	-35.42	Peak Detector
3	2405.190	115.44	-19.28	96.16	/	/	Average Detector
	2404.589	121.79	-19.28	102.51	/	/	Peak Detector

Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2474.930	119.66	-19.11	100.55	/	/	Average Detector
	2474.389	124.02	-19.11	104.91	/	/	Peak Detector
2	2483.500	56.69	-19.09	37.60	54.00	-16.40	Average Detector
	2483.500	69.48	-19.09	50.39	74.00	-23.61	Peak Detector
3	2500.000	44.75	-19.05	25.70	54.00	-28.30	Average Detector
	2500.000	57.12	-19.05	38.07	74.00	-35.93	Peak Detector


PCB antenna

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.12	-19.50	21.62	54.00	-32.38	Average Detector
	2310.000	53.11	-19.50	33.61	74.00	-40.39	Peak Detector
2	2390.000	41.96	-19.31	22.65	54.00	-31.35	Average Detector
	2390.000	53.82	-19.31	34.51	74.00	-39.49	Peak Detector
3	2405.190	109.51	-19.28	90.23	/	/	Average Detector
	2404.589	115.89	-19.28	96.61	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2474.990	108.27	-19.11	89.16	/	/	Average Detector
	2474.389	114.23	-19.11	95.12	/	/	Peak Detector
2	2483.500	46.58	-19.09	27.49	54.00	-26.51	Average Detector
	2483.500	58.51	-19.09	39.42	74.00	-34.58	Peak Detector
3	2500.000	41.10	-19.05	22.05	54.00	-31.95	Average Detector
	2500.000	53.36	-19.05	34.31	74.00	-39.69	Peak Detector

Conducted Out of Band Emissions
Please refer to Appendix D


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1819	37.78	9.56	47.34	64.39	-17.05	QP
2	0.2099	14.33	9.63	23.96	53.21	-29.25	AVG
3	0.3059	12.41	9.63	22.04	50.08	-28.04	AVG
4	0.6860	21.64	9.73	31.37	56.00	-24.63	QP
5	0.7740	11.40	9.74	21.14	46.00	-24.86	AVG
6	1.3939	22.81	9.60	32.41	56.00	-23.59	QP
7	1.3939	13.40	9.60	23.00	46.00	-23.00	AVG
8	2.1339	6.95	9.37	16.32	46.00	-29.68	AVG
9	2.2820	19.67	9.37	29.04	56.00	-26.96	QP
10	4.1900	13.38	9.48	22.86	56.00	-33.14	QP
11	21.9540	1.89	9.54	11.43	50.00	-38.57	AVG
12	22.7860	21.23	9.54	30.77	60.00	-29.23	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1539	41.11	9.45	50.56	65.78	-15.22	QP
2	0.1539	16.77	9.45	26.22	55.78	-29.56	AVG
3	0.4380	16.66	9.64	26.30	47.10	-20.80	AVG
4	0.4460	32.33	9.64	41.97	56.95	-14.98	QP
5	1.1499	23.56	9.70	33.26	56.00	-22.74	QP
6	1.3859	13.09	9.61	22.70	46.00	-23.30	AVG
7	2.2900	7.02	9.37	16.39	46.00	-29.61	AVG
8	2.2980	19.97	9.37	29.34	56.00	-26.66	QP
9	4.2460	1.05	9.48	10.53	46.00	-35.47	AVG
10	7.3540	12.63	9.79	22.42	60.00	-37.58	QP
11	22.1700	21.23	9.54	30.77	60.00	-29.23	QP
12	22.1700	2.10	9.54	11.64	50.00	-38.36	AVG

APPENDIX SUMMARY

Project No.	WTX25X10284450W002	Test Engineer	Jennifer Song
Start date	2025/11/18	Finish date	2025/11/18
Temperature	25℃	Humidity	53%
RF specifications	2.4GHZ		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	DTS Bandwidth	Compliant
C	RF Output Power	Compliant
D	Conducted Out of Band Emissions	Compliant

APPENDIX A




External Antenna

Power Spectral Density			
Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
2.4G	Low	-5.18	8
	Middle	-5.52	8
	High	-5.71	8


PCB Antenna

Power Spectral Density			
Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
2.4G	Low	-6.28	8
	Middle	-6.64	8
	High	-7.75	8

External Antenna

Low	 The spectrum plot for the Low antenna position shows a blue trace on a grid. The y-axis represents power in dBm, ranging from -80 to 20. The x-axis represents frequency in GHz, with a center frequency of 2.405 GHz and a span of 3 MHz. The plot includes a red diamond icon, a blue 'A' icon, and a green 'A' icon. The text 'Ref 20 dBm', 'Att 30 dB', 'RBW 3 kHz', 'VBW 10 kHz', 'SWT 340 ms', and 'Marker 1 [T1]' are visible. The power level is -5.18 dBm.
Middle	 The spectrum plot for the Middle antenna position shows a blue trace on a grid. The y-axis represents power in dBm, ranging from -80 to 20. The x-axis represents frequency in GHz, with a center frequency of 2.44 GHz and a span of 3 MHz. The plot includes a red diamond icon, a blue 'A' icon, and a green 'A' icon. The text 'Ref 20 dBm', 'Att 30 dB', 'RBW 3 kHz', 'VBW 10 kHz', 'SWT 340 ms', and 'Marker 1 [T1]' are visible. The power level is -5.52 dBm.
High	 The spectrum plot for the High antenna position shows a blue trace on a grid. The y-axis represents power in dBm, ranging from -80 to 20. The x-axis represents frequency in GHz, with a center frequency of 2.475 GHz and a span of 3 MHz. The plot includes a red diamond icon, a blue 'A' icon, and a green 'A' icon. The text 'Ref 20 dBm', 'Att 30 dB', 'RBW 3 kHz', 'VBW 10 kHz', 'SWT 340 ms', and 'Marker 1 [T1]' are visible. The power level is -5.71 dBm.

PCB Antenna



APPENDIX B


External Antenna

Test Mode	Test Channel	6 dB Bandwidth kHz	Limit kHz
2.4G	Low	1650	≥500
	Middle	1640	≥500
	High	1640	≥500


PCB Antenna

Test Mode	Test Channel	6 dB Bandwidth kHz	Limit kHz
2.4G	Low	1640	≥500
	Middle	1640	≥500
	High	1640	≥500

External Antenna



PCB Antenna



APPENDIX C


External Antenna

RF Output Power			
Test Mode	Test Channel	Reading dBm	Limit dBm
2.4G	Low	10.02	30.00
	Middle	9.65	30.00
	High	9.56	30.00




PCB Antenna

RF Output Power			
Test Mode	Test Channel	Reading dBm	Limit dBm
2.4G	Low	9.44	30.00
	Middle	9.01	30.00
	High	8.71	30.00

External Antenna




PCB Antenna


Low	 The spectrum plot for the Low band shows a blue curve representing the signal strength. The y-axis is labeled from -80 to 20 dBm in increments of 10. The x-axis is labeled from -10 to 10 MHz in increments of 1 MHz. A green horizontal line is drawn at 10 dBm. A blue marker labeled '1' is placed on the curve at approximately 2.405 GHz. The plot is titled 'Ref 20 dBm', 'Att 30 dB', 'RBW 3 MHz', 'VBW 10 MHz', 'SWT 2.5 ms', and 'Marker 1 [T1] 9.44 dBm 2.404460000 GHz'. The plot is also labeled '1 dB' and '10 dB' on the left side.
Middle	 The spectrum plot for the Middle band shows a blue curve representing the signal strength. The y-axis is labeled from -80 to 20 dBm in increments of 10. The x-axis is labeled from -10 to 10 MHz in increments of 1 MHz. A green horizontal line is drawn at 10 dBm. A blue marker labeled '1' is placed on the curve at approximately 2.44 GHz. The plot is titled 'Ref 20 dBm', 'Att 30 dB', 'RBW 3 MHz', 'VBW 10 MHz', 'SWT 2.5 ms', and 'Marker 1 [T1] 9.01 dBm 2.439280000 GHz'. The plot is also labeled '1 dB' and '10 dB' on the left side.
High	 The spectrum plot for the High band shows a blue curve representing the signal strength. The y-axis is labeled from -80 to 20 dBm in increments of 10. The x-axis is labeled from -10 to 10 MHz in increments of 1 MHz. A green horizontal line is drawn at 10 dBm. A blue marker labeled '1' is placed on the curve at approximately 2.475 GHz. The plot is titled 'Ref 20 dBm', 'Att 30 dB', 'RBW 3 MHz', 'VBW 10 MHz', 'SWT 2.5 ms', and 'Marker 1 [T1] 8.71 dBm 2.474320000 GHz'. The plot is also labeled '1 dB' and '10 dB' on the left side.

APPENDIX D

(External Antenna)



Conducted Out of Band Emissions







(PCB Antenna)

Low



Middle





APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****