

**Shenzhen Global Test Service Co., Ltd**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT**FCC PART 15 C(15.249)****Report Reference No.....: GTS20251128005-1-11****FCC ID.....: 2BUSS-UBI062603001**

Compiled by

(position+printed name+signature) .: File administrators Peter Xiao

Supervised by

(position+printed name+signature) .: Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) .: Manager Jason Hu



Date of issue: Feb.10, 2026

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....: Shanghai Ubiquitous Navigation Technology Co., Ltd.

Address: 11th Floor, Building 6, Lane 308, Xumin Road, Qingpu District, Shanghai, China

Test specificationStandard: **FCC CFR 47 PART 15 C(15.249)****ANSIC63.10-2020+Cor.1-2023+C63.10a-2024**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Unmanned Surface Vehicle

Trade Mark: UbiNavi

Manufacturer: Shanghai Ubiquitous Navigation Technology Co., Ltd.

Model/Type reference: iUSV-6

Listed Models: N/A

Modulation Type.....: DSSS,OFDM

Operation Frequency.....: From 5730MHz ~ 5840MHz

Hardware Version: N/A

Software Version: N/A

Rating: DC 29.6V by battery*2

Result: **PASS**

TEST REPORT

Test Report No. : GTS20251128005-1-11	Feb.10, 2026 Date of issue
---	-------------------------------

Equipment under Test : Unmanned Surface Vehicle

Model /Type : iUSV-6

Listed model : N/A

Applicant : **Shanghai Ubiquitous Navigation Technology Co., Ltd.**

Address : 11th Floor, Building 6, Lane 308, Xumin Road, Qingpu District,
Shanghai, China

Manufacturer : **Shanghai Ubiquitous Navigation Technology Co., Ltd.**

Address : 11th Floor, Building 6, Lane 308, Xumin Road, Qingpu District,
Shanghai, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	7
2.4. Short description of the Equipment under Test (EUT)	7
2.5. EUT operation mode	7
2.6. Block Diagram of Test Setup	7
2.7. EUT Exercise Software	8
2.8. Special Accessories	8
2.9. External I/O Cable	8
2.10. Related Submittal(s) / Grant (s)	8
2.11. Modifications	8
3. TEST ENVIRONMENT	9
3.1. Address of the test laboratory	9
3.2. Test Facility	9
3.3. Environmental conditions	9
3.4. Statement of the measurement uncertainty	9
3.5. Test Description	10
3.6. Equipments Used during the Test.....	11
4. TEST CONDITIONS AND RESULTS	12
4.1. AC Power Conducted Emission	12
4.2. Radiated Emission	13
4.3. 20dB Bandwidth	18
4.4. Band Edge Compliance of RF Emission	20
4.5. Antenna Requirement	22
5. TEST SETUP PHOTOS OF THE EUT	23
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	23

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249](#): Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHz, and 24.0-24.25 GHz.

[ANSI C63.10-2020+Cor.1-2023+C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Jan. 08, 2026
	:	
Testing commenced on	:	Jan. 08, 2026
	:	
Testing concluded on	:	Feb. 09, 2026

2.2. Product Description

Product Name	Unmanned Surface Vehicle
Trade Mark	UbiNavi
Model/Type reference	iUSV-6
List Models	N/A
Model Declaration	N/A
Power supply:	DC 29.6V by battery*2
Sample ID	GTS20251128005-1-S0001-1#GTS20251128005-1-S0001-2#
SRD(2.4G)	
Frequency Range	2411MHz ~ 2477MHz
Channel Number	7 channels
Channel Spacing	11MHz
Modulation Type	DSSS,OFDM
SRD(5.8G)	
Operation frequency	5730-5840MHz
Modulation Type	DSSS,OFDM
Channel Number	6 channels
Antenna Description	Dipole Antenna, 3.00dBi(Max.) for 2.4G Band and 3.00dBi (Max.) for 5G Band
3G	
UMTS Operation Frequency Band	UMTS FDD Band 2(1850 MHz -1910MHz) UMTS FDD Band 5(824 MHz -849MHz)
WCDMA Release Version	R7
HSDPA Release Version	Release 5
HSUPA Release Version	Release 6
HSPA+ Release Version	N/A
Modulation Type	QPSK for UMTS
Antenna Description	Dipole Antenna; 3.00dBi (max.) For WCDMA Band 2; 3.00dBi (max.) For WCDMA Band 5;
Power Class	Level 3
LTE	
LTE Operation Frequency Band	E-UTRA Band 2(1850 MHz -1910MHz) E-UTRA Band 4(1710 MHz -1755MHz) E-UTRA Band 5(824 MHz -849MHz) E-UTRA Band 7(2500 MHz -2570MHz) E-UTRA Band 12(699 MHz -716MHz) E-UTRA Band 25(1850 MHz -1915MHz) E-UTRA Band 26(814 MHz -824MHz)

	E-UTRA Band 26(824 MHz -849MHz) E-UTRA Band 41(2496 MHz -2690MHz) E-UTRA Band 66(1710 MHz -1780MHz)
LTE Release Version	R10
Type Of Modulation	QPSK/16QAM
Antenna Description	Dipole Antenna; 3.00dBi (max.) For LTE Band 2; 3.00dBi (max.) For LTE Band 4; 3.00dBi (max.) For LTE Band 5; 3.00dBi (max.) For LTE Band 7; 3.00dBi (max.) For LTE Band 12; 3.00dBi (max.) For LTE Band 25; 3.00dBi (max.) For LTE Band 26; 3.00dBi (max.) For LTE Band 41; 3.00dBi (max.) For LTE Band 66.

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 29.6V

2.4. Short description of the Equipment under Test (EUT)

This is an Unmanned Surface Vehicle.

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

Mode of Operations	Frequency Range (MHz)	Channel
5.8G	5730	26
5.8G	5750	27
5.8G	5780	28
5.8G	5800	29
5.8G	5820	30
5.8G	5840	31
For Conducted Emission		
Test Mode	TX Mode	
For Radiated Emission		
Test Mode	TX Mode	

Channel	Frequency(MHz)
26	5730
29	5800
31	5840


The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, which was determined to be 5.8G(MCH) mode.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be 5.8G(MCH) mode.

2.6. Block Diagram of Test Setup



2.7. EUT Exercise Software

The product continues to transmit signals after power on.

2.8. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
-	-	-	-	SDOC

2.9. External I/O Cable

I/O Port Description	Quantity	Cable
-	-	-

2.10. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2BUSS-UBI062603001** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.11. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong,China.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5. Test Description

Applied Standard: FCC Part 15 Subpart C				
FCC Rules	Description of Test	Test Sample	Result	Remark
§15.207(a)	Conduction Emissions	/	N/A	
§15.205(a) §15.209(a) §15.249(a) §15.249(c)	Radiated Emissions Measurement	GTS20251128005-1-S0001-1# GTS20251128005-1-S0001-2#	Compliant	Note 1
§15.249	Band Edges Measurement	GTS20251128005-1-S0001-1#	Compliant	Note 1
§15.249, §15.215	20 dB Bandwidth	GTS20251128005-1-S0001-1#	Compliant	Note 1
§15.203	Antenna Requirements	/	Compliant	Note 1

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (MPE Report).
5. We tested all test mode and recorded worst case in report

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Artificial Mains	CYBERTEK	EM5040A	E1850400205	2025/07/07	2026/07/06
LISN	R&S	ESH2-Z5	893606/008	2025/07/07	2026/07/06
EMI Test Receiver	R&S	ESPI 3	/	2025/07/04	2026/07/03
Test Receiver	R&S	ESCI 7	101102	2025/07/04	2026/07/03
Spectrum Analyzer	Agilent	N9020A	MY48010425	2025/07/04	2026/07/03
Spectrum Analyzer	R&S	FSV40-N	101800	2025/07/04	2026/07/03
Vector Signal generator	Agilent	N5181A	MY49060502	2025/07/15	2026/07/14
Signal generator	Agilent	N5182A	MY50141550	2025/07/04	2026/07/03
Climate Chamber	ESPEC	EL-10KA	A20120523	2025/07/15	2026/07/14
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2025/12/01	2026/11/30
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	/	2025/07/04	2026/07/03
By-log Antenna	SCHWARZBECK	VULB9163	00976	2025/07/15	2026/07/14
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2025/07/15	2026/07/14
Amplifier	SKET	LAPA_30M01G-32	SK20240104001	2025/12/01	2026/11/30
Amplifier	EMCI	EMC012645SE	980340	2025/12/01	2026/11/30
Amplifier	Schwarzbeck	BBV9179	9719-025	2025/12/01	2026/11/30
Temperature/Humidity Meter	HUATU	HTC-1	/	2025/07/16	2026/07/15
High-Pass Filter	Stest	1	/	2025/07/04	2026/07/03
High-Pass Filter	Stest	2	/	2025/07/04	2026/07/03
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2025/07/15	2026/07/14
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2025/07/15	2026/07/14
Data acquisition card	Agilent	U2531A	TW53323507	2025/07/15	2026/07/14
Power Sensor	Keysight	E9301A	MY41495308	2025/07/04	2026/07/03
Control Unit	Tonscend	JS0806-2	/	2025/07/07	2026/07/06
Control Unit	Tonscend	JS0806-2	/	2025/07/07	2026/07/06
integrated measuring instrument	R&S	CMW500	107519	2025/07/04	2026/07/03
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

Note: 1. The Cal.Interval was one year.


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 30MHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

1. The pre-test has been done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

2. According to §15.249 (a) & RSS-210§B.10(a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	millivolts/meter	dBuV/m	microvolts/meter	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

As shown in §15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

The field strength limits shall be measured using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using an International Special Committee on Radio Interference (CISPR) quasi-peak detector.

TEST RESULTS

Remark: We measured Radiated Emission at 5.8G mode from 9KHz to 10GHz in AC120V and the worst case was recorded.

Temperature	24℃	Humidity	48%
Test Engineer	Evan Ouyang	Configurations	5.8G(MCH)

For 9 KHz~30MHz

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

For 30MHz-1GHz

Horizontal

Test Graph



Suspected List


NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	50.37	28.34	-3.01	25.33	40.00	14.67	100	196	PK	Horizontal	PASS
2	175.5	37.95	-6.32	31.63	43.50	11.87	100	128	PK	Horizontal	PASS
3	247.28	39.83	-3.36	36.47	46.00	9.53	100	128	PK	Horizontal	PASS
4	374.835	33.15	-0.72	32.43	46.00	13.57	100	226	PK	Horizontal	PASS
5	499.965	34.33	2.28	36.61	46.00	9.39	100	98	PK	Horizontal	PASS
6	875.355	28.77	6.28	35.05	46.00	10.95	100	320	PK	Horizontal	PASS

Note:1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	149.795	44.23	-8.64	35.59	43.50	7.91	100	101	PK	Vertical	PASS
2	176.47	39.92	-6.41	33.51	43.50	9.99	100	325	PK	Vertical	PASS
3	247.28	36.51	-3.36	33.15	46.00	12.85	100	191	PK	Vertical	PASS
4	374.835	39.21	-0.72	38.49	46.00	7.51	100	301	PK	Vertical	PASS
5	499.965	39.50	2.28	41.78	46.00	4.22	100	207	PK	Vertical	PASS
6	875.355	35.45	6.28	41.73	46.00	4.27	100	191	PK	Vertical	PASS

Note:1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Field strength of fundamental:

Frequency (MHz)	Pol.	Measure Result(PK, dBuV/m)	Measure Result(AV, dBuV/m)	Limit PK (dBuV/m)	Limit AV (dBuV/m)	Margin PK dB	Margin AV dB	Result
5730	H	94.07	91.91	114.00	94.00	19.93	2.09	Pass
5730	V	94.54	91.74	114.00	94.00	19.46	2.26	Pass
5800	H	94.14	91.25	114.00	94.00	19.86	2.75	Pass
5800	V	94.30	91.53	114.00	94.00	19.70	2.47	Pass
5840	H	94.38	91.86	114.00	94.00	19.62	2.14	Pass
5840	V	94.58	91.91	114.00	94.00	19.42	2.09	Pass

For 1GHz to 25GHz

Channel 26 / 5730 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
11460.00	53.68	32.44	30.25	7.95	63.82	74.00	-10.18	Peak	Horizontal
11460.00	34.45	32.44	30.25	7.95	44.59	54.00	-9.41	Average	Horizontal
11460.00	50.70	31.60	36.50	7.00	52.80	74.00	-21.20	Peak	Vertical
11460.00	36.31	31.60	36.50	7.00	38.41	54.00	-15.59	Average	Vertical

Channel 29 / 5800 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
11600.00	51.57	32.52	30.31	8.12	61.90	74.00	-12.10	Peak	Horizontal
11600.00	35.01	32.52	30.31	8.12	45.34	54.00	-8.66	Average	Horizontal
11600.00	50.53	31.02	36.50	7.60	52.65	74.00	-21.35	Peak	Vertical
11600.00	36.59	31.02	36.50	7.60	38.71	54.00	-15.29	Average	Vertical

Channel 31 / 5840 MHz


Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
11680.00	50.13	32.68	30.27	7.88	60.42	74.00	-13.58	Peak	Horizontal
11680.00	31.87	32.68	30.27	7.88	42.16	54.00	-11.84	Average	Horizontal
11680.00	50.94	31.58	36.20	7.82	54.14	74.00	-19.86	Peak	Vertical
11680.00	37.91	31.58	36.20	7.82	41.11	54.00	-12.89	Average	Vertical

Notes:

- 1). Measuring frequencies from 9 KHz~10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
- 3). Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4). Measured= Reading- Pre. Fac.+ Ant. Fac.+ Cab. Loss
- 5). Margin = Measured- Limit

4.3. 20dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 1% to 5% of the 20 dB bandwidth

VBW = 3 RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

LIMIT

Non-Specified

TEST RESULTS

Temperature	24.2°C	Humidity	54.9%
Test Engineer	Evan Ouyang	Configurations	5.8G

Mode	Channel	20dB Bandwidth (MHz)	Result
5.8G	26	3.161	Pass
	29	3.182	Pass
	31	3.164	Pass




4.4. Band Edge Compliance of RF Emission

TEST REQUIREMENT

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

TEST CONFIGURATION



TEST PROCEDURE

The EUT is placed on a turntable, which is 0.8m above the ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

Peak: RBW=120MHz, RBW=300MHz / Sweep=AUTO

Repeat the procedures until the peak versus polarization are measured.

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

TEST RESULTS**4.4.1 For Radiated Bandedge Measurement**

Temperature	23.8°C	Humidity	53.7%
Test Engineer	Evan Ouyang	Configurations	5.8G

Channel 26 :5730 MHz									
Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
5650.0	45.99	35.29	29.18	8.8	60.90	68.20	-7.30	Peak	Horizontal
5700.0	35.15	35.29	29.18	8.8	50.06	68.20	-18.14	Peak	Horizontal
5720.0	47.07	35.29	29.18	8.8	61.98	68.20	-6.22	Peak	Horizontal
5725.0	35.71	35.29	29.18	8.8	50.62	68.20	-17.58	Peak	Horizontal

Channel 26 :5730 MHz									
Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
5650.0	46.10	33.21	35.82	9.52	53.01	68.20	-15.19	Peak	Vertical
5700.0	35.59	33.21	35.82	9.52	42.50	68.20	-25.70	Peak	Vertical
5720.0	47.29	32.82	35.82	9.52	53.81	68.20	-14.39	Peak	Vertical
5725.0	35.53	32.82	35.82	9.52	42.05	68.20	-26.15	Peak	Vertical

Channel 31 :5840 MHz									
Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
5850.0	45.90	35.29	29.18	8.8	60.81	68.20	-7.39	Peak	Horizontal
5855.0	34.96	35.29	29.18	8.8	49.87	68.20	-18.33	Peak	Horizontal
5875.0	46.97	35.29	29.18	8.8	61.88	68.20	-6.32	Peak	Horizontal
5925.0	35.80	35.29	29.18	8.8	50.71	68.20	-17.49	Peak	Horizontal

Channel 31 :5840 MHz									
Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
5850.0	46.11	33.21	35.82	9.52	53.02	68.20	-15.18	Peak	Vertical
5855.0	35.60	33.21	35.82	9.52	42.51	68.20	-25.69	Peak	Vertical
5875.0	47.38	32.82	35.82	9.52	53.90	68.20	-14.30	Peak	Vertical
5925.0	35.76	32.82	35.82	9.52	42.28	68.20	-25.92	Peak	Vertical

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

4.5. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The antenna used for this product is Dipole Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 3.0 dBi.

Reference to the **GTS20251128005-1-10**.

5. TEST SETUP PHOTOS OF THE EUT

Reference to the Test Report: GTS20251128005-1-10.

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the Test Report: GTS20251128005-1-10.

.....End of Report.....