

FCC PART 15.247



TEST REPORT

For

Suzhou DHMS Information Technology Co.,Ltd.

Building 11, Creative Industry Park, SuZhou, China

FCC ID: 2BUTM-DS31X

Report Type: Original Report	Product Name: Wireless Sensor
Report Number: <u> RSHA251208003-00B </u>	
Report Date: <u> 2026-03-31 </u>	
Reviewed By: <u> Bard Liu </u>	
Approved By: <u> Kyle Xu </u>	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	11
TEST EQUIPMENT LIST	12
FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
TEST SYSTEM SETUP.....	16
EMI TEST RECEIVER SETUP	17
TEST PROCEDURE	17
TEST RESULTS SUMMARY	18
TEST DATA: SEE APPENDIX	18
FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH.....	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST DATA: SEE APPENDIX	19
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST DATA: SEE APPENDIX	20
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE & CONDUCTED SPURIOUS EMISSION	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA: SEE APPENDIX	22
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA: SEE APPENDIX	23
APPENDIX - TEST DATA.....	24

SPURIOUS EMISSIONS	24
6 dB EMISSION BANDWIDTH	73
MAXIMUM CONDUCTED OUTPUT POWER.....	75
100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	78
CONDUCTED SPURIOUS EMISSION.....	80
POWER SPECTRAL DENSITY	82
EUT PHOTOGRAPHS.....	84
TEST SETUP PHOTOGRAPHS.....	85

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RSHA251208003-00B	R1V1	2026-03-31	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Suzhou DHMS Information Technology Co.,Ltd.
Tested Model:	DS310
Series Model:	DS311
Model Difference:	Antenna
Product Name:	Wireless Sensor
Power Supply:	DC 3V from the battery
RF Function:	BLE
Operating Band/Frequency:	BLE(1 Mbps/2 Mbps): 2402-2480 MHz
Maximum Peak Output Power:	BLE(1 Mbps): 14.87 dBm BLE(2 Mbps): 14.82 dBm
Channel Number:	BLE(1 Mbps/2 Mbps): 40
Channel Separation:	2 MHz
Modulation Type:	GFSK
★Maximum Antenna Gain:	DS310: -3.0 dBi DS311: -3.0 dBi
Sample/EUT Status:	Good condition

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RSHA251208003-1 (DS310), RSHA251208003-2 (DS311) (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2025-12-08.)

Objective

This report is prepared for *Suzhou DHMS Information Technology Co.,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions' rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	/
13	2428	27	2456	/	/

For BLE (1 Mbps/2 Mbps) mode, EUT was tested with channel 0, 19, 37, 38 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The system was configured for testing in an engineering mode, which was provided by manufacturer.

RF test software: SecureCRT

Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	Channel	Frequency (MHz)	★Power Level
BLE(1Mbps)	1Mbps	Low	2402	20
		Middle	2440	20
		High	2476	20
			2478	20
			2480	20
BLE(2Mbps)	2Mbps	Low	2402	20
		Middle	2440	20
		High	2480	20

Note: The power level was declared by the applicant.

Environmental Conditions & Test Information


Test Date:	2026-03-06
Temperature:	21.8°C
Relative Humidity:	52 %
ATM Pressure:	101.4 kPa
Test Engineer:	Neil Zhou

Mode	Duty Cycle (%)	Ton(ms)	Ton+off(ms)	Duty Cycle Factor(dB)
BLE(1Mbps)	85.42	2.144	2.510	0.68
BLE(2Mbps)	57.61	1.083	1.880	2.40

Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)


Duty Cycle:

BLE(1Mbps) Mode Middle Channel



ProjectNo.:RSHA251208003 Tester:Neil Zhou
Date: 6.MAR.2026 10:05:17

BLE(2Mbps) Mode Middle Channel




ProjectNo.:RSHA251208003 Tester:Neil Zhou
Date: 6.MAR.2026 10:06:12

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	104478	Notebook	TP00072B
/	Debug-1	/	/
/	Debug-2	/	/
/	Power strip	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To Port
DuPont Cable 1	0.1	EUT	Debug-1
DuPont Cable 2	0.15	Debug-1	Debug-2
USB cable	1.0	Debug-2	Notebook
Power Cable 1	1.0	Notebook	Power Strip
Power Cable 2	1.0	Power Strip	AC Source

Block Diagram of Test Setup**For Radiated Emissions (Below 1GHz):**

For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note)
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(d)	Conducted Spurious Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note: The EUT is powered by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2024-11-08	2027-11-07
Narda	6dB Attenuator	773-6	10690812-2-1	2024-11-08	2027-11-07
BACL	Active Loop Antenna	1313-1A	4041511	2024-11-22	2027-11-21
Sonoma Instrument	Pre-amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2025-04-09	2026-04-08
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2025-12-02	2026-12-01
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2025-04-09	2026-04-08
SELECTOR	Amplifier	EM18G40G	060726	2025-04-09	2026-04-08
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2025-04-08	2026-04-07
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-11	011	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-12	012	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-13	013	2025-04-09	2026-04-08

RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2025-04-09	2026-04-08
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
XHFDZ	RG316 Coaxial Cable	SMA-316	XHF-1175	Each time	N/A

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Maximuim Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	-3.0	0.5	15.0	31.62	20	0.0031	1.0

Note:

1. For the above tune up power were declared by the manufacturer.

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliant with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

DS311 has an external antenna which use a unique type of connector to attach to the EUT and DS310 has an FPC antenna which was permanently attached to the EUT. Fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


Test System Setup

9 kHz-30 MHz:



30 MHz-1 GHz:



Above 1 GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement	Detector
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	Peak/QP/Average	Peak/QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	Peak/QP/Average	Peak/QP/Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak	Peak
	/	/	120 kHz	QP	QP
Above 1GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	3 MHz	/	Average	Average

Test Procedure

According to ANSI C63.10-2020 clause 6.4, 6.5 and 6.6.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Note: The QuasiPeak (dB μ V/m), MaxPeak (dB μ V/m), Average (dB μ V/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, and Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.8.1

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “– 6 dB down amplitude” . If a marker is below this “– 6 dB down amplitude” value, then it shall be as close as possible to this value.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Data: See Appendix

FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.9.1.1

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = No faster than coupled (auto) time.
- Detector = peak.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Data: See Appendix

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE & CONDUCTED SPURIOUS EMISSION

Band Edges


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 Section 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Conducted Spurious Emission

Applicable Standard


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



Note: Offset (13dB) = Attenuator (10dB) + Cable Loss (3.0dB)

Test Data: See Appendix

FCC §15.247(E) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine Compliant, and it is optional if the maximum conducted (average) output power was used to determine Compliant:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span > 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Data: See Appendix

APPENDIX - TEST DATA

SPURIOUS EMISSIONS

Environmental Conditions & Test Information

Test Item:	SPURIOUS EMISSIONS			
	9kHz – 30MHz	30MHz - 1GHz	1 GHz - 18 GHz	18 GHz - 25 GHz
Test Date:	2025-12-17	2025-12-17	2025-12-20	2026-01-07
Temperature:	17.3 °C	17.3 °C	18.0 °C	20.3°C
Relative Humidity:	43 %	43 %	40%	52 %
ATM Pressure:	102.2 kPa	102.2 kPa	101.7kPa	102.8 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Scarf Yang	Scarf Yang	Destine Hu	Hugh Wu


Test Result: Compliant
EUT operation mode: Transmitting

Model: DS310


9 kHz-30MHz: Transmitting in maximum output power mode BLE (1 Mbps) low channel

Parallel(worst case)

9kHz-150kHz



150kHz-30MHz



9 kHz-150 kHz


Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.02028	47.53	PK	-0.56	121.46	73.93
0.028740	46.19	PK	-0.6	118.43	72.24
0.035226	45.26	PK	-1.45	116.67	71.41
0.040020	45.85	PK	-2.21	115.56	69.71

150 kHz-30 MHz

Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.150000	50.11	PK	-11.34	104.08	53.97
1.284300	43.35	PK	-28.55	65.43	22.08
3.970800	34.26	PK	-31.9	69.54	35.28
4.388700	39.43	PK	-31.97	69.54	30.11

BLE (1 Mbps) (Transmitting in maximum output power BLE (1 Mbps) low channel)
30MHz-1GHz**Low Channel: 2402MHz****Common Information**

Project No: RSHA251208003
EUT Model: DS310
Test Mode: BLE 1M
Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 17.3°C
Humidity: 43%
Barometric Pressure: 102.2kPa
Test Engineer: Scarf Yang
Test Date: 2025/12/17


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.727500	29.03	40.00	10.97	V	-5.2
58.615000	17.69	40.00	22.31	V	-17.1
120.695000	23.05	43.50	20.45	V	-10.9
199.750000	23.69	43.50	19.81	V	-12.1
555.376250	28.84	46.00	17.16	V	-4.6
955.137500	35.52	46.00	10.48	H	1.9

**BLE (1 Mbps)
1GHz-10GHz:****Low Channel: 2402MHz****Common Information**

Project No.:	RSHA251208003
EUT Model:	DS310
Test Mode:	Transmitting in BLE-1M Low Channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	18.0°C
Humidity:	40%
Atmospheric Pressure:	101.7kPa
Test Engineer:	Destine Hu
Test Date:	2025/12/20


Fundamental Test with
Band Reject Filter

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1099.000000	43.11	---	74.00	30.89	H	-14.9
1099.000000	---	27.83	54.00	26.17	H	-14.9
1119.700000	44.25	---	74.00	29.75	H	-14.8
1119.700000	---	27.98	54.00	26.02	H	-14.8
2132.200000	34.93	---	74.00	39.07	H	-9.9
2132.200000	---	25.75	54.00	28.25	H	-9.9
4803.400000	45.95	---	74.00	28.05	H	-3.4
4803.400000	---	40.48	54.00	13.52	H	-3.4
8590.600000	---	42.73	54.00	11.27	V	4.7
8590.600000	52.30	---	74.00	21.70	V	4.7
9933.400000	---	44.85	54.00	9.15	H	6.2
9933.400000	50.03	---	74.00	23.97	H	6.2

Middle Channel: 2440MHz**Common Information**


Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M Middle Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1110.700000	---	29.38	54.00	24.62	H	-14.8
1110.700000	44.05	---	74.00	29.95	H	-14.8
1125.100000	45.40	---	74.00	28.60	H	-14.8
1125.100000	---	29.43	54.00	24.57	H	-14.8
2132.200000	---	22.87	54.00	31.13	H	-9.9
2132.200000	33.09	---	74.00	40.91	H	-9.9
4880.800000	---	38.25	54.00	15.75	V	-3.2
4880.800000	44.26	---	74.00	29.74	V	-3.2
8573.500000	---	42.87	54.00	11.13	V	4.7
8573.500000	52.56	---	74.00	21.44	V	4.7
9828.100000	---	45.24	54.00	8.76	V	5.8
9828.100000	52.69	---	74.00	21.31	V	5.8

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1111.600000	37.96	---	74.00	36.04	V	-14.8
1111.600000	---	30.88	54.00	23.12	V	-14.8
1118.800000	---	27.99	54.00	26.01	H	-14.8
1118.800000	44.27	---	74.00	29.73	H	-14.8
2128.600000	---	24.42	54.00	29.58	H	-9.9
2128.600000	35.43	---	74.00	38.57	H	-9.9
4960.000000	48.23	---	74.00	25.77	H	-3.0
4960.000000	---	43.36	54.00	10.64	H	-3.0
9327.700000	52.73	---	74.00	21.27	V	4.7
9327.700000	---	41.74	54.00	12.26	V	4.7
9828.100000	---	45.15	54.00	8.85	H	5.8
9828.100000	50.54	---	74.00	23.46	H	5.8


10GHz-18GHz:

Low Channel: 2402MHz

Common Information

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10428.800000	---	43.23	54.00	10.77	H	6.7
10428.800000	53.01	---	74.00	20.99	H	6.7
13006.400000	---	44.98	54.00	9.02	V	9.2
13006.400000	55.00	---	74.00	19.00	V	9.2
14387.200000	56.42	---	74.00	17.58	H	11.8
14387.200000	---	46.51	54.00	7.49	H	11.8
14718.400000	55.30	---	74.00	18.70	V	11.2
14718.400000	---	47.40	54.00	6.60	V	11.2
16987.200000	53.65	---	74.00	20.35	V	10.9
16987.200000	---	45.83	54.00	8.17	V	10.9
17944.000000	---	46.23	54.00	7.77	H	11.6
17944.000000	53.57	---	74.00	20.43	H	11.6

Middle Channel: 2440MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M Middle Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10297.600000	---	43.16	54.00	10.84	V	6.6
10297.600000	53.87	---	74.00	20.13	V	6.6
13081.600000	---	44.94	54.00	9.06	H	9.3
13081.600000	55.67	---	74.00	18.33	H	9.3
13590.400000	---	46.03	54.00	7.97	H	10.2
13590.400000	56.92	---	74.00	17.08	H	10.2
14672.000000	---	47.25	54.00	6.75	V	11.4
14672.000000	54.42	---	74.00	19.58	V	11.4
17104.000000	53.51	---	74.00	20.49	V	10.8
17104.000000	---	45.75	54.00	8.25	V	10.8
17900.800000	---	46.26	54.00	7.74	V	11.5
17900.800000	53.43	---	74.00	20.57	V	11.5

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
 EUT Model: DS310
 Test Mode: Transmitting in BLE-1M High Channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 18.0°C
 Humidity: 40%
 Atmospheric Pressure: 101.7kPa
 Test Engineer: Destine Hu
 Test Date: 2025/12/20

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10310.400000	---	43.44	54.00	10.56	V	6.6
10310.400000	53.68	---	74.00	20.32	V	6.6
13300.800000	---	44.00	54.00	10.00	H	9.7
13300.800000	55.55	---	74.00	18.45	H	9.7
14041.600000	55.02	---	74.00	18.98	V	11.2
14041.600000	---	47.34	54.00	6.66	V	11.2
14368.000000	56.44	---	74.00	17.56	V	11.7
14368.000000	---	45.56	54.00	8.44	V	11.7
16694.400000	---	45.86	54.00	8.14	V	9.8
16694.400000	51.61	---	74.00	22.39	V	9.8
17920.000000	52.94	---	74.00	21.06	H	11.6
17920.000000	---	45.78	54.00	8.22	H	11.6

Band Edge:**Low Channel****Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2387.672000	46.13	---	74.00	27.87	H	0.4
2387.672000	---	34.96	54.00	19.04	H	0.4
2388.792000	44.62	---	74.00	29.38	H	0.4
2388.792000	---	36.17	54.00	17.83	H	0.4

High Channel: 2476 MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M High Channel-2476MHz
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2026/3/6

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.536000	52.55	---	74.00	21.45	V	0.5
2483.536000	---	40.55	54.00	13.45	V	0.5
2483.584000	49.48	---	74.00	24.52	V	0.5
2483.584000	---	41.32	54.00	12.68	V	0.5

High Channel: 2478 MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-1M High Channel-2478MHz
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2026/3/6

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.512000	---	42.31	54.00	11.69	V	0.5
2483.512000	50.23	---	74.00	23.77	V	0.5
2483.704000	---	41.35	54.00	12.65	V	0.5
2483.704000	53.41	---	74.00	20.59	V	0.5

High Channel: 2480 MHz**Common Information**



Project No.:	RSHA251208003
EUT Model:	DS310
Test Mode:	Transmitting in BLE-1M High Channel-2480MHz
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	18.0°C
Humidity:	40%
Atmospheric Pressure:	101.7kPa
Test Engineer:	Destine Hu
Test Date:	2025/12/20

Full Spectrum

**Critical Freqs**



Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.608000	---	41.68	54.00	12.32	H	0.5
2483.608000	51.03	---	74.00	22.97	H	0.5
2483.800000	---	40.26	54.00	13.74	H	0.5
2483.800000	52.52	---	74.00	21.48	H	0.5

18GHz-25GHz: Transmitting in maximum output power mode and BLE 1M low channel



Frequency (GHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
20.21	---	39.43	54	14.57	V	12.47
19.63	49.51	---	74	24.49	V	11.2
20.20	---	39.16	54	14.84	H	12.46
20.25	50.38	---	74	23.62	H	12.51

Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

9 kHz-30MHz: Transmitting in maximum output power mode BLE (2 Mbps) low channel**Parallel(worst case)****9kHz-150kHz****150kHz-30MHz****9 kHz-150 kHz**


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.02028	47.53	PK	-0.56	121.46	73.93
0.027048	46.48	PK	-0.6	118.96	72.48
0.033816	45.82	PK	-1.22	117.02	71.2
0.037764	43.59	PK	-1.85	116.06	72.47

150 kHz-30 MHz

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.150000	48.27	PK	-11.34	104.08	55.81
1.284300	42.28	PK	-28.55	65.43	23.15
3.791700	35.38	PK	-31.81	69.54	34.16
4.388700	37.69	PK	-31.97	69.54	31.85

BLE (2 Mbps) (Transmitting in maximum output power BLE (2 Mbps) low channel)
30MHz-1GHz**Low Channel: 2402MHz****Common Information**

Project No: RSHA251208003
EUT Model: DS310
Test Mode: BLE 2M
Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW:100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 17.3°C
Humidity: 43%
Barometric Pressure: 102.2kPa
Test Engineer: Scarf Yang
Test Date: 2025/12/17

**Critical_Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.121250	28.58	40.00	11.42	H	-4.8
69.770000	18.10	40.00	21.90	V	-16.6
119.725000	22.70	43.50	20.80	V	-10.9
199.507500	21.74	43.50	21.76	V	-12.1
506.876250	28.86	46.00	17.14	H	-5.3
943.255000	35.59	46.00	10.41	H	1.7

BLE (2 Mbps)
1GHz-10GHz:

Low Channel: 2402MHz

Common Information

Project No.:	RSHA251208003
EUT Model:	DS310
Test Mode:	Transmitting in BLE-2M Low Channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	18.0°C
Humidity:	40%
Atmospheric Pressure:	101.7kPa
Test Engineer:	Destine Hu
Test Date:	2025/12/20




Critical_Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1111.600000	---	26.66	54.00	27.34	H	-14.8
1111.600000	43.51	---	74.00	30.49	H	-14.8
1143.100000	---	29.91	54.00	24.09	V	-14.7
1143.100000	44.08	---	74.00	29.92	V	-14.7
1596.700000	---	24.51	54.00	29.49	V	-12.8
1596.700000	34.64	---	74.00	39.36	V	-12.8
2125.900000	---	27.56	54.00	26.44	H	-9.9
2125.900000	38.58	---	74.00	35.42	H	-9.9
4804.300000	---	36.68	54.00	17.32	H	-3.4
4804.300000	43.87	---	74.00	30.13	H	-3.4
9937.900000	51.40	---	74.00	22.60	V	6.2
9937.900000	---	45.24	54.00	8.76	V	6.2

Middle Channel: 2440MHz**Common Information**


Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M Middle Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1083.700000	---	27.26	54.00	26.74	H	-14.9
1083.700000	43.51	---	74.00	30.49	H	-14.9
1123.300000	---	26.28	54.00	27.72	H	-14.8
1123.300000	43.51	---	74.00	30.49	H	-14.8
2127.700000	---	27.89	54.00	26.11	H	-9.9
2127.700000	41.16	---	74.00	32.84	H	-9.9
4879.900000	---	38.89	54.00	15.11	V	-3.2
4879.900000	43.61	---	74.00	30.39	V	-3.2
7344.100000	---	41.91	54.00	12.09	V	2.5
7344.100000	50.27	---	74.00	23.73	V	2.5
9808.300000	51.15	---	74.00	22.85	H	5.8
9808.300000	---	45.54	54.00	8.46	H	5.8

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1100.800000	---	30.92	54.00	23.08	H	-14.9
1100.800000	45.74	---	74.00	28.26	H	-14.9
2132.200000	---	23.99	54.00	30.01	H	-9.9
2132.200000	35.42	---	74.00	38.58	H	-9.9
4959.100000	---	40.74	54.00	13.26	H	-3.0
4959.100000	45.05	---	74.00	28.95	H	-3.0
7691.500000	---	41.22	54.00	12.78	V	3.1
7691.500000	51.59	---	74.00	22.41	V	3.1
9828.100000	---	44.99	54.00	9.01	V	5.8
9828.100000	51.19	---	74.00	22.81	V	5.8
9856.000000	---	42.28	54.00	11.72	H	5.9
9856.000000	52.82	---	74.00	21.18	H	5.9


10GHz-18GHz:

Low Channel: 2402MHz

Common Information

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10323.200000	---	42.78	54.00	11.22	V	6.6
10323.200000	54.21	---	74.00	19.79	V	6.6
12969.600000	55.60	---	74.00	18.40	V	9.2
12969.600000	---	45.20	54.00	8.80	V	9.2
14102.400000	---	47.50	54.00	6.50	H	11.3
14102.400000	54.69	---	74.00	19.31	H	11.3
14475.200000	---	46.15	54.00	7.85	H	11.9
14475.200000	56.80	---	74.00	17.20	H	11.9
16588.800000	---	45.40	54.00	8.60	V	9.4
16588.800000	52.89	---	74.00	21.11	V	9.4
17934.400000	52.74	---	74.00	21.26	V	11.6
17934.400000	---	45.92	54.00	8.08	V	11.6

Middle Channel: 2440MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M Middle Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
11731.200000	---	44.00	54.00	10.00	V	8.6
11731.200000	54.40	---	74.00	19.60	V	8.6
14318.400000	---	45.63	54.00	8.37	V	11.7
14318.400000	56.98	---	74.00	17.02	V	11.7
14561.600000	---	47.27	54.00	6.73	H	11.8
14561.600000	53.91	---	74.00	20.09	H	11.8
14681.600000	---	46.47	54.00	7.53	V	11.4
14681.600000	57.08	---	74.00	16.92	V	11.4
16990.400000	52.83	---	74.00	21.17	H	10.9
16990.400000	---	45.98	54.00	8.02	H	10.9
17924.800000	---	46.14	54.00	7.86	H	11.6
17924.800000	53.40	---	74.00	20.60	H	11.6

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
11171.200000	---	43.31	54.00	10.69	H	7.1
11171.200000	53.80	---	74.00	20.20	H	7.1
13619.200000	---	45.40	54.00	8.60	V	10.2
13619.200000	56.07	---	74.00	17.93	V	10.2
14193.600000	53.88	---	74.00	20.12	V	11.4
14193.600000	---	47.09	54.00	6.91	V	11.4
14620.800000	56.64	---	74.00	17.36	H	11.6
14620.800000	---	45.43	54.00	8.57	H	11.6
17060.800000	---	45.90	54.00	8.10	H	10.9
17060.800000	53.29	---	74.00	20.71	H	10.9
17809.600000	---	46.18	54.00	7.82	H	11.3
17809.600000	55.75	---	74.00	18.25	H	11.3

Band Edge:**Low Channel****Common Information**

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum

**Critical_Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2359.784000	44.98	---	74.00	29.02	V	0.3
2359.784000	---	33.13	54.00	20.87	V	0.3
2388.848000	41.75	---	74.00	32.25	H	0.4
2388.848000	---	34.72	54.00	19.28	H	0.4

High Channel

Common Information

Project No.: RSHA251208003
EUT Model: DS310
Test Mode: Transmitting in BLE-2M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20


Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.512000	60.30	---	74.00	13.70	H	0.5
2483.512000	---	49.37	54.00	4.63	H	0.5
2484.112000	---	46.25	54.00	7.75	V	0.5
2484.112000	56.93	---	74.00	17.07	V	0.5


18GHz-25GHz: Transmitting in maximum output power mode and BLE 2M low channel



Frequency (GHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
20.22	---	39.67	54	14.33	V	12.48
20.25	49.94	---	74	24.06	V	12.51
20.21	---	39.6	54	14.4	H	12.47
20.22	50.01	---	74	23.99	H	12.48


Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

Model: DS311

9 kHz-30MHz: Transmitting in maximum output power mode BLE (1 Mbps) low channel**Parallel(worst case)****9kHz-150kHz**

Project No.RSHA251208003
 Date: 17.DEC.2025 13:23:40

Tester:Scarf Yang

150kHz-30MHz

Project No.RSHA251208003
 Date: 17.DEC.2025 13:29:03

Tester:Scarf Yang

9 kHz-150 kHz


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.018024	46.01	PK	-0.55	122.49	76.48
0.012102	47.57	PK	-0.52	125.95	78.38
0.026202	45.81	PK	-0.59	119.24	73.43
0.033816	46	PK	-1.22	117.02	71.02

150 kHz-30 MHz

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.150000	46.52	PK	-11.34	104.08	57.56
1.344000	43.03	PK	-28.75	65.04	22.01
3.851400	34.52	PK	-31.84	69.54	35.02
4.388700	39.59	PK	-31.97	69.54	29.95

BLE (1 Mbps) (Transmitting in maximum output power BLE (1 Mbps) low channel)
30MHz-1GHz**Low Channel: 2402MHz****Common Information**


Project No: RSHA251208003
EUT Model: DS311
Test Mode: BLE 1M
Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 17.3°C
Humidity: 43%
Barometric Pressure: 102.2kPa
Test Engineer: Scarf Yang
Test Date: 2025/12/17

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
31.576250	28.91	40.00	11.09	H	-5.8
68.315000	17.59	40.00	22.41	H	-16.7
143.126250	24.04	43.50	19.46	H	-11.4
195.506250	22.12	43.50	21.38	V	-12.3
553.315000	29.25	46.00	16.75	V	-4.6
933.433750	35.17	46.00	10.83	H	1.6

BLE (1 Mbps)
1GHz-10GHz:
Low Channel: 2402MHz
Common Information


Project No.:	RSHA251208003
EUT Model:	DS311
Test Mode:	Transmitting in BLE-1M Low Channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	18.0°C
Humidity:	40%
Atmospheric Pressure:	101.7kPa
Test Engineer:	Destine Hu
Test Date:	2025/12/20

Fundamental Test with
Band Reject Filter

Critical_Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1111.600000	---	29.22	54.00	24.78	H	-14.8
1111.600000	45.43	---	74.00	28.57	H	-14.8
1433.800000	---	20.79	54.00	33.21	V	-13.7
1433.800000	31.17	---	74.00	42.83	V	-13.7
2128.600000	---	24.12	54.00	29.88	H	-9.9
2128.600000	33.59	---	74.00	40.41	H	-9.9
4804.300000	44.25	---	74.00	29.75	H	-3.4
4804.300000	---	37.88	54.00	16.12	H	-3.4
8745.400000	---	43.34	54.00	10.66	V	4.7
8745.400000	52.77	---	74.00	21.23	V	4.7
9947.800000	---	44.60	54.00	9.40	V	6.2
9947.800000	50.01	---	74.00	23.99	V	6.2

Middle Channel: 2440MHz**Common Information**

Project No.: RSHA251208003
 EUT Model: DS311
 Test Mode: Transmitting in BLE-1M Middle Channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 18.0℃
 Humidity: 40%
 Atmospheric Pressure: 101.7kPa
 Test Engineer: Destine Hu
 Test Date: 2025/12/20


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1095.400000	---	27.06	54.00	26.94	H	-14.9
1095.400000	44.18	---	74.00	29.82	H	-14.9
1135.900000	---	24.31	54.00	29.69	H	-14.7
1135.900000	44.03	---	74.00	29.97	H	-14.7
2127.700000	---	27.03	54.00	26.97	H	-9.9
2127.700000	38.09	---	74.00	35.91	H	-9.9
4879.900000	---	37.93	54.00	16.07	H	-3.2
4879.900000	43.19	---	74.00	30.81	H	-3.2
8431.300000	---	42.64	54.00	11.36	V	4.5
8431.300000	51.98	---	74.00	22.02	V	4.5
9872.200000	49.51	---	74.00	24.49	V	6.0
9872.200000	---	44.51	54.00	9.49	V	6.0

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum

Fundamental Test with
Band Reject Filter**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1108.900000	---	25.51	54.00	28.49	H	-14.8
1108.900000	42.81	---	74.00	31.19	H	-14.8
1123.300000	---	28.69	54.00	25.31	H	-14.8
1123.300000	44.33	---	74.00	29.67	H	-14.8
2129.500000	---	24.27	54.00	29.73	H	-9.9
2129.500000	35.72	---	74.00	38.28	H	-9.9
4960.000000	45.79	---	74.00	28.21	H	-3.0
4960.000000	---	40.11	54.00	13.89	H	-3.0
8591.500000	---	43.47	54.00	10.53	H	4.7
8591.500000	53.05	---	74.00	20.95	H	4.7
9870.400000	---	44.60	54.00	9.40	V	6.0
9870.400000	49.81	---	74.00	24.19	V	6.0


10GHz-18GHz:

Low Channel: 2402MHz

Common Information

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10238.400000	---	42.11	54.00	11.89	V	6.5
10238.400000	53.02	---	74.00	20.98	V	6.5
13635.200000	56.22	---	74.00	17.78	H	10.3
13635.200000	---	44.90	54.00	9.10	H	10.3
14484.800000	---	45.59	54.00	8.41	H	11.9
14484.800000	56.60	---	74.00	17.40	H	11.9
14662.400000	---	47.31	54.00	6.69	H	11.4
14662.400000	54.33	---	74.00	19.67	H	11.4
17078.400000	---	46.40	54.00	7.60	V	10.9
17078.400000	53.14	---	74.00	20.86	V	10.9
17844.800000	53.27	---	74.00	20.73	V	11.4
17844.800000	---	45.84	54.00	8.16	V	11.4

Middle Channel: 2440MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M Middle Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10446.400000	---	42.46	54.00	11.54	H	6.7
10446.400000	53.01	---	74.00	20.99	H	6.7
13232.000000	---	44.07	54.00	9.93	H	9.6
13232.000000	55.57	---	74.00	18.43	H	9.6
14616.000000	---	47.46	54.00	6.54	V	11.6
14616.000000	54.95	---	74.00	19.05	V	11.6
14945.600000	---	45.80	54.00	8.20	H	10.5
14945.600000	57.03	---	74.00	16.97	H	10.5
16993.600000	53.50	---	74.00	20.50	V	10.9
16993.600000	---	45.82	54.00	8.18	V	10.9
17851.200000	---	46.44	54.00	7.56	H	11.4
17851.200000	53.51	---	74.00	20.49	H	11.4

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10288.000000	---	43.13	54.00	10.87	H	6.6
10288.000000	54.01	---	74.00	19.99	H	6.6
12590.400000	---	43.69	54.00	10.31	V	8.8
12590.400000	55.61	---	74.00	18.39	V	8.8
14041.600000	57.34	---	74.00	16.66	H	11.2
14041.600000	---	45.43	54.00	8.57	H	11.2
14875.200000	54.89	---	74.00	19.11	V	10.7
14875.200000	---	47.69	54.00	6.31	V	10.7
17112.000000	53.12	---	74.00	20.88	H	10.8
17112.000000	---	46.46	54.00	7.54	H	10.8
17923.200000	---	46.19	54.00	7.81	H	11.6
17923.200000	54.20	---	74.00	19.80	H	11.6

Band Edge:**Low Channel****Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2388.288000	47.99	---	74.00	26.01	V	0.4
2388.288000	---	36.87	54.00	17.13	V	0.4
2389.688000	47.06	---	74.00	26.94	V	0.4
2389.688000	---	38.28	54.00	15.72	V	0.4

High Channel: 2476MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M High Channel-2476MHz
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2026/3/6

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.872000	---	41.99	54.00	12.01	V	0.5
2483.872000	49.52	---	74.00	24.48	V	0.5
2484.664000	---	39.90	54.00	14.10	V	0.5
2484.664000	52.15	---	74.00	21.85	V	0.5

High Channel: 2478MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M High Channel-2478MHz
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2026/3/6

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.512000	---	43.16	54.00	10.84	V	0.5
2483.512000	52.03	---	74.00	21.97	V	0.5
2483.632000	---	42.37	54.00	11.63	V	0.5
2483.632000	53.31	---	74.00	20.69	V	0.5



High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-1M High Channel-2480MHz
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum



**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.704000	---	46.19	54.00	7.81	V	0.5
2483.704000	54.37	---	74.00	19.63	V	0.5
2483.728000	---	45.18	54.00	8.82	V	0.5
2483.728000	58.32	---	74.00	15.68	V	0.5

18GHz-25GHz: Transmitting in maximum output power mode and BLE 1M low channel**Horizontal****Vertical**

Frequency (GHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
20.23	---	39.43	54	14.57	V	12.49
20.17	50.41	---	74	23.59	V	12.43
20.22	---	39.69	54	14.31	H	12.48
20.19	50.46	---	74	23.54	H	12.45

Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

9 kHz-30MHz: Transmitting in maximum output power mode BLE (2 Mbps) low channel**Parallel(worst case)****9kHz-150kHz****150kHz-30MHz****9 kHz-150 kHz**


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.009846	47.53	PK	-0.48	127.74	80.21
0.023382	46.14	PK	-0.58	120.23	74.09
0.025356	45.99	PK	-0.59	119.52	73.53
0.030432	46.29	PK	-0.68	117.94	71.65

150 kHz-30 MHz

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.150000	50.11	PK	-11.34	104.08	53.97
1.344000	42.49	PK	-28.75	65.04	22.55
3.791700	34.04	PK	-31.81	69.54	35.50
4.388700	39.43	PK	-31.97	69.54	30.11

BLE (2 Mbps) (Transmitting in maximum output power BLE (2 Mbps) low channel)
30MHz-1GHz**Low Channel: 2402MHz****Common Information**


Project No: RSHA251208003
EUT Model: DS311
Test Mode: BLE 2M
Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 17.3°C
Humidity: 43%
Barometric Pressure: 102.2kPa
Test Engineer: Scarf Yang
Test Date: 2025/12/17

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.727500	28.18	40.00	11.82	H	-5.2
69.648750	17.35	40.00	22.65	H	-16.6
128.697500	23.36	43.50	20.14	H	-11.0
198.658750	21.90	43.50	21.60	V	-12.2
554.770000	29.34	46.00	16.66	V	-4.6
946.286250	35.16	46.00	10.84	H	1.8

**BLE (2 Mbps)
1GHz-10GHz:****Low Channel: 2402MHz****Common Information**


Project No.:	RSHA251208003
EUT Model:	DS311
Test Mode:	Transmitting in BLE-2M Low Channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	18.0°C
Humidity:	40%
Atmospheric Pressure:	101.7kPa
Test Engineer:	Destine Hu
Test Date:	2025/12/20

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1129.600000	---	30.23	54.00	23.77	H	-14.7
1129.600000	44.49	---	74.00	29.51	H	-14.7
2127.700000	---	24.31	54.00	29.69	H	-9.9
2127.700000	34.23	---	74.00	39.77	H	-9.9
4014.100000	---	32.10	54.00	21.90	V	-4.9
4014.100000	42.44	---	74.00	31.56	V	-4.9
4804.300000	---	38.60	54.00	15.40	V	-3.4
4804.300000	44.98	---	74.00	29.02	V	-3.4
8496.100000	---	43.57	54.00	10.43	H	4.7
8496.100000	52.58	---	74.00	21.42	H	4.7
9928.000000	49.70	---	74.00	24.30	H	6.1
9928.000000	---	44.99	54.00	9.01	H	6.1

Middle Channel: 2440MHz**Common Information**


Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-2M Middle Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1098.100000	43.13	---	74.00	30.87	H	-14.9
1098.100000	---	27.09	54.00	26.91	H	-14.9
1127.800000	44.32	---	74.00	29.68	H	-14.8
1127.800000	---	25.17	54.00	28.83	H	-14.8
2130.400000	35.82	---	74.00	38.18	V	-9.9
2130.400000	---	26.20	54.00	27.80	V	-9.9
4879.900000	43.81	---	74.00	30.19	H	-3.2
4879.900000	---	38.65	54.00	15.35	H	-3.2
8585.200000	---	42.11	54.00	11.89	H	4.7
8585.200000	52.10	---	74.00	21.90	H	4.7
9823.600000	---	45.19	54.00	8.81	V	5.8
9823.600000	51.41	---	74.00	22.59	V	5.8

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-2M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1099.000000	---	26.23	54.00	27.77	H	-14.9
1099.000000	42.77	---	74.00	31.23	H	-14.9
1131.400000	---	25.77	54.00	28.23	H	-14.7
1131.400000	42.26	---	74.00	31.74	H	-14.7
2126.800000	34.88	---	74.00	39.12	V	-9.9
2126.800000	---	23.04	54.00	30.96	V	-9.9
4960.000000	---	39.14	54.00	14.86	V	-3.0
4960.000000	44.28	---	74.00	29.72	V	-3.0
8408.800000	52.77	---	74.00	21.23	H	4.4
8408.800000	---	42.78	54.00	11.22	H	4.4
9820.000000	49.95	---	74.00	24.05	V	5.8
9820.000000	---	45.39	54.00	8.61	V	5.8


10GHz-18GHz:

Low Channel: 2402MHz

Common Information

Project No.: RSHA251208003
 EUT Model: DS311
 Test Mode: Transmitting in BLE-2M Low Channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 18.0°C
 Humidity: 40%
 Atmospheric Pressure: 101.7kPa
 Test Engineer: Destine Hu
 Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μV/m)	Average (dB μV/m)	Limit (dB μV/m)	Margin (dB)	Pol	Corr. (dB/m)
10299.200000	53.60	---	74.00	20.40	H	6.6
10299.200000	---	43.33	54.00	10.67	H	6.6
12097.600000	---	45.91	54.00	8.09	H	9.0
12097.600000	55.57	---	74.00	18.43	H	9.0
14561.600000	---	47.31	54.00	6.69	V	11.8
14561.600000	54.23	---	74.00	19.77	V	11.8
14875.200000	---	45.92	54.00	8.08	V	10.7
14875.200000	56.57	---	74.00	17.43	V	10.7
17289.600000	---	45.74	54.00	8.26	H	10.6
17289.600000	53.49	---	74.00	20.51	H	10.6
17828.800000	53.35	---	74.00	20.65	H	11.3
17828.800000	---	46.28	54.00	7.72	H	11.3

Middle Channel: 2440MHz**Common Information**

Project No.: RSHA251208003
 EUT Model: DS311
 Test Mode: Transmitting in BLE-2M Middle Channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 18.0℃
 Humidity: 40%
 Atmospheric Pressure: 101.7kPa
 Test Engineer: Destine Hu
 Test Date: 2025/12/20

Full Spectrum


**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10622.400000	---	42.36	54.00	11.64	V	6.7
10622.400000	53.93	---	74.00	20.07	V	6.7
12169.600000	---	44.85	54.00	9.15	H	9.0
12169.600000	55.51	---	74.00	18.49	H	9.0
14476.800000	56.87	---	74.00	17.13	H	11.9
14476.800000	---	46.61	54.00	7.39	H	11.9
14542.400000	54.52	---	74.00	19.48	V	11.8
14542.400000	---	47.19	54.00	6.81	V	11.8
17016.000000	53.34	---	74.00	20.66	H	10.9
17016.000000	---	45.69	54.00	8.31	H	10.9
17848.000000	54.40	---	74.00	19.60	H	11.4
17848.000000	---	45.93	54.00	8.07	H	11.4

High Channel: 2480MHz**Common Information**

Project No.: RSHA251208003
 EUT Model: DS311
 Test Mode: Transmitting in BLE-2M High Channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 18.0°C
 Humidity: 40%
 Atmospheric Pressure: 101.7kPa
 Test Engineer: Destine Hu
 Test Date: 2025/12/20


Full Spectrum

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
10731.200000	---	44.88	54.00	9.12	V	6.7
10731.200000	53.74	---	74.00	20.26	V	6.7
11971.200000	---	44.64	54.00	9.36	H	9.0
11971.200000	55.83	---	74.00	18.17	H	9.0
14088.000000	56.38	---	74.00	17.62	V	11.2
14088.000000	---	46.65	54.00	7.35	V	11.2
14636.800000	53.29	---	74.00	20.71	V	11.5
14636.800000	---	47.54	54.00	6.46	V	11.5
17065.600000	52.56	---	74.00	21.44	V	10.9
17065.600000	---	45.74	54.00	8.26	V	10.9
17780.800000	---	46.12	54.00	7.88	V	11.2
17780.800000	52.98	---	74.00	21.02	V	11.2

Band Edge:**Low Channel****Common Information**

Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-2M Low Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0°C
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2388.736000	48.06	---	74.00	25.94	V	0.4
2388.736000	---	38.20	54.00	15.80	V	0.4
2389.352000	48.03	---	74.00	25.97	V	0.4
2389.352000	---	38.98	54.00	15.02	V	0.4

High Channel

Common Information



Project No.: RSHA251208003
EUT Model: DS311
Test Mode: Transmitting in BLE-2M High Channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 18.0℃
Humidity: 40%
Atmospheric Pressure: 101.7kPa
Test Engineer: Destine Hu
Test Date: 2025/12/20

Full Spectrum



Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.536000	---	51.63	54.00	2.37	V	0.5
2483.536000	59.97	---	74.00	14.03	V	0.5
2483.632000	---	51.37	54.00	2.63	V	0.5
2483.632000	60.78	---	74.00	13.22	V	0.5

18GHz-25GHz: Transmitting in maximum output power mode and BLE 2M low channel**Horizontal****Vertical**

Frequency (GHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
20.23	---	39.13	54	14.87	V	12.49
20.17	50.16	---	74	23.84	V	12.43
20.19	---	39.15	54	14.85	H	12.45
19.55	50.35	---	74	23.65	H	10.97

Note: The test distance is 3m. The limit is 74dB μ V/m(Peak) and 54dB μ V/m(Average).

6 dB EMISSION BANDWIDTH**Environmental Conditions & Test Information**

Test Date:	2026-03-06
Temperature:	21.8°C
Relative Humidity:	52 %
ATM Pressure:	101.4 kPa
Test Engineer:	Neil Zhou

Test Result: Compliant.

EUT operation mode: Transmitting

Mode	Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)	Result
BLE (1 Mbps)	Low	2402	0.668	≥ 0.5	Pass
	Middle	2440	0.668	≥ 0.5	Pass
	High	2480	0.672	≥ 0.5	Pass
BLE (2 Mbps)	Low	2402	1.116	≥ 0.5	Pass
	Middle	2440	1.116	≥ 0.5	Pass
	High	2480	1.110	≥ 0.5	Pass