Test Report

Report No.	:	MTi251015002-0105E1
Date of issue	:	2026-05-13
Applicant	:	SHENZHEN HECHUANGQIHANG TECHNOLOGY LIMITED
Product	:	AI Voice Recorders
Model(s)	:	H16, H6, H7, H8, H9, H10, H11, NanoRec01, NanoRec02, NanoRec03, NanoRec05, NanoRec06, H12, H13, H14, H15, H17, H18, H19, H20, NanoRec07, NanoRec08 NewRec
FCC ID	:	2BUUI-HCQH

Shenzhen Microtest Co., Ltd.

TEST REPORT

Report No.: MTi251015002-0105E1

Table of contents

1 General Description 4

1.1 Description of the EUT 4
1.2 Description of test modes 4
1.3 Environmental Conditions 6
1.4 Description of support units 6
1.5 Measurement uncertainty 6

2 Summary of Test Result 7
3 Test Facilities and accreditations 8

3.1 Test laboratory 8

4 List of test equipment 9
5 Evaluation Results (Evaluation) 11

5.1 Antenna requirement 11

6 Radio Spectrum Matter Test Results (RF) 12

6.1 Conducted Emission at AC power line 12
6.2 6dB Bandwidth 15
6.3 Maximum Conducted Output Power 17
6.4 Power Spectral Density 18
6.5 RF conducted spurious emissions and band edge measurement 19
6.6 Band edge emissions (Radiated) 20
6.7 Radiated emissions (below 1GHz) 24
6.8 Radiated emissions (above 1GHz) 28

Photographs of the test setup 33
Photographs of the EUT 34
Appendix A: DTS Bandwidth 36
Appendix B: Maximum conducted output power 40
Appendix C: Maximum power spectral density 44
Appendix D: Band edge measurements 48
Appendix E: Conducted Spurious Emission 50
Appendix F: Duty Cycle 62

TEST REPORT

Report No.: MTi251015002-0105E1

Test Result Certification	
Applicant	SHENZHEN HECHUANGQIHANG TECHNOLOGY LIMITED
Applicant Address	Floor 2, Building 58, Zhongwu Industrial Zone, Zhongwu Community, Hangcheng Street, Baoan District, Shenzhen City
Manufacturer	SHENZHEN HECHUANGQIHANG TECHNOLOGY LIMITED
Manufacturer Address	Floor 2, Building 58, Zhongwu Industrial Zone, Zhongwu Community, Hangcheng Street, Baoan District, Shenzhen City
Factory	SHENZHEN HECHUANGQIHANG TECHNOLOGY LIMITED
Factory Address	Floor 2, Building 58, Zhongwu Industrial Zone, Zhongwu Community, Hangcheng Street, Baoan District, Shenzhen City
Product description	
Product name	AI Voice Recorders
Trademark	N/A
Model name	H16
Series Model(s)	H6, H7, H8, H9, H10, H11, NanoRec01, NanoRec02, NanoRec03, NanoRec05, NanoRec06, H12, H13, H14, H15, H17, H18, H19, H20, NanoRec07, NanoRec08 NewRec
Standards	47 CFR Part 15.247
Test Method	KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10-2020+Cor 1-2023
Testing Information	
Date of test	2026-05-06 to 2026-05-13
Test result	Pass

Prepared by:	James Qin	James Qin
Reviewed by:	David Lee	David. Lee
Approved by:	Lewis Lian	Lewis Lian

1 General Description

1.1 Description of the EUT

Product name:	AI Voice Recorders
Model name:	H16
Series Model(s):	H6, H7, H8, H9, H10, H11, NanoRec01, NanoRec02, NanoRec03, NanoRec05, NanoRec06, H12, H13, H14, H15, H17, H18, H19, H20, NanoRec07, NanoRec08 NewRec
Model difference:	All the models share the same circuit and module. Some differ from H16 in model name, appearance and size (H9, H10, H11, H12, H13, H14, H15), while others differ only in model name (H6, H7, H8, NanoRec01, NanoRec02, NanoRec03, NanoRec05, NanoRec06, H17, H18, H19, H20, NanoRec07, NanoRec08 NewRec).
Electrical rating:	Input: DC 5V/ 1A(Max) Battery: DC 3.7V, 500mAh, 1.85Wh
Accessories:	N/A
Hardware version:	X6-V2.0
Software version:	X6A-V069
Test sample(s) number:	MTi251015002-01-R003
RF specification	
Bluetooth version:	V5.3
Operating frequency range:	2402-2480MHz
Channel number:	40
Modulation type:	GFSK
Antenna(s) type:	PCB
Antenna(s) gain:	1.75dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX-GFSK-1Mbps
Mode2	TX-GFSK-2Mbps

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466

3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Test Channel List
Operation Band: 2400-2483.5 MHz

Bandwidth (MHz)	Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
2	2402	2440	2480

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software: ATS 3085
For power setting, refer to below table.

Mode	2402MHz	2440MHz	2480MHz
1M	0	0	0
2M	0	0	0

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
Laptop	e485	/	Lenovo
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
RF output power, conducted	±1 dB
Power Spectral Density, conducted	±1 dB
Unwanted Emissions, conducted	±1 dB
Radiated spurious emissions (above 1GHz)	±5.3dB
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
3	6dB Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
4	Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
5	Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
6	RF conducted spurious emissions and band edge measurement	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
7	Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
8	Radiated emissions (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
9	Radiated emissions (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2026-03-10	2027-03-09
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2026-03-11	2027-03-10
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2026-03-10	2027-03-09
4	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC-3A1	/	/	/
Emissions in non-restricted frequency bands 20dB Bandwidth Maximum Conducted Output Power Channel Separation Number of Hopping Frequencies Dwell Time						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2026-03-09	2027-03-08
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2026-03-09	2027-03-08
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2026-03-10	2027-03-09
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2026-03-10	2027-03-09
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2026-03-09	2027-03-08
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2026-03-11	2027-03-10
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2026-03-11	2027-03-10
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2026-03-10	2027-03-09
9	DC Power Supply	Agilent	E3632A	MY40027695	2026-03-09	2027-03-08
10	RF Test System	Tonscend	JS1120-3 Test System Ver. V3.5.39	/	/	/
Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2026-03-10	2027-03-09
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2025-05-27	2027-05-26
3	Amplifier	Agilent	8449B	3008A01120	2026-03-10	2027-03-09
4	MXA signal analyzer	Agilent	N9020A	MY54440859	2026-03-10	2027-03-09
5	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2026-03-10	2027-03-09

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
6	Horn antenna	Schwarzbeck	BBHA 9170	00987	2025-05-27	2027-05-26
7	Pre-amplifier	Space-Dtronics	EWLAN1840G	210405001	2026-03-11	2027-03-10
8	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC-3A1	/	/	/
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2026-03-10	2027-03-09
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2025-05-23	2027-05-22
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2026-03-08	2028-03-07
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2026-03-10	2027-03-09
5	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC-3A1	/	/	/

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached. The EUT complies with the requirement of FCC PART 15.203.

6 Radio Spectrum Matter Test Results (RF)

6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b)and (c)of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).
Test Limit:	

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.2
Procedure:	Refer to ANSI C63.10-2020+Cor 1-2023 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices

6.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	57.5 %	Atmospheric Pressure:	98.9 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				

6.1.2 Test Setup Diagram:



6.1.3 Test Data:

Mode1 / Line: Line / CH: L



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1620	38.01	10.23	48.24	65.36	-17.12	QP	
2		0.1779	36.57	10.23	46.80	64.58	-17.78	QP	
3		0.2419	14.58	10.21	24.79	52.03	-27.24	AVG	
4		0.4060	12.15	10.22	22.37	47.73	-25.36	AVG	
5	*	0.4858	33.16	10.22	43.38	56.24	-12.86	QP	
6		0.4858	14.01	10.22	24.23	46.24	-22.01	AVG	
7		0.7700	32.02	10.23	42.25	56.00	-13.75	QP	
8		0.7700	18.20	10.23	28.43	46.00	-17.57	AVG	
9		3.5139	27.09	10.33	37.42	56.00	-18.58	QP	
10		3.5139	16.05	10.33	26.38	46.00	-19.62	AVG	
11		7.6139	27.45	10.50	37.95	60.00	-22.05	QP	
12		7.6139	16.84	10.50	27.34	50.00	-22.66	AVG	

Mode1 / Line: Neutral / CH: L



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1620	18.89	10.17	29.06	55.36	-26.30	AVG	
2		0.1632	39.43	10.17	49.60	65.30	-15.70	QP	
3		0.2379	37.09	10.16	47.25	62.17	-14.92	QP	
4		0.2419	18.12	10.16	28.28	52.03	-23.75	AVG	
5	*	0.7660	31.15	10.17	41.32	56.00	-14.68	QP	
6		0.7820	20.11	10.17	30.28	46.00	-15.72	AVG	
7		1.9737	29.99	10.21	40.20	56.00	-15.80	QP	
8		2.0979	19.67	10.21	29.88	46.00	-16.12	AVG	
9		3.4020	19.03	10.25	29.28	46.00	-16.72	AVG	
10		3.5500	29.94	10.27	40.21	56.00	-15.79	QP	
11		6.2137	30.51	10.35	40.86	60.00	-19.14	QP	
12		6.3258	19.55	10.35	29.90	50.00	-20.10	AVG	

6.2 6dB Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW ≥ [3 × RBW]. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “−6 dB down amplitude”. If a marker is below this “−6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	Mode1, Mode2				

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.

6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.9.1.1 Maximum peak conducted output power

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	Mode1, Mode2				

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.

6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.10.2 Maximum power spectral density level in the fundamental emission

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	Mode1, Mode2				

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.

6.5 RF conducted spurious emissions and band edge measurement

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.3 °C	Humidity:	45.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	Mode1, Mode2				

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.

6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).
Test Limit:	

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.10.5.2

6.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24.2 °C	Humidity:	48.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				

Note:
The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
All models with different dimensions and appearances (H16, H9, H10, H11, H12, H13, H14, H15) have been tested. Only the data of the worst-case model H16 is presented in the report.

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

Mode1 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	46.13	-4.50	41.63	74.00	-32.37	peak
2		2310.000	37.43	-4.50	32.93	54.00	-21.07	AVG
3		2390.000	46.06	-4.31	41.75	74.00	-32.25	peak
4	*	2390.000	37.57	-4.31	33.26	54.00	-20.74	AVG

Mode1 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	46.15	-4.50	41.65	74.00	-32.35	peak
2		2310.000	37.35	-4.50	32.85	54.00	-21.15	AVG
3		2390.000	46.13	-4.31	41.82	74.00	-32.18	peak
4	*	2390.000	37.41	-4.31	33.10	54.00	-20.90	AVG

Mode1 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	46.33	-4.23	42.10	74.00	-31.90	peak
2	*	2483.500	37.85	-4.23	33.62	54.00	-20.38	AVG
3		2500.000	46.28	-4.15	42.13	74.00	-31.87	peak
4		2500.000	37.41	-4.15	33.26	54.00	-20.74	AVG

Mode1 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	46.23	-4.23	42.00	74.00	-32.00	peak
2		2483.500	37.58	-4.23	33.35	54.00	-20.65	AVG
3		2500.000	46.26	-4.15	42.11	74.00	-31.89	peak
4	*	2500.000	37.60	-4.15	33.45	54.00	-20.55	AVG

6.7 Radiated emissions (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).
Test Limit:	

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4

6.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24.2 °C	Humidity:	48.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				

Note:
The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.
All models with different dimensions and appearances (H16, H9, H10, H11, H12, H13, H14, H15) have been tested. Only the data of the worst-case model H16 is presented in the report.

6.7.2 Test Setup Diagram:



6.7.3 Test Data:

Mode1 / Polarization: Horizontal / CH: H



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		42.7494	28.75	-7.26	21.49	40.00	-18.51	QP	
2		49.8813	29.52	-7.59	21.93	40.00	-18.07	QP	
3	*	166.0680	35.61	-6.66	28.95	43.50	-14.55	QP	
4		228.4903	37.75	-9.27	28.48	46.00	-17.52	QP	
5		332.5187	34.96	-5.21	29.75	46.00	-16.25	QP	
6		459.1143	28.88	-2.63	26.25	46.00	-19.75	QP	

Mode1 / Polarization: Vertical / CH: H



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		40.4170	31.20	-7.10	24.10	40.00	-15.90	peak	
2	*	49.1865	33.06	-7.59	25.47	40.00	-14.53	peak	
3		123.2654	29.30	-8.73	20.57	43.50	-22.93	QP	
4		206.3975	34.03	-9.81	24.22	43.50	-19.28	QP	
5		311.0866	27.07	-5.46	21.61	46.00	-24.39	QP	
6		472.1760	29.17	-2.39	26.78	46.00	-19.22	QP	

6.8 Radiated emissions (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).
Test Limit:	

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4

6.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24.2 °C	Humidity:	48.1 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				

Note:
Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
All modes of operation of the EUT were investigated, and only the worst-case results are reported.
All models with different dimensions and appearances (H16, H9, H10, H11, H12, H13, H14, H15) have been tested. Only the data of the worst-case model H16 is presented in the report.

6.8.2 Test Setup Diagram:



6.8.3 Test Data:

Mode1 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4804.000	44.62	2.70	47.32	74.00	-26.68	peak
2		4804.000	40.85	2.70	43.55	54.00	-10.45	AVG
3		7206.000	42.27	7.46	49.73	74.00	-24.27	peak
4		7206.000	37.81	7.46	45.27	54.00	-8.73	AVG
5		9608.000	44.63	8.79	53.42	74.00	-20.58	peak
6	*	9608.000	39.34	8.79	48.13	54.00	-5.87	AVG

Mode1 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4804.000	43.39	2.70	46.09	74.00	-27.91	peak
2		4804.000	39.88	2.70	42.58	54.00	-11.42	AVG
3		7206.000	43.53	7.46	50.99	74.00	-23.01	peak
4		7206.000	38.88	7.46	46.34	54.00	-7.66	AVG
5		9608.000	44.26	8.79	53.05	74.00	-20.95	peak
6	*	9608.000	39.82	8.79	48.61	54.00	-5.39	AVG

Mode1 / Polarization: Horizontal / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4880.000	43.44	2.74	46.18	74.00	-27.82	peak
2		4880.000	38.48	2.74	41.22	54.00	-12.78	AVG
3		7320.000	42.56	7.79	50.35	74.00	-23.65	peak
4		7320.000	35.40	7.79	43.19	54.00	-10.81	AVG
5		9760.000	48.15	9.90	58.05	74.00	-15.95	peak
6	*	9760.000	33.34	9.90	43.24	54.00	-10.76	AVG

Mode1 / Polarization: Vertical / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4880.000	43.38	2.74	46.12	74.00	-27.88	peak
2		4880.000	39.09	2.74	41.83	54.00	-12.17	AVG
3		7320.000	42.90	7.79	50.69	74.00	-23.31	peak
4		7320.000	38.91	7.79	46.70	54.00	-7.30	AVG
5		9760.000	44.30	9.90	54.20	74.00	-19.80	peak
6	*	9760.000	39.73	9.90	49.63	54.00	-4.37	AVG

Mode1 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4960.000	44.49	3.10	47.59	74.00	-26.41	peak
2		4960.000	40.86	3.10	43.96	54.00	-10.04	AVG
3		7440.000	43.36	7.65	51.01	74.00	-22.99	peak
4		7440.000	39.93	7.65	47.58	54.00	-6.42	AVG
5		9920.000	44.40	9.23	53.63	74.00	-20.37	peak
6	*	9920.000	39.10	9.23	48.33	54.00	-5.67	AVG

Mode1 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4960.000	43.66	3.10	46.76	74.00	-27.24	peak
2		4960.000	39.23	3.10	42.33	54.00	-11.67	AVG
3		7440.000	43.37	7.65	51.02	74.00	-22.98	peak
4	*	7440.000	39.87	7.65	47.52	54.00	-6.48	AVG
5		9920.000	44.01	9.23	53.24	74.00	-20.76	peak
6		9920.000	38.16	9.23	47.39	54.00	-6.61	AVG

Photographs of the test setup

Refer to Appendix - Test Setup Photos

Photographs of the EUT

Refer to Appendix - EUT Photos

Appendix

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.676	0.5	PASS
		2440	0.720	0.5	PASS
		2480	0.720	0.5	PASS
BLE_2M	Ant1	2402	1.120	0.5	PASS
		2440	1.136	0.5	PASS
		2480	1.136	0.5	PASS

Test Graphs

BLE_1M_Ant1_2402

BLE_1M_Ant1_2440

BLE_1M_Ant1_2480

BLE_2M_Ant1_2402

BLE_2M_Ant1_2440

BLE_2M_Ant1_2480

Appendix B: Maximum conducted output power

Test Result-Peak

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0.11	≤30	PASS
		2440	0.10	≤30	PASS
		2480	-0.24	≤30	PASS
BLE_2M	Ant1	2402	-0.24	≤30	PASS
		2440	-0.16	≤30	PASS
		2480	-0.44	≤30	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2402

BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



Appendix C: Maximum power spectral density

Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-15.92	≤8.00	PASS
		2440	-15.89	≤8.00	PASS
		2480	-16.10	≤8.00	PASS
BLE_2M	Ant1	2402	-18.78	≤8.00	PASS
		2440	-18.73	≤8.00	PASS
		2480	-18.81	≤8.00	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



Appendix D: Band edge measurements

Test Graphs

BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480



BLE_2M_Ant1_Low_2402



BLE_2M_Ant1_High_2480



Appendix E: Conducted Spurious Emission

Test Graphs

BLE_1M_Ant1_2402_0~Reference

BLE_1M_Ant1_2402_30~1000



BLE_1M_Ant1_2402_1000~12750



BLE_1M_Ant1_2402_12750~26500

BLE_1M_Ant1_2440_0~Reference

BLE_1M_Ant1_2440_30~1000



BLE_1M_Ant1_2440_1000~12750



BLE_1M_Ant1_2440_12750~26500

BLE_1M_Ant1_2480_0~Reference

BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~12750



BLE_1M_Ant1_2480_12750~26500

BLE_2M_Ant1_2402_0~Reference

BLE_2M_Ant1_2402_30~1000



BLE_2M_Ant1_2402_1000~12750



BLE_2M_Ant1_2402_12750~26500

BLE_2M_Ant1_2440_0~Reference

BLE_2M_Ant1_2440_30~1000



BLE_2M_Ant1_2440_1000~12750



BLE_2M_Ant1_2440_12750~26500

BLE_2M_Ant1_2480_0~Reference

BLE_2M_Ant1_2480_30~1000



BLE_2M_Ant1_2480_1000~12750



BLE_2M_Ant1_2480_12750~26500

Appendix F: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	2.14	2.50	85.60	0.68
		2440	2.14	2.50	85.60	0.68
		2480	2.14	2.50	85.60	0.68
BLE_2M	Ant1	2402	1.08	1.25	86.40	0.63
		2440	1.08	1.25	86.40	0.63
		2480	1.08	1.24	87.10	0.60

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2402

BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



Statement

1. This report is invalid without the seal and signature of the laboratory.

2. The test results of this report are only responsible for the samples submitted.Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

****** END OF REPORT ******