

Exemption letter

No. 1-8898-24-01-11_TR1-R01

June 25, 2026

Applicant	Busch & Müller KG
Product Model	Remote Control Blucon 456BT
FCC ID	2BUW5-456BT
Tested Technology	Bluetooth LE
Test Standard(s)	Interim procedure KDB 447498 D04

Verdict Exemption fulfilled

The test results relate only to devices specified in this document

This test report is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.



CN = Timo Franke email = timo.franke@cetecomadvanced.com
C = DE O = cetecom advanced GmbH OU = RadioLabs
2026.06.25 11:25:53 +02'00'

authorized by

Timo Franke
Lab Manager
Radio Labs



CN = Martin Nunier email = Martin.Nunier@cetecomadvanced.com
C = DE O = cetecom advanced GmbH OU = Radio Labs
2026.06.25 10:45:16 +02'00'

created by

Martin Nunier
Coordinator Area
Radio Labs

Table of content

1	Related cetecom advanced documents	3
2	Document history	3
3	Test laboratory	3
4	Client and test sample information.....	3
5	Measurement details	4

1 Related cetekom advanced documents

Document	Contents	Reference Description	Total Pages
--	--	--	--

2 Document history

Release No.	Applied changes	Date of release
R01	Initial release	June 25, 2026

3 Test laboratory

cetekom advanced GmbH
 Untertuerkheimer Str. 6-10
 66117 Saarbruecken
 Germany

☐ **Saarbruecken lab**
 Untertuerkheimer Str. 6-10
 66117 Saarbruecken
 Germany

☒ **Essen lab**
 Im Teelbruch 116
 45219 Essen
 Germany

4 Client and test sample information

Customer	Product	Model	Type	HW Status	SW status
Busch & Müller KG	Remote Control	Blucon 456BT	--	V06	1.0.0

5 Measurement details

According to Interim procedure KDB 447498 D04 SAR testing can be exempted if the following exclusion threshold is met:

SAR-based Exemption

According 1.1307(b)(3)(i)(B) Option B – Available maximum time-averaged power or effective radiated power (ERP) at frequencies above 300 kHz and below 6 GHz, but with distances from 0.5 cm to 40 cm may be exempted as follows:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

11/29/2021

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Power Calculation

Power calculation based on external document
 "Operational Description_Blucon456BT" provided by customer.

Exemption acc. Formula of § 1.1307(b)(3)(i)(B)–SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

Band	Technology	Frequency	Distance = d	d ≥ 0.5 cm and d ≤ 40 cm fulfilled	Maximum Rated Conducted Output Power	Maximum Tolerance	Minimum Path Loss to Antenna	Maximum Antenna Gain	Duty Cycle	EIRP	ERP	ERP	Threshold ERP	SAR Exemption fulfilled
		(MHz)	(cm)		(dBm)	(dB)	(dB)	(dBi)	(%)	(dBm)	(dBm)	(mW)	(mW)	
2.4 GHz	Bluetooth LE	2402.0	1.0	yes	4.0	2.0	0.0	-3.4	100	2.6	0.5	1	10	yes
		2441.0	1.0	yes	4.0	2.0	0.0	-3.7	100	2.3	0.2	1	10	yes
		2480.0	1.0	yes	4.0	2.0	0.0	-5.6	100	0.4	-1.8	1	10	yes

The user manual must list the given usage position.

– END OF DOCUMENT –