

Prüfbericht-Nr.: <i>Test report no.:</i>	CN26WYCM 002	Auftrags-Nr.: <i>Order no.:</i>	27227126	Seite 1 von 23 Page 1 of 23
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2026-04-02	
Auftraggeber: <i>Client:</i>	fünfeinhalb Funksysteme GmbH Chemnitzer Straße 78A, 01187 Dresden, Germany			
Prüfgegenstand: <i>Test item:</i>	Access Point			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	BlitzFunk AW32R (Trademark: BlitzFunk)			
Auftrags-Inhalt: <i>Order content:</i>	Test Report			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15 Subpart E §15.407 RSS-247 Issue 4, July 2025 RSS-Gen Issue 5, February 2021			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2026-04-28	(Please refer to photo documents)		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A004250609-003 A004250609-004			
Prüfzeitraum: <i>Testing period:</i>	2026-04-28 - 2026-07-22			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	 Hardy Suo		genehmigt von: <i>authorized by:</i>	 Lin Lin
Datum: <i>Date:</i>	2026-07-29		Ausstellungsdatum: <i>Issue date:</i>	2026-07-29
Stellung / Position:	Sachverständige(r) / Expert		Stellung / Position:	Sachverständige(r) / Expert
Sonstiges / Other:	FCC ID: 2BUWU-AW32R IC: 35239-AW32R, HVIN: BlitzFunk AW32R This report is for 5 GHz Wi-Fi.			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN26WYCM 002
Test report no.:

Seite 2 von 23
Page 2 of 23

Anmerkungen Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN26WYCM 002
Test Report No.

Seite 3 von 23
Page 3 of 23

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM OUTPUT POWER

RESULT: Pass

5.1.3 POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 FREQUENCY STABILITY

RESULT: Pass

5.1.5 26dB BANDWIDTH AND 99% BANDWIDTH

RESULT: Pass

5.1.6 6dB BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.8 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

TABLE OF CONTENTS

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2.	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	UNCERTAINTY OF MEASUREMENT.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3.	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	11
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.5	SUBMITTED DOCUMENTS	11
4.	TEST SET-UP AND OPERATION MODES	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	12
4.2	TEST OPERATION	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE ERM COMPLIANCE	12
4.5	TEST SETUP DIAGRAM	12
5.	TEST RESULTS	14
5.1	RADIO TEST REQUIREMENT & TEST SUITES	14
5.1.1	Antenna Requirement	14
5.1.2	Maximum Output Power.....	15
5.1.3	Power Spectral Density.....	17
5.1.4	Frequency Stability.....	18
5.1.5	26dB Bandwidth and 99% Bandwidth.....	19
5.1.6	6dB Bandwidth	20
5.1.7	Radiated Spurious Emission.....	21
5.1.8	Conducted Emission on AC Mains	22
6.	LIST OF TABLES	23

Prüfbericht - Nr.: CN26WYCM 002
Test Report No.

Seite 5 von 23
Page 5 of 23

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 5 GHz Wi-Fi

Appendix B: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

A2LA Certificate Number: 5162.01

FCC Test Site Number: CN1260

ISED Test Lab CAB identifier: CN0078

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (SRD-Tonscend)						
Equip. No.	Description	Manufacturer	Model	Serial No.	Cal. Date (DD.MM.YYYY)	Cal. until (DD.MM.YYYY)
9039436	EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	23.09.2025	22.09.2026
9039437	MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	23.09.2025	22.09.2026
9039438	EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	23.09.2025	22.09.2026
9039439	DC Power Supply	Keysight	E3642A	MY61276100	23.09.2025	22.09.2026
9039440	Wireless Connectivity Tester	R&S	CMW270	102505	23.09.2025	22.09.2026
9039441	Power Control Unit	Tonscend	JS0806-4ADC	N/A	23.09.2025	22.09.2026
9039442	Automation Control Unit	Tonscend	JS0806-2	21C8060396	23.09.2025	22.09.2026
9039443	Test Software	Tonscend	JS1120-3	N/A	N/A	N/A
9039444	Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A	N/A
G1826483	Humid & Temp Programmable Tester	BOST	NTH090-60	19040801	02.02.2026	01.02.2027
Unwanted Emission Testing (TS9975)						
Equip. No.	Description	Manufacturer	Model	Serial No.	Cal. Date (DD.MM.YYYY)	Cal. until (DD.MM.YYYY)
G1826021	EMI Test Receiver	R&S	ESR 7	102021	22.09.2025	21.09.2026
G1826023	Signal Analyzer	R&S	FSV 40	101439	22.09.2025	21.09.2026
G1826024	System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
G1826025	Filterbank	R&S	Wlan	100759	22.09.2025	21.09.2026
G1826026	OSP	R&S	OSP 120	102040	N/A	N/A
G1826028	Pre-amplifier	R&S	SCU08F1	08320031	22.09.2025	21.09.2026
G1826029	Amplifier	R&S	SCU-18F	180070	22.09.2025	21.09.2026
G1826030	Amplifier	R&S	SCU40A	100475	22.09.2025	21.09.2026
G1826031	Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	28.09.2024	27.09.2026
G1826032	Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	28.09.2024	27.09.2026

G1826033	Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	28.09.2024	27.09.2026
G1826034	Active Loop Antenna	Schwarzbeck	FMZB 1513	302	28.09.2024	27.09.2026
G1826036	Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
G1826037	Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A
G1826433	3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	14.09.2024	13.09.2027

Conducted Emission on AC Mains					
Equip. No.	Description	Manufacturer	Model	Serial No.	Cal. Until
GC-SZ 004632	EMI Test Receiver	R&S	ESR3	102680	2027-02-03
GC-SZ 001010	Artificial Mains Network	R&S	ENV216	102333	2026-07-18
GC-SZ 004633	Artificial Mains Network	R&S	ENV216	101445	2027-02-03
G1825091	EMC32 Test Software	R&S	EMC32(Ver.10.60.20)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Uncertainty of Measurement

The value of the measurement uncertainty of each parameter is listed as below:

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	±4.17 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.70 dB / ± 3.30 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The Product is an access point which supports 2.4 GHz Wi-Fi, 5 GHz Wi-Fi and 6 GHz Wi-Fi and is intended for industrial environments. It assembles three identical wireless module #1 (Model AMLGA7921), wireless module #2 (Model AMLGA7921) and wireless module #3 (Model AMLGA7921).

The wireless module #1 (Model AMLGA7921) has one TX & RX ANT 1 and one RX ANT 3, they are for user data function.

The wireless module #2 (Model AMLGA7921) has one TX & RX ANT 2, it is only for device setup operating on 5745MHz.

The wireless module #3 (Model AMLGA7921) has one TX & RX ANT 4 and one RX ANT 5, they are for user data function.

Note: The wireless module #1, wireless module #2 and wireless module #3 are incapable of transmitting on the same frequency channel simultaneously.

ANT information for Wireless module #1 AMLGA7921		ANT information for Wireless module #2 AMLGA7921	ANT information for Wireless module #3 AMLGA7921	
ANT 1	ANT 3	ANT 2	ANT 4	ANT 5
TX & RX	RX	TX & RX	TX & RX	RX

The wireless module #1, The wireless module #2 and The wireless module #3 have identical hardware, including same antennas and same power setting level in firmware.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification

General Information of EUT	Value
Kind of Equipment:	Access Point
Type Designation:	BlitzFunk AW32R
Trademark:	BlitzFunk
FCC ID:	2BUWU-AW32R
IC:	35239-AW32R
HVIN:	BlitzFunk AW32R
Operating Voltage:	DC 12-48 V, max. 0.5 A
Testing Voltage:	AC 120 V, 60 Hz (power supply external adapter)
Adapter:	M/N: E80120 Input: AC 100-240 V, 50/60 Hz Output: DC 24V, 1.0 A, 24 W
Operating Temperature Range:	-20 °C ~ +60 °C
Radiofrequency operating mode:	1) 2.4 GHz Wi-Fi: operating within 2400-2483.5 MHz, supports IEEE 802.11 g 2) 5 GHz Wi-Fi: operating within 5150 - 5250 MHz, 5725 - 5850 MHz, 5850-5895 MHz supports IEEE 802.11 a 3) 6 GHz Wi-Fi: operating within 5925 - 7125 MHz, supports IEEE 802.11 ax20
Technical Specification of 2.4 GHz Wi-Fi	

Prüfbericht - Nr.: CN26WYCM 002
Test Report No.
Seite 9 von 23
Page 9 of 23

Operating Frequency:	2412 - 2462 MHz of IEEE 802.11 g
Type of Modulation:	OFDM
Channel Number:	3 channels
Channel Bandwidth:	20 MHz
Data Rate:	IEEE 802.11g: 54/48/36/24/18/12/9/6 Mbps
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx (1TX: ANT1 or ANT4; 1RX: ANT 3 or ANT 5)
Antenna Gain:	2.1 dBi for ANT1, ANT4 (Provided by the Client)
Technical Specification of 5 GHz Wi-Fi	
Operating Frequency:	• U-NII-1 band: 5180 - 5240 MHz of IEEE 802.11 a • U-NII-3 band: 5745 - 5825 MHz of IEEE 802.11 a • U-NII-4 band: 5845 - 5864 MHz of IEEE 802.11 a
Type of Modulation:	OFDM
Channel Number:	4 channels for U-NII-1 band: 5180 - 5240 MHz 5 channels for U-NII-3 band: 5745 - 5825 MHz 2 channels for U-NII-4 band: 5845 - 5865 MHz
Channel Bandwidth:	20 MHz
Data Rate:	802.11a: 54/48/36/24/18/12/9/6 Mbps
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx (1TX: ANT1 or ANT2 or ANT4; 1RX: ANT 3 or ANT 5)
Antenna Gain:	3.1 dBi for ANT1, ANT2, ANT4 (Provided by the Client)
DFS device type:	Master
Technical Specification of 6 GHz Wi-Fi	
Operating Frequency:	• U-NII-5 band: 5955 - 6415 MHz of IEEE 802.11 ax20 • U-NII-6 band: 6435 - 6515 MHz of IEEE 802.11 ax20 • U-NII-7 band: 6535 - 6855 MHz of IEEE 802.11 ax20 • U-NII-8 band: 6875 - 7115 MHz of IEEE 802.11 ax20
Type of Modulation:	OFDMA
Channel Number:	24 channels for U-NII-5 band: 5955 - 6415 MHz 5 channels for U-NII-6 band: 6435 - 6515 MHz 18 channels for U-NII-7 band: 6535 - 6855 MHz 12 channels for U-NII-8 band: 6875 - 7115 MHz
Channel Bandwidth:	20 MHz
Data Rate:	IEEE 802.11ax: up to 2402 Mbps
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx (1TX: ANT1 or ANT4; 1RX: ANT 3 or ANT 5)
Antenna Gain:	3.3 dBi for ANT1, ANT4 (Provided by the Client)
Equipment class:	Low-power indoor access points

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

Table 4: RF Channel and Frequency of 2.4GHz Wi-Fi

2.4GHz Wi-Fi 2412 – 2462 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
01	2412
06	2437
11	2462

Table 5: RF Channel and Frequency of 5GHz Wi-Fi

U-NII-1 5150-5250 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
36	5180
40	5200
44	5220
48	5240

U-NII-3 5725-5850 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
149	5745*
153	5765
157	5785
161	5805
165	5825

*Note: 5745MHz is for device setup, it keeps transmitting.

U-NII-4 5850-5895 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
169	5845
173	5865

Table 6: RF Channel and Frequency of 6GHz Wi-Fi

U-NII-5 5925-6425 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
1	5955
5	5975
9	5995
13	6015
17	6035
21	6055
25	6075
29	6095
33	6115
37	6135
41	6155
45	6175
49	6195
53	6215
57	6235
61	6255
65	6275
69	6295
73	6315
77	6335
81	6355
85	6375
89	6395
93	6415

U-NII-6 6425-6525 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
97	6435
101	6455
105	6475
109	6495
113	6515

U-NII-7 6525-6875 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
117	6535
121	6555
125	6575
129	6595
133	6615
137	6635
141	6655
145	6675
149	6695
153	6715
157	6735
161	6755
165	6775
169	6795
173	6815
177	6835
181	6855
185	6875

U-NII-8 6875-7125 MHz, 20MHz Bandwidth	
Channel	Frequency (MHz)
189	6895
193	6915
197	6935
201	6955
205	6975
209	6995
213	7015
217	7035
221	7055
225	7075
229	7095
233	7115

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, 5 GHz Wi-Fi wireless transmitting mode
- B. On, Co-Tx for 2.4 GHz Wi-Fi + 5 GHz Wi-Fi + 6 GHz Wi-Fi

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- User Manual
- ID Label and Location Info
- Operation Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1-2023 + Amendment 1-2024.

According to clause 3.1, all tests were performed on model BlitzFunk AW32R in this report. All tests were performed on different wireless modules with model (Model AMLGA7921) and various ANTs, and the worst case was recorded in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 7: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
Laptop	Lenovo	T480	S/N: PF-16A6N8

4.4 Countermeasures to Achieve ERM Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF). No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Radio Test Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.407(a)(1)(ii), (a)(3)(i) and Part 15.203
RSS-247 clause 7.3.4.3

The EUT has five integral antennas, three antennas are TX&RX, other two antennas for RX only, refer to the table below for details:

ANT information for Wireless module #1 AMLGA7921		ANT information for Wireless module #2 AMLGA7921	ANT information for Wireless module #3 AMLGA7921	
ANT 1	ANT 3	ANT 2	ANT 4	ANT 5
TX & RX	RX	TX & RX	TX & RX	RX
Identical ANT gain for each antenna: 1) 2.1dBi, 2400-2500MHz 2) 3.1dBi, 5150-5895MHz 3) 3.3dBi, 5925-7125MHz				

The antenna connectors are designed with permanent attachment and no consideration of replacement. Therefore, the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Output Power**RESULT:****Pass****Test Specification**

Test standard

: FCC Part 15.407(a)(1)(ii), (a)(3) (i)(ii)
: RSS-247 clause 7.3.1.2, 7.3.4.3, 7.3.5.3

Basic standard

: ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1-2023 + Amendment 1-2024

FCC:**• U-NII-1 5150-5250MHz:**

Max conducted output power <1W (30dBm)

• U-NII-3 5725-5850MHz:

Max conducted output power <1W (30dBm)

• U-NII-4 5850-5895MHz:

Max e.i.r.p. <4W (36dBm)

Limits

: **IC:****• U-NII-1 5150-5250MHz:**

Max e.i.r.p. <200mW (23dBm)

*200 mW (23dBm) or 10 dBm + 10 logB, where B is the 99% emission bandwidth in MHz, where is lesser.

• U-NII-3 5725-5850MHz:

Max conducted output power <W (30dBm)

• U-NII-4 5850-5895MHz:

Max e.i.r.p. <4W (36dBm)

Kind of test site

: Shielded Room

Test Setup

Date of testing

: 2026-04-28 - 2026-07-25

Input voltage

: AC 120V, 60Hz

Operation mode

: A

Test channel

: Low / Middle / High

Ambient temperature

: 24.5 °C

Relative humidity

: 50 %

Atmospheric pressure

: 101 kPa

Table 8: Test Result of Maximum Conducted Output Power, 5GHz Wi-Fi U-NII-1

TestMode	Antenna	Channel [MHz]	Result [dBm]	Result [dBm]	Limit [dBm]	Verdict
IEEE 802.11 a	ANT4	5180	17.20	0.0525	≤30	PASS
	ANT4	5200	16.95	0.0495	≤30	PASS
	ANT4	5240	17.22	0.0527	≤30	PASS

Note: The Duty Cycle Factor was compensated in the test results.

Table 9: Test Result of Maximum Conducted Output Power, ISED 5GHz Wi-Fi U-NII-1

TestMode	Antenna	Channel [MHz]	Result [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP [W]	EIRP Limit [dBm]	Verdict
IEEE 802.11 a	ANT4	5180	17.20	≤19.11	3.1	20.30	0.1072	≤22.21	PASS
	ANT4	5200	16.95	≤19.11	3.1	20.05	0.1012	≤22.21	PASS
	ANT4	5240	17.22	≤19.11	3.1	20.32	0.1076	≤22.21	PASS

Note: The Duty Cycle Factor was compensated in the test results. The minimum 99% bandwidth is 16.641MHz.

Table 10: Test Result of Maximum Conducted Output Power, 5GHz Wi-Fi U-NII-3

TestMode	Antenna	Channel [MHz]	Result [dBm]	Result [dBm]	Limit [dBm]	Verdict
IEEE 802.11 a	ANT2	5745	19.48	0.0887	≤30	PASS
	ANT4	5785	19.51	0.0893	≤30	PASS
	ANT4	5825	19.60	0.0912	≤30	PASS

Note: The Duty Cycle Factor was compensated in the test results.

Table 11: Test Result of Maximum Conducted Output Power, 5GHz Wi-Fi U-NII-4

TestMode	Antenna	Channel [MHz]	Result [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP [W]	EIRP Limit [dBm]	Verdict
IEEE 802.11 a	ANT4	5845	19.49	≤32.90	3.1	22.59	0.1816	≤36	PASS
	ANT4	5865	19.20	≤32.90	3.1	22.30	0.1698	≤36	PASS

Note: The Duty Cycle Factor was compensated in the test results.

5.1.3 Power Spectral Density**RESULT:****Pass****Test Specification**

Test standard

: FCC Part 15.407(a)(1)(ii), (a)(3)(i)(ii)
: RSS-247 clause 7.3.1.2, 7.3.4.3, 7.3.5.3

Basic standard

: ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1-
2023 + Amendment 1-2024**FCC:****• U-NII-1 5150-5250MHz:**

Max conducted PSD <17dBm/MHz

• U-NII-3 5725-5850MHz:

Max conducted PSD <30dBm/500kHz

• U-NII-4 5850-5895MHz:

Max e.i.r.p. PSD <20dBm/1MHz

Limits

:

IC:**• U-NII-1 5150-5250MHz:**

Max e.i.r.p. PSD <10dBm/MHz

• U-NII-3 5725-5850MHz:

Max conducted PSD <30dBm/500kHz

• U-NII-4 5850-5895MHz:

Max e.i.r.p. PSD <20dBm/1MHz

Kind of test site

:

Shielded Room

Test Setup

Date of testing

: 2026-04-28 - 2026-07-25

Input voltage

: AC 120V, 60Hz

Operation mode

: A

Test channel

: Low / Middle / High

Ambient temperature

: 24.5 °C

Relative humidity

: 50 %

Atmospheric pressure

: 101 kPa

Refer to attached Appendix A for details of test data.

Prüfbericht - Nr.: CN26WYCM 002
Test Report No.**Seite 18 von 23**
Page 18 of 23**5.1.4 Frequency Stability****RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.407(g)
	:	RSS-Gen Clause 6.11
Basic standard	:	ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1-2023 + Amendment 1-2024
Limits	:	Within assigned bands
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2026-04-28 - 2026-07-25
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.5 °C
Relative humidity	:	50 %
Atmospheric pressure	:	101 kPa

Refer to attached Appendix A for details of test data.

Prüfbericht - Nr.: CN26WYCM 002
Test Report No.**Seite 19 von 23**
Page 19 of 23**5.1.5 26dB Bandwidth and 99% Bandwidth****RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.407(a)(13) RSS-Gen Clause 6.7
Basic standard	:	ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1- 2023 + Amendment 1-2024
Limits	:	N/A
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2026-04-28 - 2026-07-25
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.5 °C
Relative humidity	:	50 %
Atmospheric pressure	:	101 kPa

Refer to attached Appendix A for details of test data.

5.1.6 6dB Bandwidth**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.407(e) RSS-247 clause 7.3.4.2
Basic standard	:	ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1- 2023 + Amendment 1-2024
Limits	:	At least 500kHz (5725-5850MHz, 5850-5895MHz)
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2026-04-28 - 2026-07-25
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	24.5 °C
Relative humidity	:	50 %
Atmospheric pressure	:	101 kPa

Refer to attached Appendix A for details of test data.

5.1.7 Radiated Spurious Emission

RESULT:

Pass

Test Specification

Test standard	:	FCC Part 15.407(b) & FCC Part 15.205 & FCC Part 15.209 RSS-247 clause 7.3.1.3, 7.3.4.4, 7.3.5.4 & RSS-GEN clause 8.9 and 8.10
Basic standard	:	ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1- 2023 + Amendment 1-2024
Limits	:	• For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. • For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. • For transmitters operating in the 5.850-5.895 GHz band: For an indoor access point or subordinate device, all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of 15 dBm/MHz and shall decrease linearly to an e.i.r.p. of -7 dBm/MHz at or above 5.925 GHz. • Restricted Bands meet the requirement of 15.209 limit and RSS-GEN
Kind of test site	:	3m Semi-Anechoic Chamber (below 1GHz) 3m Anechoic Chamber (above 1GHz)

Test Setup

Date of testing	:	2026-04-28 - 2026-07-25
Input voltage	:	AC 120V, 60Hz
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test data
Relative humidity	:	Refer to test data
Atmospheric pressure	:	101 kPa

Refer to attached Appendix A for details of test data.

Prüfbericht - Nr.: CN26WYCM 002
Test Report No.**Seite 22 von 23**
Page 22 of 23**5.1.8 Conducted Emission on AC Mains****RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.207 RSS-GEN clause 8.8
Basic standard	:	ANSI C63.10-2020, ANSI C63.10-2020 + Corrigendum 1- 2023 + Amendment 1-2024
Frequency range	:	0.15 - 30MHz
Limits	:	FCC Part 15.207 RSS-Gen Table 4
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	2026-04-28 - 2026-06-15
Input voltage	:	AC 120V, 60Hz
Operation mode	:	B
Earthing	:	Not connected
Ambient temperature	:	Refer to test data
Relative humidity	:	Refer to test data
Atmospheric pressure	:	101 kPa

Refer to attached Appendix A for details of test data.

6. List of Tables

Table 1: List of Test and Measurement Equipment	6
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification.....	8
Table 4: RF Channel and Frequency of 2.4GHz Wi-Fi	10
Table 5: RF Channel and Frequency of 5GHz Wi-Fi	10
Table 6: RF Channel and Frequency of 6GHz Wi-Fi	10
Table 7: List of Accessories and Auxiliary Equipment	12
Table 8: Test Result of Maximum Conducted Output Power, 5GHz Wi-Fi U-NII-1.....	16
Table 9: Test Result of Maximum Conducted Output Power, ISM 5GHz Wi-Fi U-NII-1	16
Table 10: Test Result of Maximum Conducted Output Power, 5GHz Wi-Fi U-NII-3.....	16
Table 11: Test Result of Maximum Conducted Output Power, 5GHz Wi-Fi U-NII-4.....	16

Appendix A: Test Results of 5GHz Wi-Fi

APPENDIX A: TEST RESULTS OF 5GHZ WI-FI.....	1
APPENDIX A.1: TEST RESULTS OF 26DB BANDWIDTH	2
Test Result.....	2
Test Graphs.....	3
APPENDIX A.2: TEST RESULTS OF 99% BANDWIDTH.....	4
Test Result.....	4
Test Graphs.....	5
APPENDIX A.3: TEST RESULTS OF 6DB BANDWIDTH	8
Test Result.....	8
Test Graphs.....	9
APPENDIX A.4: TEST RESULTS OF MAXIMUM POWER SPECTRAL DENSITY	11
Test Result.....	11
Test Graphs.....	12
APPENDIX A.5: TEST RESULTS OF FREQUENCY STABILITY	15
Test Result.....	15
APPENDIX A.6: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	16
30MHz - 1GHz.....	16
1GHz - 18GHz.....	20
APPENDIX A.7: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS.....	32
APPENDIX A.8: TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS.....	44

Appendix A.1: Test Results of 26dB Bandwidth

Test Result

TestMode	Antenna	Channel	26db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	20.520	5169.440	5189.960	---	---
		5200	21.440	5189.200	5210.640	---	---
		5240	18.960	5230.440	5249.400	---	---

Test Graphs




Appendix A.2: Test Results of 99% Bandwidth


Test Result

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	17.120	5171.3988	5188.5188	---	---
		5200	17.117	5191.3772	5208.4942	---	---
		5240	16.641	5231.6287	5248.2697	---	---
		5745	18.802	5735.2091	5754.0111	---	---
		5785	17.312	5776.2907	5793.6027	---	---
		5825	17.087	5816.4041	5833.4911	---	---
		5845	17.217	5836.3812	5853.5982	---	---
		5865	17.137	5856.4086	5873.5456	---	---

Test Graphs



11A Ant1 5745




11A Ant1 5785




11A Ant1 5825



11A Ant1 5845



11A_Ant1_5865



Appendix A.3: Test Results of 6dB Bandwidth

Test Result

TestMode	Antenna	Channel	6db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5745	15.680	5737.400	5753.080	0.5	PASS
		5785	16.360	5776.800	5793.160	0.5	PASS
		5825	14.400	5818.080	5832.480	0.5	PASS
		5845	16.360	5836.760	5853.120	0.5	PASS
		5865	16.200	5856.840	5873.040	0.5	PASS

Test Graphs





Appendix A.4: Test Results of Maximum Power Spectral Density

Test Result

TestMode	Antenna	Channel	Result [dBm/500kHz]	Result [dBm/MHz]	EIRP spectral density [dBm/MHz]	FCC Limit [dBm/MHz]	IC Limit [dBm/MHz]	Verdict
11A	Ant1	5180	/	4.65	7.75	≤17.00 (Cond.)	≤10.00 (EIRP)	PASS
		5200	/	4.37	7.47			PASS
		5240	/	4.84	7.94			PASS
		5845	4.28	7.20*	10.50	≤20.00 (EIRP)		PASS
		5865	7.20	10.12*	13.42	≤20.00 (EIRP)		PASS

Note:

1. The Compensation Factor is 2.92dB for 5850-5895MHz while test RBW was 510kHz and 1MHz.
2. The Duty Cycle Factor and RBW Factor is compensated in the graph.

TestMode	Antenna	Channel	Result [dBm/MHz]	FCC Limit [dBm/500kHz]	IC Limit [dBm/500kHz]	Verdict
11A	Ant1	5745	4.85	≤30.00 (Cond.)		PASS
		5785	5.45			PASS
		5825	4.78			PASS


Note:

1. The Duty Cycle Factor and RBW Factor is compensated in the graph.

Test Graphs







11A_Ant1_5865



Appendix A.5: Test Results of Frequency Stability

Test Result

Voltage								
TestMode	Antenna	Channel	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
11A	Ant1	5180	NV	NT	-80000.00	-15.444015	20	PASS
		5200	NV	NT	-80000.00	-15.384615	20	PASS
		5240	NV	NT	-80000.00	-15.267176	20	PASS
		5745	NV	NT	-60000.00	-10.443864	20	PASS
		5785	NV	NT	-80000.00	-13.828868	20	PASS
		5825	NV	NT	-80000.00	-13.733906	20	PASS
		5845	NV	NT	-80000.00	-13.686912	20	PASS
		5865	NV	NT	-80000.00	-13.640239	20	PASS

Temperature								
TestMode	Antenna	Channel	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
11A	Ant1	5180	NV	0	-80000.00	-15.444015	20	PASS
			NV	40	-80000.00	-15.444015	20	PASS
		5200	NV	0	-80000.00	-15.384615	20	PASS
			NV	40	-80000.00	-15.384615	20	PASS
		5240	NV	0	-80000.00	-15.267176	20	PASS
			NV	40	-80000.00	-15.267176	20	PASS
		5745	NV	0	-80000.00	-13.925152	20	PASS
			NV	40	-80000.00	-13.925152	20	PASS
		5785	NV	0	-80000.00	-13.828868	20	PASS
			NV	40	-80000.00	-13.828868	20	PASS
		5825	NV	0	-80000.00	-13.733906	20	PASS
			NV	40	-80000.00	-13.733906	20	PASS
		5845	NV	0	-80000.00	-13.686912	20	PASS
			NV	40	-80000.00	-13.686912	20	PASS
		5865	NV	0	-80000.00	-13.640239	20	PASS
			NV	40	-80000.00	-13.640239	20	PASS

Appendix A.6: Test Results of Radiated Spurious Emissions


Note:

- 1) This testing was carried out on different modulations, but only the worst case was presented in this report.
- 2) Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 40GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

30MHz - 1GHz

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
41.252000	14.61	40.00	25.39	100.0	H	0.0	-19.9
45.859500	14.53	40.00	25.47	100.0	H	54.0	-18.8
106.824000	22.78	43.50	20.72	100.0	H	166.0	-19.0
134.566000	15.23	43.50	28.27	100.0	H	316.0	-22.1
228.753000	16.67	46.00	29.33	100.0	H	89.0	-18.2
442.832000	20.16	46.00	25.84	100.0	H	316.0	-12.9
700.027500	28.34	46.00	17.66	100.0	H	236.0	-7.9
936.950000	28.24	46.00	17.76	100.0	H	0.0	-4.4

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.917000	23.23	40.00	16.77	100.0	V	23.0	-21.6
42.270500	21.38	40.00	18.62	100.0	V	142.0	-19.6
99.306500	21.90	43.50	21.60	100.0	V	284.0	-19.2
197.082500	12.72	43.50	30.78	100.0	V	0.0	-19.2
543.566500	20.37	46.00	25.63	100.0	V	15.0	-10.9
700.076000	28.81	46.00	17.19	100.0	V	236.0	-7.9
936.950000	28.89	46.00	17.11	100.0	V	135.0	-4.4

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch157
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.538500	15.97	40.00	24.03	100.0	H	225.0	-18.7
106.387500	24.61	43.50	18.89	100.0	H	149.0	-19.0
195.627500	14.78	43.50	28.72	100.0	H	22.0	-19.3
420.764500	20.58	46.00	25.42	100.0	H	286.0	-13.2
691.103500	28.50	46.00	17.50	100.0	H	225.0	-8.1
936.950000	29.07	46.00	16.93	100.0	H	215.0	-4.4

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch157
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
42.028000	22.51	40.00	17.49	100.0	V	83.0	-19.7
63.222500	15.81	40.00	24.19	100.0	V	153.0	-19.8
99.355000	24.13	43.50	19.37	100.0	V	310.0	-19.2
197.082500	11.54	43.50	31.96	100.0	V	0.0	-19.2
445.402500	17.84	46.00	28.16	100.0	V	222.0	-12.9
700.076000	28.77	46.00	17.23	100.0	V	231.0	-7.9
960.230000	29.57	54.00	24.43	100.0	V	169.0	-4.1

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---


1GHz - 18GHz

Note: The highest waveform in the figure is 5GHz Wi-Fi Fundamental.

*Note: 5745MHz is for device setup, it keeps transmitting.

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1519.500000	49.84	---	74.00	24.16	150.0	H	230.0	3.3
1519.500000	---	40.35	54.00	13.65	150.0	H	230.0	3.3
2176.000000	51.08	---	74.00	22.92	150.0	H	57.0	8.7
2208.500000	---	41.82	54.00	12.18	150.0	H	57.0	8.8
3484.000000	---	44.68	54.00	9.32	150.0	H	250.0	12.4
3494.500000	54.63	---	74.00	19.37	150.0	H	237.0	12.4

Final Result

[illegible]

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1521.000000	49.97	---	74.00	24.03	150.0	V	278.0	3.4
1521.000000	---	40.45	54.00	13.55	150.0	V	278.0	3.4
2166.000000	51.86	---	74.00	22.14	150.0	V	77.0	8.6
2175.000000	---	42.10	54.00	11.90	150.0	V	77.0	8.7
3472.000000	---	43.41	54.00	10.59	150.0	V	318.0	12.4
3476.500000	54.17	---	74.00	19.83	150.0	V	272.0	12.4

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7326.408333	---	39.39	54.00	14.61	150.0	H	6.0	8.2
7328.866667	46.58	---	74.00	27.42	150.0	H	6.0	8.1
12150.641667	---	42.10	54.00	11.90	150.0	H	358.0	16.7
12154.083333	50.75	---	74.00	23.25	150.0	H	296.0	16.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	PoI	Azimuth (deg)	Corr. (dB/m)
7043.700000	46.56	---	74.00	27.44	150.0	V	318.0	8.5
7043.700000	---	39.32	54.00	14.68	150.0	V	318.0	8.5
12141.791667	---	42.77	54.00	11.23	150.0	V	148.0	16.5
12155.066667	50.75	---	74.00	23.25	150.0	V	225.0	16.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch157
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1515.500000	48.60	---	74.00	25.40	150.0	H	234.0	3.3
1518.500000	---	40.49	54.00	13.51	150.0	H	234.0	3.3
2040.000000	---	40.73	54.00	13.27	150.0	H	228.0	8.3
2052.000000	52.62	---	74.00	21.38	150.0	H	242.0	8.3
2939.000000	---	41.53	54.00	12.47	150.0	H	248.0	10.9
2956.500000	52.27	---	74.00	21.73	150.0	H	248.0	11.0
4690.500000	---	43.74	54.00	10.26	150.0	H	5.0	13.5
4717.500000	55.34	---	74.00	18.66	150.0	H	300.0	13.4

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch157
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1312.000000	49.00	---	74.00	25.00	150.0	V	253.0	3.6
1312.500000	---	39.35	54.00	14.65	150.0	V	253.0	3.6
1518.500000	---	40.01	54.00	13.99	150.0	V	280.0	3.3
1520.000000	50.68	---	74.00	23.32	150.0	V	280.0	3.3
2159.500000	51.09	---	74.00	22.91	150.0	V	76.0	8.6
2168.500000	---	42.63	54.00	11.37	150.0	V	76.0	8.6
4649.500000	55.03	---	74.00	18.97	150.0	V	67.0	13.5
4694.500000	---	43.63	54.00	10.37	150.0	V	304.0	13.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch157
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7317.558333	45.83	---	74.00	28.17	150.0	H	7.0	8.2
7330.341667	---	38.73	54.00	15.27	150.0	H	1.0	8.1
12145.725000	---	42.95	54.00	11.05	150.0	H	95.0	16.6
12154.575000	51.00	---	74.00	23.00	150.0	H	118.0	16.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch157
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7203.491667	---	38.51	54.00	15.49	150.0	V	328.0	8.8
7256.100000	46.59	---	74.00	27.41	150.0	V	328.0	8.5
12149.166667	---	42.63	54.00	11.37	150.0	V	274.0	16.7
12156.050000	50.95	---	74.00	23.05	150.0	V	193.0	16.4

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch169
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1343.500000	44.03	---	74.00	29.97	150.0	H	16.0	3.9
1349.500000	---	33.17	54.00	20.83	150.0	H	340.0	3.9
2534.500000	---	40.32	54.00	13.68	150.0	H	225.0	10.4
2541.000000	50.79	---	74.00	23.21	150.0	H	296.0	10.5
4685.500000	54.64	---	74.00	19.36	150.0	H	172.0	13.5
4687.000000	---	43.33	54.00	10.67	150.0	H	138.0	13.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch169
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1402.000000	43.97	---	74.00	30.03	150.0	V	273.0	3.6
1402.000000	---	35.07	54.00	18.93	150.0	V	273.0	3.6
2644.500000	---	40.25	54.00	13.75	150.0	V	106.0	11.0
2646.000000	50.88	---	74.00	23.12	150.0	V	36.0	11.0
4685.000000	---	43.99	54.00	10.01	150.0	V	63.0	13.5
4698.500000	55.27	---	74.00	18.73	150.0	V	82.0	13.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch169
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7414.416667	---	35.49	54.00	18.51	150.0	H	104.0	8.3
7472.433333	44.20	---	74.00	29.80	150.0	H	247.0	8.6
12146.708333	51.40	---	74.00	22.60	150.0	H	4.0	16.6
12149.166667	---	42.94	54.00	11.06	150.0	H	93.0	16.7

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
----	----	----	----	----	----		----	----

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch169
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7444.408333	43.50	---	74.00	30.50	150.0	V	351.0	8.5
7447.850000	---	35.67	54.00	18.33	150.0	V	252.0	8.5
12143.758333	---	43.08	54.00	10.92	150.0	V	358.0	16.6
12144.250000	50.38	---	74.00	23.62	150.0	V	239.0	16.6


Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

Appendix A.7: Test Results of Radiated Emissions in Restricted Bands

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5134.877778	55.05	---	74.00	18.95	150.0	H	235.0	13.9
5139.138889	---	44.29	54.00	9.71	150.0	H	95.0	13.9

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
93.750000	120.000000	110.000000	120.000000	0.000000	30.000000	V	0.000000	0.000000

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch36
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5143.400000	---	47.61	54.00	6.39	150.0	V	98.0	13.9
5146.677778	59.38	---	74.00	14.62	150.0	V	142.0	13.9

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
93.750000	122.000000	118.000000	120.000000	2.000000	100.000000	000	000	000

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch48
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5409.355556	---	45.33	54.00	8.67	150.0	H	191.0	15.0
5409.650000	56.41	---	74.00	17.59	150.0	H	330.0	15.0

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
100.0	100.0	100.0	100.0	100.0	100.0		100.0	100.0

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch48
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5374.905556	---	45.71	54.00	8.29	150.0	V	145.0	14.9
5399.050000	56.73	---	74.00	17.27	150.0	V	293.0	14.9

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
93.750000	93.750000	93.750000	93.750000	93.750000	93.750000		93.750000	93.750000

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch149
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5618.150000	57.05	68.20	11.15	150.0	H	276.0	15.3

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch149
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5646.627778	58.23	68.20	9.97	150.0	V	107.0	15.3

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch165
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5991.138889	58.89	68.20	9.31	150.0	H	178.0	16.5

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch165
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5950.041667	59.32	68.20	8.88	150.0	V	263.0	16.3

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch169
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5633.444445	57.07	68.20	11.13	150.0	H	10.0	15.3


Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

*Note: 5745MHz is for device setup, it keeps transmitting.

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch169
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5638.777778	57.26	68.20	10.94	150.0	V	44.0	15.3


Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

*Note: 5745MHz is for device setup, it keeps transmitting.

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch173
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5926.333333	59.38	68.20	8.82	150.0	H	181.0	16.2

Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name:	Access Point
Model:	BlitzFunk AW32R
Test Mode:	WIFI 5G_11a_Ch173
Order No/Sample No:	27227126/A004250609-003
Test Voltage:	AC 120V/60Hz
Remark:	Temp 23.2°C Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5939.222222	58.97	68.20	9.23	150.0	V	33.0	16.2


Final_Result

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Appendix A.8: Test Results of Conducted Emission on AC Mains

EUT Information

EUT Name:	Access Point
Order Number:	27227126 10-(P02301552)
Model:	BlitzFunk AW32R
Test Mode:	On, normal operation by 2.4 GHz Wi-Fi + 5 GHz Wi-Fi + 6 GHz Wi-Fi traffic with Ethernet port data transmission
Test Voltage:	AC 120V 60Hz
Standard:	FCC PART 15 B
Test By:/Review By:	Charron Chen / Charlie Zha
Tem./Hum./Pressure:	24.0°C/51.1%/101kPa
Remark:	SR 3



Critical Freqs


Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.150	59.0	---	66.00	6.98	L1	9.5
0.150	---	43.1	56.00	12.88	L1	9.5
0.177	---	38.6	54.61	16.01	L1	9.7
0.177	56.7	---	64.61	7.89	L1	9.7
0.351	---	34.4	48.93	14.48	L1	9.6
0.354	43.6	---	58.87	15.23	L1	9.6
2.822	---	28.3	46.00	17.67	L1	9.6
2.851	40.5	---	56.00	15.51	L1	9.6
5.819	39.1	---	60.00	20.89	L1	9.8
5.879	---	26.7	50.00	23.25	L1	9.8
11.886	43.0	---	60.00	16.97	L1	9.8
11.968	---	26.4	50.00	23.57	L1	9.8

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150	56.1	---	66.00	9.93	1000.0	9.0	L1	9.5

EUT Information

EUT Name:	Access Point
Order Number:	27227126 10-(P02301552)
Model:	BlitzFunk AW32R
Test Mode:	On, normal operation by 2.4 GHz Wi-Fi + 5 GHz Wi-Fi + 6 GHz Wi-Fi traffic with Ethernet port data transmission
Test Voltage:	AC 120V 60Hz
Standard:	FCC PART 15 B
Test By./Review By:	Charron Chen / Charlie Zha
Tem./Hum./Pressure:	24.0°C/51.1%/101kPa
Remark:	SR 3



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.150	58.7	---	66.00	7.35	N	9.7
0.150	---	42.8	56.00	13.22	N	9.7
0.162	---	39.5	55.34	15.81	N	9.8
0.162	56.4	---	65.34	8.97	N	9.8
2.807	41.0	---	56.00	14.97	N	9.8
2.827	---	28.5	46.00	17.48	N	9.8
5.824	41.7	---	60.00	18.32	N	9.8
5.919	---	25.5	50.00	24.53	N	9.8
11.821	40.9	---	60.00	19.15	N	9.6
11.864	---	26.3	50.00	23.70	N	9.6
15.070	---	24.4	50.00	25.62	N	9.6
15.438	38.0	---	60.00	22.04	N	9.6

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150	56.2	---	66.00	9.77	1000.0	9.0	N	9.7
0.162	53.3	---	65.34	12.01	1000.0	9.0	N	9.8