


Test Report No:
2680357R-RFUSV03S-B

Test Result for Inspection (Class II Permissive Change)

Product Name	WIRELESS SUBWOOFER
Brand Name	ASUS
Model No.	S701(SW)
FCC ID	2BUYE-S701SW
Applicant's Name / Address	Luxshare Intelligent Manufacturing Electronic Services (Kunshan) Co.,LTD. Room 2, No.66, Third Avenue, Comprehensive Bonded Zone, Kunshan Development Zone, Suzhou City, jiangsu, P.R.China
Manufacturer's Name	ASUSTeK COMPUTER INC.
Test Method Requested, Standard	FCC CFR Title 47 Part 15 Subpart E Section 15.407
Verdict Summary	IN COMPLIANCE
Documented By Genie Chang	
Approved By Steven Tsai	
Date of Receipt	2026/08/12
Date of Issue	2026/09/02
Report Version	V1.0

INDEX

	page
Competences and Guarantees.....	4
General Conditions	4
Revision History	5
Permissive Change.....	6
Summary of Test Result	7
1. General Information.....	8
1.1. EUT Description	8
1.2. EUT Information	9
1.3. Testing Applied Standards	9
1.4. Testing Location Information	10
1.5. Ambient Conditions In The Laboratory	11
1.6. Measurement Uncertainty	11
1.7. List of Test Equipment	12
2. Test Configuration of EUT	13
2.1. Test Condition	13
2.2. Test Frequency Mode	13
2.3. Duty Cycle	14
2.4. Measurement Configuration	15
2.5. Tested System Details	16
2.6. Configuration of Tested System	16
3. AC Power Line Conducted Emission	17
3.1. Test Setup.....	17
3.2. Test Limit	17
3.3. Test Procedure	17
3.4. Test Result of AC Power Line Conducted Emission.....	17
4. Emission Bandwidth	18
4.1. Test Setup.....	18
4.2. Test Limit	18
4.3. Test Procedure	18
4.4. Test Result of Emission Bandwidth	18
5. Maximum Conducted Output Power	19
5.1. Test Setup.....	19
5.2. Test Limit	20
5.3. Test Procedure	20
5.4. Test Result of Maximum Conducted Output Power	20
6. Maximum Power Spectral Density	21

6.1.	Test Setup.....	21
6.2.	Test Limit	21
6.3.	Test Procedure	21
6.4.	Test Result of Maximum Power Spectral Density	21
7.	Radiated Emission.....	22
7.1.	Test Setup.....	22
7.2.	Test Limit	23
7.3.	Test Procedure	24
7.4.	Test Result of Radiated Emission (Below 30 MHz).....	24
7.5.	Test Result of Radiated Emission.....	24
Appendix A. Test Result of AC Power Line Conducted Emission		
Appendix B. Test Result of Emission Bandwidth		
Appendix C. Test Result of Maximum Conducted Output Power		
Appendix D. Test Result of Maximum Power Spectral Density		
Appendix E. Test Result of Radiated Emission		
Appendix F. Test Setup Photograph		

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	2026/09/02

Permissive Change

Report No.	Version	Description	Issued Date
2630134R-RFUSV03S-B	V1.0	Original application.	2026/05/29
2680357R-RFUSV03S-B	V1.0	This is to request a Class II permissive change. The major change filed under this application is: Change #1: Addition of 802.11n (20 MHz) functionality.	2026/09/02

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
3	AC Power Line Conducted Emission	PASS	-
4	Emission Bandwidth	PASS	-
5	Maximum Conducted Output Power	PASS	-
6	Maximum Power Spectral Density	PASS	-
7	Radiated Emission	PASS	-

Comments and Explanations

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1. General Information

1.1. EUT Description

Frequency Range	5150 ~ 5250 MHz 5725 ~ 5850 MHz	
Operating Frequency / Channel Number	IEEE 802.11n (20 MHz)	5180 ~ 5240 MHz / 4 Channels 5745 ~ 5825 MHz / 5 Channels
	IEEE 802.11n (40 MHz)	5190 ~ 5230 MHz / 2 Channels 5755 ~ 5795 MHz / 2 Channels
Type of Modulation	IEEE 802.11n	OFDM-BPSK, QPSK, 16QAM, 64QAM

Accessories Information		
No.	Equipment Name	Description
1	Power Cable	Non-shielded, 1.5m

Antenna Information					
Item.	Brand Name	Model No.	Type	Antenna Gain (dBi)	
1	SUNPLUS TECHNOLOGY CO.,LTD	SPA-MW21xx-M (2.4G+5G)	PCB	U-NII 1	2.67
				U-NII 3	4.62
2	SUNPLUS TECHNOLOGY CO.,LTD	SPA-MW21xx-M (5G)	PCB	U-NII 1	3.04
				U-NII 3	3.98

For IEEE 802.11n Mode: (1TX, 1RX)

Note: The antenna of EUT conforms to FCC 15.203.

1.2. EUT Information

EUT Power Type	From Host		
EUT Function	☒	Point-to-multipoint	☐ Point-to-point
Operating Mode	☐	Master	
	☐	Slave with radar detection	
	☒	Slave without radar detection	

1.3. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC CFR Title 47 Part 15 Subpart E Section 15.407
- ♦ ANSI C63.10-2020
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

The following reference test guidance is not within the scope of accreditation of TAF:

- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

1.4. Testing Location Information

Testing Location Information			
Test Laboratory : DEKRA Testing and Certification Co., Ltd.			
V	Address	No. 85, Wenlin St., Linkou Dist., New Taipei City 244017, Taiwan, R.O.C.	
	Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.	
	Phone/Fax Number	TEL: +886-3-275-7255	FAX: +886-3-327-8031
	USA	FCC Designation Number: TW0033 / FCC Registration Number: 647365	
	Canada	CAB Identifier Number: TW3023 / Company Number: 26930	
	Site Description	Accredited by TAF Accredited Number: 3023	
	Address/ Performed Location	No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.	
	Phone/Fax Number	TEL: +886-3-582-8001	FAX: +886-3-582-8958
	USA	Test site Designation No. TW3024 with FCC.	
	Canada	CAB Identifier Number: TW3024 / Company Number: 22397	
	Site Description	Accredited by TAF Accredited Number: 3024	
	Address/ Performed Location	No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.	
	Phone/Fax Number	TEL: +886-3-582-8001	FAX: +886-3-582-8958
	USA	Test site Designation No. TW3024 with FCC.	
	Canada	CAB Identifier Number: TW3024 / Company Number: 22397	
	Site Description	Accredited by TAF Accredited Number: 3024	

1.5. Ambient Conditions In The Laboratory

Performed Item	Items	Required	Actual	Test Date	Tested By
AC Power Line	Temperature (°C)	10~40 °C	26.8 °C	2026/08/24	Shane Sun
Conducted Emission	Humidity (%RH)	10~90 %	54.2%		
RF Conducted Emission	Temperature (°C)	10~40 °C	24.1~25.0 °C	2026/08/11 ~	Neko Chen
	Humidity (%RH)	10~90 %	51.5~55.2 %	2026/08/12	
Radiated Emission	Temperature (°C)	10~40 °C	24.9~25.7 °C	2026/08/10 ~	Rock Liang
	Humidity (%RH)	10~90 %	58.3~60.8 %	2026/08/11	

1.6. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
AC Power Line Conducted Emission	± 3.73 dB
Emission Bandwidth	± 1580.61 Hz
Maximum Conducted Output Power	Spectrum Analyzer: ± 2.13 dB Power Meter: ± 1.06 dB
Maximum Power Spectral Density	± 2.13 dB
Radiated Emission	9 kHz~30 MHz: ± 3.30 dB 30 MHz~1 GHz: ± 5.39 dB 1 GHz~18 GHz: ± 4.24 dB 18 GHz~40 GHz: ± 3.62 dB
Duty Cycle	± 0.65 %

1.7. List of Test Equipment

For Conduction Measurements / HY-SR01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2026/04/20	2027/04/19
V	Two-Line V-Network	R&S	ENV216	101306	2026/03/27	2027/03/26
V	Two-Line V-Network	R&S	ENV216	101307	2025/08/06	2027/08/05
V	Coaxial Cable	SUHNER	RG400_BNC	RF001	2026/01/10	2027/01/09

Note:

1. Two-Line V-Network is calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Conducted Measurements / HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103467	2026/04/24	2027/04/23
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2026/04/30	2027/04/29
V	Wideband Power Sensor	KEYSIGHT	N1923A	MY59240002	2026/05/06	2027/05/05
V	Wideband Power Sensor	KEYSIGHT	N1923A	MY59240003	2026/05/06	2027/05/05

Note:

1. All equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version : DTC_RF_Tool_Release V2.0.37

For Radiated Measurements /HY-CB03

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Loop Antenna	TESEQ	HLA6121	49611	2026/02/04	2027/02/03
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0675	2025/08/14	2027/08/13
V	Horn Antenna	Com-Power	AH-840	101100	2025/10/07	2027/10/06
V	Horn Antenna	RF SPIN	DRH18-E	210507A18ES	2026/04/24	2028/04/23
V	Pre-Amplifier	SGH	SGH0301-9	20211007-11	2026/01/10	2027/01/09
V	Pre-Amplifier	SGH	PRAMP118	20200701	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980310	2026/01/10	2027/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2026/01/10	2027/01/09
V	Coaxial Cable	EMCI	EMC102-KM-KM-600	160311	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HC360-2.92M/2.92M-7.0M	202108-1	2026/01/10	2027/01/09
V	Filter	MICRO TRONICS	BRM50716	G196	2026/01/05	2027/01/04
V	EMI Test Receiver	R&S	ESR3	102793	2025/12/01	2026/11/30
V	Spectrum Analyzer	R&S	FSV3044	101114	2026/04/08	2027/04/07
V	Coaxial Cable	SGH	HA800	202602-3	2026/07/17	2027/07/16
V	Coaxial Cable	SGH	SGH18	2021005-1	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	SGH18	202108-4	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800	GD20110223-1	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800	GD20110222-8	2026/01/10	2027/01/09

Note:

1. Bi-Log Antenna and Horn Antenna are calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition	
Testing Voltage	AC 120V/60Hz


2.2. Test Frequency Mode

Test Software Version	AmebaDPlus_mptool / Version 1V12
-----------------------	----------------------------------

Modulation	Frequency (MHz)	Power Setting			
		SISO A	SISO B	MIMO A	MIMO B
802.11n (20 MHz)	5180	75	81	--	--
	5220	78	81	--	--
	5240	77	81	--	--
	5745	69	74	--	--
	5785	70	75	--	--
	5825	73	77	--	--

2.3. Duty Cycle

Modulation	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (Hz)
802.11n (20 MHz)	1.8700	2.9000	64.48	1.91	1000



2.4. Measurement Configuration

Tests Item	AC Power Line Conducted Emission
Test Condition	AC power line conducted measurement for line and neutral
Operating Mode	Transmit

Tests Item	Emission Bandwidth Maximum Conducted Output Power Maximum Power Spectral Density
Test Condition	Conducted measurement at transmit chains
Operating Mode	Transmit

Tests Item	Radiated Emission
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	Transmit
Operating Mode > 1GHz	Transmit


Note:

1. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
3. For radiated emission below 1 GHz and AC power line conducted emission have performed all modes of operation were investigated and the worst-case emissions are reported.
4. The lowest data rates are tested in each mode. Only the worst case is shown in the report.
(802.11n is MCS0)

2.5. Tested System Details


No.	Equipment	Brand Name	Model No.	Serial No.	Power Cord
1	Notebook PC	ASUS	P5430U	G8NXCV07J11032C	N/A
2	Test Fixture	NC	FT232RL	N/A	N/A

2.6. Configuration of Tested System



3. AC Power Line Conducted Emission

3.1. Test Setup



3.2. Test Limit

Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

3.3. Test Procedure


The EUT was setup according to ANSI C63.10-2020 for AC Power Line Conducted Emissions.

3.4. Test Result of AC Power Line Conducted Emission

Refer as Appendix A

4. Emission Bandwidth

4.1. Test Setup



4.2. Test Limit

26dB Bandwidth & 99% Occupied Bandwidth : No Required

DTS Bandwidth $\geq$ 500kHz

4.3. Test Procedure

The EUT was setup to ANSI C63.10-2020; tested to U-NII test procedure of KDB 789033.


4.4. Test Result of Emission Bandwidth

Refer as Appendix B


5. Maximum Conducted Output Power

5.1. Test Setup

For straddle channels:



For other channels:



5.2. Test Limit

1. For an outdoor access point and an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure


The EUT was setup to ANSI C63.10-2020; tested to U-NII test procedure of KDB 789033.

5.4. Test Result of Maximum Conducted Output Power

Refer as Appendix C

6. Maximum Power Spectral Density

6.1. Test Setup



6.2. Test Limit

1. For the band 5.15 ~ 5.25 GHz, the peak power spectral density shall not exceed 17 dBm in any 1 MHz band. If transmitting antenna of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.
2. For client devices in the 5.15 ~ 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi
3. For the 5.25 ~ 5.35 GHz ,5470 ~ 5600 MHz and 5650 ~ 5725 MHz, the peak power spectral density shall not exceed 11 dBm in any 1-MHz band. If transmitting antenna of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.
4. For the band 5.725 ~ 5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antenna of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that directional gain of the antenna exceeds 6 dBi.

6.3. Test Procedure

The EUT was setup to ANSI C63.10-2020; tested to U-NII test procedure of KDB 789033.


6.4. Test Result of Maximum Power Spectral Density

Refer as Appendix D


7. Radiated Emission

7.1. Test Setup


9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



Above 1 GHz



7.2. Test Limit

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	20 log (2400/F(kHz))	300
0.490 – 1.705	24000/F(kHz)	20 log (24000/F(kHz))	30
1.705 - 30	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Remarks:

1. Field strength (dBμV/m) = 20 log Field strength (μV/m)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Unwanted Emission out of the restricted bands Test Limit

Frequency (MHz)	EIRP Limit (dBm/MHz)	Equivalent Field Strength (dBμV/m@3m)
5150 – 5250	-27	68.2
5250 – 5350	-27	68.2
5470 – 5725	-27	68.2
5725 – 5850	-27 ^{*1}	68.2 ^{*1}
	10 ^{*2}	105.2 ^{*2}
	15.6 ^{*3}	110.8 ^{*3}
	27 ^{*4}	122.2 ^{*4}

^{*1} beyond 75 MHz or more above of the band edge.

^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts).}$$

7.3. Test Procedure

The EUT and all the supporting units are placed on a turn table which is 0.8 or 1.5 meters above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10-2020 on radiated measurement.

On any frequency or frequencies from 9 kHz (include the lowest oscillator frequency generated within the device up to the 10th harmonic) to 1000 MHz, the limit shown are based on measuring equipment employing a quasi-peak detector function and on any frequency or frequencies above 1000 MHz the radiated limit shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth below 1 GHz setting on the field strength meter is 120 kHz and above 1 GHz is 1 MHz.

7.4. Test Result of Radiated Emission (Below 30 MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

7.5. Test Result of Radiated Emission

Refer as Appendix E