

TEST REPORT

Product Name : CASEPLAY Art Panel Speaker
Model Number : BD-WH-11-OT-OT2229
FCC ID : 2BUYHBDWH11OTOT2229

Prepared for : FOX.INC
Address : Hibiya Mitsui Tower 12F, 1-1-2 Yurakucho, Chiyoda-ku,
Tokyo, 100-0006. JAPAN

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2511280265W00902R
Date of sample receipt : Nov 28, 2025
Date(s) of Tests : Nov 28, 2025 to Jan 31, 2026
Date of issue : Feb 03, 2026

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : FOX.INC

Address : Hibiya Mitsui Tower 12F,1-1-2 Yurakucho, Chiyoda-ku, Tokyo,100-0006. JAPAN

Manufacturer : Dongguan G.K Technology Co.,Ltd

Address : 4F,No. 7, Donger Street, Xingfa South Road, Wusha, Chang'an Town, Dongguan City, Guangdong Province, China

Factory : Dongguan G.K Technology Co.,Ltd

Address : 4F,No. 7, Donger Street, Xingfa South Road, Wusha, Chang'an Town, Dongguan City, Guangdong Province, China

EUT : CASEPLAY Art Panel Speaker

Model Name : BD-WH-11-OT-OT2229

Trademark : N/A

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1091	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1091.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Nov 28, 2025 to Jan 31, 2026

Prepared by : 
Yu Xiaolan /Editor

Reviewer : 
Xia Lili/Supervisor

Approve & Authorized Signer : 
Wang Li/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2511280265W00902R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	CASEPLAY Art Panel Speaker
Model Number:	BD-WH-11-OT-OT2229
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	-0.17 dBm(0.000962W)
Antenna Type:	PCB Antenna
Antenna Gain:	-3.78 dBi
Power supply:	DC 12V from adapter Adapter:Model:HCX2402-1202000J INPUT:100-240V~ 50-60Hz 0.8A Output: 12V= 2A
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R =20, distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Antenna gain: -3.78 dBi

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-0.27	0±1	1	1.259	-3.78	0.42	0.0001	1
2441		-1.31	-1±1	0	1.000	-3.78	0.42	0.0001	1
2480		-3.75	-3±1	-2	0.631	-3.78	0.42	0.0001	1
2402	π/4-DQPSK	-0.37	0±1	1	1.259	-3.78	0.42	0.0001	1
2441		-1.36	-1±1	0	1.000	-3.78	0.42	0.0001	1
2480		-3.91	-3±1	-2	0.631	-3.78	0.42	0.0001	1
2402	8-DPSK	-0.17	0±1	1	1.259	-3.78	0.42	0.0001	1
2441		-1.07	-1±1	0	1.000	-3.78	0.42	0.0001	1
2480		-3.87	-3±1	-2	0.631	-3.78	0.42	0.0001	1

According to KDB 447498, no stand-alone required for WIFI/BLE antenna, and no simultaneous SAR measurement is required.

*** End of Report ***