



Shenzhen Huaxia Testing Technology Co., Ltd.

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD 102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20260100283E-05
Applicant: Shenzhen Kingone Information Technology Co., Ltd.
Address of Applicant: 7th floor, Building 6, Hengda Fashion Huigu, Henglang Community, Dalang Street, Longhua Dist, Shenzhen
Equipment Under Test (EUT):
EUT Name: MINI PC
Model No.: BOX-1213, L10
Test Model No.: BOX-1213
Brand Name: N/A
FCC ID: 2BUYS-BOX-1213
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2026-01-29
Date of Test: 2026-01-29 to 2026-03-05
Date of Issue: 2026-3-30
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260100283E-05	Rev.01	Initial report	2026-3-30

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	5
3.4 GENERAL DESCRIPTION OF BLE	5
3.5 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
3.6 GENERAL DESCRIPTION OF 5G WIFI CLASSIC	6
4 MPE EVALUATION	8
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	8
4.1.1 Limits	8
4.1.2 Test Procedure	8
4.1.3 EUT RF Exposure	9

3 General Information

3.1 Client Information

Applicant:	Shenzhen Kingone Information Technology Co., Ltd.
Address of Applicant:	7th floor, Building 6, Hengda Fashion Huigu, Henglang Community, Dalang Street, Longhua Dist, Shenzhen
Manufacturer:	Shenzhen Kingone Information Technology Co., Ltd.
Address of Manufacturer:	7th floor, Building 6, Hengda Fashion Huigu, Henglang Community, Dalang Street, Longhua Dist, Shenzhen
Factory:	SHENZHEN ZEROONE TECHNOLOGY CO., LIMITED
Address of Factory:	220, Bldg #8, Hengda Fashion Huigu Building, Fulong Road, Henglang Community, Dalang Street, Longhua Dist, Shenzhen

3.2 General Description of EUT

Product Name:	MINI PC
Model No.:	BOX-1213, L10
Test Model No.:	BOX-1213
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
EUT Power Supply:	Power supply DC19V form adapter Adapter: Model:AD1002-1904740D6 Input:100-240V~50/60Hz 1.5A MAX Output:19.0V---4.74A 90.0W Max

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	3.07dBi

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps, 2Mbps, 125Kbps, 500Kbps,
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	FPC antenna
Antenna Gain:	3.07dBi

3.5 General Description of 2.4G WIFI Classic

Operation Frequency:	IEEE 802.11b/g/n(HT20)/ax(HE20): 2412MHz to 2462MHz IEEE 802.11n(HT40)/ax(HE40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11ax(HE20 and HE40): OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20/ax HE20: 11 Channels IEEE 802.11n HT40/ax HE40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps IEEE for 802.11ax(HE20):

	8.6Mbps/17.2Mbps/25.8Mbps/34.4Mbps/51.6Mbps/68.8Mbps/77.4Mbps /86.7Mbps/103.3Mbps/114.7Mbps/129.0Mbps/143.4Mbps IEEE for 802.11ax(HE40): 17.2Mbps/34.4Mbps/51.6Mbps/68.8Mbps/103.2Mbps/137.6Mbps/154.9Mbps /173.3Mbps/206.5Mbps/229.4Mbps/258.1Mbps/286.8Mbps
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	ANT1:3.07dBi ANT2:3.58dBi ANT1+ANT2:6.34dBi

3.6 General Description of 5G WIFI Classic

Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250 MHz IEEE802.11n/ac/ax(40M): 5150MHz ~5250 MHz IEEE802.11ac/ax(80M): 5150MHz ~5250 MHz IEEE 802.11a/n/ac/ax(20M): 5250MHz ~5350 MHz IEEE802.11n/ac/ax(40M): 5250MHz ~5350 MHz IEEE802.11ac/ax(80M): 5250MHz ~5350 MHz IEEE 802.11a/n/ac/ax(20M): 5470MHz ~5725 MHz IEEE802.11n/ac/ax(40M): 5470MHz ~5725 MHz IEEE802.11ac/ax(80M): 5470MHz ~5725 MHz IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850 MHz IEEE802.11n/ac/ax(40M): 5725MHz ~5850 MHz IEEE802.11ac/ax(80M): 5725MHz ~5850 MHz
Channel Numbers:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11ac/ax(80M): 5150MHz ~5250MHz/ 1 channel IEEE 802.11a/n/ac/ax(20M): 5250MHz ~5350MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5250MHz ~5350MHz/ 2 channel IEEE 802.11ac/ax(80M): 5250MHz ~5350MHz/ 1 channel IEEE 802.11a/n/ac/ax(20M): 5470MHz ~5725MHz/ 9 channel IEEE 802.11n/ac/ax(40M): 5470MHz ~5725MHz/ 4 channel IEEE 802.11ac/ax(80M): 5470MHz ~5725MHz/ 2 channel IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac/ax(40M): 5725MHz ~5850MHz/ 2 channel IEEE 802.11ac/ax(80M): 5725MHz ~5850MHz/ 1 channel
Type of Modulation:	IEEE for 802.11ax: OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11a/n/ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna

Antenna gain:	ANT1:4.92dBi ANT2:4.98dBi ANT1+ANT2:7.96dBi
Cable loss:	1.0 dB

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BLE

Antenna Gain: 3.07dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.03 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	8.33	8.5±1	9.5	8.91
Middle(2440MHz)	9.01	9.5±1	10.5	11.22
Highest(2480MHz)	9.26	9.5±1	10.5	11.22

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
11.22	3.07	0.0045261519	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100283E-02 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (11.22 \cdot 2.03) / (4 \cdot 3.1416 \cdot 20^2) = 0.0045261519$

2) For BT

Antenna Gain: 3.07dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.03 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	9.84	10.0±1	11	12.59
Middle(2440MHz)	10.63	11.0±1	12	15.85
Highest(2480MHz)	10.10	10.5±1	11.5	14.13

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
15.85	3.07	0.0063933596	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100283E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (15.85 * 2.03) / (4 * 3.1416 * 20^2) = 0.0063933596$

3) For 2.4G WIFI

Antenna Gain: 6.34dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.31 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11AX20 MIMO mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	18.52	19.0±1	20	100.00
Middle(2437MHz)	19.89	20.0±1	21	125.89
Highest(2462MHz)	20.49	20.5±1	21.5	141.25

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
141.25	6.34	0.1209843315	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100283E-03 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (141.25 * 4.31) / (4 * 3.1416 * 20^2) = 0.1209843315$

4) For 5G WIFI Classic

Antenna Gain: 7.96dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 6.25 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11N20MIMO mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5260MHz)	16.82	17.0±1	18	63.10
Middle(5280MHz)	15.02	15.5±1	16.5	44.67
Highest(5320MHz)	15.88	16.0±1	17	50.12

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
63.10	7.96	0.0784746033	1.0	PASS

Note: 1) Refer to report No. CQASZ20260100283E-04 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (63.1 \cdot 6.25) / (4 \cdot 3.1416 \cdot 20^2) = 0.0784746033$

*** END OF REPORT ***