Shenzhen Xinjike Cross-border E-commerce Co., Ltd.

TEST REPORT

SCOPE OF WORK
FCC TESTING–X08

REPORT NUMBER
260302011SZN-001

ISSUE DATE	**[REVISED DATE]**
29 May 2026	[----------]

PAGES
25

DOCUMENT CONTROL NUMBER
FCC ID 249_C
© 2017 INTERTEK

Shenzhen Xinjike Cross-border E-commerce Co., Ltd.

Application
For
Certification

FCC ID: 2BV3D-X08

True Wireless Earbuds

Model: X08

Brand Name: N/A

2.4GHz Transceiver

Report No.: 260302011SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-24]

Prepared and Checked by:

Hyman Huang
Engineer

Approved by:

Johnny Wang
Project Engineer
Date: 29 May 2026

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one:) Original Grant X Class II Change _____

Equipment Type: DXX - Part 15 Low Power Communication Device Transmitter

---

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No X

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date
of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes _____ No X

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-24 Edition] provision.

Report prepared by:

Hyman Huang
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue,
Zhangkengjing Community, GuanHu Subdistrict,
LongHua District, ShenZhen, P.R. China
Tel / Fax: 86-755-8614 0743/86-755-8601 6661

Table of Contents

1.0 Summary of Test Result 4

2.0 General Description 5

2.1 Product Description 5
2.2 Related Submittal(s) Grants 5
2.3 Test Methodology 5
2.4 Test Facility 5

3.0 System Test Configuration 6

3.1 Justification 6
3.2 EUT Exercising Software 6
3.3 Special Accessories 6
3.4 Equipment Modification 6
3.5 Measurement Uncertainty 7
3.6 Support Equipment List and Description 7

4.0 Emission Results 8

4.1 Radiated Test Results 8
4.1.1 Field Strength Calculation 8
4.1.2 Radiated Emission Configuration Photograph 9
4.1.3 Radiated Emissions 9
4.1.4 Transmitter Spurious Emissions 12

5.0 Equipment Photographs 16

6.0 Product Labelling 16

7.0 Technical Specifications 16

8.0 Instruction Manual 16

9.0 Miscellaneous Information 17

9.1 Bandedge Plot 17
9.2 20dB Bandwidth 20
9.3 Discussion of Pulse Desensitization 22
9.4 Calculation of Average Factor 22
9.5 Emissions Test Procedures 23

10.0 Test Equipment List 25

1.0 Summary of Test Result

Applicant: Shenzhen Xinjike Cross-border E-commerce Co., Ltd.
Applicant Address: D-111,bldg.D,Qingnianchuangyeyuan,No.18 Jianshe E Rd,Qinghua Comm, Longhua St, Longhua Dist, Shenzhen, China
Manufacturer: Besing Technology(Shenzhen) Co., Ltd.
Manufacturer Address: Floor2, ShentongSciencePark, No.47, Kengwei Avenue, Shangwu Community, Shiyan Town, Bao'an District, Shenzhen

MODEL: X08
FCC ID: 2BV3D-X08

Test Specification	Reference	Results
Transmitter Radiated Emission	15.249 &15.209 &15.205	Pass
Band edge	15.249 &15.209 &15.205	Pass
20dB Bandwidth	15.215(c)	Pass

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The equipment under test (EUT) is a True Wireless Earbuds with Bluetooth 6.0 (Single Mode EDR) function operating in 2402-2480MHz. The EUT is powered by lithium battery 3.7V . For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna
Modulation Type: GFSK, π/4-DQPSK and 8-DPSK
Antenna Gain: 1.8dBi Max (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)
Bluetooth Version: 6.0 (Single Mode EDR)

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the True Wireless Earbuds which has Bluetooth function, and related report for FCC SDOC is subjected to report number: 260302011SZN-002.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2020). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst-case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: CN1188).

3.0 System Test Configuration

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2020).

The EUT is powered by lithium battery 3.7V during the test, only the worst data was reported in this report.

All packets DH1, DH3 & DH5 mode in modulation type GFSK, π/4-DQPSK and 8-DPSK were tested and only the worst data was reported in this report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the bottom of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Section 4.

The EUT and transmitting antenna was centered on the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

3.3 Special Accessories

No special accessories used.

3.4 Equipment Modification

Any modifications installed previous to testing by Shenzhen Xinjike Cross-border E-commerce Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

3.6 Support Equipment List and Description

Description	Manufacturer	Remark
USB cable (Provided by Intertek)	Provided by Intertek	unshielded, 0.5m
Adapter (Provided by Intertek)	XIAOMI	MDY-08-EO

4.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

4.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

4.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

FS = RA + AF + CF - AG + PD + AV

Where FS = Field Strength in dBµV/m
RA = Receiver Amplitude (including preamplifier) in dBµV
CF = Cable Attenuation Factor in dB
AF = Antenna Factor in dB/m
AG = Amplifier Gain in dB
PD = Pulse Desensitization in dB
AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

FS = RA + AF + CF - AG + PD + AV

Assume a receiver reading of 62.0 dBµV is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dBµV/m. This value in dBµV/m was converted to its corresponding level in µV/m.

RA = 62.0 dBµV
AF = 7.4 dB/m
CF = 1.6 dB
AG = 29.0 dB
PD = 0 dB
AV = -10 dB
FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 dBµV/m

Level in µV/m = Common Antilogarithm [(42 dBµV/m)/20] = 125.9 µV/m

4.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

4.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission
at
848.841667 MHz

Judgement: Passed by 12.2 dB

TEST PERSONNEL:

Sign on file

Hyman Huang, Engineer
Typed/Printed Name

04 April 2026
Date

Applicant: Shenzhen Xinjike Cross-border E-commerce Co., Ltd.
Date of Test: 04 April 2026 Model: X08
Worst Case Operating Mode: Transmitting

ANT Polarity: Horizontal



Frequency (MHz)	Quasi Peak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit – QPK (dBµV/m)
558.941000	28.5	1000.0	120.000	H	29.1	17.5	46.0
709.776000	31.1	1000.0	120.000	H	31.1	14.9	46.0
848.841667	33.8	1000.0	120.000	H	31.8	12.2	46.0

Remark:
1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBµV/m) = Corr. (dB/m) + Read Level (dBµV)
3. Margin (dB) = Limit Line (dBµV/m) – Level (dBµV/m)

Applicant: Shenzhen Xinjike Cross-border E-commerce Co., Ltd.
Date of Test: 04 April 2026 Model: X08
Worst Case Operating Mode: Transmitting

ANT Polarity: Vertical



Frequency (MHz)	Quasi Peak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit – QPK (dBµV/m)
572.036000	28.7	1000.0	120.000	V	29.0	17.3	46.0
728.400000	31.0	1000.0	120.000	V	31.0	15.0	46.0
999.191667	34.3	1000.0	120.000	V	33.7	19.7	54.0

Remark:
1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dBµV/m) = Corr. (dB/m) + Read Level (dBµV)
3. Margin (dB) = Limit Line (dBµV/m) – Level (dBµV/m)

4.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission
at
9920.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 20.4 dB

TEST PERSONNEL:

Sign on file

Hyman Huang, Engineer
Typed/Printed Name

04 April 2026
Date

Applicant: Shenzhen Xinjike Cross-border E-commerce Co., Ltd.
Date of Test: 04 April 2026 Model: X08
Worst Case Operating Mode: Transmitting

Table 1

Radiated Emissions

(2402MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2402.000	88.5	36.7	28.1	79.9	114.0	-34.1
Horizontal	4804.000	46.8	36.7	35.5	45.6	74.0	-28.4
Horizontal	7206.000	49.2	36.1	36.5	49.6	74.0	-24.4
Horizontal	9608.000	50.0	36.3	38.0	51.7	74.0	-22.3

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2402.000	88.5	36.7	28.1	22.5	57.4	94.0	-36.6
Horizontal	4804.000	46.8	36.7	35.5	22.5	23.1	54.0	-30.9
Horizontal	7206.000	49.2	36.1	36.5	22.5	27.1	54.0	-26.9
Horizontal	9608.000	50.0	36.3	38.0	22.5	29.2	54.0	-24.8

Notes:
1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Applicant: Shenzhen Xinjike Cross-border E-commerce Co., Ltd.
Date of Test: 04 April 2026 Model: X08
Worst Case Operating Mode: Transmitting

Table 2

Radiated Emissions

(2441MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2441.000	86.0	36.7	28.1	77.4	114.0	-36.6
Horizontal	4882.000	44.4	36.7	35.5	43.2	74.0	-30.8
Horizontal	7323.000	47.9	36.1	37.2	49.0	74.0	-25.0
Horizontal	9764.000	52.4	36.2	37.0	53.2	74.0	-20.8

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2441.000	86.0	36.7	28.1	22.5	54.9	94.0	-39.1
Horizontal	4882.000	44.4	36.7	35.5	22.5	20.7	54.0	-33.3
Horizontal	7323.000	47.9	36.1	37.2	22.5	26.5	54.0	-27.5
Horizontal	9764.000	52.4	36.2	37.0	22.5	30.7	54.0	-23.3

Notes:
1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Applicant: Shenzhen Xinjike Cross-border E-commerce Co., Ltd.
Date of Test: 04 April 2026 Model: X08
Worst Case Operating Mode: Transmitting

Table 3

Radiated Emissions

(2480MHz)

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2480.000	78.3	36.7	28.1	69.7	114.0	-44.3
Horizontal	4960.000	43.9	36.7	35.5	42.7	74.0	-31.3
Horizontal	7440.000	48.5	36.1	37.2	49.6	74.0	-24.4
Horizontal	9920.000	51.0	36.3	38.9	53.6	74.0	-20.4

Polarization	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Average Factor (-dB)	Net at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
Horizontal	2480.000	78.3	36.7	28.1	22.5	47.2	94.0	-46.8
Horizontal	4960.000	43.9	36.7	35.5	22.5	20.2	54.0	-33.8
Horizontal	7440.000	48.5	36.1	37.2	22.5	27.1	54.0	-26.9
Horizontal	9920.000	51.0	36.3	38.9	22.5	31.1	54.0	-22.9

Notes:
1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

5.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, 20dB Bandwidth, the test procedure and calculation of factor such as pulse desensitization.

9.1 Bandedge Plot

The test plots are attached as below. From the below plots, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lowest frequency channel (2402MHz):

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

= 79.9 dBµv/m-48.0dB
= 31.9 dBµv/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the bandedge plot

= 57.4 dBµv/m-48.0dB
= 9.4 dBµv/m

(ii) Highest frequency channel (2480MHz):

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

= 69.7 dBµv/m-48.0 dB
= 21.7 dBµv/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the bandedge plot

= 47.2 dBµv/m-48.0 dB
= -0.8 dBµv/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dBµv/m (Peak Limit) and 54dBµv/m (Average Limit).

Hopping function off
Lowest frequency Channel



Highest frequency Channel



Hopping function on
Lowest frequency Channel



Highest frequency Channel



9.2 20dB bandwidth

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered. The test plots are reported as below.







Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4800608 GHz	90.11 dBµV	ndB down	1.2851 MHz
T1		1	2.4794313 GHz	70.48 dBµV	ndB	20.00 dB
T2		1	2.4807164 GHz	70.02 dBµV	Q factor	1929.9

9.3 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 625μs for Bluetooth. With a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

9.4 Calculation of Average Factor

Based on the Bluetooth Specification Version 6.0 (EDR mode) and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = 1 / 133.33 hops/second = 7.5 ms

Time to cycle through all channels = 7.5 x 20 channels = 150 ms

Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)

Worst case dwell time = 7.5 ms

Duty cycle connection factor = 20log10 (7.5ms / 100ms) = -22.5 dB

9.5 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2020.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter up to 1GHz and 1.5 meter above 1GHz in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 9.4.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

9.5 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10 - 2020.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW 3MHz used for fundamental emission).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2025-04-21	2026-04-21
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2025-04-21	2026-04-21
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2025-12-01	2026-12-01
SZ062-10	RF Cable	Bedea	RG 58	--	2025-05-01	2026-05-01
SZ056-08	Signal Analyzer	R&S	FSV 40	101430	2025-12-01	2026-12-01
SZ185-03	EMI Receiver	R&S	ESR7	101975	2025-04-13	2026-04-13
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2024-05-05	2027-05-05
SZ061-13	BiConiLog Antenna	ETS	3142E	00166158	2025-05-29	2028-05-29
SZ061-09	Double-Ridged Waveguide Horn Antenna	ETS	3115	00092347	2025-10-20	2028-10-20
SZ181-08	Microwave System Amplifier	Agilent	83017A	MY57280108	2025-07-30	2026-07-30
SZ188-05	Anechoic Chamber	ETS	FACT 3-2.0	CT001880-Q1391	2025-06-18	2028-06-18
SZ062-35	RF Cable	RADIALL	A50-3.5M 3.5M-8M	-	2025-09-30	2026-09-30
SZ062-30	RF Cable	RADIALL	A50-3.5M 3.5M-4.5M	-	2025-09-30	2026-09-30
SZ062-31	RF Cable	RADIALL	A50-3.5M 3.5M-1M	-	2025-09-30	2026-09-30
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	015	2024-04-23	2027-04-23

********** End of Report**********