



FCC RADIO TEST REPORT

FCC ID : 2BV7P-RT710L0
Equipment : Rugged Tablet PC
Brand Name : Honeywell
Model Name : RT710-L0
Applicant : HAND HELD PRODUCTS, INC.
9680 Old Bailes Road, Fort Mill, SC
29707, USA
Manufacturer : HAND HELD PRODUCTS, INC.
9680 Old Bailes Road, Fort Mill, SC
29707, USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jul. 16, 2026 and testing was performed from Jul. 18, 2026 to Aug. 03, 2026. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

1	General Description	5
1.1	Product Feature of Equipment Under Test.....	5
1.2	Modification of EUT	8
1.3	Testing Location	8
1.4	Applicable Standards.....	8
2	Test Configuration of Equipment Under Test	9
2.1	Carrier Frequency and Channel	9
2.2	Test Mode.....	10
2.3	Connection Diagram of Test System.....	11
2.4	Support Unit used in test configuration and system	11
2.5	EUT Operation Test Setup	12
2.6	Measurement Results Explanation Example.....	12
3	Test Result	13
3.1	6dB and 99% Bandwidth Measurement	13
3.2	Output Power Measurement.....	14
3.3	Power Spectral Density Measurement	16
3.4	Conducted Band Edges and Spurious Emission Measurement	18
3.5	Radiated Band Edges and Spurious Emission Measurement	19
3.6	AC Conducted Emission Measurement.....	24
3.7	Antenna Requirements	26
4	List of Measuring Equipment.....	27
5	Measurement Uncertainty	28
Appendix A. Conducted Test Results		
Appendix B. AC Conducted Emission Test Result		
Appendix C. Radiated Spurious Emission		
Appendix D. Duty Cycle Plots		
Appendix E. Setup Photographs		



History of this test report

Report No.	Version	Description	Issue Date
FR670105B	01	Initial issue of report	Aug. 21, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	-	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Lili Lu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
General Specs	Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax/be, Wi-Fi 5GHz 802.11a/n/ac/ax/be, Wi-Fi 6GHz 802.11a/ax/be and NFC.
Sample 1	Sku1
Sample 2	Sku4
Sample 3	Sku2
Sample 4	Sku9
Sample 5	Sku5
Sample 6	Sku8
Sample 7	Sku3
Sample 8	Sku6
Sample 9	Sku7
Maximum Output Power to antenna	802.11b : 14.47 dBm (0.0280 W) 802.11g : 14.82 dBm (0.0303 W) 802.11n HT20 : 14.78 dBm (0.0301 W) 802.11n HT40 : 14.82 dBm (0.0303 W) 802.11ax HE20 : 14.80 dBm (0.0302 W) 802.11ax HE40 : 14.82 dBm (0.0303 W) 802.11be EHT20 : 14.84 dBm (0.0305 W) 802.11be EHT40 : 14.83 dBm (0.0304 W)
99% Occupied Bandwidth	802.11b : 13.34MHz 802.11g : 17.46MHz 802.11be EHT20 : 19.18MHz 802.11be EHT40 : 38.27MHz
Antenna Type	<Ant.8>: LDS Antenna <Ant.9>: LDS Antenna
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ax : OFDMA (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) 802.11be: OFDMA (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM / 4096QAM)

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	<ANT.8>:0 <ANT.9>:0.5

Remark:

1. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.
2. The EUT supports STBC and CDD mode, Base on CDD mode with power setting equal or higher than STBC mode, so CDD mode is chosen to perform all RF test and cover STBC mode.
3. MIMO Ant. 8+9 Directional Gain is a calculated result from MIMO Ant. 8 and MIMO Ant. 9. The formula used in calculation is documented in section 1.1.1.
4. All test items were performed with Sample 1.

EUT Information List	
SN	Performed Test Item
26168X00AB	Conducted
26168X0061	Conducted Emission
26168X0063 26168X00A8	Radiated Spurious Emission

1.1.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;

G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

			DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
	Ant 8 (dBi)	Ant 9 (dBi)				
2.4GHz	0.00	0.50	0.50	3.26	0.00	0.00

Calculation example:

If a device has two antenna, $G_{ANT1} = 3.0$ dBi; $G_{ANT2} = 3.2$ dBi

Directional gain of power measurement = $\max(3.0, 3.2) + 0 = 3.2$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \{ [10^{(3.00 \text{ dBi} / 20)} + 10^{(3.20 \text{ dBi} / 20)}]^2 / 2 \}$$

$$= 6.11 \text{ dBi}$$

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)

Power and PSD limit reduction = Composite gain – 6dBi, (min = 0)



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. The Conduction test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode

This device support 26/52/106-tone RU

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2018.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel and 484-tone RU is covered by 40MHz channel.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n and 802.11ac mode is smaller than 802.11ax mode, so all other conducted and radiated test is covered by 802.11ax mode.

The final test modes include the worst data rates for each modulation shown in the table below.


MIMO Mode

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.

Test Cases	
AC Conducted Emission	Mode 1 :BT Link + WLAN Link(2.4G) + Charging from adaptor
Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Jlab Jbund Mini	2AHYV	FCC DoC	N/A	N/A
2.	WLAN AP	ASUS	GT-AXE11000	FCC DoC	N/A	Unshielded, 1.8m
3.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
4.	iPod Earphone	Apple	A1285	Doc	N/A	UnShielded, 1.2m



2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.33 dB and 20 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.33 + 20 = 24.33 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

<CDD Modes>

1. For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.2 PKPM1
2. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
3. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.
6. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power (Reporting Only)

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2020 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01:

Method (a): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.


Method (b): Measure and sum spectral maxima across the outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

Method (c): Measure and add $10 \log(N_{ANT})$ dB, where N_{ANT} is the number of outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The quantity $10 \log(N_{ANT})$ dB is added to each spectrum value before comparing to the emission limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
6. The frequency range from 150 kHz to 30 MHz is scanned.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9 kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 02, 2026	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 16, 2025	Aug. 02, 2026	Dec. 15, 2026	Conduction (CO05-HY)
Hygrometer	TECEPEL	DTM-303A	TP210031	N/A	Jun. 15, 2026	Aug. 02, 2026	Jun. 14, 2027	Conduction (CO05-HY)
Two-Line V-Network	Rohde & Schwarz	ENV 216 +EMCI-EXP-US S	100080+N-021	N/A	Apr. 22, 2026	Aug. 02, 2026	Apr. 21, 2027	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Aug. 02, 2026	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00373	N/A	Oct. 20, 2025	Aug. 02, 2026	Oct. 19, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 14, 2025	Aug. 02, 2026	Oct. 13, 2026	Conduction (CO05-HY)
Hygrometer	TECEPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Jul. 24, 2026 ~ Aug. 03, 2026	Nov. 03, 2026	Conducted (TH05-HY)
USB RF Power Sensor	DARE	RPR3006W	17I00015SNO37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Jul. 24, 2026 ~ Aug. 03, 2026	Nov. 13, 2026	Conducted (TH05-HY)
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Nov. 12, 2025	Jul. 24, 2026 ~ Aug. 03, 2026	Nov. 11, 2026	Conducted (TH05-HY)
Switch Control Mainframe	EM Electronics	EMSW18SE	SW191204 (BOX8)	N/A	Dec. 29, 2025	Jul. 24, 2026 ~ Aug. 03, 2026	Dec. 28, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Jul. 24, 2026 ~ Aug. 03, 2026	N/A	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9kHz~30MHz	Dec. 21, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Dec. 20, 2026	Radiation (03CH22-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Nov. 26, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Nov. 25, 2026	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 12, 2026	Jul. 18, 2026 ~ Jul. 29, 2026	Jul. 11, 2027	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18EN	1GHz~18GHz	May. 20, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	May. 19, 2026	Radiation (03CH22-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	1230	18GHz~40GHz	Nov. 05, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Nov. 04, 2026	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 26, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Sep. 25, 2026	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060872	18-40GHz	Dec. 02, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Dec. 01, 2026	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Sep. 22, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Sep. 21, 2026	Radiation (03CH22-HY)
Hygrometer	TECEPEL	DTM-303A	TP211469	N/A	Dec. 15, 2025	Jul. 18, 2026 ~ Jul. 29, 2026	Dec. 14, 2026	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 18, 2026 ~ Jul. 29, 2026	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 18, 2026 ~ Jul. 29, 2026	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 18, 2026 ~ Jul. 29, 2026	N/A	Radiation (03CH22-HY)
Software	Audix	E3	RK-002347	N/A	N/A	Jul. 18, 2026 ~ Jul. 29, 2026	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 04, 2026	Jul. 18, 2026 ~ Jul. 29, 2026	Mar. 03, 2027	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER/EMCI	SUCOFLEX 102/EMCI01Y-KM-KM-500/EMCI01Y-KM-KM-9000	804611/2,240914, 25043351,25043350	30MHz~40GHz	May. 18, 2026	Jul. 18, 2026 ~ Jul. 29, 2026	May. 17, 2027	Radiation (03CH22-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7dB
--	-------

A1. Conducted Test Results

Test Engineer:	Eason Huang/Derek Hsu	Temperature:	21~25	°C
Test Date:	2026/07/24~2026/08/03	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band MIMO										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant8	Ant9	Ant8	Ant9		
11b	1Mbps	2	1	2412	13.18	13.20	8.10	8.10	0.50	Pass
11b	1Mbps	2	6	2437	13.18	13.20	8.10	8.11	0.50	Pass
11b	1Mbps	2	11	2462	13.28	13.34	8.11	8.12	0.50	Pass
11g	6Mbps	2	1	2412	17.38	17.09	16.36	16.41	0.50	Pass
11g	6Mbps	2	6	2437	17.42	17.09	16.37	16.44	0.50	Pass
11g	6Mbps	2	11	2462	17.46	17.16	16.35	16.46	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	
11b	1Mbps	2	1	2412	10.90	11.60	14.27	30.00		0.50		14.77		36.00		Pass
11b	1Mbps	2	6	2437	11.10	11.80	14.47	30.00		0.50		14.97		36.00		Pass
11b	1Mbps	2	11	2462	11.10	11.60	14.37	30.00		0.50		14.87		36.00		Pass
11g	6Mbps	2	1	2412	11.79	11.50	14.66	30.00		0.50		15.16		36.00		Pass
11g	6Mbps	2	6	2437	11.78	11.60	14.70	30.00		0.50		15.20		36.00		Pass
11g	6Mbps	2	11	2462	11.99	11.62	14.82	30.00		0.50		15.32		36.00		Pass
HT20	MCS0	2	1	2412	11.67	11.40	14.55	30.00		0.50		15.05		36.00		Pass
HT20	MCS0	2	6	2437	11.65	11.55	14.61	30.00		0.50		15.11		36.00		Pass
HT20	MCS0	2	11	2462	11.97	11.57	14.78	30.00		0.50		15.28		36.00		Pass
HT40	MCS0	2	3	2422	11.75	11.48	14.63	30.00		0.50		15.13		36.00		Pass
HT40	MCS0	2	6	2437	11.80	11.59	14.71	30.00		0.50		15.21		36.00		Pass
HT40	MCS0	2	9	2452	11.98	11.63	14.82	30.00		0.50		15.32		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band MIMO												
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant8	Ant9	Worse + 3.01	Ant8	Ant9	Ant8	Ant9	
11b	1Mbps	2	1	2412	-12.47	-13.06	-9.46	3.26		8.00		Pass
11b	1Mbps	2	6	2437	-13.58	-13.25	-10.24	3.26		8.00		Pass
11b	1Mbps	2	11	2462	-12.58	-12.91	-9.57	3.26		8.00		Pass
11g	6Mbps	2	1	2412	-15.24	-15.41	-12.23	3.26		8.00		Pass
11g	6Mbps	2	6	2437	-15.39	-15.05	-12.04	3.26		8.00		Pass
11g	6Mbps	2	11	2462	-15.17	-15.69	-12.16	3.26		8.00		Pass

Measured power density (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																	
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	
HE20	MCS0	2	1	2412	Full	11.69	11.49	14.60	30.00		0.50		15.10		36.00		Pass
HE20	MCS0	2	1	2412	26/0	2.09	1.83	4.97	30.00		0.50		5.47		36.00		Pass
HE20	MCS0	2	1	2412	52/37	4.58	4.39	7.50	30.00		0.50		8.00		36.00		Pass
HE20	MCS0	2	1	2412	106/53	7.59	7.30	10.46	30.00		0.50		10.96		36.00		Pass
HE20	MCS0	2	6	2437	Full	11.65	11.53	14.60	30.00		0.50		15.10		36.00		Pass
HE20	MCS0	2	6	2437	26/4	2.27	1.89	5.09	30.00		0.50		5.59		36.00		Pass
HE20	MCS0	2	6	2437	52/38	4.72	4.02	7.39	30.00		0.50		7.89		36.00		Pass
HE20	MCS0	2	6	2437	106/53	7.74	7.20	10.49	30.00		0.50		10.99		36.00		Pass
HE20	MCS0	2	11	2462	Full	11.98	11.59	14.80	30.00		0.50		15.30		36.00		Pass
HE20	MCS0	2	11	2462	26/8	2.72	2.00	5.39	30.00		0.50		5.89		36.00		Pass
HE20	MCS0	2	11	2462	52/40	5.09	4.49	7.81	30.00		0.50		8.31		36.00		Pass
HE20	MCS0	2	11	2462	106/54	7.79	7.60	10.71	30.00		0.50		11.21		36.00		Pass
HE40	MCS0	2	3	2422	Full	11.65	11.40	14.54	30.00		0.50		15.04		36.00		Pass
HE40	MCS0	2	6	2437	Full	11.74	11.54	14.65	30.00		0.50		15.15		36.00		Pass
HE40	MCS0	2	9	2452	Full	11.98	11.63	14.82	30.00		0.50		15.32		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band MIMO													
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
						Ant8	Ant9	Worse + 3.01	Ant8	Ant9	Ant8	Ant9	
HE20	MCS0	2	1	2412	Full	-15.51	-15.66	-12.50	3.26		8.00		Pass
HE20	MCS0	2	1	2412	26/0	-15.82	-16.40	-12.81	3.26		8.00		Pass
HE20	MCS0	2	1	2412	52/37	-15.71	-15.73	-12.70	3.26		8.00		Pass
HE20	MCS0	2	1	2412	106/53	-15.69	-15.96	-12.68	3.26		8.00		Pass
HE20	MCS0	2	6	2437	Full	-15.28	-15.75	-12.27	3.26		8.00		Pass
HE20	MCS0	2	6	2437	26/4	-16.06	-16.47	-13.05	3.26		8.00		Pass
HE20	MCS0	2	6	2437	52/38	-15.73	-15.91	-12.72	3.26		8.00		Pass
HE20	MCS0	2	6	2437	106/53	-15.60	-16.22	-12.59	3.26		8.00		Pass
HE20	MCS0	2	11	2462	Full	-15.02	-15.58	-12.01	3.26		8.00		Pass
HE20	MCS0	2	11	2462	26/8	-15.48	-16.12	-12.47	3.26		8.00		Pass
HE20	MCS0	2	11	2462	52/40	-16.43	-16.88	-13.42	3.26		8.00		Pass
HE20	MCS0	2	11	2462	106/54	-15.33	-15.43	-12.32	3.26		8.00		Pass
HE40	MCS0	2	3	2422	Full	-17.73	-18.10	-14.72	3.26		8.00		Pass
HE40	MCS0	2	6	2437	Full	-17.29	-17.54	-14.28	3.26		8.00		Pass
HE40	MCS0	2	9	2452	Full	-17.27	-17.83	-14.26	3.26		8.00		Pass

Measured power density (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band MIMO											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config.	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
						Ant8	Ant9	Ant8	Ant9		
EHT20	MCS0	2	1	2412	Full	19.17	19.15	18.78	18.92	0.50	Pass
EHT20	MCS0	2	6	2437	Full	19.17	19.16	18.88	18.86	0.50	Pass
EHT20	MCS0	2	11	2462	Full	19.18	19.17	18.90	18.88	0.50	Pass
EHT40	MCS0	2	3	2422	Full	38.19	38.25	37.76	37.99	0.50	Pass
EHT40	MCS0	2	6	2437	Full	38.27	38.25	37.86	37.75	0.50	Pass
EHT40	MCS0	2	9	2452	Full	38.25	38.21	37.83	37.75	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																	
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant8	Ant9	SUM	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	Ant8	Ant9	
EHT20	MCS0	2	1	2412	Full	11.70	11.50	14.61	30.00		0.50		15.11		36.00		Pass
EHT20	MCS0	2	1	2412	26/0	2.10	1.84	4.98	30.00		0.50		5.48		36.00		Pass
EHT20	MCS0	2	1	2412	52/37	4.59	4.40	7.51	30.00		0.50		8.01		36.00		Pass
EHT20	MCS0	2	1	2412	106/53	7.60	7.31	10.47	30.00		0.50		10.97		36.00		Pass
EHT20	MCS0	2	6	2437	Full	11.79	11.62	14.72	30.00		0.50		15.22		36.00		Pass
EHT20	MCS0	2	6	2437	26/4	2.28	1.90	5.10	30.00		0.50		5.60		36.00		Pass
EHT20	MCS0	2	6	2437	52/38	5.01	4.52	7.78	30.00		0.50		8.28		36.00		Pass
EHT20	MCS0	2	6	2437	106/53	7.90	7.21	10.58	30.00		0.50		11.08		36.00		Pass
EHT20	MCS0	2	11	2462	Full	11.99	11.67	14.84	30.00		0.50		15.34		36.00		Pass
EHT20	MCS0	2	11	2462	26/8	2.73	2.15	5.46	30.00		0.50		5.96		36.00		Pass
EHT20	MCS0	2	11	2462	52/40	5.10	4.60	7.87	30.00		0.50		8.37		36.00		Pass
EHT20	MCS0	2	11	2462	106/54	7.90	7.80	10.86	30.00		0.50		11.36		36.00		Pass
EHT40	MCS0	2	3	2422	Full	11.77	11.49	14.64	30.00		0.50		15.14		36.00		Pass
EHT40	MCS0	2	6	2437	Full	11.81	11.63	14.73	30.00		0.50		15.23		36.00		Pass
EHT40	MCS0	2	9	2452	Full	11.99	11.64	14.83	30.00		0.50		15.33		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density


2.4GHz Band MIMO													
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
						Ant8	Ant9	Worse + 3.01	Ant8	Ant9	Ant8	Ant9	
EHT20	MCS0	2	1	2412	Full	-15.09	-15.20	-12.08	3.26		8.00		Pass
EHT20	MCS0	2	1	2412	26/0	-15.43	-16.11	-12.42	3.26		8.00		Pass
EHT20	MCS0	2	1	2412	52/37	-15.31	-15.52	-12.30	3.26		8.00		Pass
EHT20	MCS0	2	1	2412	106/53	-15.20	-15.64	-12.19	3.26		8.00		Pass
EHT20	MCS0	2	6	2437	Full	-15.46	-15.11	-12.10	3.26		8.00		Pass
EHT20	MCS0	2	6	2437	26/4	-15.60	-15.91	-12.59	3.26		8.00		Pass
EHT20	MCS0	2	6	2437	52/38	-15.53	-15.99	-12.52	3.26		8.00		Pass
EHT20	MCS0	2	6	2437	106/53	-15.28	-15.48	-12.27	3.26		8.00		Pass
EHT20	MCS0	2	11	2462	Full	-14.79	-15.46	-11.78	3.26		8.00		Pass
EHT20	MCS0	2	11	2462	26/8	-15.09	-15.59	-12.08	3.26		8.00		Pass
EHT20	MCS0	2	11	2462	52/40	-15.81	-16.44	-12.80	3.26		8.00		Pass
EHT20	MCS0	2	11	2462	106/54	-15.06	-15.34	-12.05	3.26		8.00		Pass
EHT40	MCS0	2	3	2422	Full	-17.70	-17.87	-14.69	3.26		8.00		Pass
EHT40	MCS0	2	6	2437	Full	-17.19	-17.54	-14.18	3.26		8.00		Pass
EHT40	MCS0	2	9	2452	Full	-17.23	-17.50	-14.22	3.26		8.00		Pass

Measured power density (dBm) has offset with cable loss.

**6dB and 99% Occupied Bandwidth**

MIMO <Ant. 8+9>


<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11g>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11be EHT20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11be EHT40>





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

**Power Spectral Density(dBm/3kHz)**

MIMO <Ant. 8+9>

<802.11b>


Maximum Power Density Plot (dBm/3kHz)**MIMO Ant. 8****MIMO Ant. 9**




<802.11g>

Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9






<802.11ax HE20>






26RU Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9






52RU Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9






106RU Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9






<802.11ax HE40>






<802.11be EHT20>






26RU Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9






52RU Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9






106RU Maximum Power Density Plot (dBm/3kHz)

MIMO Ant. 8




MIMO Ant. 9







<802.11be EHT40>



**Band Edges and Spurious Emission**

Number of TX = 2, Ant. 8 (Measured)









Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot




Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz









Test Mode : 802.11g

Test Channel : 11


100kHz PSD reference Level



Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz

