

FCC PART 15 SUBPART C

Car wireless charging bracket

MODEL No.:H6

FCC ID: 2BV9I-H6

REPORT NO.: SZNTT26019601E1-1

ISSUE DATE: May.25, 2026

Prepared for

Shenzhen hangku industry Co., Ltd

Exit 1, 5th floor, Building 24, Lianchuang Science Park Phase II, No.23
Bulan Road, Longgang District, Shenzhen,China

Prepared by

Shenzhen NTT Testing Technology Co.,Ltd.

1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang
Industrial Park, No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district,
Bao'an District, Shenzhen City, Guangdong, China

TABLE OF CONTENT

Test Report Description	Page
1. SUMMARY OF TEST RESULTS.....	5
2. GENERAL INFORMATION	6
2.1. Description of Device (EUT)	6
2.2. Description of Support Units	6
2.3. Independent Operation Modes	7
2.4. Test Mode	7
2.5. Description of Test Facility	8
2.6. Measurement Uncertainty.....	8
3. MEASURING DEVICE AND TEST EQUIPMENT	9
4. 20DB BANDWIDTH	11
4.1. Test Procedure.....	11
4.2. Test Setup	11
4.3. Test Results	11
5. POWER LINE CONDUCTED EMISSION MEASUREMENT	13
5.1. Block Diagram of Test Setup	13
5.2. Limits.....	13
5.3. Test Procedure.....	13
5.4. Measuring Results	14
6. RADIATED EMISSION TEST.....	17
6.1. Measurement Procedure	17
6.2. Test SET-UP (Block Diagram of Configuration).....	17
6.3. Radiated Emission Limit	18
6.4. Measurement Result.....	20
7. TEST PHOTOGRAPHS AND EUT PHOTOGRAPHS	24

TEST REPORT DESCRIPTION

Applicant : Shenzhen hangku industry Co., Ltd
 Address : Exit 1, 5th floor, Building 24, Lianchuang Science Park Phase II, No.23 Bulan Road, Longgang District, Shenzhen,China
 Manufacturer : Shenzhen hangku industry Co., Ltd
 Address : Exit 1, 5th floor, Building 24, Lianchuang Science Park Phase II, No.23 Bulan Road, Longgang District, Shenzhen,China
 EUT : Car wireless charging bracket
 Model Name : H6
 Trademark : /

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by Shenzhen NTT Testing Technology Co.,Ltd.The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2020+Cor 1+2023 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15C

The test results of this report relate only to the tested sample identified in this report.

Prepared by(Test Engineer): Cindy Qin	
Reviewer(Supervisor): Ken Wu	
Approved(Manager): Abel Yu	 

Modified Information

Version	Report No.	Revision Data	Summary
Ver.1.0	SZNTT26019601E1-1	May.25,2026	Original Version

1. SUMMARY OF TEST RESULTS

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT : Car wireless charging bracket

Model Number : H6,H6-S,H6-P,H6-M,H6-X

Different : /

Model different : /

Power Rating : Input:
Type-C: DC5V/3A, DC9V/3A
Output: Wireless: 5W/7.5W/10W/15W (Max)

Operation : 111-205 KHz
Frequency for WPT

Modulation : MSK

Antenna Type: : Coil Antenna

Date of Received : May.14, 2026

Date of Test : May.14, 2026 to May.25, 2026

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Car wireless charging bracket	N/A	H6	N/A	EUT
E-2	Phone	SAMSUNG	S24	N/A	Auxiliary
E-3	Adapter	N/A	HW-090200CH0	N/A	Auxiliary

Note: (1)The support equipment was authorized by Declaration of Confirmation.
(2)For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.3. Independent Operation Modes

Pretest Test Mode	Description of Mode
1	Adapter+WPT Mode (Phone(15W))
2	Adapter+WPT Mode (Phone(10W))
3	Adapter+WPT Mode (Phone(7.5W))
4	Adapter+WPT Mode (Phone(5W))

2.4. Test Mode

Test Items	Final Test Mode
Conducted Emissions	Mode 1
Radiated Emissions	Mode 1
20dB bandwidth	Mode 1
Remark: All the modes have tested and recorded the worst mode in the report	

2.5. Description of Test Facility

Site Description

Designation Number: CN3446
 Test Firm Registration Number: 129414
 Accredited by ANAB, Dec. 19, 2025
 The Certificate Registration Number is AT-3446

Name of Firm: Shenzhen NTT Testing Technology Co.,Ltd.

Site Location: 1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang Industrial Park, No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district, Bao 'an District, Shenzhen City, Guangdong, China

2.6. Measurement Uncertainty

Item	MU	Remark
Uncertainty for radio frequency	$\pm 7 \times 10^{-8}$	
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$	
Radiated Emission(9KHz~30MHz)	$\pm 4.51\text{dB}$	
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$	
Radiated Emission(1GHz~6GHz)	$\pm 3.92\text{dB}$	
Radiated Emission(6GHz~18GHz)	$\pm 4.33\text{dB}$	
Radiated Emission(18GHz~40GHz)	$\pm 3.38\text{dB}$	
Uncertainty for conducted RF Power	$\pm 0.20\text{dB}$	
Conducted spurious emissions	$\pm 0.24\text{dB}$	
Uncertainty for temperature	0.6°C	
Uncertainty for humidity	1%	
Bandwidth	$\pm 1.5 \times 10^{-6}$	
Time	$\pm 2\%$	
Duty Cycle	$\pm 2\%$	
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%		

3. MEASURING DEVICE AND TEST EQUIPMENT

Conducted Test Site

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	HSRCE944	/	HTEC	2025/4/30	2028/4/29
EMI Test Receiver	ESPI	/	RS	2025/9/8	2026/9/7
LISN	NNLK 8129	00603	Schwarzbeck	2025/9/8	2026/9/7
LISN	NNHV 8123-400	00694	Schwarzbeck	2025/9/8	2026/9/7
LISN	NNHV 8123-400	00680	Schwarzbeck	2025/9/8	2026/9/7
Cable	RG223-1500MM	NA	RG	2025/9/8	2026/9/7

Radiated Test Site(Below 1G and Above 1G)&RF Test Site

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2025/7/24	2028/7/23
EMI Test Receiver	ESCI	101018	RS	2025/9/8	2026/9/7
Amplifier (30MHz-1GHz)	BBV 9718D	00042	SCHWARZBECK	2025/9/8	2026/9/7
Bilog Antenna (30MHz-1GHz)	VULB9168	1858	SCHWARZBECK	2025/9/9	2026/9/8
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHWARZBECK	2025/9/9	2026/9/8
Preamplifier (1GHz-18GHz)	BBV 9718D	0024	SCHWARZBECK	2025/9/8	2026/9/7
Spectrum Analyzer (10Hz-40GHz)	FSV 40	100952	Rohde & Schwarz	2025/9/8	2026/9/7
Preamplifier (18GHz-40GHz)	BBV 9721	0056	SCHWARZBECK	2025/9/8	2026/9/7
Double Ridge Guide Horn Antenna (18GHz-40GHz)	SAS-574	588	A.H.System	2025/9/8	2026/9/7
Loop Antenna (9KHz-30MHz)	FMZB1519B	014	SCHWARZBECK	2025/9/8	2026/9/7
Amplifier (9KHz-30MHz)	CVP 9222 C	00109	SCHWARZBECK	2025/9/8	2026/9/7

MXG Signal Analyzer	N9020A	MY50510202	Agilent	2025/9/8	2026/9/7
MXG Vector Signal Generator	N5182A	MY50140020	Agilent	2025/9/8	2026/9/7
MXG Analog Signal Generator	N5181A	MY47420919	Agilent	2025/9/8	2026/9/7
Power Sensor	TR1029-2	512364	Techoy	2025/9/8	2026/9/7
RF Swith	TR1029-1	512364	Techoy	2025/9/8	2026/9/7
Cable	DA800-4000MM	NA	DA	2025/9/8	2026/9/7
Cable	DA800-11000MM	NA	DA	2025/9/8	2026/9/7

Test software

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ-EMC	Ver.EMC-CON 3A1.1+
2	EMC radiation test system	FALA	EZ-EMC	Ver.FA-03A2 RE+
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

4. 20DB BANDWIDTH

4.1. Test Procedure

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1-5%OBW.

Set the video bandwidth (VBW) =3RBW.

Set Span= approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

Set Detector = Peak.


Set Trace mode = Max hold.

Set Sweep = auto couple.

Measure and record the results in the test report.


Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 100 Hz to perform the occupied bandwidth test.

4.2. Test Setup



4.3. Test Results


Frequency (KHz)	20dB bandwidth (Hz)	99% bandwidth (Hz)	Result
125	247	210	Pass



Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 100 Hz to perform the occupied bandwidth test.

5. POWER LINE CONDUCTED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup



LISN: Line Impedance Stabilization Network

AE: Associated equipment

EUT: Equipment under test

5.2. Limits

FCC Part 15.207

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50 ~ 5.00	56.0	46.0
5.00 ~ 30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

5.3. Test Procedure

The EUT was placed on a desk 0.8 m height from the metal ground plane and 0.4 m from the conducting wall of the shielding room and it was kept at least 0.8 m from any other grounded conducting surface. The size of the table will nominally be 1.5 m x1.0 m.

The rear of the arrangement shall be flush with the back of the supporting tabletop unless that would not be possible or typical of normal use.

All units of equipment forming the system under test (includes the EUT as well as connected peripherals and associated equipment or devices) shall be arranged such that a nominal 0.1 m separation is achieved between the neighboring units.

Connect EUT to the power mains through a line impedance stabilization network (LISN). Where the mains cable supplied by the manufacturer is longer than 1 m, the excess should be folded at the

centre into a bundle no longer than 0.4 m, so that its length is shortened to 1 m.

All the support units are connecting to the other LISN.

The LISN provides 50 ohm coupling impedance for the measuring instrument.

Both sides of AC line were checked for maximum conducted interference.

The frequency range from 150 kHz to 30 MHz was sweep.

Set the test-receiver system to quasi peak detect function and average detect function, and to measure the conducted emissions values.

Test results were obtained from the following equation:


Emission Level (dB μ V) = LISN Factor (dB) + Cable Loss (dB) + Reading (dB μ V)

Margin (dB) = Emission Level (dB μ V) - Limit (dB μ V)

5.4. Measuring Results

PASS.

EUT:	Car wireless charging bracket	Model Name:	H6
Test Mode:	Wireless charging	Phase:	L
Test Voltage:	AC120V/60Hz		




Remark:

1. Factor = Insertion Loss + Cable Loss + Pulse limit.
2. '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1539	48.79	10.16	58.95	65.79	-6.84	peak	P
2	0.1539	24.96	10.16	35.12	55.79	-20.67	AVG	P
3	0.1776	45.88	10.14	56.02	64.60	-8.58	peak	P
4	0.1776	26.95	10.14	37.09	54.60	-17.51	AVG	P
5	3.0339	35.42	10.29	45.71	56.00	-10.29	peak	P
6	3.0339	33.21	10.29	43.50	46.00	-2.50	AVG	P
7	3.2740	36.21	10.28	46.49	56.00	-9.51	peak	P
8 *	3.2740	34.80	10.28	45.08	46.00	-0.92	AVG	P
9	3.3740	34.84	10.28	45.12	56.00	-10.88	peak	P
10	3.3740	32.92	10.28	43.20	46.00	-2.80	AVG	P
11	3.6819	34.10	10.27	44.37	56.00	-11.63	peak	P
12	3.6819	31.94	10.27	42.21	46.00	-3.79	AVG	P

EUT:	Car wireless charging bracket	Model Name:	H6
Test Mode:	Wireless charging	Phase:	N
Test Voltage:	AC120V/60Hz		



Remark:

- Factor = Insertion Loss + Cable Loss + Pulse limit.
- '*' means the worst case

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1737	47.31	10.14	57.45	64.78	-7.33	peak	P
2	0.1737	27.73	10.14	37.87	54.78	-16.91	AVG	P
3	0.1819	47.18	10.13	57.31	64.40	-7.09	peak	P
4	0.1819	27.24	10.13	37.37	54.40	-17.03	AVG	P
5	3.0178	33.27	10.29	43.56	56.00	-12.44	peak	P
6	3.0178	32.35	10.29	42.64	46.00	-3.36	AVG	P
7	3.1619	30.68	10.29	40.97	56.00	-15.03	peak	P
8	3.1819	25.82	10.29	36.11	46.00	-9.89	AVG	P
9	3.3900	35.09	10.28	45.37	56.00	-10.63	peak	P
10 *	3.3900	33.25	10.28	43.53	46.00	-2.47	AVG	P
11	14.7140	20.32	25.13	45.45	60.00	-14.55	peak	P
12	14.7140	13.41	25.13	38.54	50.00	-11.46	AVG	P


6. RADIATED EMISSION TEST

6.1. Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.
5. Use the following receiver/spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW=200Hz for 9KHz to 150KHz,
RBW=9kHz for 150KHz to 30MHz,
RBW=120KHz for 30MHz to 1GHz
VBW $\geq 3 \times$ RBW
Sweep = auto
Detector function = QP
Trace = max hold

6.2. Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



6.3. Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation Frequency tion at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	$2400 / F(\text{KHz})$	300m	$10000 * 2400/F(\text{KHz})$	$20\log 2400/F(\text{KHz}) + 80$
0.490 – 1.705	$24000 / F(\text{KHz})$	30m	$100 * 24000/F(\text{KHz})$	$20\log 24000/F(\text{KHz}) + 40$
1.705 – 30.00	30	30m	$100 * 30$	$20\log 30 + 40$
30.0 – 88.0	100	3m	100	$20\log 100$
88.0 – 216.0	150	3m	150	$20\log 150$
216.0 – 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.4.Measurement Result


Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40


9 kHz~30 MHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Pol.	Coplanar
Test Voltage :	AC120V/60Hz	Mode:	Mode 1--125KHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0461	51.32	25.64	76.96	114.35	-37.39	QP
2	0.0691	53.05	23.93	76.98	111.07	-34.09	QP
3 *	0.1252	55.71	21.57	77.28	106.26	-28.98	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Pol.	Coaxial
Test Voltage :	AC120V/60Hz	Mode:	Mode 1--125KHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.4786	26.16	20.92	47.08	94.02	-46.94	QP
2	0.5047	28.50	20.88	49.38	73.54	-24.16	QP
3	0.5523	28.79	20.92	49.71	72.76	-23.05	QP
4 *	0.6238	29.72	20.98	50.70	71.70	-21.00	QP
5	9.4015	14.85	24.22	39.07	69.54	-30.47	QP

Note:

Pre-scan the data of both directions, and the report will only display the data of the worst mode.

Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level- Limit.


30MHz-1GHz:



Shenzhen NTT Testing Technology Co.,Ltd.


Report No.:SZNTT26019601E1-1

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC120V/60Hz	Mode:	Model 1



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna	Verdict
1	157.038	30.15	-12.97	43.5	13.35	157.038	Horizontal	Pass
2	294.016	43.74	-7.47	46.0	2.26	294.016	Horizontal	Pass
3	320.685	41.07	-7.30	46.0	4.93	320.685	Horizontal	Pass
4	355.596	37.57	-4.80	46.0	8.43	355.596	Horizontal	Pass
5	809.928	32.09	0.85	46.0	13.91	809.928	Horizontal	Pass
6	910.782	35.63	2.64	46.0	10.37	910.782	Horizontal	Pass

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Vertical
Test Voltage:	AC120V/60Hz	Mode:	Model 1



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna	Verdict
1	30.485	31.64	-10.39	40.0	8.36	Peak	Vertical	Pass
2	34.849	30.58	-9.88	40.0	9.42	Peak	Vertical	Pass
3	74.366	29.80	-12.43	40.0	10.20	Peak	Vertical	Pass
4	157.038	31.47	-12.97	43.5	12.03	Peak	Vertical	Pass
5	286.016	30.21	-7.87	46.0	15.79	Peak	Vertical	Pass
6	370.385	31.01	-5.00	46.0	14.99	Peak	Vertical	Pass

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.

7. TEST PHOTOGRAPHS AND EUT PHOTOGRAPHS

Please the attachment for details.

-----The end-----