

RF TEST REPORT

For

Guangzhou Toujing Electronic Equipment Co., Ltd.

Product Name: Rugged Tablet

Test Model(s): TJ-101ED02

Report Reference No. : DACE260122021RL005

FCC ID : 2BVAQTJ-101ED02

Applicant's Name : Guangzhou Toujing Electronic Equipment Co., Ltd.

Address : 201/2nd Floor, No. 26, Hecun Industrial Road, Dashi Street, Panyu District, Guangzhou City, Guangdong Province

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15E

Date of Receipt : January 22, 2026

Date of Test : January 22, 2026 to March 3, 2026

Date of Issue : March 3, 2026

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample

Apply for company information

Applicant's Name	:	Guangzhou Toujing Electronic Equipment Co., Ltd.
Address	:	201/2nd Floor, No. 26, Hecun Industrial Road, Dashi Street, Panyu District, Guangzhou City, Guangdong Province
Product Name	:	Rugged Tablet
Test Model(s)	:	TJ-101ED02
Series Model(s)	:	TJ-120TC04, TJ-190SW03, TJ190VH, TJ-150TC04, TJ-550SW03, TJ-650SW03, TJ-156TC04
Test Specification Standard(s)	:	47 CFR Part 15E

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Lucy Mo

Lucy Mo / Test Engineer

March 3, 2026

Supervised by:

Ben Tang

Ben Tang / Project Engineer

March 3, 2026

Approved by:

Machael Mo

Machael Mo / Manager

March 3, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260122021RL005	March 3, 2026

CONTENTS

1 TEST SUMMARY	6
1.1 TEST STANDARDS	6
1.2 SUMMARY OF TEST RESULT	6
2 GENERAL INFORMATION	7
2.1 CLIENT INFORMATION	7
2.2 DESCRIPTION OF DEVICE (EUT)	7
2.3 DESCRIPTION OF TEST MODES	9
2.4 DESCRIPTION OF SUPPORT UNITS	9
2.5 EQUIPMENTS USED DURING THE TEST	10
2.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	12
2.7 IDENTIFICATION OF TESTING LABORATORY	12
2.8 ANNOUNCEMENT	12
3 EVALUATION RESULTS (EVALUATION)	13
3.1 ANTENNA REQUIREMENT	13
3.1.1 Conclusion:	13
4 RADIO SPECTRUM MATTER TEST RESULTS (RF)	14
4.1 CONDUCTED EMISSION AT AC POWER LINE	14
4.1.1 E.U.T. Operation:	14
4.1.2 Test Setup Diagram:	14
4.1.3 Test Data:	15
4.2 DUTY CYCLE	19
4.2.1 E.U.T. Operation:	19
4.2.2 Test Setup Diagram:	19
4.2.3 Test Data:	19
4.3 EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	20
4.3.1 E.U.T. Operation:	21
4.3.2 Test Setup Diagram:	21
4.3.3 Test Data:	21
4.4 MAXIMUM CONDUCTED OUTPUT POWER	22
4.4.1 E.U.T. Operation:	22
4.4.2 Test Setup Diagram:	22
4.4.3 Test Data:	22
4.5 POWER SPECTRAL DENSITY	23
4.5.1 E.U.T. Operation:	23
4.5.2 Test Setup Diagram:	23
4.5.3 Test Data:	23
4.6 FREQUENCY STABILITY	24
4.6.1 E.U.T. Operation:	24
4.6.2 Test Setup Diagram:	24
4.6.3 Test Data:	24
4.7 BAND EDGE EMISSIONS (CONDUCTED)	25
4.7.1 E.U.T. Operation:	26
4.7.2 Test Setup Diagram:	27
4.7.3 Test Data:	27
4.8 BAND EDGE EMISSIONS (RADIATED)	28
4.8.1 E.U.T. Operation:	29

4.8.2 Test Data:	30
4.9 UNDESIRABLE EMISSION LIMITS (BELOW 1GHz)	34
4.9.1 E.U.T. Operation:	35
4.9.2 Test Data:	36
4.10 UNDESIRABLE EMISSION LIMITS (ABOVE 1GHz)	40
4.10.1 E.U.T. Operation:	42
4.10.2 Test Data:	42
5 TEST SETUP PHOTOS	48
6 PHOTOS OF THE EUT	48
APPENDIX-5.2G	49
1. -26dB AND 99% EMISSION BANDWIDTH	50
2. DUTY CYCLE	79
3. MAXIMUM CONDUCTED OUTPUT POWER	94
4. POWER SPECTRAL DENSITY	95
5. BANDEDGE	116
6. SPURIOUS EMISSION	128
7. FREQUENCY STABILITY	143
APPENDIX-5.8G	145
1. -6dB EMISSION BANDWIDTH	146
2. -26dB AND 99% EMISSION BANDWIDTH	161
3. DUTY CYCLE	190
4. MAXIMUM CONDUCTED OUTPUT POWER	205
5. POWER SPECTRAL DENSITY	206
6. BANDEDGE	227
7. SPURIOUS EMISSION	241
8. FREQUENCY STABILITY	256

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15E: Unlicensed National Information Infrastructure Devices

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Conducted Emission at AC power line	47 CFR Part 15E	ANSI C63.10-2020 section 6.2	47 CFR Part 15.207(a)	Pass
Duty Cycle	47 CFR Part 15E	ANSI C63.10-2020 section 12.2 (b)		Pass
Emission bandwidth and occupied bandwidth	47 CFR Part 15E	ANSI C63.10-2020, section 6.9 & 12.5 KDB 789033 D02, Clause C.2	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. 47 CFR Part 15.407(e)	Pass
Maximum conducted output power	47 CFR Part 15E	ANSI C63.10-2020, section 12.4	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)	Pass
Power spectral density	47 CFR Part 15E	ANSI C63.10-2020, section 12.6	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)	Pass
Frequency stability	47 CFR Part 15E	ANSI C63.10-2020, section 6.8	47 CFR Part 15.407(g)	Pass
Band edge emissions (Conducted)	47 CFR Part 15E	ANSI C63.10-2020, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass
Band edge emissions (Radiated)	47 CFR Part 15E	ANSI C63.10-2020, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass
Undesirable emission limits (below 1GHz)	47 CFR Part 15E	ANSI C63.10-2020, section 12.7.4, 12.7.5	47 CFR Part 15.407(b)(9)	Pass
Undesirable emission limits (above 1GHz)	47 CFR Part 15E	ANSI C63.10-2020, section 12.7.4, 12.7.6, 12.7.7	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Guangzhou Toujing Electronic Equipment Co., Ltd.
Address : 201/2nd Floor, No. 26, Hecun Industrial Road, Dashi Street, Panyu District, Guangzhou City, Guangdong Province

Manufacturer : Guangzhou Toujing Electronic Equipment Co., Ltd.
Address : 201/2nd Floor, No. 26, Hecun Industrial Road, Dashi Street, Panyu District, Guangzhou City, Guangdong Province

2.2 Description of Device (EUT)

Product Name:	Rugged Tablet
Model/Type reference:	TJ-101ED02
Series Model:	TJ-120TC04, TJ-190SW03, TJ190VH, TJ-150TC04, TJ-550SW03, TJ-650SW03, TJ-156TC04
Model Difference:	The product has many models, only the model name and color is different, and the other parts such as the circuit principle, pcb and electrical structure are the same.
Trade Mark:	N/A
Power Supply:	DC 19V/3.42A from adapter Battery:DC7.6V 8000mAh
Power Adaptor:	MODEL:BYX-19003420G INPUT:100-240V~50/60Hz 1.5A Max OUTPUT:DC19V/3.42A
Operation Frequency:	802.11a/n(HT20)/ac(HT20): U-NII Band 1: 5180MHz to 5240MHz; U-NII Band 3: 5745MHz to 5825MHz; 802.11n(HT40)/ac(HT40): U-NII Band 1: 5190MHz to 5230MHz; U-NII Band 3: 5755MHz to 5795MHz; 802.11ac(HT80): U-NII Band 1: 5210MHz; U-NII Band 3: 5775MHz
Number of Channels:	802.11a/n(HT20)/ac(HT20): U-NII Band 1: 4; U-NII Band 3: 5; 802.11n(HT40)/ac(HT40): U-NII Band 1: 2; U-NII Band 3: 2; 802.11ac(HT80): U-NII Band 1: 1; U-NII Band 3: 1
Modulation Type:	802.11a: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM);
Antenna Type:	FPC Antenna
Antenna Gain:	ANT1:3.37dBi;ANT2:3.80dBi;
Hardware Version:	V1.0
Software Version:	V1.0

Remark: The Antenna Gain is supplied by the customer. DACE is not responsible for this data and the related calculations associated with it

Operation Frequency each of channel

802.11a/n(HT20)/ac(HT20)

	U-NII Band 1	U-NII Band 3
Channel	Frequency	Frequency
1	5180 MHz	5745 MHz
2	5200 MHz	5765 MHz
3	5220 MHz	5785 MHz
4	5240 MHz	5805 MHz
5	/	5825 MHz

802.11n(HT40)/ac(HT40)

	U-NII Band 1	U-NII Band 3
Channel	Frequency	Frequency
1	5190 MHz	5755 MHz
2	5230 MHz	5795 MHz

802.11ac(HT80)

	U-NII Band 1	U-NII Band 3
Channel	Frequency	Frequency
1	5210 MHz	5775 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11a/n(HT20)/ac(HT20)

	U-NII Band 1	U-NII Band 3
Test channel	Frequency (MHz)	Frequency (MHz)
Lowest channel	5180 MHz	5745 MHz
Middle channel	5200 MHz	5785 MHz
Highest channel	5240 MHz	5825 MHz

802.11n(HT40)/ac(HT40)

	U-NII Band 1	U-NII Band 3
Test channel	Frequency (MHz)	Frequency (MHz)
Lowest channel	5190 MHz	5755 MHz
Highest channel	5230 MHz	5795 MHz

802.11ac(HT80)

	U-NII Band 1	U-NII Band 3
Test channel	Frequency (MHz)	Frequency (MHz)
Middle channel	5210 MHz	5775 MHz

2.3 Description of Test Modes

No	Title	Description
TM1	802.11a mode	Keep the EUT in continuously transmitting mode with 802.11a modulation type at lowest, middle and highest channel. All data rates has been tested and found the data rate @ 6Mbps is the worst case. Only the data of worst case is recorded in the report.
TM2	802.11n mode	Keep the EUT in continuously transmitting mode with 802.11n modulation type at lowest, middle and highest channel. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.
TM3	802.11ac mode	Keep the EUT in continuously transmitting mode with 802.11ac modulation type at lowest, middle and highest channel. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case. Only the data of worst case is recorded in the report.

Remark: were performed with duty cycle above 98%, meet the requirements of KDB789033. Only the data of the worst mode would be recorded in this report.

2.4 Description of Support Units

The EUT was tested as an independent device.

2.5 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2025-04-23	2026-04-22
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	2025-04-18	2026-04-17
Cable	SCHWARZ BECK	/	/	2025-04-18	2026-04-17
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Attenuation	561-G071	2025-12-02	2026-12-01
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	1164.6607K03 -102109-MH	2025-04-25	2026-04-24
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2025-04-18	2026-04-17
L.I.S.N	SCHWARZ BECK	NSLK 8126	05055	2025-04-18	2026-04-17
Pulse Limiter	CYBERTEK	EM5010A	/	2025-04-25	2026-04-24
EMI test software	EZ -EMC	EZ	V1.1.42	/	/

Emission bandwidth and occupied bandwidth

Maximum conducted output power

Power spectral density

Frequency stability

Band edge emissions (Conducted)

Duty Cycle

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(she nzheng) Co.,Ltd.	RTS-01	V1.0.0	/	/
Power divider	MIDEWEST	PWD-2533	SMA-79	2025-04-18	2026-05-10
RF Sensor Unit	Tachoy Information Technology(she nzheng) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2025-04-25	2026-04-24
Vector Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01
Power meter	Agilent	E4416	MY48200166	2025-12-06	2026-12-05

Band edge emissions (Radiated)**Undesirable emission limits (below 1GHz)****Undesirable emission limits (above 1GHz)**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2025-04-28	2026-04-27
Cable(LF)#2	Schwarzbeck	/	/	2025-04-12	2026-04-11
Cable(LF)#1	Schwarzbeck	/	/	2025-04-17	2026-04-16
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2025-04-25	2026-04-24
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2025-04-25	2026-04-24
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2025-04-29	2026-04-28
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2025-04-29	2026-04-28
Wideband radio communication tester	R&S	CMW500	113410	2025-04-25	2026-04-24
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2025-04-18	2026-04-17
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2025-04-18	2026-04-17
Horn Antenna	Sunol Sciences	DRH-118	A091114	2025-04-21	2026-04-20
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2024-09-28	2026-09-27

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	±3.41dB
Duty cycle	±3.1%
Occupied Bandwidth	±3.63%
RF conducted power	±0.733dB
RF power density	±0.234%
Conducted Spurious emissions	±1.98dB
Radiated Emission (Above 1GHz)	±5.46dB
Radiated Emission (Below 1GHz)	±5.79dB
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

2.7 Identification of Testing Laboratory

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
Designation Number:	CN1342
Test Firm Registration Number:	778666
A2LA Certificate Number:	6270.01

2.8 Announcement


- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)


4.1 Conducted Emission at AC power line

Test Requirement:	47 CFR Part 15.207(a)		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dBµV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2020 section 6.2		

4.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	23.8 °C	Humidity:	49 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:		TM1			
Final test mode:		TM1			

4.1.2 Test Setup Diagram:




4.1.3 Test Data:

TM1 / Line: Line / Band: 5150-5250 MHz / BW: 20 / CH: L




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1539	52.62	10.08	62.70	65.79	-3.09	QP	
2		0.1539	34.38	10.08	44.46	55.79	-11.33	AVG	
3		0.4100	33.43	10.08	43.51	57.65	-14.14	QP	
4		0.4100	21.55	10.08	31.63	47.65	-16.02	AVG	
5		1.0220	22.97	10.08	33.05	56.00	-22.95	QP	
6		1.0220	14.31	10.08	24.39	46.00	-21.61	AVG	
7		3.2659	23.56	10.11	33.67	56.00	-22.33	QP	
8		3.2659	16.47	10.11	26.58	46.00	-19.42	AVG	
9		15.8740	15.76	10.50	26.26	60.00	-33.74	QP	
10		15.8740	5.09	10.50	15.59	50.00	-34.41	AVG	
11		29.7340	13.29	11.15	24.44	60.00	-35.56	QP	
12		29.7340	2.84	11.15	13.99	50.00	-36.01	AVG	

TM1 / Line: Neutral / Band: 5150-5250 MHz / BW: 20 / CH: L




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	52.03	10.11	62.14	66.00	-3.86	QP	
2		0.1500	32.76	10.11	42.87	56.00	-13.13	AVG	
3		0.3899	35.39	10.09	45.48	58.07	-12.59	QP	
4		0.3899	19.29	10.09	29.38	48.07	-18.69	AVG	
5		1.4020	23.18	10.06	33.24	56.00	-22.76	QP	
6		1.4020	18.43	10.06	28.49	46.00	-17.51	AVG	
7		2.3340	23.26	10.02	33.28	56.00	-22.72	QP	
8		2.3340	18.42	10.02	28.44	46.00	-17.56	AVG	
9		15.7140	16.09	10.52	26.61	60.00	-33.39	QP	
10		15.7140	4.01	10.52	14.53	50.00	-35.47	AVG	
11		29.6820	10.83	11.10	21.93	60.00	-38.07	QP	
12		29.6820	-0.54	11.10	10.56	50.00	-39.44	AVG	

TM1 / Line: Line / Band: 5725-5850 MHz / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	52.19	10.11	62.30	66.00	-3.70	QP	
2		0.1500	37.80	10.11	47.91	56.00	-8.09	AVG	
3		0.4060	34.01	10.10	44.11	57.73	-13.62	QP	
4		0.4060	21.35	10.10	31.45	47.73	-16.28	AVG	
5		1.3060	22.99	10.08	33.07	56.00	-22.93	QP	
6		1.3060	10.02	10.08	20.10	46.00	-25.90	AVG	
7		2.3340	22.97	10.02	32.99	56.00	-23.01	QP	
8		2.3340	17.78	10.02	27.80	46.00	-18.20	AVG	
9		4.5500	19.72	10.17	29.89	56.00	-26.11	QP	
10		4.5500	9.27	10.17	19.44	46.00	-26.56	AVG	
11		16.2979	15.68	10.53	26.21	60.00	-33.79	QP	
12		16.2979	5.40	10.53	15.93	50.00	-34.07	AVG	

TM1 / Line: Neutral / Band: 5725-5850 MHz / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1580	52.21	10.08	62.29	65.57	-3.28	QP	
2		0.1580	32.61	10.08	42.69	55.57	-12.88	AVG	
3		0.3860	33.63	10.07	43.70	58.15	-14.45	QP	
4		0.3860	20.40	10.07	30.47	48.15	-17.68	AVG	
5		1.4020	23.26	10.05	33.31	56.00	-22.69	QP	
6		1.4020	18.09	10.05	28.14	46.00	-17.86	AVG	
7		3.2659	21.54	10.11	31.65	56.00	-24.35	QP	
8		3.2659	15.91	10.11	26.02	46.00	-19.98	AVG	
9		16.6140	16.33	10.52	26.85	60.00	-33.15	QP	
10		16.6140	4.77	10.52	15.29	50.00	-34.71	AVG	
11		30.0000	10.47	11.17	21.64	60.00	-38.36	QP	
12		30.0000	2.98	11.17	14.15	50.00	-35.85	AVG	

NOTE:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor, Over = Limit - Measurement


4.2 Duty Cycle

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum-power transmission duration, T, are required for each tested mode of operation.
Test Limit:	No limits, only for report use.
Test Method:	ANSI C63.10-2020 section 12.2 (b)
Procedure:	i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW $\geq$ RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	46 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Please Refer to Appendix for Details.


4.3 Emission bandwidth and occupied bandwidth

Test Requirement:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: 47 CFR Part 15.407(e)
Test Limit:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 6.9 & 12.5 KDB 789033 D02, Clause C.2
Procedure:	Emission bandwidth: - Set RBW = approximately 1% of the emission bandwidth. - Set the VBW > RBW. - Detector = peak. - Trace mode = max hold. - Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. Occupied bandwidth: - The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. - The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. - Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. - Step a) through step c) might require iteration to adjust within the specified range. - Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. - Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. - If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies. - The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s). 6 dB emission bandwidth: - Set RBW = 100 kHz. - Set the video bandwidth (VBW) $\geq 3 \times$ RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.1 °C	Humidity:	51 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Maximum conducted output power

Test Requirement:	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2020, section 12.4
Procedure:	Refer to ANSI C63.10-2020 section 12.4

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.6 °C	Humidity:	53 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.


4.5 Power spectral density

Test Requirement:	47 CFR Part 15.407(a)(1)(iv) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2020, section 12.6
Procedure:	Refer to ANSI C63.10-2020, section 12.6

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.1 °C	Humidity:	55 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.


4.6 Frequency stability

Test Requirement:	47 CFR Part 15.407(g)
Test Limit:	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.
Test Method:	ANSI C63.10-2020, section 6.8
Procedure:	Refer to ANSI C63.10-2020 section 6.8

4.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.8 °C	Humidity:	49 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.6.2 Test Setup Diagram:



4.6.3 Test Data:

Please Refer to Appendix for Details.

4.7 Band edge emissions (Conducted)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																							
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table><tr><th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr><tr><td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr><tr><td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr><tr><td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr><tr><td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr><tr><td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr><tr><td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr><tr><td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr><tr><td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr><tr><td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr><tr><td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr><tr><td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr><tr><td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr><tr><td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr><tr><td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr><tr><td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr><tr><td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr><tr><td>13.36-13.41</td><td></td><td></td><td></td></tr></table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr></table>				MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41				Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30
MHz	MHz	MHz	GHz																																																																																					
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																																					
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																																					
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																																					
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																																					
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																																					
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																																					
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																																					
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																																					
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																																					
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																																					
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																																					
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																																					
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																																					
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																																					
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																																					
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																																					
13.36-13.41																																																																																								
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																																																																						
0.009-0.490	2400/F(kHz)	300																																																																																						
0.490-1.705	24000/F(kHz)	30																																																																																						
1.705-30.0	30	30																																																																																						


	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020, section 12.7.4, 12.7.6, 12.7.7		
Procedure:	Above 1GHz: - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. - Test the EUT in the lowest channel, the middle channel, the Highest channel. - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. - Repeat above procedures until all frequencies measured was complete. Remark: - Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor - Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. - As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. - The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.		

4.7.1 E.U.T. Operation:

Operating Environment:

Temperature:	23.1 °C	Humidity:	50 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.7.2 Test Setup Diagram:



4.7.3 Test Data:

Please Refer to Appendix for Details.

4.8 Band edge emissions (Radiated)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																							
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table><tr><th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr><tr><td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr><tr><td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr><tr><td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr><tr><td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr><tr><td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr><tr><td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr><tr><td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr><tr><td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr><tr><td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr><tr><td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr><tr><td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr><tr><td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr><tr><td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr><tr><td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr><tr><td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr><tr><td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr><tr><td>13.36-13.41</td><td></td><td></td><td></td></tr></table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr></table>				MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41				Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30
MHz	MHz	MHz	GHz																																																																																					
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																																					
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																																					
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																																					
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																																					
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																																					
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																																					
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																																					
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																																					
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																																					
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																																					
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																																					
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																																					
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																																					
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																																					
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																																					
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																																					
13.36-13.41																																																																																								
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																																																																						
0.009-0.490	2400/F(kHz)	300																																																																																						
0.490-1.705	24000/F(kHz)	30																																																																																						
1.705-30.0	30	30																																																																																						

	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020, section 12.7.4, 12.7.6, 12.7.7		
Procedure:	Above 1GHz: - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. - Test the EUT in the lowest channel, the middle channel, the Highest channel. - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. - Repeat above procedures until all frequencies measured was complete. Remark: - Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor - Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. - As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. - The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.		

4.8.1 E.U.T. Operation:

Operating Environment:

Temperature:	22.5 °C	Humidity:	48 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.8.2 Test Data:

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin (dBuV/m)	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)				
802.11a-ant1_Low Channel: 5180MHz								
H	5100	47.63	0.16	47.79	74	-26.21	PK	Pass
H	5100	37.12	0.16	37.28	54	-16.72	AV	Pass
H	5150	48.10	0.25	48.35	74	-25.65	PK	Pass
H	5150	39.06	0.25	39.31	54	-14.69	AV	Pass
V	5100	48.92	0.16	49.08	74	-24.92	PK	Pass
V	5100	38.12	0.16	38.28	54	-15.72	AV	Pass
V	5150	47.72	0.25	47.97	74	-26.03	PK	Pass
V	5150	38.52	0.25	38.77	54	-15.23	AV	Pass
802.11a-ant1_High Channel: 5240MHz								
H	5150	57.49	0.16	57.65	74	-16.35	PK	Pass
H	5150	43.11	0.16	43.27	54	-10.73	AV	Pass
H	5350	56.80	0.25	57.05	74	-16.95	PK	Pass
H	5350	44.65	0.25	44.90	54	-9.10	AV	Pass
V	5150	58.13	0.16	58.29	74	-15.71	PK	Pass
V	5150	43.90	0.16	44.06	54	-9.94	AV	Pass
V	5350	57.46	0.25	57.71	74	-16.29	PK	Pass
V	5350	43.67	0.25	43.92	54	-10.08	AV	Pass
802.11a-ant2_Low Channel: 5180MHz								
H	5100	47.79	0.16	47.95	74	-26.05	PK	Pass
H	5100	37.15	0.16	37.31	54	-16.69	AV	Pass
H	5150	47.97	0.25	48.22	74	-25.78	PK	Pass
H	5150	37.59	0.25	37.84	54	-16.16	AV	Pass
V	5100	47.85	0.16	48.01	74	-25.99	PK	Pass
V	5100	39.47	0.16	39.63	54	-14.37	AV	Pass
V	5150	47.68	0.25	47.93	74	-26.07	PK	Pass
V	5150	38.51	0.25	38.76	54	-15.24	AV	Pass
802.11a-ant2_High Channel: 5240MHz								
H	5100	47.38	0.16	47.54	74	-26.46	PK	Pass
H	5100	38.90	0.16	39.06	54	-14.94	AV	Pass
H	5150	49.07	0.25	49.32	74	-24.68	PK	Pass
H	5150	39.30	0.25	39.55	54	-14.45	AV	Pass
V	5100	48.14	0.16	48.30	74	-25.70	PK	Pass
V	5100	37.17	0.16	37.33	54	-16.67	AV	Pass
V	5150	47.36	0.25	47.61	74	-26.39	PK	Pass

V	5150	37.02	0.25	37.27	54	-16.73	AV	Pass
---	------	-------	------	-------	----	--------	----	------

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)		
802.11a-ant1_Low Channel: 5745MHz								
H	5647	49.16	0.71	49.87	68.2	-18.33	PK	Pass
H	5725	59.24	1.17	60.41	122.2	-61.79	PK	Pass
V	5647	47.03	0.71	47.74	68.2	-20.46	PK	Pass
V	5725	58.45	1.17	59.62	122.2	-62.58	PK	Pass
802.11a-ant1_High Channel: 5825MHz								
H	5850	57.68	1.33	59.01	122.2	-63.19	PK	Pass
H	5950	48.01	1.39	49.40	68.2	-18.80	PK	Pass
V	5850	57.82	1.33	59.15	122.2	-63.05	PK	Pass
V	5950	48.36	1.39	49.75	68.2	-18.45	PK	Pass
802.11a-ant2_Low Channel: 5745MHz								
H	5647	47.22	0.71	47.93	68.2	-20.27	PK	Pass
H	5725	57.64	1.17	58.81	122.2	-63.39	PK	Pass
V	5647	48.26	0.71	48.97	68.2	-19.23	PK	Pass
V	5725	59.38	1.17	60.55	122.2	-61.65	PK	Pass
802.11a-ant2_High Channel: 5825MHz								
H	5850	58.82	1.33	60.15	122.2	-62.05	PK	Pass
H	5950	48.00	1.39	49.39	68.2	-18.81	PK	Pass
V	5850	57.55	1.33	58.88	122.2	-63.32	PK	Pass
V	5950	47.03	1.39	48.42	68.2	-19.78	PK	Pass

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)		
802.11ac20-MIMO_Low Channel: 5180MHz								
H	5100	47.47	0.16	47.63	74	-26.37	PK	Pass
H	5100	38.15	0.16	38.31	54	-15.69	AV	Pass
H	5150	48.43	0.25	48.68	74	-25.32	PK	Pass
H	5150	37.88	0.25	38.13	54	-15.87	AV	Pass
V	5100	47.38	0.16	47.54	74	-26.46	PK	Pass
V	5100	38.19	0.16	38.35	54	-15.65	AV	Pass
V	5150	48.63	0.25	48.88	74	-25.12	PK	Pass
V	5150	38.33	0.25	38.58	54	-15.42	AV	Pass
802.11ac20-MIMO_High Channel: 5240MHz								
H	5150	57.81	0.16	57.97	74	-16.03	PK	Pass
H	5150	45.32	0.16	45.48	54	-8.52	AV	Pass
H	5350	57.03	0.25	57.28	74	-16.72	PK	Pass
H	5350	45.33	0.25	45.58	54	-8.42	AV	Pass

V	5150	56.60	0.16	56.76	74	-17.24	PK	Pass
V	5150	45.35	0.16	45.51	54	-8.49	AV	Pass
V	5350	57.63	0.25	57.88	74	-16.12	PK	Pass
V	5350	45.06	0.25	45.31	54	-8.69	AV	Pass

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)		
802.11ac20-MIMO_Low Channel: 5745MHz								
H	5647	49.21	0.71	49.92	68.2	-18.28	PK	Pass
H	5725	57.81	1.17	58.98	122.2	-63.22	PK	Pass
V	5647	48.97	0.71	49.68	68.2	-18.52	PK	Pass
V	5725	57.41	1.17	58.58	122.2	-63.62	PK	Pass
802.11ac20-MIMO_High Channel: 5825MHz								
H	5850	59.15	1.33	60.48	122.2	-61.72	PK	Pass
H	5950	47.25	1.39	48.64	68.2	-19.56	PK	Pass
V	5850	59.02	1.33	60.35	122.2	-61.85	PK	Pass
V	5950	49.50	1.39	50.89	68.2	-17.31	PK	Pass

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)		
802.11ac40-MIMO_Low Channel: 5190MHz								
H	5100	47.28	0.16	47.44	74	-26.56	PK	Pass
H	5100	38.84	0.16	39.00	54	-15.00	AV	Pass
H	5150	49.20	0.25	49.45	74	-24.55	PK	Pass
H	5150	38.88	0.25	39.13	54	-14.87	AV	Pass
V	5100	47.57	0.16	47.73	74	-26.27	PK	Pass
V	5100	38.79	0.16	38.95	54	-15.05	AV	Pass
V	5150	48.85	0.25	49.10	74	-24.90	PK	Pass
V	5150	39.22	0.25	39.47	54	-14.53	AV	Pass
802.11ac40-MIMO_Low Channel: 5230MHz								
H	5150	58.59	0.16	58.75	74	-15.25	PK	Pass
H	5150	43.62	0.16	43.78	54	-10.22	AV	Pass
H	5350	57.25	0.25	57.50	74	-16.50	PK	Pass
H	5350	43.55	0.25	43.80	54	-10.20	AV	Pass
V	5150	58.18	0.16	58.34	74	-15.66	PK	Pass
V	5150	43.33	0.16	43.49	54	-10.51	AV	Pass
V	5350	56.30	0.25	56.55	74	-17.45	PK	Pass
V	5350	45.58	0.25	45.83	54	-8.17	AV	Pass

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)		
802.11ac40-MIMO_Low Channel: 5755MHz								
H	5647	49.01	0.71	49.72	68.2	-18.48	PK	Pass
H	5725	58.20	1.17	59.37	122.2	-62.83	PK	Pass
V	5647	49.46	0.71	50.17	68.2	-18.03	PK	Pass
V	5725	57.24	1.17	58.41	122.2	-63.79	PK	Pass
802.11ac40-MIMO_High Channel: 5795MHz								
H	5850	57.41	1.33	58.74	122.2	-63.46	PK	Pass
H	5950	47.24	1.39	48.63	68.2	-19.57	PK	Pass
V	5850	57.95	1.33	59.28	122.2	-62.92	PK	Pass
V	5950	49.04	1.39	50.43	68.2	-17.77	PK	Pass

802.11ac80-MIMO_Low Channel: 5210MHz								
H	5100	47.12	0.16	47.28	74	-26.72	PK	Pass
H	5100	38.91	0.16	39.07	54	-14.93	AV	Pass
H	5150	49.59	0.25	49.84	74	-24.16	PK	Pass
H	5150	37.08	0.25	37.33	54	-16.67	AV	Pass
V	5100	47.83	0.16	47.99	74	-26.01	PK	Pass
V	5100	38.53	0.16	38.69	54	-15.31	AV	Pass
V	5150	48.52	0.25	48.77	74	-25.23	PK	Pass
V	5150	37.31	0.25	37.56	54	-16.44	AV	Pass

802.11ac80-MIMO_Low Channel: 5775MHz								
H	5647	48.01	0.71	48.72	68.2	-19.48	PK	Pass
H	5725	58.30	1.17	59.47	122.2	-62.73	PK	Pass
V	5647	49.36	0.71	50.07	68.2	-18.13	PK	Pass
V	5725	58.17	1.17	59.34	122.2	-62.86	PK	Pass
H	5850	58.19	1.33	59.52	122.2	-62.68	PK	Pass
H	5950	47.47	1.39	48.86	68.2	-19.34	PK	Pass
V	5850	58.79	1.33	60.12	122.2	-62.08	PK	Pass
V	5950	48.84	1.39	50.23	68.2	-17.97	PK	Pass

Note: All the mode have been tested, and only the worst case 802.11a and 802.11ac MIMO mode are in the report

4.9 Undesirable emission limits (below 1GHz)

Test Requirement:	47 CFR Part 15.407(b)(9)																								
Test Limit:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020, section 12.7.4, 12.7.5																								
Procedure:	Below 1GHz: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz. the disturbance below 30MHz was very low. The																								

points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

Above 1GHz:

- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:


- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

4.9.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.9 °C	Humidity:	50 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				


4.9.2 Test Data:

TM1 / Polarization: Horizontal / Band: 5150-5250 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	115.7256	27.48	-7.03	20.45	43.50	-23.05	QP	100		P	
2	150.5378	38.40	-7.81	30.59	43.50	-12.91	QP	100		P	
3	207.8501	38.22	-9.96	28.26	43.50	-15.24	QP	100		P	
4	387.9920	32.60	-6.26	26.34	46.00	-19.66	QP	100		P	
5	462.3455	32.61	-4.05	28.56	46.00	-17.44	QP	100		P	
6 *	790.6188	35.17	2.12	37.29	46.00	-8.71	QP	100		P	

TM1 / Polarization: Vertical / Band: 5150-5250 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	72.8466	33.70	-12.85	20.85	40.00	-19.15	QP	100		P	
2	84.1100	33.37	-12.90	20.47	40.00	-19.53	QP	100		P	
3	153.2004	29.53	-8.23	21.30	43.50	-22.20	QP	100		P	
4	356.6758	28.00	-6.82	21.18	46.00	-24.82	QP	100		P	
5	549.0195	29.70	-3.15	26.55	46.00	-19.45	QP	100		P	
6 *	790.6188	29.99	2.10	32.09	46.00	-13.91	QP	100		P	

TM1 / Polarization: Horizontal / Band: 5725-5850 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	72.8466	33.70	-12.85	20.85	40.00	-19.15	QP	100		P	
2	89.9047	38.45	-12.72	25.73	43.50	-17.77	QP	100		P	
3	153.2004	29.53	-8.23	21.30	43.50	-22.20	QP	100		P	
4	204.9551	28.95	-9.64	19.31	43.50	-24.19	QP	100		P	
5	549.0195	29.70	-3.15	26.55	46.00	-19.45	QP	100		P	
6 *	790.6188	29.99	2.10	32.09	46.00	-13.91	QP	100		P	

TM1 / Polarization: Vertical / Band: 5725-5850 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	151.5972	37.98	-7.79	30.19	43.50	-13.31	QP			P	
2	205.6750	37.53	-9.96	27.57	43.50	-15.93	QP			P	
3	297.2240	30.69	-8.07	22.62	46.00	-23.38	QP			P	
4	377.2590	31.75	-6.56	25.19	46.00	-20.81	QP			P	
5	467.2350	32.89	-3.78	29.11	46.00	-16.89	QP			P	
6 *	787.8512	33.95	2.00	35.95	46.00	-10.05	QP			P	

4.10 Undesirable emission limits (above 1GHz)

Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																	
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table><tr><th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr><tr><td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr><tr><td>¹ 0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr><tr><td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr><tr><td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr><tr><td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr><tr><td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr><tr><td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr><tr><td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr><tr><td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr><tr><td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr><tr><td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr><tr><td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr><tr><td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr><tr><td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr><tr><td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr><tr><td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr><tr><td>13.36-13.41</td><td></td><td></td><td></td></tr></table> ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ² Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr></table>				MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41				Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300
MHz	MHz	MHz	GHz																																																																															
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																															
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																															
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																															
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																															
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																															
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																															
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																															
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																															
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																															
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																															
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																															
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																															
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																															
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																															
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																															
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																															
13.36-13.41																																																																																		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																																																																
0.009-0.490	2400/F(kHz)	300																																																																																

	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020, section 12.7.4, 12.7.6, 12.7.7		
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.		

4.10.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.1 °C	Humidity:	52 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.10.2 Test Data:

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin (dBuV/m)	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)				
802.11a-ant1_Low Channel: 5180MHz								
V	5655.56	55.33	1.02	56.35	74	-17.65	PK	Pass
V	5655.56	34.07	1.02	35.09	54	-18.91	AV	Pass
V	10360	53.45	8.78	62.23	74	-11.77	PK	Pass
V	10360	33.21	8.78	41.99	54	-12.01	AV	Pass
H	5654.54	54.08	1.02	55.10	74	-18.90	PK	Pass
H	5654.54	33.89	1.02	34.91	54	-19.09	AV	Pass
H	10360	55.17	8.78	63.95	74	-10.05	PK	Pass
H	10360	33.51	8.78	42.29	54	-11.71	AV	Pass
802.11a-ant1Middle Channel:5200MHz								
V	5654.54	53.39	1.02	54.41	74	-19.59	PK	Pass
V	5654.54	35.23	1.02	36.25	54	-17.75	AV	Pass
V	10360	54.05	8.78	62.83	74	-11.17	PK	Pass
V	10360	35.29	8.78	44.07	54	-9.93	AV	Pass
H	5654.06	53.59	1.02	54.61	74	-19.39	PK	Pass
H	5654.06	34.31	1.02	35.33	54	-18.67	AV	Pass
H	10360	53.38	8.78	62.16	74	-11.84	PK	Pass
H	10360	34.86	8.78	43.64	54	-10.36	AV	Pass
802.11a-ant1High Channel:5240MHz								
V	5654.78	53.84	1.02	54.86	74	-19.14	PK	Pass
V	5654.78	33.03	1.02	34.05	54	-19.95	AV	Pass
V	10360	54.19	8.78	62.97	74	-11.03	PK	Pass
V	10360	33.53	8.78	42.31	54	-11.69	AV	Pass
H	5655.49	54.07	1.02	55.09	74	-18.91	PK	Pass
H	5655.49	34.04	1.02	35.06	54	-18.94	AV	Pass
H	10360	54.05	8.78	62.83	74	-11.17	PK	Pass
H	10360	33.59	8.78	42.37	54	-11.63	AV	Pass

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)		(dBuV/m)		
802.11a-ant2_Low Channel: 5180MHz								
V	5655.50	55.39	1.02	56.41	74	-17.59	PK	Pass
V	5655.50	34.76	1.02	35.78	54	-18.22	AV	Pass
V	10360	54.86	8.78	63.64	74	-10.36	PK	Pass
V	10360	35.18	8.78	43.96	54	-10.04	AV	Pass
H	5654.51	53.45	1.02	54.47	74	-19.53	PK	Pass
H	5654.51	34.06	1.02	35.08	54	-18.92	AV	Pass
H	10360	55.13	8.78	63.91	74	-10.09	PK	Pass
H	10360	34.31	8.78	43.09	54	-10.91	AV	Pass
Middle Channel:5200MHz								
V	5654.10	55.08	1.02	56.10	74	-17.90	PK	Pass
V	5654.10	34.07	1.02	35.09	54	-18.91	AV	Pass
V	10360	53.55	8.78	62.33	74	-11.67	PK	Pass
V	10360	33.66	8.78	42.44	54	-11.56	AV	Pass
H	5653.40	55.28	1.02	56.30	74	-17.70	PK	Pass
H	5653.40	35.14	1.02	36.16	54	-17.84	AV	Pass
H	10360	54.97	8.78	63.75	74	-10.25	PK	Pass
H	10360	33.59	8.78	42.37	54	-11.63	AV	Pass
High Channel:5240MHz								
V	5654.13	53.17	1.02	54.19	74	-19.81	PK	Pass
V	5654.13	33.92	1.02	34.94	54	-19.06	AV	Pass
V	10360	53.13	8.78	61.91	74	-12.09	PK	Pass
V	10360	34.72	8.78	43.50	54	-10.50	AV	Pass
H	5654.18	53.42	1.02	54.44	74	-19.56	PK	Pass
H	5654.18	33.87	1.02	34.89	54	-19.11	AV	Pass
H	10360	54.65	8.78	63.43	74	-10.57	PK	Pass
H	10360	33.63	8.78	42.41	54	-11.59	AV	Pass

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin (dBuV/m)	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)				
802.11a-ant1_Low Channel: 5745MHz								
V	5654.08	54.11	1.02	55.13	74	-18.87	PK	Pass
V	5654.08	33.66	1.02	34.68	54	-19.32	AV	Pass
V	11490	53.44	8.78	62.22	74	-11.78	PK	Pass
V	11490	34.19	8.78	42.97	54	-11.03	AV	Pass
H	5654.69	53.68	1.02	54.70	74	-19.30	PK	Pass
H	5654.69	35.57	1.02	36.59	54	-17.41	AV	Pass
H	11490	54.94	8.78	63.72	74	-10.28	PK	Pass
H	11490	34.35	8.78	43.13	54	-10.87	AV	Pass
Middle Channel:5785MHz								
V	5655.59	54.12	1.02	55.14	74	-18.86	PK	Pass
V	5655.59	35.11	1.02	36.13	54	-17.87	AV	Pass
V	11570	54.47	8.78	63.25	74	-10.75	PK	Pass
V	11570	35.49	8.78	44.27	54	-9.73	AV	Pass
H	5655.00	54.76	1.02	55.78	74	-18.22	PK	Pass
H	5655.00	33.80	1.02	34.82	54	-19.18	AV	Pass
H	11570	53.12	8.78	61.90	74	-12.10	PK	Pass
H	11570	34.07	8.78	42.85	54	-11.15	AV	Pass
High Channel:5825MHz								
V	5653.46	53.99	1.02	55.01	74	-18.99	PK	Pass
V	5653.46	34.83	1.02	35.85	54	-18.15	AV	Pass
V	11650	53.44	8.78	62.22	74	-11.78	PK	Pass
V	11650	35.16	8.78	43.94	54	-10.06	AV	Pass
H	5655.18	53.39	1.02	54.41	74	-19.59	PK	Pass
H	5655.18	33.22	1.02	34.24	54	-19.76	AV	Pass
H	11650	54.24	8.78	63.02	74	-10.98	PK	Pass
H	11650	35.53	8.78	44.31	54	-9.69	AV	Pass

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin (dBuV/m)	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)				
802.11a-ant2_Low Channel: 5745MHz								
V	5653.31	55.46	1.02	56.48	74	-17.52	PK	Pass
V	5653.31	34.55	1.02	35.57	54	-18.43	AV	Pass
V	11490	54.95	8.78	63.73	74	-10.27	PK	Pass
V	11490	33.86	8.78	42.64	54	-11.36	AV	Pass
H	5654.90	55.51	1.02	56.53	74	-17.47	PK	Pass
H	5654.90	33.50	1.02	34.52	54	-19.48	AV	Pass
H	11490	54.89	8.78	63.67	74	-10.33	PK	Pass
H	11490	34.25	8.78	43.03	54	-10.97	AV	Pass
Middle Channel:5785MHz								
V	5653.78	54.87	1.02	55.89	74	-18.11	PK	Pass
V	5653.78	34.84	1.02	35.86	54	-18.14	AV	Pass
V	11570	55.34	8.78	64.12	74	-9.88	PK	Pass
V	11570	33.80	8.78	42.58	54	-11.42	AV	Pass
H	5654.12	53.86	1.02	54.88	74	-19.12	PK	Pass
H	5654.12	35.01	1.02	36.03	54	-17.97	AV	Pass
H	11570	54.30	8.78	63.08	74	-10.92	PK	Pass
H	11570	33.19	8.78	41.97	54	-12.03	AV	Pass
High Channel:5825MHz								
V	5654.37	54.00	1.02	55.02	74	-18.98	PK	Pass
V	5654.37	34.18	1.02	35.20	54	-18.80	AV	Pass
V	11650	53.58	8.78	62.36	74	-11.64	PK	Pass
V	11650	33.16	8.78	41.94	54	-12.06	AV	Pass
H	5653.70	53.33	1.02	54.35	74	-19.65	PK	Pass
H	5653.70	34.94	1.02	35.96	54	-18.04	AV	Pass
H	11650	53.45	8.78	62.23	74	-11.77	PK	Pass
H	11650	33.83	8.78	42.61	54	-11.39	AV	Pass

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)		(dBuV/m)		
802.11ac40-MIMO_Low Channel: 5190MHz								
V	5655.18	55.21	1.02	56.23	74	-17.77	PK	Pass
V	5655.18	33.09	1.02	34.11	54	-19.89	AV	Pass
V	10380	54.52	8.78	63.30	74	-10.70	PK	Pass
V	10380	35.53	8.78	44.31	54	-9.69	AV	Pass
H	5655.27	53.01	1.02	54.03	74	-19.97	PK	Pass
H	5655.27	33.35	1.02	34.37	54	-19.63	AV	Pass
H	10380	54.22	8.78	63.00	74	-11.00	PK	Pass
H	10380	34.17	8.78	42.95	54	-11.05	AV	Pass
High Channel:5230MHz								
V	5655.09	53.34	1.02	54.36	74	-19.64	PK	Pass
V	5655.09	33.93	1.02	34.95	54	-19.05	AV	Pass
V	10460	54.32	8.78	63.10	74	-10.90	PK	Pass
V	10460	33.96	8.78	42.74	54	-11.26	AV	Pass
H	5655.03	53.54	1.02	54.56	74	-19.44	PK	Pass
H	5655.03	35.00	1.02	36.02	54	-17.98	AV	Pass
H	10460	53.90	8.78	62.68	74	-11.32	PK	Pass
H	10460	33.08	8.78	41.86	54	-12.14	AV	Pass

Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)		(dBuV/m)		
802.11ac40-MIMO_Low Channel: 5755MHz								
V	5655.32	54.86	1.02	55.88	74	-18.12	PK	Pass
V	5655.32	34.66	1.02	35.68	54	-18.32	AV	Pass
V	11510	53.22	8.78	62.00	74	-12.00	PK	Pass
V	11510	34.28	8.78	43.06	54	-10.94	AV	Pass
H	5654.77	54.63	1.02	55.65	74	-18.35	PK	Pass
H	5654.77	33.02	1.02	34.04	54	-19.96	AV	Pass
H	11510	55.41	8.78	64.19	74	-9.81	PK	Pass
H	11510	34.62	8.78	43.40	54	-10.60	AV	Pass
High Channel:5795.MHz								
V	5655.38	54.97	1.02	55.99	74	-18.01	PK	Pass
V	5655.38	33.34	1.02	34.36	54	-19.64	AV	Pass
V	11590	54.11	8.78	62.89	74	-11.11	PK	Pass
V	11590	33.16	8.78	41.94	54	-12.06	AV	Pass
H	5653.06	55.37	1.02	56.39	74	-17.61	PK	Pass
H	5653.06	34.29	1.02	35.31	54	-18.69	AV	Pass
H	11590	53.98	8.78	62.76	74	-11.24	PK	Pass

H	11590	34.02	8.78	42.80	54	-11.20	AV	Pass
---	-------	-------	------	-------	----	--------	----	------

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin (dBuV/m)	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)				
802.11ac80-MIMO_Low Channel: 5210MHz								
V	5655.03	54.88	1.02	55.90	74	-18.10	PK	Pass
V	5655.03	33.74	1.02	34.76	54	-19.24	AV	Pass
V	10420	53.13	8.78	61.91	74	-12.09	PK	Pass
V	10420	34.49	8.78	43.27	54	-10.73	AV	Pass
H	5653.97	55.17	1.02	56.19	74	-17.81	PK	Pass
H	5653.97	34.80	1.02	35.82	54	-18.18	AV	Pass
H	10420	54.73	8.78	63.51	74	-10.49	PK	Pass
H	10420	33.19	8.78	41.97	54	-12.03	AV	Pass

WIFI								
Polar	Frequency	Meter Reading	Cable Loss	Level	Limit (dBuV/m)	Margin (dBuV/m)	Detector Type	Result
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)				
802.11ac80-MIMO_Low Channel: 5755MHz								
V	5654.99	53.30	1.02	54.32	74	-19.68	PK	Pass
V	5654.99	34.57	1.02	35.59	54	-18.41	AV	Pass
V	11510	54.68	8.78	63.46	74	-10.54	PK	Pass
V	11510	35.02	8.78	43.80	54	-10.20	AV	Pass
H	5653.25	54.10	1.02	55.12	74	-18.88	PK	Pass
H	5653.25	35.03	1.02	36.05	54	-17.95	AV	Pass
H	11510	53.27	8.78	62.05	74	-11.95	PK	Pass
H	11510	33.86	8.78	42.64	54	-11.36	AV	Pass

Note: All the mode have been tested, and only the worst case 802.11a and 802.11ac MIMO mode are in the report

5 TEST SETUP PHOTOS

Please refer to Setup Photo file

6 PHOTOS OF THE EUT

Please refer to external photos file and internal photos file

Appendix-5.2G


HT260122009-TJ-101ED02-FCC ID-5.2GWIFI

FCC_5.2G_WIFI (Part15.407) Test Data

1. -26dB and 99% Emission Bandwidth

Condition	Antenna	Modulation	Frequency(MHz)	-26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5180.00	23.12	16.44
NVNT	ANT2	802.11a	5180.00	22.57	16.45
NVNT	ANT1	802.11a	5200.00	22.82	16.45
NVNT	ANT2	802.11a	5200.00	23.27	16.45
NVNT	ANT1	802.11a	5240.00	22.97	16.46
NVNT	ANT2	802.11a	5240.00	22.49	16.45
NVNT	ANT1	802.11n(HT20)	5180.00	23.85	17.70
NVNT	ANT2	802.11n(HT20)	5180.00	23.78	17.68
NVNT	ANT1	802.11n(HT20)	5200.00	23.38	17.72
NVNT	ANT2	802.11n(HT20)	5200.00	23.95	17.62
NVNT	ANT1	802.11n(HT20)	5240.00	23.16	17.69
NVNT	ANT2	802.11n(HT20)	5240.00	22.44	17.66
NVNT	ANT1	802.11ac(VHT20)	5180.00	23.22	17.65
NVNT	ANT2	802.11ac(VHT20)	5180.00	23.06	17.65
NVNT	ANT1	802.11ac(VHT20)	5200.00	23.57	17.65
NVNT	ANT2	802.11ac(VHT20)	5200.00	23.08	17.63
NVNT	ANT1	802.11ac(VHT20)	5240.00	23.96	17.62
NVNT	ANT2	802.11ac(VHT20)	5240.00	23.58	17.65
NVNT	ANT1	802.11n(HT40)	5190.00	45.70	36.19
NVNT	ANT2	802.11n(HT40)	5190.00	44.80	36.14
NVNT	ANT1	802.11n(HT40)	5230.00	40.48	36.19
NVNT	ANT2	802.11n(HT40)	5230.00	45.54	36.18
NVNT	ANT1	802.11ac(VHT40)	5190.00	45.41	36.19
NVNT	ANT2	802.11ac(VHT40)	5190.00	44.15	36.09
NVNT	ANT1	802.11ac(VHT40)	5230.00	45.35	36.12
NVNT	ANT2	802.11ac(VHT40)	5230.00	43.80	36.13
NVNT	ANT1	802.11ac(VHT80)	5210.00	84.41	74.81
NVNT	ANT2	802.11ac(VHT80)	5210.00	84.42	74.74

99%_OCB_NVNT_ANT1_802_11a_5180



-26BW_NVNT_ANT1_802_11a_5180



99%_OCB_NVNT_ANT2_802_11a_5180



-26BW_NVNT_ANT2_802_11a_5180



99%_OCB_NVNT_ANT1_802_11a_5200



-26BW_NVNT_ANT1_802_11a_5200




99%_OCB_NVNT_ANT2_802_11a_5200



-26BW_NVNT_ANT2_802_11a_5200



99%_OCB_NVNT_ANT1_802_11a_5240



-26BW_NVNT_ANT1_802_11a_5240



99%_OCB_NVNT_ANT2_802_11a_5240



-26BW_NVNT_ANT2_802_11a_5240




99%_OCB_NVNT_ANT1_802_11n(HT20)_5180



-26BW_NVNT_ANT1_802_11n(HT20)_5180




99%_OCB_NVNT_ANT2_802_11n(HT20)_5180



-26BW_NVNT_ANT2_802_11n(HT20)_5180




99%_OCB_NVNT_ANT1_802_11n(HT20)_5200



-26BW_NVNT_ANT1_802_11n(HT20)_5200



99%_OCB_NVNT_ANT2_802_11n(HT20)_5200



-26BW_NVNT_ANT2_802_11n(HT20)_5200



99%_OCB_NVNT_ANT1_802_11n(HT20)_5240



-26BW_NVNT_ANT1_802_11n(HT20)_5240




99%_OCB_NVNT_ANT2_802_11n(HT20)_5240



-26BW_NVNT_ANT2_802_11n(HT20)_5240




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5180



-26BW_NVNT_ANT1_802_11ac(VHT20)_5180



99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5180



-26BW_NVNT_ANT2_802_11ac(VHT20)_5180




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5200



-26BW_NVNT_ANT1_802_11ac(VHT20)_5200



99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5200



-26BW_NVNT_ANT2_802_11ac(VHT20)_5200



99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5240



-26BW_NVNT_ANT1_802_11ac(VHT20)_5240




99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5240



-26BW_NVNT_ANT2_802_11ac(VHT20)_5240




99%_OCB_NVNT_ANT1_802_11n(HT40)_5190



-26BW_NVNT_ANT1_802_11n(HT40)_5190




99%_OCB_NVNT_ANT2_802_11n(HT40)_5190



-26BW_NVNT_ANT2_802_11n(HT40)_5190




99%_OCB_NVNT_ANT1_802_11n(HT40)_5230



-26BW_NVNT_ANT1_802_11n(HT40)_5230




99%_OCB_NVNT_ANT2_802_11n(HT40)_5230



-26BW_NVNT_ANT2_802_11n(HT40)_5230



99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5190



-26BW_NVNT_ANT1_802_11ac(VHT40)_5190




99%_OCB_NVNT_ANT2_802_11ac(VHT40)_5190



-26BW_NVNT_ANT2_802_11ac(VHT40)_5190




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5230



-26BW_NVNT_ANT1_802_11ac(VHT40)_5230




99%_OCB_NVNT_ANT2_802_11ac(VHT40)_5230




-26BW_NVNT_ANT2_802_11ac(VHT40)_5230



99%_OCB_NVNT_ANT1_802_11ac(VHT80)_5210




-26BW_NVNT_ANT1_802_11ac(VHT80)_5210



99%_OCB_NVNT_ANT2_802_11ac(VHT80)_5210




-26BW_NVNT_ANT2_802_11ac(VHT80)_5210




2. Duty Cycle

Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty_factor
NVNT	ANT1	802.11a	5180.00	94.44	0.25
NVNT	ANT2	802.11a	5180.00	94.50	0.25
NVNT	ANT1	802.11a	5200.00	97.17	0.12
NVNT	ANT2	802.11a	5200.00	97.17	0.12
NVNT	ANT1	802.11a	5240.00	96.23	0.17
NVNT	ANT2	802.11a	5240.00	97.17	0.12
NVNT	ANT1	802.11n(HT20)	5180.00	96.97	0.13
NVNT	ANT2	802.11n(HT20)	5180.00	95.96	0.18
NVNT	ANT1	802.11n(HT20)	5200.00	95.96	0.18
NVNT	ANT2	802.11n(HT20)	5200.00	96.97	0.13
NVNT	ANT1	802.11n(HT20)	5240.00	96.94	0.14
NVNT	ANT2	802.11n(HT20)	5240.00	96.97	0.13
NVNT	ANT1	802.11ac(VHT20)	5180.00	96.08	0.17
NVNT	ANT2	802.11ac(VHT20)	5180.00	96.08	0.17
NVNT	ANT1	802.11ac(VHT20)	5200.00	96.08	0.17
NVNT	ANT2	802.11ac(VHT20)	5200.00	96.15	0.17
NVNT	ANT1	802.11ac(VHT20)	5240.00	96.08	0.17
NVNT	ANT2	802.11ac(VHT20)	5240.00	96.08	0.17
NVNT	ANT1	802.11n(HT40)	5190.00	95.92	0.18
NVNT	ANT2	802.11n(HT40)	5190.00	95.92	0.18
NVNT	ANT1	802.11n(HT40)	5230.00	97.94	0.09
NVNT	ANT2	802.11n(HT40)	5230.00	95.92	0.18
NVNT	ANT1	802.11ac(VHT40)	5190.00	96.23	0.17
NVNT	ANT2	802.11ac(VHT40)	5190.00	92.31	0.35
NVNT	ANT1	802.11ac(VHT40)	5230.00	83.33	0.79
NVNT	ANT2	802.11ac(VHT40)	5230.00	100	0.00
NVNT	ANT1	802.11ac(VHT80)	5210.00	86.67	0.62
NVNT	ANT2	802.11ac(VHT80)	5210.00	85.71	0.67


Duty_Cycle_NVNT_ANT1_802_11a_5180




Duty_Cycle_NVNT_ANT2_802_11a_5180




Duty_Cycle_NVNT_ANT1_802_11a_5200




Duty_Cycle_NVNT_ANT2_802_11a_5200




Duty_Cycle_NVNT_ANT1_802_11a_5240




Duty_Cycle_NVNT_ANT2_802_11a_5240




Duty_Cycle_NVNT_ANT1_802_11n(HT20)_5180




Duty_Cycle_NVNT_ANT2_802_11n(HT20)_5180




Duty_Cycle_NVNT_ANT1_802_11n(HT20)_5200




Duty_Cycle_NVNT_ANT2_802_11n(HT20)_5200




Duty_Cycle_NVNT_ANT1_802_11n(HT20)_5240




Duty_Cycle_NVNT_ANT2_802_11n(HT20)_5240




Duty_Cycle_NVNT_ANT1_802_11ac(VHT20)_5180




Duty_Cycle_NVNT_ANT2_802_11ac(VHT20)_5180




Duty_Cycle_NVNT_ANT1_802_11ac(VHT20)_5200




Duty_Cycle_NVNT_ANT2_802_11ac(VHT20)_5200




Duty_Cycle_NVNT_ANT1_802_11ac(VHT20)_5240




Duty_Cycle_NVNT_ANT2_802_11ac(VHT20)_5240




Duty_Cycle_NVNT_ANT1_802_11n(HT40)_5190




Duty_Cycle_NVNT_ANT2_802_11n(HT40)_5190




Duty_Cycle_NVNT_ANT1_802_11n(HT40)_5230




Duty_Cycle_NVNT_ANT2_802_11n(HT40)_5230




Duty_Cycle_NVNT_ANT1_802_11ac(VHT40)_5190




Duty_Cycle_NVNT_ANT2_802_11ac(VHT40)_5190




Duty_Cycle_NVNT_ANT1_802_11ac(VHT40)_5230




Duty_Cycle_NVNT_ANT2_802_11ac(VHT40)_5230



Duty_Cycle_NVNT_ANT1_802_11ac(VHT80)_5210



Duty_Cycle_NVNT_ANT2_802_11ac(VHT80)_5210



3. Maximum Conducted Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11a	5180.00	12.08	0.25	12.33	24	Pass
NVNT	ANT2	802.11a	5180.00	14.25	0.25	14.50	24	Pass
NVNT	ANT1	802.11a	5200.00	12.50	0.12	12.62	24	Pass
NVNT	ANT2	802.11a	5200.00	14.47	0.12	14.59	24	Pass
NVNT	ANT1	802.11a	5240.00	12.29	0.17	12.46	24	Pass
NVNT	ANT2	802.11a	5240.00	15.01	0.12	15.13	24	Pass
NVNT	ANT1	802.11n(HT20)	5180.00	11.97	0.13	12.10	24	Pass
NVNT	ANT2	802.11n(HT20)	5180.00	14.20	0.18	14.38	24	Pass
NVNT	ANT1	802.11n(HT20)	5200.00	12.43	0.18	12.61	24	Pass
NVNT	ANT2	802.11n(HT20)	5200.00	14.35	0.13	14.48	24	Pass
NVNT	ANT1	802.11n(HT20)	5240.00	12.15	0.14	12.29	24	Pass
NVNT	ANT2	802.11n(HT20)	5240.00	14.88	0.13	15.01	24	Pass
NVNT	ANT1	802.11ac(VHT20)	5180.00	12.18	0.17	12.35	24	Pass
NVNT	ANT2	802.11ac(VHT20)	5180.00	14.35	0.17	14.52	24	Pass
NVNT	ANT1	802.11ac(VHT20)	5200.00	12.45	0.17	12.62	24	Pass
NVNT	ANT2	802.11ac(VHT20)	5200.00	14.39	0.17	14.56	24	Pass
NVNT	ANT1	802.11ac(VHT20)	5240.00	12.21	0.17	12.38	24	Pass
NVNT	ANT2	802.11ac(VHT20)	5240.00	14.99	0.17	15.16	24	Pass
NVNT	ANT1	802.11n(HT40)	5190.00	11.34	0.18	11.52	24	Pass
NVNT	ANT2	802.11n(HT40)	5190.00	13.51	0.18	13.69	24	Pass
NVNT	ANT1	802.11n(HT40)	5230.00	11.40	0.09	11.49	24	Pass
NVNT	ANT2	802.11n(HT40)	5230.00	13.47	0.18	13.65	24	Pass
NVNT	ANT1	802.11ac(VHT40)	5190.00	11.08	0.17	11.25	24	Pass
NVNT	ANT2	802.11ac(VHT40)	5190.00	13.41	0.35	13.76	24	Pass
NVNT	ANT1	802.11ac(VHT40)	5230.00	10.95	0.79	11.74	24	Pass
NVNT	ANT2	802.11ac(VHT40)	5230.00	12.92	0.00	12.92	24	Pass
NVNT	ANT1	802.11ac(VHT80)	5210.00	9.86	0.62	10.48	24	Pass
NVNT	ANT2	802.11ac(VHT80)	5210.00	11.90	0.67	12.57	24	Pass

Condition	Antenna	Mode	Frequency(MHz)	MIMO_Conducted_Power(dBm)	Limit(dBm)	Result
NVNT	MIMO_TX	802.11n(HT20)	5180.00	16.40	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	5200.00	16.65	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	5240.00	16.87	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5180.00	16.58	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5200.00	16.71	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5240.00	17.00	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	5190.00	15.75	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	5230.00	15.72	30	Pass
NVNT	MIMO_TX	802.11ac(VHT40)	5190.00	15.69	30	Pass
NVNT	MIMO_TX	802.11ac(VHT40)	5230.00	15.38	30	Pass
NVNT	MIMO_TX	802.11ac(VHT80)	5210.00	14.66	30	Pass

4. Power Spectral Density

Condition	Antenna	Modulation	Frequency (MHz)	PSD(dBm/MHz)	Duty factor(dB)	Total PSD(dBm/MHz)	limit(dBm)	Result
NVNT	ANT1	802.11a	5180.00	-4.99	0.25	-4.74	11	Pass
NVNT	ANT2	802.11a	5180.00	-1.66	0.25	-1.41	11	Pass
NVNT	ANT1	802.11a	5200.00	-2.32	0.12	-2.20	11	Pass
NVNT	ANT2	802.11a	5200.00	0.56	0.12	0.68	11	Pass
NVNT	ANT1	802.11a	5240.00	-2.21	0.17	-2.04	11	Pass
NVNT	ANT2	802.11a	5240.00	0.48	0.12	0.60	11	Pass
NVNT	ANT1	802.11n(HT20)	5180.00	-1.21	0.13	-1.08	11	Pass
NVNT	ANT2	802.11n(HT20)	5180.00	0.69	0.18	0.87	11	Pass
NVNT	ANT1	802.11n(HT20)	5200.00	-1.15	0.18	-0.97	11	Pass
NVNT	ANT2	802.11n(HT20)	5200.00	-0.14	0.13	-0.01	11	Pass
NVNT	ANT1	802.11n(HT20)	5240.00	-3.60	0.14	-3.46	11	Pass
NVNT	ANT2	802.11n(HT20)	5240.00	0.06	0.13	0.19	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5180.00	-1.55	0.17	-1.39	11	Pass
NVNT	ANT2	802.11ac(VHT20)	5180.00	0.26	0.17	0.43	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5200.00	-2.27	0.17	-2.10	11	Pass
NVNT	ANT2	802.11ac(VHT20)	5200.00	-0.42	0.17	-0.25	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5240.00	-1.79	0.17	-1.62	11	Pass
NVNT	ANT2	802.11ac(VHT20)	5240.00	-0.78	0.17	-0.61	11	Pass
NVNT	ANT1	802.11n(HT40)	5190.00	-5.81	0.18	-5.63	11	Pass
NVNT	ANT2	802.11n(HT40)	5190.00	-3.85	0.18	-3.67	11	Pass
NVNT	ANT1	802.11n(HT40)	5230.00	-5.77	0.09	-5.68	11	Pass
NVNT	ANT2	802.11n(HT40)	5230.00	-3.53	0.18	-3.35	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5190.00	-7.47	0.17	-7.30	11	Pass
NVNT	ANT2	802.11ac(VHT40)	5190.00	-6.55	0.35	-6.21	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5230.00	-10.70	0.79	-9.91	11	Pass
NVNT	ANT2	802.11ac(VHT40)	5230.00	-8.91	0.00	-8.91	11	Pass
NVNT	ANT1	802.11ac(VHT80)	5210.00	-12.98	0.62	-12.36	11	Pass
NVNT	ANT2	802.11ac(VHT80)	5210.00	-10.89	0.67	-10.22	11	Pass

Power_Spectral_Density_NVNT_ANT1_802_11a_5180



Power_Spectral_Density_NVNT_ANT2_802_11a_5180



Power_Spectral_Density_NVNT_ANT1_802_11a_5200



Power_Spectral_Density_NVNT_ANT2_802_11a_5200



Power_Spectral_Density_NVNT_ANT1_802_11a_5240



Power_Spectral_Density_NVNT_ANT2_802_11a_5240



Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_5180



Power_Spectral_Density_NVNT_ANT2_802_11n(HT20)_5180



Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_5200



Power_Spectral_Density_NVNT_ANT2_802_11n(HT20)_5200

