

RF TEST REPORT

For

Shenzhen Udfine Technology Co., Ltd.

Product Name: Udfine AudioLink

Test Model(s): YS06

Report Reference No. : DACE260205005RL001

FCC ID : 2BVB3-YS06

Applicant's Name : Shenzhen Udfine Technology Co., Ltd.

Address : Room 308, Building K, No. 17 Wan'an Road, Ma'anshan Community,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong Province

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park,
Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen,
Guangdong, China

Test Specification Standard : 47 CFR Part 15.247


Date of Receipt : February 5, 2026

Date of Test : February 5, 2026 to March 13, 2026

Date of Issue : March 13, 2026

Result : **Pass**

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Apply for company information

Applicant's Name	:	Shenzhen Udfine Technology Co., Ltd.
Address	:	Room 308, Building K, No. 17 Wan'an Road, Ma'anshan Community, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong Province
Product Name	:	Udfine AudioLink
Test Model(s)	:	YS06
Test Specification Standard(s)	:	47 CFR Part 15.247

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Amy Zhu / Test Engineer

March 13, 2026

Supervised by:

Stone Yin / Project Engineer

March 13, 2026

Approved by:

Tom Chen / Manager

March 13, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260205005RL001	March 13, 2026

CONTENTS

1	TEST SUMMARY	6
1.1	TEST STANDARDS	6
1.2	SUMMARY OF TEST RESULT	6
2	GENERAL INFORMATION	8
2.1	CLIENT INFORMATION	8
2.2	DESCRIPTION OF DEVICE (EUT)	8
2.3	DESCRIPTION OF TEST MODES	8
2.4	DESCRIPTION OF SUPPORT UNITS	8
2.5	OPERATION FREQUENCY EACH OF CHANNEL	9
2.6	EQUIPMENTS USED DURING THE TEST	10
2.7	STATEMENT OF THE MEASUREMENT UNCERTAINTY	12
3	EVALUATION RESULTS (EVALUATION)	13
3.1	ANTENNA REQUIREMENT	13
3.1.1	Conclusion:	13
4	RADIO SPECTRUM MATTER TEST RESULTS (RF)	14
4.1	CONDUCTED EMISSION AT AC POWER LINE	14
4.1.1	E.U.T. Operation:	14
4.1.2	Test Setup Diagram:	14
4.1.3	Test Data:	15
4.2	20dB BANDWIDTH	17
4.2.1	E.U.T. Operation:	17
4.2.2	Test Setup Diagram:	17
4.2.3	Test Data:	18
4.3	MAXIMUM CONDUCTED OUTPUT POWER	19
4.3.1	E.U.T. Operation:	19
4.3.2	Test Setup Diagram:	19
4.3.3	Test Data:	20
4.4	CHANNEL SEPARATION	21
4.4.1	E.U.T. Operation:	21
4.4.2	Test Setup Diagram:	21
4.4.3	Test Data:	22
4.5	NUMBER OF HOPPING FREQUENCIES	23
4.5.1	E.U.T. Operation:	23
4.5.2	Test Setup Diagram:	23
4.5.3	Test Data:	24
4.6	DWELL TIME	25
4.6.1	E.U.T. Operation:	26
4.6.2	Test Setup Diagram:	26
4.6.3	Test Data:	26
4.7	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	27
4.7.1	E.U.T. Operation:	28
4.7.2	Test Setup Diagram:	28
4.7.3	Test Data:	28
4.8	BAND EDGE EMISSIONS (RADIATED)	29
4.8.1	E.U.T. Operation:	29
4.8.2	Test Data:	30

4.9	EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz)	34
4.9.1	E.U.T. Operation:	35
4.9.2	Test Data:	36
4.10	EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz)	38
4.10.1	E.U.T. Operation:	39
4.10.2	Test Data:	40
5	TEST SETUP PHOTOS	46
6	PHOTOS OF THE EUT	48
1.	DUTY CYCLE	50
2.	-20DB BANDWIDTH	55
3.	99% OCCUPIED BANDWIDTH	60
4.	PEAK OUTPUT POWER	65
5.	SPURIOUS EMISSIONS	70
6.	BANDEDGE	80
7.	CARRIER FREQUENCIES SEPARATION (HOPPING)	93
8.	NUMBER OF HOPPING CHANNEL (HOPPING)	95
9.	DWELL TIME (HOPPING)	97

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.247	---	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	ANSI C63.10-2020 section 6.2	47 CFR 15.207(a)	Pass
20dB Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020, section 7.8.6 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2020, section 7.8.5 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(1)	Pass
Channel Separation	47 CFR Part 15.247	ANSI C63.10-2020, section 7.8.2 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)	Pass
Number of Hopping Frequencies	47 CFR Part 15.247	ANSI C63.10-2020, section 7.8.3 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)(iii)	Pass
Dwell Time	47 CFR Part 15.247	ANSI C63.10-2020, section 7.8.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)(iii)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2020 section 7.8.7 ANSI C63.10-2020+Cor 1-2023 section 7.8.7 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01	47 CFR 15.247(d), 15.209, 15.205	Pass

		15.247 Meas Guidance v05r02		
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Shenzhen Udfine Technology Co., Ltd.
Address : Room 308, Building K, No. 17 Wan'an Road, Ma'anshan Community, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong Province

Manufacturer : Shenzhen Udfine Technology Co., Ltd.
Address : Room 308, Building K, No. 17 Wan'an Road, Ma'anshan Community, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong Province

2.2 Description of Device (EUT)

Product Name:	Udfine AudioLink
Model/Type reference:	YS06
Trade Mark:	UDFINE
Power Supply:	AC 100-240V 50/60Hz
Operation Frequency:	2402-2480MHz
Number of Channels:	79CH
Modulation Type:	GFSK, ($\pi/4$)DQPSK, 8DPSK
Antenna Type:	PCB Antenna
Antenna Gain:	1.9dBi
Bluetooth Version:	V5.3
Hardware Version:	V1.0
Software Version:	V1.0

2.3 Description of Test Modes

No	Title	Description
TM1	TX mode	Keep the EUT in TX mode
Test Environment		Normal Voltage(AC): 120V

2.4 Description of Support Units

Title	Manufacturer	Model No.	Serial No.
Speaker	CONCN	801	/

2.5 Operation Frequency each of channel

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	/	/

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	GFSK, ($\pi/4$)DQPSK, 8DPSK
Lowest channel	2402MHz
Middle channel	2441MHz
Highest channel	2480MHz

2.6 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2025-04-23	2026-04-22
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	2025-04-18	2026-04-17
Cable	SCHWARZ BECK	/	/	2025-04-18	2026-04-17
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Attenuation	561-G071	2025-12-02	2026-12-01
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	1164.6607K03 -102109-MH	2025-04-25	2026-04-24
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2025-04-18	2026-04-17
L.I.S.N	SCHWARZ BECK	NSLK 8126	05055	2025-04-18	2026-04-17
Pulse Limiter	CYBERTEK	EM5010A	/	2025-04-25	2026-04-24
EMI test software	EZ -EMC	EZ	V1.1.42	/	/

Emissions in non-restricted frequency bands

20dB Bandwidth

Maximum Conducted Output Power

Channel Separation

Number of Hopping Frequencies

Dwell Time

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(she nzen) Co.,Ltd.	RTS-01	V1.0.0	/	/
RF Sensor Unit	Tachoy Information Technology(she nzen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2025-04-25	2026-04-24
Vector Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01

Band edge emissions (Radiated)
Emissions in frequency bands (below 1GHz)
Emissions in frequency bands (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2025-04-28	2026-04-27
Cable(LF)#2	Schwarzbeck	/	/	2025-04-12	2026-04-11
Cable(LF)#1	Schwarzbeck	/	/	2025-04-17	2026-04-16
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2025-04-25	2026-04-24
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2025-04-25	2026-04-24
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2025-04-29	2026-04-28
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2025-04-29	2026-04-28
Wideband radio communication tester	R&S	CMW500	113410	2025-04-25	2026-04-24
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2025-04-18	2026-04-17
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2025-04-18	2026-04-17
Horn Antenna	Sunol Sciences	DRH-118	A091114	2025-04-21	2026-04-20
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2024-09-28	2026-09-27

2.7 Statement Of The Measurement Uncertainty


Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	±3.41dB
Occupied Bandwidth	±3.63%
RF conducted power	±0.733dB
Duty cycle	±3.1%
Conducted Spurious emissions	±1.98dB
Radiated Emission (Above 1GHz)	±5.46dB
Radiated Emission (Below 1GHz)	±5.79dB
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)


4.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2020 section 6.2		
Procedure:	Refer to ANSI C63.10-2020 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

4.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	22.1 °C	Humidity:	51 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.1.2 Test Setup Diagram:




4.1.3 Test Data:

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.2378	45.42	10.09	55.51	62.17	-6.66	QP	
2		0.2378	24.55	10.09	34.64	52.17	-17.53	AVG	
3		0.5420	36.81	10.10	46.91	56.00	-9.09	QP	
4		0.5420	22.80	10.10	32.90	46.00	-13.10	AVG	
5		0.8460	35.78	10.10	45.88	56.00	-10.12	QP	
6		0.8460	20.79	10.10	30.89	46.00	-15.11	AVG	
7		2.1420	34.01	10.01	44.02	56.00	-11.98	QP	
8		2.1420	24.94	10.01	34.95	46.00	-11.05	AVG	
9		4.8659	29.94	10.18	40.12	56.00	-15.88	QP	
10		4.8659	18.71	10.18	28.89	46.00	-17.11	AVG	
11		12.2460	29.51	10.41	39.92	60.00	-20.08	QP	
12		12.2460	15.93	10.41	26.34	50.00	-23.66	AVG	

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2420	44.53	10.08	54.61	62.03	-7.42	QP	
2		0.2420	22.25	10.08	32.33	52.03	-19.70	AVG	
3	*	0.3580	41.71	10.07	51.78	58.77	-6.99	QP	
4		0.3580	23.47	10.07	33.54	48.77	-15.23	AVG	
5		0.8540	36.81	10.08	46.89	56.00	-9.11	QP	
6		0.8540	22.19	10.08	32.27	46.00	-13.73	AVG	
7		1.9580	36.37	10.00	46.37	56.00	-9.63	QP	
8		1.9580	22.30	10.00	32.30	46.00	-13.70	AVG	
9		4.2980	36.33	10.18	46.51	56.00	-9.49	QP	
10		4.2980	24.48	10.18	34.66	46.00	-11.34	AVG	
11		29.5380	30.68	11.14	41.82	60.00	-18.18	QP	
12		29.5380	18.31	11.14	29.45	50.00	-20.55	AVG	

NOTE:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor, Over = Limit - Measurement

4.2 20dB Bandwidth


Test Requirement:	47 CFR 15.247(a)(1)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2020, section 7.8.6, For occupied bandwidth measurements, use the procedure in 6.9.3. Frequency hopping shall be disabled for this test. KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth: a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2. d) Step a) through step c) might require iteration to adjust within the specified range. e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used. f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies. h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.7 °C	Humidity:	50 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.2.2 Test Setup Diagram:

--



4.2.3 Test Data:

Please Refer to Appendix for Details.

4.3 Maximum Conducted Output Power


Test Requirement:	47 CFR 15.247(b)(1)
Test Limit:	Refer to 47 CFR 15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test Method:	ANSI C63.10-2020, section 7.8.5 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Frequency hopping shall be disabled for this test. Use the following spectrum analyzer settings: a) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel. b) RBW > 20 dB bandwidth of the emission being measured. c) VBW ≥ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow trace to stabilize. h) Use the marker-to-peak function to set the marker to the peak of the emission. i) The indicated level is the peak output power, after any corrections for external attenuators and cables. j) A spectral plot of the test results and setup description shall be included in the test report. NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.6 °C	Humidity:	51 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.3.2 Test Setup Diagram:

--



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Channel Separation

Test Requirement:	47 CFR 15.247(a)(1)
Test Limit:	Refer to 47 CFR 15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Test Method:	ANSI C63.10-2020, section 7.8.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: Wide enough to capture the peaks of two adjacent channels. b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. c) Video (or average) bandwidth (VBW) $\geq$ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A spectral plot of the data shall be included in the test report.

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.5 °C	Humidity:	51 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.


4.5 Number of Hopping Frequencies

Test Requirement:	47 CFR 15.247(a)(1)(iii)
Test Limit:	Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	ANSI C63.10-2020, section 7.8.3 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen. b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. c) VBW $\geq$ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow the trace to stabilize. It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A spectral plot of the data shall be included in the test report.

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.6 °C	Humidity:	49 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.

4.6 Dwell Time

Test Requirement:	47 CFR 15.247(a)(1)(iii)
Test Limit:	Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	ANSI C63.10-2020, section 7.8.4 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The dwell time per hop on a channel is the time from the start of the first transmission to the end of the last transmission for that hop. If the device has a single transmission per hop then the dwell time is the duration of that transmission. If the device has a multiple transmissions per hop then the dwell time is measured from the start of the first transmission to the end of the last transmission. The time of occupancy is the total time that the device dwells on a channel over an observation period specified in the regulatory requirement. To determine the time of occupancy the spectrum analyzer will be configured to measure both the dwell time per hop and the number of times the device transmits on a specific channel in a given period. The EUT shall have its hopping function enabled. Compliance with the requirements shall be made with the minimum and with the maximum number of channels enabled. If the dwell time per channel does not vary with the number of channels then compliance with the requirements may be based on the minimum number of channels. If the device supports different dwell times per channel (example Bluetooth devices can dwell on a channel for 1, 3 or 5 time slots) then measurements can be limited to the longest dwell time with the minimum number of channels. Use the following spectrum analyzer settings to determine the dwell time per hop: a) Span: Zero span, centered on a hopping channel. b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected transmission time per hop. c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this. d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel. e) Detector function: Peak. f) Trace: Clear-write, single sweep. g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers. To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time. The average number of hops on the same channel within the regulatory observation


period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is $3 / 0.5 \times 10$, or 60 hops.

The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.

4.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23 °C	Humidity:	55 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.6.2 Test Setup Diagram:



4.6.3 Test Data:

Please Refer to Appendix for Details.

4.7 Emissions in non-restricted frequency bands


Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 7.8.7 ANSI C63.10-2020+Cor 1-2023 section 7.8.7 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	7.8.7.1 General considerations To demonstrate compliance with the relative out-of-band emissions requirements conducted spurious emissions shall be measured for the transmit frequencies, per 5.5 and 5.6, and at the maximum transmit powers. Frequency hopping shall be disabled for this test with the exception of measurements at the allocated band-edges which shall be repeated with hopping enabled. Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The frequency range of testing shall span 30 MHz to 10 times the operating frequency and this may be done in a single sweep or, to aid resolution, across a number of sweeps. The resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector. The limit is based on the highest in-band level across all channels measured using the same instrument settings (resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector). To help clearly demonstrate compliance a display line may be set at the required offset (typically 20 dB) below the highest in-band level. Where the highest in-band level is not clearly identified in the out-of-band measurements a separate spectral plot showing the in-band level shall be provided. When conducted measurements cannot be made (for example a device with integrated, non-removable antenna) radiated measurements shall be used. The reference level for determining the limit shall be established by maximizing the field strength from the highest power channel and measuring using the resolution and video bandwidth settings and peak detector as described above. The field strength limit for spurious emissions outside of restricted-bands shall then be set at the required offset (typically 20 dB) below the highest in-band level. Radiated measurements will follow the standards measurement procedures described in Clause 6 with the exception that the resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector. Note that use of wider measurement bandwidths are acceptable for measuring the spurious emissions provided that the peak detector is used and that the measured value of spurious emissions are compared to the highest in-band level measured with the 100 kHz / 300 kHz bandwidth settings to determine compliance. 7.8.7.2 Band-edges Compliance with a relative limit at the band-edges (e.g., -20 dBc) shall be made on the lowest and on the highest channels with frequency hopping disabled and repeated with frequency hopping enabled. For the latter test the hopping sequence shall include the lowest and highest channels.

	For measurements with the hopping disabled the analyzer screen shall clearly show compliance with the requirement within 10 MHz of the allocated band-edge. For measurements with the hopping enabled the analyzer screen shall clearly show compliance with the requirement within 10 MHz of both of the allocated band-edges. This could require separate spectral plots for each band-edge.
--	--

4.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23 °C	Humidity:	52 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.7.2 Test Setup Diagram:



4.7.3 Test Data:

Please Refer to Appendix for Details.

4.8 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.10.5.2		

4.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.4 °C	Humidity:	52 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.8.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	2310.000	41.41	-6.63	34.78	74.00	-39.22	peak		P	
2	2310.000	29.98	-6.63	23.35	54.00	-30.65	AVG		P	
3 *	2390.000	60.80	-6.42	54.38	74.00	-19.62	peak		P	
4	2390.000	34.85	-6.42	28.43	54.00	-25.57	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2310.000	42.97	-6.63	36.34	74.00	-37.66	peak			P	
2	2310.000	31.86	-6.63	25.23	54.00	-28.77	AVG			P	
3 *	2390.000	56.38	-6.42	49.96	74.00	-24.04	peak			P	
4	2390.000	35.97	-6.42	29.55	54.00	-24.45	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	70.75	-6.17	64.58	74.00	-9.42	peak	149		P	
2 *	2483.500	56.80	-6.17	50.63	54.00	-3.37	AVG	149		P	
3	2484.725	74.07	-6.17	67.90	74.00	-6.10	peak			P	
4	2484.750	51.78	-6.17	45.61	54.00	-8.39	AVG			P	
5	2488.675	72.61	-6.16	66.45	74.00	-7.55	peak			P	
6	2488.700	43.24	-6.16	37.08	54.00	-16.92	AVG			P	
7	2491.725	38.81	-6.15	32.66	54.00	-21.34	AVG			P	
8	2492.000	66.34	-6.15	60.19	74.00	-13.81	peak			P	
9	2500.000	53.16	-6.13	47.03	74.00	-26.97	peak	149		P	
10	2500.000	32.25	-6.13	26.12	54.00	-27.88	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	67.32	-6.17	61.15	74.00	-12.85	peak	149		P	
2	2483.500	50.68	-6.17	44.51	54.00	-9.49	AVG	149		P	
3	2484.575	69.06	-6.17	62.89	74.00	-11.11	peak			P	
4	2484.575	45.35	-6.17	39.18	54.00	-14.82	AVG			P	
5	2487.450	68.02	-6.16	61.86	74.00	-12.14	peak			P	
6 *	2487.525	51.01	-6.16	44.85	54.00	-9.15	AVG			P	
7	2488.225	45.72	-6.16	39.56	54.00	-14.44	AVG			P	
8	2488.325	67.26	-6.16	61.10	74.00	-12.90	peak			P	
9	2491.575	65.85	-6.16	59.69	74.00	-14.31	peak			P	
10	2491.650	46.59	-6.16	40.43	54.00	-13.57	AVG			P	
11	2499.125	62.52	-6.13	56.39	74.00	-17.61	peak			P	
12	2499.125	45.05	-6.13	38.92	54.00	-15.08	AVG			P	
13	2500.000	53.63	-6.13	47.50	74.00	-26.50	peak	149		P	
14	2500.000	33.69	-6.13	27.56	54.00	-26.44	AVG	149		P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be of GFSK recorded in the test report.

4.9 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Remark: 1) For emission below 1GHz, through pre-scan found the worst case is the lowest		


	channel. Only the worst case is recorded in the report. 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
--	---

4.9.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.4 °C	Humidity:	49 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.9.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	30.0000	39.64	-4.07	35.57	40.00	-4.43	QP			P	
2	35.7490	40.06	-6.10	33.96	40.00	-6.04	QP			P	
3	53.8817	47.74	-13.93	33.81	40.00	-6.19	QP			P	
4	122.8340	40.13	-6.87	33.26	43.50	-10.24	QP			P	
5	221.3920	43.14	-9.75	33.39	46.00	-12.61	QP			P	
6	270.3747	40.84	-8.59	32.25	46.00	-13.75	QP			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	31.9544	34.36	-2.75	31.61	40.00	-8.39	QP			P	
2	53.3180	40.33	-13.83	26.50	40.00	-13.50	QP			P	
3	72.0841	32.40	-12.88	19.52	40.00	-20.48	QP			P	
4	147.4036	28.41	-7.58	20.83	43.50	-22.67	QP			P	
5	270.3747	41.75	-8.68	33.07	46.00	-12.93	QP			P	
6	614.2142	29.76	-1.31	28.45	46.00	-17.55	QP			P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be of GFSK recorded in the test report.

4.10 Emissions in frequency bands (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Remark:		


	1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report. 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
--	--

4.10.1E.U.T. Operation:

Operating Environment:					
Temperature:	22.6 °C	Humidity:	53 %	Atmospheric Pressure:	101.5 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.10.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	4877.500	58.94	-0.45	58.49	74.00	-15.51	peak		P	
2 *	4877.500	42.24	-0.45	41.79	54.00	-12.21	AVG		P	
3	7309.750	40.98	4.55	45.53	74.00	-28.47	peak		P	
4	7309.750	31.87	4.55	36.42	54.00	-17.58	AVG		P	
5	10740.750	38.68	9.18	47.86	74.00	-26.14	peak		P	
6	10740.750	25.91	9.18	35.09	54.00	-18.91	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4807.000	51.65	-0.69	50.96	74.00	-23.04	peak			P	
2	4807.000	35.86	-0.69	35.17	54.00	-18.83	AVG			P	
3	9319.000	38.33	8.17	46.50	74.00	-27.50	peak			P	
4	9319.000	26.14	8.17	34.31	54.00	-19.69	AVG			P	
5	12738.250	38.05	11.42	49.47	74.00	-24.53	peak			P	
6 *	12738.250	25.15	11.42	36.57	54.00	-17.43	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	51.11	-0.45	50.66	74.00	-23.34	peak			P	
2	4877.500	36.12	-0.45	35.67	54.00	-18.33	AVG			P	
3	9354.250	38.66	8.15	46.81	74.00	-27.19	peak			P	
4	9354.250	26.47	8.15	34.62	54.00	-19.38	AVG			P	
5	11951.000	38.24	9.97	48.21	74.00	-25.79	peak			P	
6 *	11951.000	26.00	9.97	35.97	54.00	-18.03	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	48.33	-0.45	47.88	74.00	-26.12	peak			P	
2	4877.500	33.59	-0.45	33.14	54.00	-20.86	AVG			P	
3	9342.500	38.65	8.16	46.81	74.00	-27.19	peak			P	
4	9342.500	26.38	8.16	34.54	54.00	-19.46	AVG			P	
5	12691.250	37.97	11.34	49.31	74.00	-24.69	peak			P	
6 *	12691.250	24.90	11.34	36.24	54.00	-17.76	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	51.50	-0.45	51.05	74.00	-22.95	peak			P	
2 *	4877.500	36.46	-0.45	36.01	54.00	-17.99	AVG			P	
3	9342.500	38.54	8.16	46.70	74.00	-27.30	peak			P	
4	9342.500	26.18	8.16	34.34	54.00	-19.66	AVG			P	
5	11798.250	38.38	9.87	48.25	74.00	-25.75	peak			P	
6	11798.250	25.50	9.87	35.37	54.00	-18.63	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	4959.750	42.72	-0.17	42.55	74.00	-31.45	peak		P	
2	4959.750	29.51	-0.17	29.34	54.00	-24.66	AVG		P	
3	9330.750	37.61	8.16	45.77	74.00	-28.23	peak		P	
4	9330.750	26.02	8.16	34.18	54.00	-19.82	AVG		P	
5	12374.000	37.46	10.77	48.23	74.00	-25.77	peak		P	
6 *	12374.000	25.19	10.77	35.96	54.00	-18.04	AVG		P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor


The test software will only record the worst test angle and height, and only the worst case will be of GFSK recorded in the test report.

5 TEST SETUP PHOTOS

Conducted Emission at AC power line



Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)

6 PHOTOS OF THE EUT


Refer to Appendix - EUT Photos for EUT External Photo and Internal Photo.

Appendix



1. Duty Cycle


Condition	Antenna	Rate	Frequency (MHz)	Dutycycle(%)	Duty_factor
NVNT	ANT1	1-DH5	2402.00	78.19	1.07
NVNT	ANT1	1-DH5	2441.00	78.07	1.07
NVNT	ANT1	1-DH5	2480.00	78.19	1.07
NVNT	ANT1	2-DH5	2402.00	77.66	1.10
NVNT	ANT1	2-DH5	2441.00	78.61	1.05
NVNT	ANT1	2-DH5	2480.00	78.19	1.07
NVNT	ANT1	3-DH5	2402.00	77.66	1.10
NVNT	ANT1	3-DH5	2441.00	78.07	1.07
NVNT	ANT1	3-DH5	2480.00	78.19	1.07

Duty_Cycle_NVNT_ANT1_1-DH5_2402




Duty_Cycle_NVNT_ANT1_1-DH5_2441









Duty Cycle_NVNT_ANT1_2-DH5_2441



Duty Cycle_NVNT_ANT1_2-DH5_2480







2. -20dB Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	if larger than CFS
NVNT	ANT1	1-DH5	2402.00	0.930	No
NVNT	ANT1	1-DH5	2441.00	0.929	No
NVNT	ANT1	1-DH5	2480.00	0.925	No
NVNT	ANT1	2-DH5	2402.00	1.287	Yes
NVNT	ANT1	2-DH5	2441.00	1.286	Yes
NVNT	ANT1	2-DH5	2480.00	1.288	Yes
NVNT	ANT1	3-DH5	2402.00	1.292	Yes
NVNT	ANT1	3-DH5	2441.00	1.301	Yes
NVNT	ANT1	3-DH5	2480.00	1.296	Yes

-20dB_Bandwidth_NVNT_ANT1_1-DH5_2402_00




-20dB_Bandwidth_NVNT_ANT1_1-DH5_2441_00







-20dB_Bandwidth_NVNT_ANT1_2-DH5_2480_00




-20dB_Bandwidth_NVNT_ANT1_3-DH5_2441_00






3. 99% Occupied Bandwidth




Condition	Antenna	Modulation	Frequency (MHz)	99%OBW(MHz)
NVNT	ANT1	1-DH5	2402.00	0.830
NVNT	ANT1	1-DH5	2441.00	0.829
NVNT	ANT1	1-DH5	2480.00	0.833
NVNT	ANT1	2-DH5	2402.00	1.175
NVNT	ANT1	2-DH5	2441.00	1.174
NVNT	ANT1	2-DH5	2480.00	1.172
NVNT	ANT1	3-DH5	2402.00	1.183
NVNT	ANT1	3-DH5	2441.00	1.180
NVNT	ANT1	3-DH5	2480.00	1.181




99%_Occupied_Bandwidth_NVNT_ANT1_1-DH5_2402_00





99%_Occupied_Bandwidth_NVNT_ANT1_1-DH5_2441_00












4. Peak Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1-DH5	2402.00	-0.54	0.88	1000	Pass
NVNT	ANT1	1-DH5	2441.00	-1.47	0.71	1000	Pass
NVNT	ANT1	1-DH5	2480.00	-2.99	0.50	1000	Pass
NVNT	ANT1	2-DH5	2402.00	1.76	1.50	125	Pass
NVNT	ANT1	2-DH5	2441.00	0.98	1.25	125	Pass
NVNT	ANT1	2-DH5	2480.00	-0.41	0.91	125	Pass
NVNT	ANT1	3-DH5	2402.00	2.27	1.69	125	Pass
NVNT	ANT1	3-DH5	2441.00	1.43	1.39	125	Pass
NVNT	ANT1	3-DH5	2480.00	-0.05	0.99	125	Pass



Peak Output Power NVNT ANT1 1-DH5 2402 00





Peak Output Power NVNT ANT1 1-DH5 2441 00





Peak Output Power_NVNT_ANT1_2-DH5_2402_00



Peak Output Power_NVNT_ANT1_2-DH5_2480_00







5. Spurious Emissions

Condition	Antenna	Modulation	TX Mode	Ref_level(dBm)	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1-DH5	2402.00	-0.703	-35.575	-20.703	Pass
NVNT	ANT1	1-DH5	2441.00	-1.608	-38.707	-21.608	Pass
NVNT	ANT1	1-DH5	2480.00	-3.169	-38.353	-23.169	Pass
NVNT	ANT1	2-DH5	2402.00	-0.782	-38.690	-20.782	Pass
NVNT	ANT1	2-DH5	2441.00	-1.419	-40.276	-21.419	Pass
NVNT	ANT1	2-DH5	2480.00	-2.982	-34.297	-22.982	Pass
NVNT	ANT1	3-DH5	2402.00	-0.736	-38.190	-20.736	Pass
NVNT	ANT1	3-DH5	2441.00	-1.567	-38.890	-21.567	Pass
NVNT	ANT1	3-DH5	2480.00	-3.089	-37.118	-23.089	Pass

1 Reference Level NVNT ANT1 1-DH5 2402 00




2 Spurious Emissions NVNT ANT1 1-DH5 2402 00



1 Reference_Level_NVNT_ANT1_1-DH5_2441_00




2 Spurious Emissions_NVNT_ANT1_1-DH5_2441_00




1 Reference_Level_NVNT_ANT1_1-DH5_2480_00




2 Spurious Emissions_NVNT_ANT1_1-DH5_2480_00




1 Reference_Level_NVNT_ANT1_2-DH5_2402_00




2 Spurious Emissions_NVNT_ANT1_2-DH5_2402_00




1 Reference_Level_NVNT_ANT1_2-DH5_2441_00




2 Spurious Emissions_NVNT_ANT1_2-DH5_2441_00




1 Reference_Level_NVNT_ANT1_2-DH5_2480_00




2 Spurious_Emissions_NVNT_ANT1_2-DH5_2480_00



1 Reference_Level_NVNT_ANT1_3-DH5_2402_00




2 Spurious Emissions_NVNT_ANT1_3-DH5_2402_00




1 Reference_Level_NVNT_ANT1_3-DH5_2441_00




2 Spurious Emissions_NVNT_ANT1_3-DH5_2441_00



1 Reference_Level_NVNT_ANT1_3-DH5_2480_00




2 Spurious Emissions_NVNT_ANT1_3-DH5_2480_00




6. Bandedge

Condition	Antenna	Modulation	TX Mode	Ref_level(dBm)	Bandedge MAX.Value	Limit	Result
NVNT	ANT1	1-DH5	2402.00	-0.703	-52.667	-20.703	Pass
NVNT	ANT1	1-DH5	Hopping_LCH	-0.737	-59.729	-20.737	Pass
NVNT	ANT1	1-DH5	2480.00	-3.169	-59.391	-23.169	Pass
NVNT	ANT1	1-DH5	Hopping_HCH	-0.656	-60.526	-20.656	Pass
NVNT	ANT1	2-DH5	2402.00	-0.782	-54.139	-20.782	Pass
NVNT	ANT1	2-DH5	Hopping_LCH	-0.726	-57.628	-20.726	Pass
NVNT	ANT1	2-DH5	2480.00	-2.982	-59.936	-22.982	Pass
NVNT	ANT1	2-DH5	Hopping_HCH	-0.697	-60.005	-20.697	Pass
NVNT	ANT1	3-DH5	2402.00	-0.736	-53.961	-20.736	Pass
NVNT	ANT1	3-DH5	Hopping_LCH	-0.728	-57.544	-20.728	Pass
NVNT	ANT1	3-DH5	2480.00	-3.089	-58.961	-23.089	Pass
NVNT	ANT1	3-DH5	Hopping_HCH	-0.751	-62.377	-20.751	Pass


1_Reference_Level_NVNT_ANT1_1-DH5_2402_00




2_Bandedge_NVNT_ANT1_1-DH5_2402_00



1 Reference_Level_Hopping_NVNT_ANT1_1-DH5_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_1-DH5_Hopping




1 Reference_Level_NVNT_ANT1_1-DH5_2480_00




2 Bandedge_NVNT_ANT1_1-DH5_2480_00




1 Reference Level Hopping NVNT_ANT1_1-DH5_Hopping




2 Band Edge (Hopping) NVNT_ANT1_1-DH5_Hopping




1 Reference_Level_NVNT_ANT1_2-DH5_2402_00




2 Bandedge_NVNT_ANT1_2-DH5_2402_00




1 Reference_Level_Hopping_NVNT_ANT1_2-DH5_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_2-DH5_Hopping




1 Reference_Level_NVNT_ANT1_2-DH5_2480_00




2 Bandedge_NVNT_ANT1_2-DH5_2480_00




1 Reference_Level_Hopping_NVNT_ANT1_2-DH5_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_2-DH5_Hopping




1 Reference_Level_NVNT_ANT1_3-DH5_2402_00




2 Bandedge_NVNT_ANT1_3-DH5_2402_00




1 Reference Level Hopping NVNT_ANT1_3-DH5_Hopping




2 Band Edge (Hopping) NVNT_ANT1_3-DH5_Hopping




1 Reference_Level_NVNT_ANT1_3-DH5_2480_00




2 Bandedge_NVNT_ANT1_3-DH5_2480_00



1 Reference_Level_Hopping_NVNT_ANT1_3-DH5_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_3-DH5_Hopping




7. Carrier Frequencies Separation (Hopping)

Condition	Antenna	Modulation	Frequency(MHz)	Hopping NO.0 (MHz)	Hopping NO.1 (MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	1-DH5	2441.00	2440.831	2441.833	1.00	0.929	Pass
NVNT	ANT1	2-DH5	2441.00	2440.831	2442.151	1.32	0.857	Pass
NVNT	ANT1	3-DH5	2441.00	2440.822	2441.827	1.00	0.867	Fail


Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_1-DH5_Hopping



Carrier_Frequencies_Separation_(Hopping) NVNT_ANT1_2-DH5_Hopping




Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_3-DH5_Hopping




8. Number of Hopping Channel (Hopping)

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	1-DH5	79	15	Pass
NVNT	ANT1	2-DH5	79	15	Pass
NVNT	ANT1	3-DH5	79	15	Pass


Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_1-DH5_Hopping



Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_2-DH5_Hopping




Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_3-DH5_Hopping





9. Dwell Time (Hopping)

Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	1-DH5	2.930	107.00	313.510	0.40	Pass
NVNT	ANT1	2-DH5	2.930	94.00	275.420	0.40	Pass
NVNT	ANT1	3-DH5	2.940	92.00	270.480	0.40	Pass
NVNT	ANT1	1-DH1	0.420	319.00	133.980	0.40	Pass
NVNT	ANT1	1-DH3	1.680	172.00	288.960	0.40	Pass
NVNT	ANT1	2-DH1	0.430	321.00	138.030	0.40	Pass
NVNT	ANT1	2-DH3	1.690	146.00	246.740	0.40	Pass
NVNT	ANT1	3-DH1	0.430	320.00	137.600	0.40	Pass
NVNT	ANT1	3-DH3	1.680	155.00	260.400	0.40	Pass



Dwell_Time_(Hopping)_NVNT_ANT1_1-DH5_2441_00_One_Burst_Time





Dwell_Time_(Hopping)_NVNT_ANT1_1-DH5_2441_00_Accumulated





Dwell_Time_(Hopping)_NVNT_ANT1_2-DH5_2441_00_Accumulated









Dwell_Time_(Hopping)_NVNT_ANT1_1-DH1_2441_00_Accumulated





Dwell_Time_(Hopping)_NVNT_ANT1_1-DH3_2441_00_Accumulated





Dwell_Time_(Hopping)_NVNT_ANT1_2-DH1_2441_00_Accumulated




Dwell_Time_(Hopping)_NVNT_ANT1_2-DH3_2441_00_Accumulated



Dwell_Time_(Hopping)_NVNT_ANT1_3-DH1_2441_00_Accumulated



Dwell_Time_(Hopping)_NVNT_ANT1_3-DH3_2441_00_Accumulated



***** End of Report *****