

Test Report No:
2620024R-RFUSV07S-A

TEST REPORT

FCC Rules & Regulations

Product Name	e-bike
Brand Name	ALSO
Model No.	TMB-CON
FCC ID	2BVBP-TMB-CON
Contains FCC ID	2ANPO00NRF9151
Applicant's Name / Address	ALSO INC 450 Lambert Ave, Palo Alto, CA 94306 USA
Manufacturer's Name	ALSO INC
Test Method Requested, Standard	FCC CFR Title 47 Part 15 Subpart C Section 15.225
Verdict Summary	IN COMPLIANCE
Documented by Jinn Chen	
Approved by Alan Chen	
Date of Receipt	2026/02/02
Date of Issue	2026/06/02
Report Version	V1.0

INDEX

	page
Competences and Guarantees.....	4
General Conditions.....	4
Revision History.....	5
Summary of Test Result.....	6
1. General Information.....	7
1.1. EUT Description	7
1.2. EUT Information	8
1.3. Testing Location Information	8
1.4. Measurement Uncertainty	9
1.5. List of Test Equipment	10
2. Test Configuration of EUT.....	11
2.1. Test Condition.....	11
2.2. Test Frequency Mode.....	11
2.3. Measurement Configuration	11
2.4. Tested System Details	12
2.5. Configuration of Tested System	12
2.6. EUT Operating Procedures	13
3. AC Power Line Conducted Emission	14
3.1. Test Setup.....	14
3.2. Test Limit	14
3.3. Test Procedure	14
3.4. Test Result of AC Power Line Conducted Emission.....	14
4. Emission Bandwidth	15
4.1. Test Setup.....	15
4.2. Test Limit	15
4.3. Test Procedures.....	15
4.4. Test Result of Emission Bandwidth	15
5. Frequency Stability	16
5.1. Test Setup.....	16
5.2. Test Limit	16
5.3. Test Procedures.....	16
5.4. Test Result of Frequency Stability	16
6. Field Strength of Fundamental Emissions and Spectrum Mask	17
6.1. Test Setup.....	17
6.2. Test Limit	17
6.3. Test Procedure	18

6.4.	Test Result of Field Strength of Fundamental Emissions and Spectrum Mask	18
7.	Radiated Emission.....	19
7.1.	Test Setup.....	19
7.2.	Test Limit	20
7.3.	Test Procedure	20
7.4.	Test Result of Radiated Emission.....	21
Appendix A.	Test Result of AC Power Line Conducted Emission	
Appendix B.	Test Result of Emission Bandwidth	
Appendix C.	Test Result of Frequency Stability	
Appendix D.	Test Result of Field Strength of Fundamental Emissions and Spectrum Mask	
Appendix E.	Test Result of Radiated Emission	
Appendix F.	Test Setup Photograph	

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	2026/06/02

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
3	AC Power Line Conducted Emission	N/A	-
4	Emission Bandwidth	PASS	-
6	Field Strength of Fundamental Emissions and Spectrum Mask	PASS	-
7	Radiated Emission	PASS	-
5	Frequency Stability	PASS	-

Comments and Explanations

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1. General Information

1.1. EUT Description

Frequency Range	13.553 ~ 13.567 MHz
Operation Frequency	13.56 MHz
Channel Number	1 Channel
Type of Modulation	ASK

Antenna Information		
Item.	Brand Name	Type
1	Hong-Bo	Loop

1.2. EUT Information

EUT Power Type	From Battery
----------------	--------------

1.3. Testing Location Information

USA	FCC Designation Number: TW0033 / FCC Registration Number: 647365
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No. 85, Wenlin St., Linkou Dist., New Taipei City 244017, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual	Test Date	Tested By
RF Conducted Emission	Temperature (°C)	10~40 °C	22.3~24.1 °C	2026/02/24 ~ 2026/03/09	NEKO
	Humidity (%RH)	10~90 %	53.5~65.6 %		
Radiated Emission	Temperature (°C)	10~40 °C	24.2~24.3 °C	2026/01/22 ~ 2026/03/05	Nova Chu
	Humidity (%RH)	10~90 %	60~63.5 %		

1.4. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.

The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
AC Power Line Conducted Emission	± 3.50 dB
Emission Bandwidth	± 1580.61 Hz
Field Strength of Fundamental Emissions and Spectrum Mask	± 3.88 dB
Radiated Emission	9 kHz~30 MHz: ± 3.30 dB 30 MHz~1 GHz: ± 5.19 dB 1 GHz~18 GHz: ± 4.46 dB
Frequency Stability	± 1580.61 Hz

1.5. List of Test Equipment

For Conducted measurements / HY-SR03

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Temperature Chamber	KSON	THS-D4T-100	A0606	2026/02/24	2027/02/23
V	DC Power Supply	KEYSIGHT	E36234A	MY59001234	2025/10/27	2026/10/26
V	Spectrum Analyzer	R&S	FSV30	103464	2025/06/19	2026/06/18

Note:

1. All equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.

For Radiated Measurements /HY-CB02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Loop Antenna	AMETEK	HLA6121	49611	2025/02/18	2026/02/17
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0675	2025/08/14	2027/08/13
	Horn Antenna	Com-Power	AH-840	101100	2025/10/07	2027/10/06
	Horn Antenna	RF SPIN	DRH18-E	210503A18ES	2026/02/06	2028/02/05
V	Pre-Amplifier	Queitek	MPA0301	AP-180C	2026/01/10	2027/01/09
	Pre-Amplifier	SGH	PRAMP118	20200203	2026/01/10	2027/01/09
	Pre-Amplifier	EMCI	EMC05820SE	980285	2026/01/10	2027/01/09
	Pre-Amplifier	EMCI	EMC184045SE	980369	2026/01/10	2027/01/09
	Coaxial Cable	EMCI	EMC102-KM-KM-600	160311	2026/01/10	2027/01/09
	Coaxial Cable	SGH	HC360-2.92M/2.92M-7.0M	202108-1	2026/01/10	2027/01/09
V	EMI Test Receiver	R&S	ESR3	102793	2025/12/01	2026/11/30
V	Spectrum Analyzer	R&S	FSV3044	101113	2025/12/23	2026/12/22
V	Coaxial Cable	SGH	HA800	GD20110223-2	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800	GD20110222-4	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	SGH18	202108-5	2026/01/10	2027/01/09
V	Coaxial Cable	SGH	HA800-SMASMA-10M	202212-1	2026/01/10	2027/01/09

Note:

1. Bi-Log Antenna and Horn Antenna are calibrated every two years, the other equipment is calibrated every year.
2. The test instruments marked with "V" are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition			
Testing Voltage	V _{nom} (DC 12V)	V _{min} (DC 10.2V)	V _{max} (DC 13.8V)

2.2. Test Frequency Mode

Test Software Version	cmd / Version 10.0.26100.7840
-----------------------	-------------------------------

Modulation	Frequency (MHz)	Power Setting
ASK	13.56	N/A

2.3. Measurement Configuration

Test Mode	Mode 1	Transmit
-----------	--------	----------


Note:

1. Determining compliance shall be based on the results of the compliance measurement, without taking measurement instrumentation uncertainty into account.
2. For radiated emissions below 1 GHz, all modes of operation were investigated, and the worst-case emissions are reported.

2.4. Tested System Details

No.	Equipment	Brand Name	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	Latitude 5501	GS9GL13	N/A
2	Test Fixture	ALSO	N/A	N/A	N/A
3	REAR BRAKE	ALSO	N/A	N/A	N/A
4	HU	ALSO	N/A	N/A	N/A
5	FRONT BRAKE LEVER	ALSO	N/A	N/A	N/A
6	Battery	BOSCH	60044	N/A	N/A

2.5. Configuration of Tested System




2.6. EUT Operating Procedures

1	Setup the EUT as shown in Section 2.5.
2	Execute software “cmd / Version 10.0.26100.7840” on the Notebook PC.
3	Configure the test mode.
4	Verify that the EUT works properly.

3. AC Power Line Conducted Emission

3.1. Test Setup



3.2. Test Limit

Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

3.3. Test Procedure


The EUT was setup according to ANSI C63.10-2020 for AC Power Line Conducted Emissions.

3.4. Test Result of AC Power Line Conducted Emission

Refer as Appendix A

4. Emission Bandwidth

4.1. Test Setup



4.2. Test Limit

Intentional radiators must be designed to ensure that the 20dB emission bandwidth in the specific band 13.553 ~ 13.567 MHz.

4.3. Test Procedures


1. For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.
2. Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

4.4. Test Result of Emission Bandwidth

Refer as Appendix B

5. Frequency Stability

5.1. Test Setup



5.2. Test Limit

Carrier frequency stability shall be maintained to $\pm 0.01\%$ (± 100 ppm).

5.3. Test Procedures

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.


For battery operated equipment, the equipment tests shall be performed using a new battery.

5.4. Test Result of Frequency Stability

Refer as Appendix C

6. Field Strength of Fundamental Emissions and Spectrum Mask

6.1. Test Setup



6.2. Test Limit

Field Strength of Fundamental Emissions			
Frequencies (MHz)	Field Strength (microvolts/meter) at 30m	Field Strength (dB μ V/m) at 10m	Field Strength (dB μ V/m) at 3m
13.553 – 13.567 MHz	15848	103.08 (QP)	124 (QP)
Quasi peak measurement of the fundamental.			

Spectrum Mask					
Description	Compliance with the spectrum mask is tested using a spectrum analyzer with RBW set to a 9kHz for the band 13.553 – 13.567 MHz.				
Limit	Freq. of Emission (MHz)	Field Strength			
		(μ V/m)@30m	(dB μ V/m)@30m	(dB μ V/m)@10m	(dB μ V/m)@3m
	1.705~13.110	30	29.5	48.6	69.5
	13.110~13.410	106	40.5	59.6	80.5
	13.410~13.553	334	50.5	69.6	90.5
	13.553~13.567	15848	84.0	103.1	124.0
	13.567~13.710	334	50.5	69.6	90.5
	13.710~14.010	106	40.5	59.6	80.5
	14.010~30.000	30	29.5	48.6	69.5

6.3. Test Procedure

1. Configure the EUT according to ANSI C63.10-2020. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested using a spectrum analyzer with RBW set to a 9 kHz for the band 13.553 – 13.567 MHz.


6.4. Test Result of Field Strength of Fundamental Emissions and Spectrum Mask

Refer as Appendix D


7. Radiated Emission

7.1. Test Setup

9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



7.2. Test Limit

The field strength of any emissions which appear outside of 13.553 ~ 13.567MHz band shall not exceed the general radiated emissions limits.

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	20 log (2400/F(kHz))	300
0.490 – 1.705	24000/F(kHz)	20 log (24000/F(kHz))	30
1.705 - 30	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Remarks:

1. Field strength ($\text{dB}\mu\text{V/m}$) = 20 log Field strength ($\mu\text{V/m}$)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

7.3. Test Procedure

1. Configure the EUT according to ANSI C63.10-2020 . The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

7.4. Test Result of Radiated Emission

Refer as Appendix E