

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road,
Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation**Report Reference No. : GTS20251203023-1-06****FCC ID. : 2BVC3DJ-VEND100**

Compiled by


(position+printed name+signature): File administrators Peter Xiao

Supervised by

(position+printed name+signature): Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) : Manager Jason Hu



Date of issue : Mar.13, 2026

Representative Laboratory Name : Shenzhen Global Test Service Co.,Ltd.

..... :

Address

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and
Creative Garden, No.98, Pingxin North Road, Shangmugu
Community, Pinghu Street, Longgang District, Shenzhen,
Guangdong

Applicant's name..... : ACCU-Drop LLC

Address : 590 N. Sierra Way, San Bernardino, CA 92410

Test specification

Standard..... : 47CFR §1.1310 Basis and purpose
47CFR §2.1091 Radiofrequency radiation exposure evaluation:
mobile devices
TRF Originator : Shenzhen Global Test Service Co.,Ltd.
Master TRF : Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the
Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material.
Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages
resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : Vending Machine

Trade Mark : N/A

Manufacturer : Guangdong Dongji Intelligent Device Co. Ltd

Model/Type reference : DJ-VEND-100

Listed Models : DJ-VEND-200, DJ-VEND-300, DJ-VEND-600

Hardware Version : N/A

Software Version : N/A

Rating : AC 110.0-220.0V, 50/60Hz

Result : **PASS**

TEST REPORT

Test Report No. :	GTS20251203023-1-06	Mar.13, 2026
		Date of issue

Equipment under Test : Vending Machine

Model /Type : DJ-VEND-100

Listed model : DJ-VEND-200, DJ-VEND-300, DJ-VEND-600

Applicant : **ACCU-Drop LLC**

Address : 590 N. Sierra Way, San Bernardino, CA 92410

Manufacturer : **Guangdong Dongji Intelligent Device Co. Ltd.**

Address : No. 30, Duruan Middle Rd., Duruan Town, Pengjiang District, Jiangmen, Guangdong, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY 4

1.1 EUT CONFIGURATION..... 4

1.2 PRODUCT DESCRIPTION 4

2. TEST ENVIRONMENT 6

2.1 ADDRESS OF THE TEST LABORATORY 6

2.2 TEST FACILITY 6

2.3 ENVIRONMENTAL CONDITIONS 6

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 6

3. METHOD OF MEASUREMENT 7

3.1 APPLICABLE STANDARD..... 7

3.2 REQUIREMENT 7

3.3 LIMIT 7

3.4 MPE CALCULATION METHOD 8

3.5 ANTENNA INFORMATION 8

4. CONDUCTED POWER RESULTS..... 9

5. MANUFACTURING TOLERANCE 11

6. MEASUREMENT RESULTS 14

6.1 STANDALONE MPE EVALUATION..... 14

6.2 SIMULTANEOUS TRANSMISSION MPE 15

7. CONCLUSION 16

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○ /	M/N: /
	Manufacturer: /

1.2 Product Description

Product Name:	Vending Machine
Trade Mark:	N/A
Model/Type reference:	DJ-VEND-100
List Model:	DJ-VEND-600 DJ-VEND-200, DJ-VEND-300,
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	AC 110.0-220.0V, 50/60Hz
Hardware Version	N/A
Software Version	N/A
Sample ID	GTS20251203023-1-S001-1#>S20251203023-1-S001-2#
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	79 channels for Bluetooth (DSS) 40 channels for Bluetooth (DTS)
Channel Spacing	1MHz for Bluetooth (DSS) 2MHz for Bluetooth (DTS)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK for Bluetooth (DSS) GFSK for Bluetooth (DTS)
2.4GWLAN	
WLAN Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz IEEE 802.11ax HE20:2412-2462MHz IEEE 802.11ax HE40:2422-2452MHz
WLAN Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE40: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel number:	11 Channel for IEEE 802.11b/g/n/ax (HT20) 7 Channel for IEEE 802.11n/ax (HT40)
Channel separation:	5MHz
WIFI(5.2G/5.8G Band)	
WLAN Operation frequency	5180MHz to 5240MHz/ 5745MHz to 5825MHz
WLAN Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)

	IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11acVHT20: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11acVHT40: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE40: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel number:	4 Channels for 20MHz bandwidth(5180-5240MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5755~5795MHz)
Antenna Description	InternalAntenna, 2.95dBi(Max.) for 2.4G Band and2.28dBi(Max.) for 5G Band
LTE	
LTE Operation Frequency Band	E-UTRA Band 2(1850 MHz -1910MHz) E-UTRA Band 4(1710 MHz -1755MHz) E-UTRA Band 12(699 MHz -716MHz)
LTE Release Version	R10
Type Of Modulation	QPSK/16QAM
Antenna Description	Internal Antenna; 0dBi (max.) For LTE Band 2; 0dBi (max.) For LTE Band 4; 0dBi (max.) For LTE Band 12;
GPS(RX)	Support

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Global Test Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT's maximum duty cycle transmission based on the appendix, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 2.95dBi&2.28dBi for BT&WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

DJ-VEND-100 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	BT&WLAN ANT 1	Internal Antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	2.95dBi(Max.) for 2.4G band 2.28dBi(Max.) for 5G band
Antenna2	LTE ANT 2	InternalAntenna	600 MHz -800MHz 1700 MHz -3000MHz	0dBi (max.) For LTE Band2; 0dBi (max.) For LTE Band 4; 0dBi (max.) For LTE Band 12;

4. Conducted Power Results

Antenna 1:

Bluetooth

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	8.19
	39	2441	8.57
	78	2480	8.48
$\pi/4$ DQPSK	0	2402	10.52
	39	2441	10.95
	78	2480	10.78
8DPSK	0	2402	10.63
	39	2440	11.14
	78	2480	10.97
GFSK(BT LE)	0	2402	8.18
	19	2440	8.63
	39	2480	8.44

2.4G WLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	11.61
	06	2437	12.14
	11	2462	12.82
802.11g	01	2412	13.60
	06	2437	14.45
	11	2462	15.22
802.11n(HT20)	01	2412	13.57
	06	2437	14.38
	11	2462	15.21
802.11n(HT40)	03	2422	13.29
	06	2437	14.40
	09	2452	14.75
802.11ax(HE20)	01	2412	14.23
	06	2437	15.01
	11	2462	15.75
802.11ax(HE40)	03	2422	13.87
	06	2437	14.90
	09	2452	15.17

5.2GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	13.27
	40	5200	13.20
	48	5240	13.37
802.11n20	36	5180	12.85
	40	5200	13.11
	48	5240	13.03
802.11n40	38	5190	12.44
	46	5230	13.23
802.11ac20	36	5180	12.38
	40	5200	12.41
	48	5240	12.77
802.11ac40	38	5190	12.46
	46	5230	12.87
802.11ax20	36	5180	12.81
	40	5200	12.90
	48	5240	13.17
802.11ax40	38	5190	12.26
	46	5230	12.73

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	10.63
	157	5785	10.83
	165	5825	11.48
802.11n20	149	5745	10.30
	157	5785	11.00
	165	5825	11.59
802.11n40	151	5755	10.15
	159	5795	11.04
802.11ac20	149	5745	10.58
	157	5785	10.97
	165	5825	11.59
802.11ac40	151	5755	10.38
	159	5795	10.99
802.11ax20	149	5745	10.65
	157	5785	10.99
	165	5825	11.60
802.11ax40	151	5755	10.47
	159	5795	11.06

Antenna 2:**LTE Max Conducted Power**

Test Mode		Channel	Max Conducted Power(dBm)
LTE	Band 2	LCH	22.30
		MCH	22.36
		HCH	22.51
	Band 4	LCH	22.97
		MCH	22.81
		HCH	23.15
	Band 12	LCH	23.61
		MCH	23.85
		HCH	24.30

5. Manufacturing Tolerance

Antenna 1:

Bluetooth

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8.00	8.00	8.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	10.00	10.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	10.00	11.00	10.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
GFSK BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	8.00	8.00	8.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	11.00	12.00	12.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.00	14.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	13.00	14.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	13.00	14.00	14.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	14.00	15.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	13.00	14.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.00	13.00	13.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.00	13.00	13.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	12.00	13.00	
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.00	12.00	12.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	12.00	12.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ax HE20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.00	12.00	13.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	12.00	12.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	10.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	11.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	10.00	11.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ac VHT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	10.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	10.00	10.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/
IEEE 802.11ax HE20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.00	10.00	11.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE40 (Average)			
Channel	Channel 151	Channel 159	/
Target (dBm)	10.00	11.00	/
Tolerance $\pm$ (dB)	1.0	1.0	/

Antenna 2:**LTE**

Mode	Target Power
LTE BAND 2	22 ± 1.0 dBm
LTE BAND 4	23 ± 1.0 dBm
LTE BAND 12	24 ± 1.0 dBm

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Antenna 1:

BT

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	9.00	7.9433	2.95	1.9724	0.0031	1.0000
$\pi/4$ DQPSK	11.00	12.5893	2.95	1.9724	0.0049	1.0000
8DPSK	12.00	15.8489	2.95	1.9724	0.0062	1.0000
GFSK(BT LE)	9.00	7.9433	2.95	1.9724	0.0031	1.0000

2.4G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	13.00	19.9526	2.95	1.9724	0.0078	1.0000
802.11g	16.00	39.8107	2.95	1.9724	0.0156	1.0000
802.11n(HT20)	16.00	39.8107	2.95	1.9724	0.0156	1.0000
802.11n(HT40)	15.00	31.6228	2.95	1.9724	0.0124	1.0000
802.11ax(HE20)	16.00	39.8107	2.95	1.9724	0.0156	1.0000
802.11ax(HE40)	16.00	39.8107	2.95	1.9724	0.0156	1.0000

5.2G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	14.00	25.1189	2.28	1.6904	0.0084	1.0000
802.11n20	14.00	25.1189	2.28	1.6904	0.0084	1.0000
802.11n40	14.00	25.1189	2.28	1.6904	0.0084	1.0000
802.11ac20	13.00	19.9526	2.28	1.6904	0.0067	1.0000
802.11ac40	13.00	19.9526	2.28	1.6904	0.0067	1.0000
802.11ax20	14.00	25.1189	2.28	1.6904	0.0084	1.0000
802.11ax40	13.00	19.9526	2.28	1.6904	0.0067	1.0000

5.8GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	12.00	15.8489	2.28	1.6904	0.0053	1.0000
802.11n20	12.00	15.8489	2.28	1.6904	0.0053	1.0000
802.11n40	12.00	15.8489	2.28	1.6904	0.0053	1.0000
802.11ac20	12.00	15.8489	2.28	1.6904	0.0053	1.0000
802.11ac40	11.00	12.5893	2.28	1.6904	0.0042	1.0000
802.11ax20	12.00	15.8489	2.28	1.6904	0.0053	1.0000
802.11ax40	12.00	15.8489	2.28	1.6904	0.0053	1.0000

Antenna 2:**LTE**

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
LTE BAND 2	23.00	199.5262	0	1.0000	0.0397	1.00
LTE BAND 4	24.00	251.1886	0	1.0000	0.0500	1.00
LTE BAND 12	25.00	316.2278	0	1.0000	0.0629	0.47

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

6.2 Simultaneous Transmission MPE

The sample support one BT&WLAN modular,one LTE modular,and oneBT&WLAN antenna, and oneLTE antenna, Need consider simultaneous transmission ;

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$ of MPE ratios ≤ 1.0

6.2.1 Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for **2.4GWLAN, LTE band 12.**

Maximum MPE ratio 2.4GWLAN	Maximum MPE ratio LTE band 4	$\sum$ MPE ratios	Limit	Results
0.0156	0.1338	0.1494	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....