



FCC Part 15C Test Report

FCC ID: 2BVF8WTI4200

Applicant: Worldwide Telecommunications, Inc.

Address: 4505 Las Virgenes Road, Suite 115, Calabasas, California 91302, United States

Manufacturer: HOMTECS M2M TECHNOLOGY COMPANY LIMITED

Address: 201, F5 Building, TCL Science Park, NO.1001, Zhongshan Park Road, Shuguang Community, Xili Street, Nanshan District, Shenzhen, China 518052

EUT: Industrial Router

Trade Mark:  WTI WIRELESS

Model Number: 4200,4230,4240,4250,4260

Date of Receipt: Apr 02, 2026

Test Date: Apr 02, 2026 - Apr 13, 2026

Date of Report: Apr 13, 2026

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

Applicable Standards: FCC PART 15 C 15.247
ANSI C63.10:2020

Test Result: Pass

Report Number: DLE-260408032R

Prepared (Test Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1. SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	4
2. GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	6
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	6
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	7
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	7
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	8
3. EMC EMISSION TEST	9
3.1 CONDUCTED EMISSION MEASUREMENT	9
3.1.1 POWER LINE CONDUCTED EMISSION Limits	9
3.1.2 TEST PROCEDURE	9
3.1.3 DEVIATION FROM TEST STANDARD	9
3.1.4 TEST SETUP	10
3.1.5 EUT OPERATING CONDITIONS	10
3.1.6 TEST RESULTS	10
3.2 RADIATED EMISSION MEASUREMENT	13
3.2.1 RADIATED EMISSION LIMITS	13
3.2.2 TEST PROCEDURE	14
3.2.3 DEVIATION FROM TEST STANDARD	14
3.2.4 TEST SETUP	14
3.2.5 EUT OPERATING CONDITIONS	15
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	16
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	17
3.2.8 TEST RESULTS (1GHZ~25GHZ)	19
3.3 RADIATED BAND EMISSION MEASUREMENT	23
3.3.1 TEST REQUIREMENT:	23
3.3.2 TEST PROCEDURE	23
3.3.3 DEVIATION FROM TEST STANDARD	23
3.3.4 TEST SETUP	24
3.3.5 EUT OPERATING CONDITIONS	24
3.4 CONDUCTED BAND EDGE EMISSION&CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	29
3.4.1 APPLICABLE STANDARD	29
3.4.2 TEST PROCEDURE	29
3.4.3 DEVIATION FROM STANDARD	29



Table of Contents	Page
3.4.4 TEST SETUP	29
3.4.5 EUT OPERATION CONDITIONS	29
3.4.6 TEST RESULTS	29
4. AVERAGE OUTPUT POWER	30
4.1 APPLIED PROCEDURES / LIMIT	30
4.1.1 TEST PROCEDURE	30
4.1.2 DEVIATION FROM STANDARD	30
4.1.3 TEST SETUP	30
4.1.4 EUT OPERATION CONDITIONS	30
4.1.5 TEST RESULTS	30
5. POWER SPECTRAL DENSITY TEST	31
5.1 APPLIED PROCEDURES / LIMIT	31
5.1.1 TEST PROCEDURE	31
5.1.2 DEVIATION FROM STANDARD	31
5.1.3 TEST SETUP	31
5.1.4 EUT OPERATION CONDITIONS	31
5.1.5 TEST RESULTS	31
6. 6DB BANDWIDTH TEST & 99% EMISSION BANDWIDTH	32
6.1 APPLIED PROCEDURES / LIMIT	32
6.1.1 TEST PROCEDURE	32
6.1.2 DEVIATION FROM STANDARD	33
6.1.3 TEST SETUP	33
6.1.4 EUT OPERATION CONDITIONS	33
6.1.5 TEST RESULTS	33
7. ANTENNA REQUIREMENT	34
7.1 STANDARD REQUIREMENT	34
7.2 EUT ANTENNA	34
8. TEST SEUUP PHOTO	35
9. EUT PHOTO	35



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.205, 15.209, 15.247(d)	Radiated Spurious Emission	PASS	
15.205, 15.247(d)	Band Edge Emission& Conducted Spurious Emissions	PASS	
15.247(b)	Average Output Power	PASS	
15.247(a)(2)	6dB Bandwidth & 99% Emission Bandwidth	PASS	
15.247(e)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1
Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$
8	6dB Bandwidth	$\pm 0.2\text{MHz}$
9	Power Spectral Density	$\pm 2.45\text{dBm}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Industrial Router
Trademark	WTI WIRELESS
Model No.:	4200,4230,4240,4250,4260
Model difference:	Differences in shell mold opening and product production batches are not the same, no product function differences, will not affect the test.
Hardware Version	4200
Software Version	0.2.3
FCC ID:	2BVF8WTI4200
Contains modular FCC ID:	XMR201808EC25AF
Operation Frequency:	2412~2462 MHz for 802.11b/g/nHT20 2422~2452 MHz for 802.11nHT40
Channel numbers:	11 Channels for 802.11b/g/n(HT20)/axHT20 7 channels for 802.11nHT40
Channel separation:	5MHz
Modulation technology:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n(20/40): OFDM(QPSK, BPSK, 16-QAM, 64-QAM)
Rate of Transmitter	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
Antenna Type:	ANT : External Antenna
Antenna gain:	ANT : 1.6 dBi
Power Supply:	Model No:GQ24-120150-DU Input:100-240V ~50/60Hz 1.0A Max Output: 12V= 1.5A

Note:

1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.The EUT's all information provided by client.

2. Channel List(802.11b/g/nHT20/axHT20)

Channel	Frequency (GHz)	Channel	Frequency (GHz)
01	2.412	07	2.442
02	2.417	08	2.447
03	2.422	09	2.452
04	2.427	10	2.457
05	2.432	11	2.462
06	2.437		

Channel List(802.11nHT40)

Channel	Frequency (GHz)	Channel	Frequency (GHz)
03	2.422	07	2.442
04	2.427	08	2.447
05	2.432	09	2.452
06	2.437		



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11nHT20 CH1/ CH6/ CH11
Mode 4	802.11nHT40 CH3/ CH6/ CH09
Mode 5	Link Mode
For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode
For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n HT20 CH1/ CH6/ CH11
Mode 4	802.11n HT40 CH3/ CH6/ CH09
Mode 5	Link Mode

Note: 1. The measurements are performed at the highest, middle, lowest available channels.


2. During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Power Line Conducted Emission Test





2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Industrial Router	4200	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting				
Test software Version	Test program: WiFi Test V1.0.1			
Mode	802.11b	802.11g	802.11n HT20	802.11n HT40
Data Rate	1Mbps	6Mbps	MSC0	MSC0
Power Setting of Softwave	60	60	60	66



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 01, 2025	Oct. 31, 2026
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 01, 2025	Oct. 31, 2026
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 01, 2025	Oct. 31, 2026
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 01, 2025	Oct. 31, 2026
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 01, 2025	Oct. 31, 2026
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 01, 2025	Oct. 31, 2026
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 01, 2025	Oct. 31, 2026
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 01, 2025	Oct. 31, 2026
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 01, 2025	Oct. 31, 2026
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 01, 2025	Oct. 31, 2026
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 01, 2025	Oct. 31, 2026
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 01, 2025	Oct. 31, 2026
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 01, 2025	Oct. 31, 2026
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 01, 2025	Oct. 31, 2026
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 01, 2025	Oct. 31, 2026
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 01, 2025	Oct. 31, 2026
17	Power Meter	Ceyear	2438PA/PB	/	Nov. 01, 2025	Oct. 31, 2026
18	Peak/continuous wave power probe	Ceyear	81702F	/	Nov. 01, 2025	Oct. 31, 2026

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	YIHENG	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 01, 2025	Oct. 31, 2026
3	LISN	R&S	ENV216	102417	Nov. 01, 2025	Oct. 31, 2026
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2025	Oct. 31, 2026

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.50	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1 *	0.1635	50.67	9.97	60.64	65.28	-4.64	QP	P
2	0.1635	32.66	9.97	42.63	55.28	-12.65	AVG	P
3	0.3660	37.49	9.95	47.44	58.59	-11.15	QP	P
4	0.3660	19.35	9.95	29.30	48.59	-19.29	AVG	P
5	0.9060	20.88	9.87	30.75	56.00	-25.25	QP	P
6	0.9060	1.95	9.87	11.82	46.00	-34.18	AVG	P
7	2.4090	16.88	9.95	26.83	56.00	-29.17	QP	P
8	2.4090	1.70	9.95	11.65	46.00	-34.35	AVG	P
9	9.3300	28.37	10.21	38.58	60.00	-21.42	QP	P
10	9.3300	13.97	10.21	24.18	50.00	-25.82	AVG	P
11	16.1655	25.97	10.18	36.15	60.00	-23.85	QP	P
12	16.1655	15.39	10.18	25.57	50.00	-24.43	AVG	P

Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1 *	0.1635	49.42	9.96	59.38	65.28	-5.90	QP	P
2	0.1635	25.80	9.96	35.76	55.28	-19.52	AVG	P
3	0.6000	34.86	9.90	44.76	56.00	-11.24	QP	P
4	0.6000	21.61	9.90	31.51	46.00	-14.49	AVG	P
5	1.5630	24.76	9.83	34.59	56.00	-21.41	QP	P
6	1.5630	14.05	9.83	23.88	46.00	-22.12	AVG	P
7	3.7860	21.79	10.09	31.88	56.00	-24.12	QP	P
8	3.7860	9.52	10.09	19.61	46.00	-26.39	AVG	P
9	10.0590	26.22	10.22	36.44	60.00	-23.56	QP	P
10	10.0590	10.45	10.22	20.67	50.00	-29.33	AVG	P
11	21.6645	26.29	10.33	36.62	60.00	-23.38	QP	P
12	21.6645	19.14	10.33	29.47	50.00	-20.53	AVG	P

Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre.
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.6 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 5	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 5		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	68.8721	45.80	-10.95	34.85	40.00	-5.15	QP
2		81.2117	45.07	-13.28	31.79	40.00	-8.21	QP
3		157.5588	48.05	-11.99	36.06	43.50	-7.44	QP
4		210.0482	44.69	-8.62	36.07	43.50	-7.43	QP
5		264.7457	46.97	-7.13	39.84	46.00	-6.16	QP
6		334.8589	39.26	-4.79	34.47	46.00	-11.53	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 5		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector
1	*	43.5057	43.77	-7.33	36.44	40.00	-3.56	QP
2	!	56.0007	43.72	-7.59	36.13	40.00	-3.87	QP
3	!	68.8721	46.88	-10.95	35.93	40.00	-4.07	QP
4	!	156.4578	51.50	-11.94	39.56	43.50	-3.94	QP
5		261.9753	40.36	-7.09	33.27	46.00	-12.73	QP
6		580.7026	33.85	0.04	33.89	46.00	-12.11	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Level - Limit;

**3.2.8 TEST RESULTS (1GHZ~25GHZ)**

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	4824	67.8	50.65	6.88	31.29	55.32	74	-18.68	PK
V	4824	56.35	50.65	6.88	31.29	43.87	54	-10.13	AV
V	7236	67.05	49.98	7.16	36.63	60.86	74	-13.14	PK
V	7236	46.98	49.98	7.16	36.63	40.79	54	-13.21	AV
V	16087	49.6	51.53	11.34	41.52	50.93	74	-23.07	PK
H	4824	66.66	50.65	6.88	31.29	54.18	74	-19.82	PK
H	4824	56.26	50.65	6.88	31.29	43.78	54	-10.22	AV
H	7236	70.55	49.98	7.16	36.63	64.36	74	-9.64	PK
H	7236	45.97	49.98	7.16	36.63	39.78	54	-14.22	AV
H	16087	49.03	51.53	11.34	41.52	50.36	74	-26.64	PK
operation frequency:2437									
V	4874	67.98	50.67	6.89	31.38	55.58	74	-18.42	PK
V	4874	55.94	50.67	6.89	31.38	43.54	54	-10.46	AV
V	7311	69.62	50.02	7.24	36.63	63.47	74	-10.53	PK
V	7311	46.68	50.02	7.24	36.63	40.53	54	-13.47	AV
V	16087	49.57	51.53	11.34	41.52	50.9	74	-23.1	PK
H	4874	67.23	50.67	6.89	31.38	54.83	74	-19.17	PK
H	4874	55.92	50.67	6.89	31.38	43.52	54	-10.48	AV
H	7311	70.6	50.02	7.24	36.63	64.45	74	-9.55	PK
H	7311	48.35	50.02	7.24	36.63	42.2	54	-11.8	AV
H	16087	48.85	51.53	11.34	41.52	50.18	74	-23.82	PK
operation frequency:2462									
V	4924	68.93	50.79	6.83	31.36	56.33	74	-17.67	PK
V	4924	56.08	50.79	6.83	31.36	43.48	54	-10.52	AV
V	7386	70.05	50.11	7.25	36.58	63.77	74	-10.23	PK
V	7386	46.96	50.11	7.25	36.58	40.68	54	-13.32	AV
V	16087	49.7	51.53	11.34	41.52	51.03	74	-22.97	PK
H	4924	67.86	50.79	6.83	31.36	55.26	74	-18.74	PK
H	4924	56.25	50.79	6.83	31.36	43.65	54	-10.35	AV
H	7386	68.35	50.11	7.25	36.58	62.07	74	-11.93	PK
H	7386	49.28	50.11	7.25	36.58	43	54	-11	AV
H	16087	50.62	51.53	11.34	41.52	51.95	74	-22.05	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412									
V	4824	68.08	50.65	6.88	31.29	55.6	74	-18.4	PK
V	4824	56.04	50.65	6.88	31.29	43.56	54	-10.44	AV
V	7236	67.01	49.98	7.16	36.63	60.82	74	-13.18	PK
V	7236	47.05	49.98	7.16	36.63	40.86	54	-13.14	AV
V	16087	49.3	51.53	11.34	41.52	50.63	74	-23.37	PK
H	4824	66.97	50.65	6.88	31.29	54.49	74	-19.51	PK
H	4824	55.92	50.65	6.88	31.29	43.44	54	-10.56	AV
H	7236	70.5	49.98	7.16	36.63	64.31	74	-9.69	PK
H	7236	45.92	49.98	7.16	36.63	39.73	54	-14.27	AV
H	16087	49.44	51.53	11.34	41.52	50.77	74	-23.23	PK
operation frequency:2437									
V	4874	67.73	50.67	6.89	31.38	55.33	74	-18.67	PK
V	4874	56.28	50.67	6.89	31.38	43.88	54	-10.12	AV
V	7311	69.91	50.02	7.24	36.63	63.76	74	-10.24	PK
V	7311	46.63	50.02	7.24	36.63	40.48	54	-13.52	AV
V	16087	49.57	51.53	11.34	41.52	50.9	74	-23.1	PK
H	4874	66.95	50.67	6.89	31.38	54.55	74	-19.45	PK
H	4874	55.98	50.67	6.89	31.38	43.58	54	-10.42	AV
H	7311	70.24	50.02	7.24	36.63	64.09	74	-9.91	PK
H	7311	48.34	50.02	7.24	36.63	42.19	54	-11.81	AV
H	16087	48.48	51.53	11.34	41.52	49.81	74	-24.19	PK
operation frequency:2462									
V	4924	68.95	50.79	6.83	31.36	56.35	74	-17.65	PK
V	4924	56.09	50.79	6.83	31.36	43.49	54	-10.51	AV
V	7386	69.67	50.11	7.25	36.58	63.39	74	-10.61	PK
V	7386	47.21	50.11	7.25	36.58	40.93	54	-13.07	AV
V	16087	50.04	51.53	11.34	41.52	51.37	74	-22.63	PK
H	4924	67.9	50.79	6.83	31.36	55.3	74	-18.7	PK
H	4924	56.27	50.79	6.83	31.36	43.67	54	-10.33	AV
H	7386	68.05	50.11	7.25	36.58	61.77	74	-12.23	PK
H	7386	49.31	50.11	7.25	36.58	43.03	54	-10.97	AV
H	16087	50.3	51.53	11.34	41.52	51.63	74	-22.37	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	4824	67.34	50.65	6.88	31.29	54.86	74	-19.14	PK
V	4824	55.96	50.65	6.88	31.29	43.48	54	-10.52	AV
V	7236	67.59	49.98	7.16	36.63	61.4	74	-12.6	PK
V	7236	47.5	49.98	7.16	36.63	41.31	54	-12.69	AV
V	16087	47.65	51.53	11.34	41.52	48.98	74	-25.02	PK
H	4824	67.95	50.65	6.88	31.29	55.47	74	-18.53	PK
H	4824	56.2	50.65	6.88	31.29	43.72	54	-10.28	AV
H	7236	65.48	49.98	7.16	36.63	59.29	74	-14.71	PK
H	7236	48.7	49.98	7.16	36.63	42.51	54	-11.49	AV
H	16087	48.51	51.53	11.34	41.52	49.84	74	-24.16	PK
operation frequency:2437									
V	4874	67.49	50.67	6.89	31.38	55.09	74	-18.91	PK
V	4874	55.78	50.67	6.89	31.38	43.38	54	-10.62	AV
V	7311	66.5	50.02	7.24	36.63	60.35	74	-13.65	PK
V	7311	48.29	50.02	7.24	36.63	42.14	54	-11.86	AV
V	16087	48.68	51.53	11.34	41.52	50.01	74	-23.99	PK
H	4874	66.52	50.67	6.89	31.38	54.12	74	-19.88	PK
H	4874	54.78	50.67	6.89	31.38	42.38	54	-11.62	AV
H	7311	66.95	50.02	7.24	36.63	60.8	74	-13.2	PK
H	7311	47.78	50.02	7.24	36.63	41.63	54	-12.37	AV
H	16087	47.85	51.53	11.34	41.52	49.18	74	-24.82	PK
operation frequency:2462									
V	4924	68.45	50.79	6.83	31.36	55.85	74	-18.15	PK
V	4924	55.49	50.79	6.83	31.36	42.89	54	-11.11	AV
V	7386	65.8	50.11	7.25	36.58	59.52	74	-14.48	PK
V	7386	47.44	50.11	7.25	36.58	41.16	54	-12.84	AV
V	16087	49.29	51.53	11.34	41.52	50.62	74	-23.38	PK
H	4924	68.99	50.79	6.83	31.36	56.39	74	-17.61	PK
H	4924	55.48	50.79	6.83	31.36	42.88	54	-11.12	AV
H	7386	66.27	50.11	7.25	36.58	59.99	74	-14.01	PK
H	7386	48.33	50.11	7.25	36.58	42.05	54	-11.95	AV
H	16087	48.52	51.53	11.34	41.52	49.85	74	-24.15	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2422									
V	4844	67.42	50.67	6.89	31.32	54.96	74	-19.04	PK
V	4844	56.8	50.67	6.89	31.32	44.34	54	-9.66	AV
V	7266	67.5	50.01	7.15	36.62	61.26	74	-12.74	PK
V	7266	47.51	50.01	7.15	36.62	41.27	54	-12.73	AV
V	16087	47.68	51.53	11.34	41.52	49.01	74	-24.99	PK
H	4844	67.8	50.67	6.89	31.32	55.34	74	-18.66	PK
H	4844	56.18	50.67	6.89	31.32	43.72	54	-10.28	AV
H	7266	65.29	50.01	7.15	36.62	59.05	74	-14.95	PK
H	7266	48.6	50.01	7.15	36.62	42.36	54	-11.64	AV
H	16087	48.83	51.53	11.34	41.52	50.16	74	-23.84	PK
operation frequency:2437									
V	4874	67.36	50.67	6.89	31.38	54.96	74	-19.04	PK
V	4874	55.73	50.67	6.89	31.38	43.33	54	-10.67	AV
V	7311	66.75	50.02	7.24	36.63	60.6	74	-13.4	PK
V	7311	47.32	50.02	7.24	36.63	41.17	54	-12.83	AV
V	16087	48.48	51.53	11.34	41.52	49.81	74	-24.19	PK
H	4874	67.01	50.67	6.89	31.38	54.61	74	-19.39	PK
H	4874	51.75	50.67	6.89	31.38	41.94	54	-12.06	AV
H	7311	66.7	50.02	7.24	36.63	60.55	74	-13.45	PK
H	7311	48.28	50.02	7.24	36.63	42.13	54	-11.87	AV
H	16087	47.8	51.53	11.34	41.52	49.13	74	-24.87	PK
operation frequency:2452									
V	4904	68.51	50.76	6.81	31.31	55.87	74	-18.13	PK
V	4904	55.43	50.76	6.81	31.31	42.79	54	-11.21	AV
V	7356	65.38	50.08	7.21	36.52	59.03	74	-14.97	PK
V	7356	48.57	50.08	7.21	36.52	42.22	54	-11.78	AV
V	16087	49.78	51.53	11.34	41.52	51.11	74	-22.89	PK
H	4904	68.7	50.76	6.81	31.31	56.06	74	-17.94	PK
H	4904	55.45	50.76	6.81	31.31	42.81	54	-11.19	AV
H	7356	66.4	50.08	7.21	36.52	60.05	74	-13.95	PK
H	7356	47.42	50.08	7.21	36.52	41.07	54	-12.93	AV
H	16087	48.77	51.53	11.34	41.52	50.1	74	-23.9	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.6 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	2390	77.36	52.12	2.73	27.38	55.35	74	-18.65	PK
V	2390	66.14	52.12	2.73	27.38	44.13	54	-9.87	AV
V	2400	77.62	52.16	2.78	27.41	55.65	74	-18.35	PK
V	2400	65.85	52.16	2.78	27.41	43.88	54	-10.12	AV
H	2390	77.21	52.12	2.73	27.38	55.2	74	-18.8	PK
H	2390	66.81	52.12	2.73	27.38	44.8	54	-9.2	AV
H	2400	77.12	52.16	2.78	27.41	55.15	74	-18.85	PK
H	2400	66.72	52.16	2.78	27.41	44.75	54	-9.25	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462									
V	2483.5	77.61	52.23	2.86	27.44	55.68	74	-18.32	PK
V	2483.5	66.52	52.23	2.86	27.44	44.59	54	-9.41	AV
V	2500	77.81	52.26	2.88	27.49	55.92	74	-18.08	PK
V	2500	65.46	52.26	2.88	27.49	43.57	54	-10.43	AV
H	2483.5	77.64	52.23	2.86	27.44	55.71	74	-18.29	PK
H	2483.5	66.78	52.23	2.86	27.44	44.85	54	-9.15	AV
H	2500	77.84	52.26	2.88	27.49	55.95	74	-18.05	PK
H	2500	66.76	52.26	2.88	27.49	44.87	54	-9.13	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

002.1 Hz

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	2390	77.61	52.12	2.73	27.38	55.6	74	-18.4	PK
V	2390	66.12	52.12	2.73	27.38	44.11	54	-9.89	AV
V	2400	77.14	52.16	2.78	27.41	55.17	74	-18.83	PK
V	2400	65.25	52.16	2.78	27.41	43.28	54	-10.72	AV
H	2390	77.33	52.12	2.73	27.38	55.32	74	-18.68	PK
H	2390	66.54	52.12	2.73	27.38	44.53	54	-9.47	AV
H	2400	77.85	52.16	2.78	27.41	55.88	74	-18.12	PK
H	2400	66.37	52.16	2.78	27.41	44.4	54	-9.6	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462									
V	2483.5	77.5	52.23	2.86	27.44	55.57	74	-18.43	PK
V	2483.5	66.21	52.23	2.86	27.44	44.28	54	-9.72	AV
V	2500	77.72	52.26	2.88	27.49	55.83	74	-18.17	PK
V	2500	66.64	52.26	2.88	27.49	44.75	54	-9.25	AV
H	2483.5	77.63	52.23	2.86	27.44	55.7	74	-18.3	PK
H	2483.5	66.34	52.23	2.86	27.44	44.41	54	-9.59	AV
H	2500	77.39	52.26	2.88	27.49	55.5	74	-18.5	PK
H	2500	66.34	52.26	2.88	27.49	44.45	54	-9.55	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	2390	77.83	52.12	2.73	27.38	55.82	74	-18.18	PK
V	2390	66.29	52.12	2.73	27.38	44.28	54	-9.72	AV
V	2400	78.54	52.16	2.78	27.41	56.57	74	-17.43	PK
V	2400	66.66	52.16	2.78	27.41	44.69	54	-9.31	AV
H	2390	78.54	52.12	2.73	27.38	56.53	74	-17.47	PK
H	2390	66.24	52.12	2.73	27.38	44.23	54	-9.77	AV
H	2400	77.35	52.16	2.78	27.41	55.38	74	-18.62	PK
H	2400	66.11	52.16	2.78	27.41	44.14	54	-9.86	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462									
V	2483.5	78.5	52.23	2.86	27.44	56.57	74	-17.43	PK
V	2483.5	66.19	52.23	2.86	27.44	44.26	54	-9.74	AV
V	2500	77.34	52.26	2.88	27.49	55.45	74	-18.55	PK
V	2500	66.55	52.26	2.88	27.49	44.66	54	-9.34	AV
H	2483.5	78.3	52.23	2.86	27.44	56.37	74	-17.63	PK
H	2483.5	66.61	52.23	2.86	27.44	44.68	54	-9.32	AV
H	2500	77.52	52.26	2.88	27.49	55.63	74	-18.37	PK
H	2500	67.66	52.26	2.88	27.49	45.77	54	-8.23	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2422									
V	2390	77.64	52.12	2.73	27.38	55.63	74	-18.37	PK
V	2390	66.56	52.12	2.73	27.38	44.55	54	-9.45	AV
V	2400	78.52	52.16	2.78	27.41	56.55	74	-17.45	PK
V	2400	66.75	52.16	2.78	27.41	44.78	54	-9.22	AV
H	2390	78.54	52.12	2.73	27.38	56.53	74	-17.47	PK
H	2390	66.66	52.12	2.73	27.38	44.65	54	-9.35	AV
H	2400	77.33	52.16	2.78	27.41	55.36	74	-18.64	PK
H	2400	66.41	52.16	2.78	27.41	44.44	54	-9.56	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2452									
V	2483.5	78.45	52.23	2.86	27.44	56.52	74	-17.48	PK
V	2483.5	66.21	52.23	2.86	27.44	44.28	54	-9.72	AV
V	2500	77.53	52.26	2.88	27.49	55.64	74	-18.36	PK
V	2500	66.64	52.26	2.88	27.49	44.75	54	-9.25	AV
H	2483.5	78.65	52.23	2.86	27.44	56.72	74	-17.28	PK
H	2483.5	66.82	52.23	2.86	27.44	44.89	54	-9.11	AV
H	2500	77.41	52.26	2.88	27.49	55.52	74	-18.48	PK
H	2500	67.66	52.26	2.88	27.49	45.77	54	-8.23	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.4 CONDUCTED BAND EDGE EMISSION&CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

3.4.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

3.4.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

Set the RBW = 100KHz.

Set the VBW = 300KHz.

Sweep time = auto couple.

Detector function = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

3.4.3 DEVIATION FROM STANDARD

No deviation.

3.4.4 TEST SETUP



3.4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.6 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.6 TEST RESULTS

Measurement Data : The detailed test data see Appendix I



4. AVERAGE OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

Method AVGPM is a measurement using an RF average power meter, as follows:

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent (see Figure 24) if all of the conditions listed below are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle, D , of the transmitter output signal as described in 11.6.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Correct the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.6 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

Measurement Data : The detailed test data see Appendix I



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	$RBW \geq 3kHz$
VB	$VBW \geq 3RBW$
Detector	RMS
Trace	Trace Average.
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.6 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

Measurement Data : The detailed test data see Appendix I



6. 6DB BANDWIDTH TEST & 99% EMISSION BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

99% BANDWIDTH

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

6 DB BANDWIDTH

The steps for the first option are as follows:


- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.



6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.6 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

Measurement Data : The detailed test data see Appendix I



7. ANTENNA REQUIREMENT

7.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2 EUT ANTENNA

The EUT antenna is External Antenna, It comply with the standard requirement.



8. TEST SEUUP PHOTO

Reference to the appendix - Setup Photos for details.

9. EUT PHOTO

Reference to the EUT PHOTO for details.

***** END OF REPORT *****