

TEST REPORT

Applicant Name: Walnut Technology Corporation
Address: 233 Nahanton St Newton, MA 02459
Report Number: 2604V39919E-RF-00C
FCC ID: 2BVGO-CHB001

Test Standard (s)

47 CFR §2.1091

Sample Description

Product Name: CliQ Hub
Model No.: CHB001
Trade Mark: CliQ
Received Date: 2026-07-29
Report Date: 2026-08-12

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Amanda Wei

Amanda Wei
Engineer

Approved By:

Bob. Liao

Bob.Liao
Supervisor

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked. This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Bay Area Compliance Laboratories Corp. (Shenzhen, Guangming)

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY 3

GENERAL INFORMATION 4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

 OBJECTIVE 4

 TEST FACILITY 4

MAXIMUM PERMISSIBLE EXPOSURE (MPE) 5

 APPLICABLE STANDARD..... 5

 CALCULATED RESULT..... 5

EXHIBIT A-EUT PHOTOGRAPHS 6

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2604V39919E-RF-00C	Original Report	2026-08-12

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name	CliQ Hub
Tested Model	CHB001
Voltage Range [#]	AC120V
Frequency Range	2.4G Wi-Fi: 2412-2462 MHz 900M: 902.4-927.6 MHz
Maximum Conducted Output Power(Peak) (actual test result)	2.4G Wi-Fi: 20.79 dBm 900M: 8.84 dBm
Antenna Specification [#]	PCB Antenna (The gain is provided by the applicant.) 2.4G Wi-Fi Gain: 2.72dBi, 900M Gain: -0.52 dBi
Sample Serial Number	3R0K-1, 3R0K-3 (Assigned by BACL, Shenzhen, Guangming)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with 47 CFR §2.1091 rules.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen, Guangming) to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

MPE Calculated Formulary:

- Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Calculated Result

Radio	Frequency (MHz)	Tune up conducted power [#] (dBm)	Antenna Gain [#] (dBi)	EIRP		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
				(dBm)	(mW)			
2.4G Wi-Fi	2412-2462	21.0	2.72	23.72	235.50	20	0.0469	1.0
900M	902.4-927.6	9.0	-0.52	8.48	7.05	20	0.0014	0.602

Note 1: The tune-up power and antenna gain are declared by the applicant.

Note 2: EIRP= Tune up conducted power + Antenna Gain

Note 3: The 2.4G Wi-Fi and 900M can't transmission simultaneously.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2604V39919E-RF-00 EUT External Photos and Attachment No.2 2604V39919E-RF-00 EUT Internal Photos.

***** END OF REPORT *****