

FCC RADIO TEST REPORT

FCC ID: 2BVG-VINAAF1MINI

Product : Vinabot AI Interactive Display

Trade Mark : Vinabot

Model Name : Vina AF1 mini

Family Model : N/A

Report No. : N26072400905E

Prepared for

LAIPIC AI TECHNOLOGY COMPANY LIMITED

Room 3, Level 15, Core F, Cyberport 3, 100 Cyberport Road,
Hong Kong

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : LAIPIC AI TECHNOLOGY COMPANY LIMITED

Address..... : Room 3, Level 15, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong

Manufacturer's Name : Shenzhen Qianhai Hand-painted Technology and Culture Co., Ltd.

Address..... : Room 501A1, Building 3, North Distict, Youth Dream Factory, No. 5188 Menghai Avenue, Nanshan Street, Nanshan District, Shenzhen, Guangdong Province

Product description

Product name : Vinabot AI Interactive Display

Model and/or type reference : Vina AF1 mini

Family Model..... : N/A

Sample number : S2607250018-1#

Standards : FCC Part15.407

Test procedure ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and KDB 789033 D02 General UNII Test Procedures New Rules v02r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements.. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... Jul. 31, 2026 ~ Aug. 31, 2026

Date of Issue Aug. 31, 2026

Test Result..... **Pass**

Prepared By : Nikki Yang
Nikki Yang
(Project Engineer)

Reviewed By : Aaron Cheng
Aaron Cheng
(Supervisor)

Approved By : Alex Li
Alex Li
(Manager)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 FACILITIES AND ACCREDITATIONS	6
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . TEST REQUIREMENTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION MEASUREMENT	18
3.3 POWER SPECTRAL DENSITY TEST	56
3.4 26DB & 99% EMISSION BANDWIDTH	59
3.5 MINIMUM 6 DB BANDWIDTH	61
3.6 MAXIMUM CONDUCTED OUTPUT POWER	63
3.7 OUT OF BAND EMISSIONS	67
3.8 SPURIOUS RF CONDUCTED EMISSIONS	69
3.9 FREQUENCY STABILITY MEASUREMENT	70
4. ANTENNA REQUIREMENT	73
4.1 STANDARD REQUIREMENT	73
4.2 EUT ANTENNA	73

Revision History

Report No.	Version	Description	Issued Date
N26072400905E	Rev.01	Initial issue of report	Aug. 31, 2026

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(4)	Spurious Radiated Emissions	PASS	
15.407 (a)(1) 15.407 (a)(3)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test(9-150kHz)	3.7dB
2	Conducted Emission Test(0.15-30MHz)	3.3dB
3	RF power, conducted	1.34dB
4	Power Spectral Density, conducted	0.91dB
5	Occupied bandwidth	1.00%
6	Spurious emissions, conducted	2.71dB
7	Radio Frequency	0.21ppm
8	All emissions, radiated(9kHz~30MHz)	5.26dB
9	All emissions, radiated(30MHz~1G)	4.90dB
10	All emissions, radiated(1G~18G)	5.10dB
11	All emissions, radiated(18G~40G)	5.76dB
12	Time	5%
13	Temperature	1°C
14	Humidity	5%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Vinabot AI Interactive Display	
Trade Mark	Vinabot	
Model Name	Vina AF1 mini	
Family Model	N/A	
Model Difference	N/A	
FCC ID	2BVGV-VINAAF1MINI	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/n/ac/ax (20MHz channel bandwidth) ☒ 802.11n/ac/ax (40MHz channel bandwidth)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac/ax(VHT20):MCS0-MCS8; 802.11ac/ax(VHT40):MCS0-MCS9;
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac; OFDMA with QPSK/BPSK/16QAM/64QAM/256QAM/1024QAM for 802.11ax
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/n(HT20)/ac(VHT20)/ax20; 5190-5230MHz for 802.11n(HT40)/ac(VHT40)/ax40; ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac(VHT20)/ax20; 5755-5795 MHz for 802.11n(HT40)/ac(VHT40)/ax40;
	Number of Channels	☒ 4 channels for 802.11a/n20/ac20/ax20 in the 5180-5240MHz band ; 2 channels for 802.11 n40/ac40/ax40 in the 5190-5230MHz band ; ☒ 5 channels for 802.11a/n20/ac20/ax20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40/ax40 in the 5755-5795MHz band ;
	Antenna Type	FPC Antenna
	Antenna Gain	WIFI 5.2G: 4.13dBi; WIFI 5.8G: 4.13dBi;
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.	
Adapter	Model: XC024WH-1201500U Input: 100-240V~50/60Hz 1A Max Output: 12.0V---1.5A, 18W	
Battery	N/A	
Power supply	DC 12V from Adapter	
Connecting I/O Port(s)	Please refer to the User's Manual	
HW Version	N/A	
SW Version	N/A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Frequency and Channel list for 802.11a/n/ac/ax(20MHz) band I (5180-5240MHz):

802.11a/n/ac/ax(20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

Frequency and Channel list for 802.11n/ac/ax(40MHz) band I (5190-5230MHz):

802.11n/ac/ax(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n/ac/ax(20 MHz) band IV (5745-5825MHz):

802.11a/n/ac/ax(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

Frequency and Channel list for 802.11n/ac/ax(40MHz) band IV (5755-5795MHz):

802.11n/ac/ax(40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 / ac 20 / ax20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20 / ax20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40 / ax40 CH38/ CH 46 802.11n 40 / ac 40 / ax40 CH 151 / CH 159


For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 / ac 20 / ax20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20 / ax20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40 / ax40 CH38/ CH 46 802.11n 40 / ac 40 / ax40 CH 151 / CH 159

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Vinabot AI Interactive Display	Vina AF1 mini	N/A	EUT
AE-2	Adapter	XC024WH-1201500U	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	YES	NO	1.0m
C-2	RF Cable	YES	NO	0.1m
C-3				

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2026.04.15	2027.04.14	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2026.04.08	2027.04.07	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2026.04.08	2027.04.07	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
5	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
6	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
7	Amplifier	EMC	EMC051835SE	980246	2026.04.08	2027.04.07	1 year
8	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
9	Power Meter	DARE	RPR3006W	15I00041SN084	2026.04.08	2027.04.07	1 year
10	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2024.05.06	2027.05.05	3 year
11	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2024.05.06	2027.05.05	3 year
12	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2024.05.06	2027.05.05	3 year
13	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2026.04.08	2027.04.07	1 year
2	LISN	R&S	ENV216	101313	2026.04.08	2027.04.07	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2026.04.08	2027.04.07	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2024.05.06	2027.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2024.05.06	2027.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2024.05.06	2027.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. TEST REQUIREMENTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD

According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION

3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


3.1.5 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name :	Vina AF1 mini
Temperature :	25.5℃	Relative Humidity :	55.5%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (WIFI 5G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2380	26.34	20.47	46.81	62.17	-15.36	QP
0.2380	14.76	20.47	35.23	52.17	-16.94	AVG
0.5700	23.02	20.46	43.48	56.00	-12.52	QP
0.5700	8.84	20.46	29.30	46.00	-16.70	AVG
1.0339	21.72	20.29	42.01	56.00	-13.99	QP
1.0339	12.28	20.29	32.57	46.00	-13.43	AVG
1.7220	18.52	20.28	38.80	56.00	-17.20	QP
1.7220	10.42	20.28	30.70	46.00	-15.30	AVG
5.1660	16.15	20.31	36.46	60.00	-23.54	QP
5.1660	4.73	20.31	25.04	50.00	-24.96	AVG
14.0860	17.52	20.46	37.98	60.00	-22.02	QP
14.0860	2.70	20.46	23.16	50.00	-26.84	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Vinabot AI Interactive Display	Model Name :	Vina AF1 mini
Temperature :	25.6℃	Relative Humidity :	55.9%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1 (WIFI 5G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	33.87	20.38	54.25	65.57	-11.32	QP
0.1580	21.30	20.38	41.68	55.57	-13.89	AVG
0.5540	26.98	20.43	47.41	56.00	-8.59	QP
0.5540	16.92	20.43	37.35	46.00	-8.65	AVG
1.0339	22.57	20.25	42.82	56.00	-13.18	QP
1.0339	15.82	20.25	36.07	46.00	-9.93	AVG
1.7220	23.43	20.27	43.70	56.00	-12.30	QP
1.7220	13.83	20.27	34.10	46.00	-11.90	AVG
5.5100	21.44	20.26	41.70	60.00	-18.30	QP
5.5100	7.01	20.26	27.27	50.00	-22.73	AVG
10.3300	23.21	20.24	43.45	60.00	-16.55	QP
10.3300	8.70	20.24	28.94	50.00	-21.06	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(b) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHz – 30 MHz)

EUT:	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHz – 1GHz)

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	24.6℃	Relative Humidity :	53.8%
Pressure :	1010 hPa	Test Voltage :	DC 12V from Adapter AC 120V/60Hz
Test Mode :	TX(5G WIFI)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	44.9004	11.14	19.63	30.77	40.00	-9.23	QP
V	124.5690	16.86	15.28	32.14	43.50	-11.36	QP
V	172.5987	15.66	15.57	31.23	43.50	-12.27	QP
V	199.9855	15.22	17.71	32.93	43.50	-10.57	QP
V	359.1860	8.30	21.70	30.00	46.00	-16.00	QP
V	836.2441	5.62	29.69	35.31	46.00	-10.69	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	49.5328	5.82	20.02	25.84	40.00	-14.16	QP
H	119.4360	10.02	16.34	26.36	43.50	-17.14	QP
H	168.4137	16.44	15.50	31.94	43.50	-11.56	QP
H	249.4250	16.13	19.12	35.25	46.00	-10.75	QP
H	354.1831	11.95	21.83	33.78	46.00	-12.22	QP
H	499.4245	8.99	24.59	33.58	46.00	-12.42	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note (1) All modes have been tested, just the worst mode has been recorded in the report.
 (2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25.7 °C	Relative Humidity :	55.4%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX(5.2G) - 802.11a_5180~5240MHz		

5180

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1089.675	60.13	-18.05	42.08	74.00	-31.92	peak
V	1089.675	51.75	-18.05	33.70	54.00	-20.30	AVG
V	1589.900	57.01	-16.50	40.51	74.00	-33.49	peak
V	1589.900	49.44	-16.50	32.94	54.00	-21.06	AVG
V	1973.675	55.44	-14.20	41.24	68.20	-26.96	peak
V	2046.350	46.42	-12.94	33.48	68.20	-34.72	AVG
V	4144.575	48.33	-8.62	39.71	74.00	-34.29	peak
V	4144.575	39.71	-8.62	31.09	54.00	-22.91	AVG
V	6421.725	49.06	-4.02	45.04	68.20	-23.16	peak
V	6536.475	40.32	-3.55	36.77	68.20	-31.43	AVG
V	12020.250	44.17	5.18	49.35	74.00	-24.65	peak
V	12020.250	36.41	5.18	41.59	54.00	-12.41	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	1140.675	60.04	-18.73	41.31	74.00	-32.69	peak
H	1140.675	50.50	-18.73	31.77	54.00	-22.23	AVG
H	1591.600	57.87	-16.49	41.38	74.00	-32.62	peak
H	1591.600	50.25	-16.49	33.76	54.00	-20.24	AVG
H	2078.225	54.82	-12.66	42.16	68.20	-26.04	peak
H	2095.650	47.91	-12.52	35.39	68.20	-32.81	AVG
H	4144.575	56.22	-8.62	47.60	74.00	-26.40	peak
H	4144.575	46.31	-8.62	37.69	54.00	-16.31	AVG
H	6467.200	43.36	-4.08	39.28	68.20	-28.92	AVG
H	6483.775	49.22	-4.07	45.15	68.20	-23.05	peak
H	12007.075	43.42	5.24	48.66	74.00	-25.34	peak
H	12007.075	36.08	5.24	41.32	54.00	-12.68	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5200

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1099.875	59.01	-17.95	41.06	74.00	-32.94	peak
V	1099.875	51.50	-17.95	33.55	54.00	-20.45	AVG
V	1576.300	58.07	-16.65	41.42	74.00	-32.58	peak
V	1576.300	49.17	-16.65	32.52	54.00	-21.48	AVG
V	2079.075	55.56	-12.66	42.90	68.20	-25.30	peak
V	2079.075	47.12	-12.66	34.46	68.20	-33.74	AVG
V	3992.425	46.89	-7.97	38.92	74.00	-35.08	peak
V	3992.425	39.45	-7.97	31.48	54.00	-22.52	AVG
V	6604.475	48.18	-3.29	44.89	68.20	-23.31	peak
V	6695.850	40.42	-2.90	37.52	68.20	-30.68	AVG
V	11920.375	43.94	5.18	49.12	74.00	-24.88	peak
V	11920.375	35.62	5.18	40.80	54.00	-13.20	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	1116.450	59.36	-18.27	41.09	74.00	-32.91	peak
H	1116.450	50.62	-18.27	32.35	54.00	-21.65	AVG
H	1567.375	58.76	-16.74	42.02	74.00	-31.98	peak
H	1567.375	49.93	-16.74	33.19	54.00	-20.81	AVG
H	2088.000	47.21	-12.58	34.63	68.20	-33.57	AVG
H	2152.600	55.08	-12.82	42.26	68.20	-25.94	peak
H	4160.300	49.90	-8.47	41.43	74.00	-32.57	peak
H	4160.300	42.78	-8.47	34.31	54.00	-19.69	AVG
H	6492.700	49.08	-4.07	45.01	68.20	-23.19	peak
H	6492.700	42.21	-4.07	38.14	68.20	-30.06	AVG
H	12108.650	44.64	4.76	49.40	74.00	-24.60	peak
H	12108.650	36.54	4.76	41.30	54.00	-12.70	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5240

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1070.975	59.70	-18.25	41.45	74.00	-32.55	peak
V	1070.975	51.95	-18.25	33.70	54.00	-20.30	AVG
V	1521.900	57.28	-16.99	40.29	74.00	-33.71	peak
V	1521.900	48.81	-16.99	31.82	54.00	-22.18	AVG
V	2079.925	54.96	-12.65	42.31	68.20	-25.89	peak
V	2112.650	47.17	-12.55	34.62	68.20	-33.58	AVG
V	4192.175	48.25	-8.03	40.22	74.00	-33.78	peak
V	4192.175	40.41	-8.03	32.38	54.00	-21.62	AVG
V	6514.375	48.60	-3.87	44.73	68.20	-23.47	peak
V	6605.750	40.93	-3.30	37.63	68.20	-30.57	AVG
V	11887.650	44.26	5.08	49.34	74.00	-24.66	peak
V	11887.650	35.43	5.08	40.51	54.00	-13.49	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	1144.500	59.99	-18.82	41.17	74.00	-32.83	peak
H	1144.500	51.58	-18.82	32.76	54.00	-21.24	AVG
H	1494.275	57.79	-17.11	40.68	74.00	-33.32	peak
H	1494.275	51.59	-17.11	34.48	54.00	-19.52	AVG
H	2077.375	48.20	-12.67	35.53	68.20	-32.67	AVG
H	2081.200	55.07	-12.62	42.45	68.20	-25.75	peak
H	4192.175	47.68	-8.03	39.65	74.00	-34.35	peak
H	4192.175	44.25	-8.03	36.22	54.00	-17.78	AVG
H	6542.425	48.34	-3.47	44.87	68.20	-23.33	peak
H	6542.425	41.94	-3.47	38.47	68.20	-29.73	AVG
H	12143.500	44.53	4.66	49.19	74.00	-24.81	peak
H	12143.500	35.97	4.66	40.63	54.00	-13.37	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25.7 °C	Relative Humidity :	55.4%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.8G) - 802.11a_5745~5825MHz		

5745

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	1069.275	59.42	-18.27	41.15	74.00	-32.85	peak
V	1069.275	51.54	-18.27	33.27	54.00	-20.73	AVG
V	1531.675	58.15	-16.97	41.18	74.00	-32.82	peak
V	1531.675	49.35	-16.97	32.38	54.00	-21.62	AVG
V	2079.075	47.61	-12.66	34.95	68.20	-33.25	AVG
V	2088.850	56.19	-12.57	43.62	68.20	-24.58	peak
V	3960.975	47.13	-8.01	39.12	74.00	-34.88	peak
V	3960.975	39.26	-8.01	31.25	54.00	-22.75	AVG
V	6500.775	49.18	-4.06	45.12	68.20	-23.08	peak
V	6706.050	40.71	-2.94	37.77	68.20	-30.43	AVG
V	11936.950	43.64	5.21	48.85	74.00	-25.15	peak
V	11936.950	35.39	5.21	40.60	54.00	-13.40	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	1080.325	60.66	-18.16	42.50	74.00	-31.50	peak
H	1080.325	51.42	-18.16	33.26	54.00	-20.74	AVG
H	1589.900	57.41	-16.50	40.91	74.00	-33.09	peak
H	1589.900	49.02	-16.50	32.52	54.00	-21.48	AVG
H	2057.400	55.25	-12.84	42.41	68.20	-25.79	peak
H	2090.125	47.48	-12.56	34.92	68.20	-33.28	AVG
H	4037.050	47.28	-8.34	38.94	74.00	-35.06	peak
H	4037.050	39.63	-8.34	31.29	54.00	-22.71	AVG
H	6697.125	40.85	-2.88	37.97	68.20	-30.23	AVG
H	6704.775	48.07	-2.92	45.15	68.20	-23.05	peak
H	11905.075	43.94	5.16	49.10	74.00	-24.90	peak
H	11905.075	35.73	5.16	40.89	54.00	-13.11	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5785

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1031.025	59.75	-18.60	41.15	74.00	-32.85	peak
V	1031.025	51.43	-18.60	32.83	54.00	-21.17	AVG
V	1536.350	57.97	-16.96	41.01	74.00	-32.99	peak
V	1536.350	50.24	-16.96	33.28	54.00	-20.72	AVG
V	2121.575	55.20	-12.60	42.60	68.20	-25.60	peak
V	2142.825	47.91	-12.72	35.19	68.20	-33.01	AVG
V	3971.600	48.14	-8.00	40.14	74.00	-33.86	peak
V	3971.600	39.22	-8.00	31.22	54.00	-22.78	AVG
V	6667.800	41.35	-3.36	37.99	68.20	-30.21	AVG
V	6700.100	48.28	-2.83	45.45	68.20	-22.75	peak
V	12015.150	44.09	5.20	49.29	74.00	-24.71	peak
V	12015.150	36.82	5.20	42.02	54.00	-11.98	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	1097.750	59.20	-17.97	41.23	74.00	-32.77	peak
H	1097.750	50.98	-17.97	33.01	54.00	-20.99	AVG
H	1598.825	57.30	-16.41	40.89	74.00	-33.11	peak
H	1598.825	49.69	-16.41	33.28	54.00	-20.72	AVG
H	2089.700	47.39	-12.56	34.83	68.20	-33.37	AVG
H	2110.525	54.82	-12.54	42.28	68.20	-25.92	peak
H	3916.350	47.38	-8.27	39.11	74.00	-34.89	peak
H	3916.350	38.75	-8.27	30.48	54.00	-23.52	AVG
H	6535.200	40.95	-3.57	37.38	68.20	-30.82	AVG
H	6608.725	48.22	-3.32	44.90	68.20	-23.30	peak
H	11967.975	44.34	5.24	49.58	74.00	-24.42	peak
H	11967.975	35.79	5.24	41.03	54.00	-12.97	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5825

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	1102.425	59.41	-17.99	41.42	74.00	-32.58	peak
V	1102.425	50.70	-17.99	32.71	54.00	-21.29	AVG
V	1584.800	57.74	-16.56	41.18	74.00	-32.82	peak
V	1584.800	48.77	-16.56	32.21	54.00	-21.79	AVG
V	2073.550	55.04	-12.69	42.35	68.20	-25.85	peak
V	2079.075	47.78	-12.66	35.12	68.20	-33.08	AVG
V	3927.400	48.16	-8.18	39.98	74.00	-34.02	peak
V	3927.400	38.80	-8.18	30.62	54.00	-23.38	AVG
V	6697.975	40.58	-2.86	37.72	68.20	-30.48	AVG
V	6709.450	48.06	-3.00	45.06	68.20	-23.14	peak
V	11909.750	43.90	5.17	49.07	74.00	-24.93	peak
V	11909.750	35.78	5.17	40.95	54.00	-13.05	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	1060.775	59.73	-18.36	41.37	74.00	-32.63	peak
H	1060.775	51.54	-18.36	33.18	54.00	-20.82	AVG
H	1592.875	57.85	-16.47	41.38	74.00	-32.62	peak
H	1592.875	49.18	-16.47	32.71	54.00	-21.29	AVG
H	2076.950	54.86	-12.67	42.19	68.20	-26.01	peak
H	2097.775	47.29	-12.49	34.80	68.20	-33.40	AVG
H	3921.025	47.31	-8.22	39.09	74.00	-34.91	peak
H	3921.025	38.69	-8.22	30.47	54.00	-23.53	AVG
H	6703.925	40.64	-2.90	37.74	68.20	-30.46	AVG
H	6785.525	48.46	-3.35	45.11	68.20	-23.09	peak
H	11979.450	44.59	5.26	49.85	74.00	-24.15	peak
H	11979.450	35.83	5.26	41.09	54.00	-12.91	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25.7 °C	Relative Humidity :	55.4%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (WIFI 5.2G)		

5180

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	19142.350	63.07	-13.91	49.16	74.00	-24.84	peak
V	19142.350	54.44	-13.91	40.53	54.00	-13.47	AVG
V	22403.850	62.15	-11.61	50.54	74.00	-23.46	peak
V	22403.850	53.63	-11.61	42.02	54.00	-11.98	AVG
V	25323.250	61.32	-9.64	51.68	68.20	-16.52	peak
V	28538.000	58.48	-9.44	49.04	68.20	-19.16	peak
V	34768.950	58.76	-4.15	54.61	68.20	-13.59	peak
V	39104.600	59.34	-3.76	55.58	68.20	-12.62	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	19920.050	62.70	-12.63	50.07	74.00	-23.93	peak
H	19920.050	54.56	-12.63	41.93	54.00	-12.07	AVG
H	22386.250	61.46	-11.63	49.83	74.00	-24.17	peak
H	22386.250	53.43	-11.63	41.80	54.00	-12.20	AVG
H	25009.750	59.50	-9.71	49.79	68.20	-18.41	peak
H	27882.400	59.21	-9.51	49.70	68.20	-18.50	peak
H	33960.450	59.25	-5.00	54.25	68.20	-13.95	peak
H	37909.450	59.18	-4.24	54.94	68.20	-13.26	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5200

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	19125.300	61.79	-13.93	47.86	74.00	-26.14	peak
V	19125.300	54.26	-13.93	40.33	54.00	-13.67	AVG
V	20690.600	61.01	-12.13	48.88	74.00	-25.12	peak
V	20690.600	52.70	-12.13	40.57	54.00	-13.43	AVG
V	22369.750	61.28	-11.65	49.63	74.00	-24.37	peak
V	22369.750	52.85	-11.65	41.20	54.00	-12.80	AVG
V	25301.250	60.75	-9.63	51.12	68.20	-17.08	peak
V	29371.250	59.17	-8.76	50.41	68.20	-17.79	peak
V	34390.000	58.46	-4.44	54.02	68.20	-14.18	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	19832.600	62.92	-12.76	50.16	74.00	-23.84	peak
H	19832.600	53.77	-12.76	41.01	54.00	-12.99	AVG
H	22385.700	61.03	-11.63	49.40	74.00	-24.60	peak
H	22385.700	52.87	-11.63	41.24	54.00	-12.76	AVG
H	27323.050	59.33	-9.02	50.31	68.20	-17.89	peak
H	30055.450	59.42	-8.04	51.38	68.20	-16.82	peak
H	33708.550	59.85	-5.22	54.63	68.20	-13.57	peak
H	38415.450	59.00	-4.06	54.94	68.20	-13.26	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5240

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	19086.800	61.51	-13.97	47.54	74.00	-26.46	peak
V	19086.800	53.37	-13.97	39.40	54.00	-14.60	AVG
V	22451.700	61.49	-11.55	49.94	74.00	-24.06	peak
V	22451.700	52.54	-11.55	40.99	54.00	-13.01	AVG
V	25075.200	58.79	-9.67	49.12	68.20	-19.08	peak
V	28980.200	59.74	-9.57	50.17	68.20	-18.03	peak
V	34758.500	58.26	-4.17	54.09	68.20	-14.11	peak
V	38738.300	59.06	-3.77	55.29	68.20	-12.91	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	19450.350	62.53	-13.54	48.99	74.00	-25.01	peak
H	19450.350	54.19	-13.54	40.65	54.00	-13.35	AVG
H	22368.100	61.14	-11.65	49.49	74.00	-24.51	peak
H	22368.100	53.16	-11.65	41.51	54.00	-12.49	AVG
H	25278.150	61.23	-9.61	51.62	68.20	-16.58	peak
H	28386.200	58.71	-9.47	49.24	68.20	-18.96	peak
H	34529.700	58.17	-4.20	53.97	68.20	-14.23	peak
H	38807.050	58.57	-3.73	54.84	68.20	-13.36	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25.7 °C	Relative Humidity :	55.4%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (WIFI 5.8G)		

5745

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	19146.750	62.89	-13.90	48.99	74.00	-25.01	peak
V	19146.750	54.07	-13.90	40.17	54.00	-13.83	AVG
V	22447.850	60.92	-11.55	49.37	74.00	-24.63	peak
V	22447.850	53.02	-11.55	41.47	54.00	-12.53	AVG
V	24886.000	61.21	-10.25	50.96	68.20	-17.24	peak
V	27098.100	58.55	-9.01	49.54	68.20	-18.66	peak
V	30341.450	59.35	-8.07	51.28	68.20	-16.92	peak
V	33827.350	59.19	-5.11	54.08	68.20	-14.12	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	19064.800	62.34	-14.00	48.34	74.00	-25.66	peak
H	19064.800	54.22	-14.00	40.22	54.00	-13.78	AVG
H	22389.000	61.28	-11.62	49.66	74.00	-24.34	peak
H	22389.000	52.91	-11.62	41.29	54.00	-12.71	AVG
H	25183.000	59.65	-9.62	50.03	68.20	-18.17	peak
H	27900.000	58.84	-9.53	49.31	68.20	-18.89	peak
H	34201.350	58.55	-4.78	53.77	68.20	-14.43	peak
H	38656.900	59.46	-3.88	55.58	68.20	-12.62	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5785

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	19754.500	61.11	-12.88	48.23	74.00	-25.77	peak
V	19754.500	53.58	-12.88	40.70	54.00	-13.30	AVG
V	22369.200	61.45	-11.65	49.80	74.00	-24.20	peak
V	22369.200	53.54	-11.65	41.89	54.00	-12.11	AVG
V	24868.400	61.06	-10.34	50.72	68.20	-17.48	peak
V	27465.500	59.37	-9.03	50.34	68.20	-17.86	peak
V	34417.500	59.64	-4.38	55.26	68.20	-12.94	peak
V	38956.650	59.28	-3.67	55.61	68.20	-12.59	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	19746.250	62.52	-12.90	49.62	74.00	-24.38	peak
H	19746.250	53.28	-12.90	40.38	54.00	-13.62	AVG
H	22751.450	61.66	-11.79	49.87	74.00	-24.13	peak
H	22751.450	53.77	-11.79	41.98	54.00	-12.02	AVG
H	25002.600	61.01	-9.71	51.30	68.20	-16.90	peak
H	28624.350	60.37	-9.50	50.87	68.20	-17.33	peak
H	33646.950	59.90	-5.26	54.64	68.20	-13.56	peak
H	38649.750	60.41	-3.89	56.52	68.20	-11.68	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



5825

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	19104.400	61.77	-13.95	47.82	74.00	-26.18	peak
V	19104.400	53.84	-13.95	39.89	54.00	-14.11	AVG
V	22387.350	61.93	-11.63	50.30	74.00	-23.70	peak
V	22387.350	53.54	-11.63	41.91	54.00	-12.09	AVG
V	25206.650	60.28	-9.61	50.67	68.20	-17.53	peak
V	28666.700	59.48	-9.53	49.95	68.20	-18.25	peak
V	34709.550	59.38	-4.17	55.21	68.20	-12.99	peak
V	39077.650	60.54	-3.73	56.81	68.20	-11.39	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	19081.850	61.72	-13.97	47.75	74.00	-26.25	peak
H	19081.850	54.22	-13.97	40.25	54.00	-13.75	AVG
H	22386.250	61.22	-11.63	49.59	74.00	-24.41	peak
H	22386.250	53.71	-11.63	42.08	54.00	-11.92	AVG
H	24924.500	60.34	-10.07	50.27	68.20	-17.93	peak
H	29333.850	60.52	-8.85	51.67	68.20	-16.53	peak
H	33949.450	59.41	-5.00	54.41	68.20	-13.79	peak
H	37864.350	59.34	-4.25	55.09	68.20	-13.11	peak


Remark:

Emission Level = Meter Reading + Factor, Margin = Emission Level - Limit, Factor = Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



3.2.10 Radiated Spurious at Band Edges

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25.1 °C	Relative Humidity :	50.2%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.2G)-802.11a 5180MHz~5240MHz, TX (5.8G)-802.11a 5745MHz~5825MHz		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	5150.000	12.44	38.51	50.95	74.00	-23.05	peak
V	5150.000	2.08	38.51	40.59	54.00	-13.41	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5180MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5150.000	19.33	38.51	57.84	74.00	-16.16	peak
H	5150.000	6.40	38.51	44.91	54.00	-9.09	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5180MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	5350.000	7.75	37.64	45.39	74.00	-28.61	peak
V	5350.000	-1.22	37.64	36.42	54.00	-17.58	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5240MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5350.000	8.27	37.64	45.91	74.00	-28.09	peak
H	5350.000	-1.16	37.64	36.48	54.00	-17.52	AVG


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamplifier Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5240MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	5620.434	-102.38	38.66	-63.72	-27.00	-36.72	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5745MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5630.233	-96.11	38.70	-57.41	-27.00	-30.41	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5745MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	5930.818	-102.64	51.73	-50.91	-27.00	-23.91	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5825MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	5931.388	-99.57	51.73	-47.84	-27.00	-20.84	peak


Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit, Factor= Antenna Factor + Cable Loss - Preamp Factor

All the modulation modes have been tested, and the worst-case result was 802.11a 5825MHz. Only the worst-case mode reported.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

When PK value is lower than the Average value limit, average don't record.



3.3 POWER SPECTRAL DENSITY TEST

3.3.1 Applied procedures / limit

According to FCC §15.407(a)(3)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

3.3.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

3.3.3 DEVIATION FROM STANDARD

No deviation.

3.3.4 TEST SETUP



3.3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.4 26DB & 99% EMISSION BANDWIDTH

3.4.1 Applied procedures / limit


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

3.4.2 TEST PROCEDURE

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

- Set center frequency to the nominal EUT channel center frequency.
- Set span = 1.5 times to 5.0 times the OBW.
- Set RBW = 1 % to 5 % of the OBW
- Set VBW $\geq 3 \cdot$ RBW
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99 % power bandwidth function of the instrument (if available).
- If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



3.4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.4 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.5 MINIMUM 6 DB BANDWIDTH

3.5.1 Applied procedures / limit

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.5.2 TEST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.5.3 DEVIATION FROM STANDARD

No deviation.

3.5.4 TEST SETUP



3.5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.5.6 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5G) Mode Frequency Band IV (5725-5850MHz)		

Test data reference attachment.

3.6 MAXIMUM CONDUCTED OUTPUT POWER

3.6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

3.6.2 TEST PROCEDURE

- Maximum conducted output power may be measured using a spectrum analyzer/EMI receiver or an RF power meter.

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.¹ However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

- The EUT transmits continuously (or with a duty cycle ≥ 98 percent).
- Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".


(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

3.6.3 DEVIATION FROM STANDARD

No deviation.

3.6.4 TEST SETUP



3.6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6.6 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5G) Mode Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.7 OUT OF BAND EMISSIONS

3.7.1 Applicable Standard

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


3.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

3.7.3 DEVIATION FROM STANDARD

No deviation.

3.7.4 TEST SETUP



3.7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.7.6 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V

Test data reference attachment.

3.8 SPURIOUS RF CONDUCTED EMISSIONS

3.8.1 Conformance Limit

According to FCC §15.407(b)(1) (2) (3) (4)

3.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

3.8.3 Test Setup

Please refer to Section 6.1 of this test report.

3.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and measure frequency range from 30MHz to 40GHz.

3.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

Test data reference attachment.

3.9 FREQUENCY STABILITY MEASUREMENT


3.9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6 \text{ ppm}$.
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^\circ\text{C} \sim 70^\circ\text{C}$.

3.9.3 TEST SETUP LAYOUT



3.9.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

3.9.5 TEST RESULTS

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Test data reference attachment.

EUT :	Vinabot AI Interactive Display	Model Name. :	Vina AF1 mini
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency(5745-5825MHz)		

Test data reference attachment.

4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA

The EUT antenna is permanent attached FPC Antenna (antenna gain: WIFI 5.2G: 4.13dBi; WIFI 5.8G: 4.13dBi). It comply with the standard requirement.

END OF REPORT