TEST REPORT

Applicant:	HOT FOCUS,INC
Address of Applicant:	4471 State St., Montclair, California 91763, United States
Manufacturer:	HOT FOCUS,INC
Address of Manufacturer:	4471 State St., Montclair, California 91763, United States
Equipment Under Test (EUT)	
Product Name:	Microphone
Model No.:	60704VA, 60704KP
Trade Mark:	Hot Focus
FCC ID:	2BVI3-60704-1
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	July 07, 2026
Date of Test:	July 24, 2026-August 31, 2026
Date of report issued:	August 31, 2026
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

深圳市环球众一科技有限公司 Global United Technology Services Co., Ltd. 检验检测专用章 Inspection&Testing Services

Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*August 31, 2026*	*Original*

Tested By:	***Test Engineer***	***Date:***	*August 31, 2026*
Prepared By:	***Project Engineer***	***Date:***	*August 31, 2026*
Check By:	***Reviewer***	***Date:***	*August 31, 2026*

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 DESCRIPTION OF SUPPORT UNITS 7
5.4 DEVIATION FROM STANDARDS 7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS 7
5.6 TEST FACILITY 7
5.7 TEST LOCATION 7
5.8 ADDITIONAL INSTRUCTIONS 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED OUTPUT POWER 14
7.4 CHANNEL BANDWIDTH 15
7.5 POWER SPECTRAL DENSITY 16
7.6 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS 17
7.6.1 Conducted Emission Method 17
7.6.2 Radiated Emission Method 18

8 TEST SETUP PHOTO 33

9 EUT CONSTRUCTIONAL DETAILS 33

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remarks:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10:2020*
3. *N/A: Not applicable.*

Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25\times 10^{-8}$
2	Duty cycle	±0.37%
3	Occupied Bandwidth	±3%
4	RF conducted power	±0.75dB
5	RF power density	±3dB
6	Conducted Spurious emissions	±2.58dB
7	AC Power Line Conducted Emission	±3.44dB (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	±3.1dB (9kHz-30MHz)
		±3.8039dB (30MHz-200MHz)
		±3.9679dB (200MHz-1GHz)
		±4.29dB (1GHz-18GHz)
		±3.30dB (18GHz-40GHz)
9	Temperature test	±1°C
10	Humidity test	±3%
11	Time	±3%

5 General Information

5.1 General Description of EUT

Product Name:	Microphone
Model No.:	60704VA, 60704KP
Test Model No.:	60704VA
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Test sample(s) ID:	GTS2026070133-1
Sample(s) Status:	Engineer sample
S/N:	N/A
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	PCB antenna
Antenna Gain:	2.93dBi(Declared by applicant)
Power Supply:	DC 3.7V, 400mAh, 1.48Wh for Li-ion battery The battery is charged via USB DC 5V

Disclaimer statement:
1. Antenna gain information provided by the customer, and the laboratory is not responsible for its authenticity.
2. The information in this section is provided by the applicant or manufacturer, GTS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
UGREEN	USB Charger	CD244	20700
APPLE	Mobile Phone	IPHONE XR	DX3ZG240KXM7

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

● **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test software provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 10, 2026	Apr. 09, 2031
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 10, 2026	Apr. 09, 2027
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 11, 2026	Apr. 10, 2027
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2026	Apr. 10, 2027
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul 17, 2026	Jul 16, 2027
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.22, 2025	Nov.21, 2026
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 10, 2026	Apr. 09, 2027
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 10, 2026	Apr. 09, 2027
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2026	Apr. 10, 2027
11	Spectrum analyzer (9kHz-40GHz)	Rohde & Schwarz	FSV40-N	GTS666	Mar. 10, 2026	Mar. 09, 2027
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 10, 2026	Apr. 09, 2027
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 24, 2025	Nov. 23, 2026
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 10, 2026	Apr. 09, 2027
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 13, 2026	Apr. 12, 2027
16	RE cable 1	GTS	N/A	GTS675	Jul. 17, 2026	Jul. 16, 2027
17	RE cable 2	GTS	N/A	GTS676	Jul. 17, 2026	Jul. 16, 2027
18	RE cable 3	GTS	N/A	GTS677	Jul. 17, 2026	Jul. 16, 2027
19	RE cable 4	GTS	N/A	GTS678	Jul. 17, 2026	Jul. 16, 2027
20	RE cable 5	GTS	N/A	GTS679	Jul. 17, 2026	Jul. 16, 2027
21	RE cable 6	GTS	N/A	GTS680	Jul. 17, 2026	Jul. 16, 2027
22	RE cable 7	GTS	N/A	GTS681	Jul. 22, 2026	Jul. 21, 2027
23	RE cable 8	GTS	N/A	GTS682	Jul. 22, 2026	Jul. 21, 2027
24	CE cable 9	GTS	N/A	GTS683	Jul. 23, 2026	Jul. 22, 2027
25	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Jun. 03, 2026	Jun. 02, 2027
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 10, 2026	Apr. 09, 2027
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 14, 2026	Apr. 13, 2027
6	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 11, 2026	Apr. 10, 2027
7	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 10, 2026	Apr. 09, 2027
8	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 10, 2026	Apr. 09, 2027
9	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 10, 2026	Apr. 09, 2027
10	EMI Test Software	AUDIX	E3-6.100622	GTS726	N/A	N/A
11	Current probe	CYBERTEK	EM5011	GTS698	Jan. 27, 2026	Jan. 26, 2027

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 10, 2026	Apr. 09, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Jun. 03, 2026	Jun. 02, 2027
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 10, 2026	Apr. 09, 2027
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 10, 2026	Apr. 09, 2027
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 10, 2026	Apr. 09, 2027
6	Wideband Power Meter	Keysighte	N1924A	GTS673	Apr. 10, 2026	Apr. 09, 2027
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 10, 2026	Apr. 09, 2027
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 10, 2026	Apr. 09, 2027
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 10, 2026	Apr. 09, 2027
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 14, 2026	Apr. 13, 2027
11	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 01, 2025	Oct. 31, 2026

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Barometer	KUMAO	SF132	GTS647	Jul. 21, 2026	Jul. 20, 2027

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The antenna is PCB antenna, reference to the appendix II for details	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2020
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data

Pre-scan all test modes, found worst case at 2440MHz, and so only show the test result of it.

Line:



Freq	Reading level	Correct Factor	Final level	Limit level	Over limit	Remark
MHz	dBuV	dB	dBuV	level	dBuV	
0.15	12.23	19.60	31.83	65.78	-33.95	QP
0.15	-4.93	19.60	14.67	55.78	-41.11	Average
0.23	5.92	19.60	25.52	62.44	-36.92	QP
0.23	-8.53	19.60	11.07	52.44	-41.37	Average
0.77	5.66	19.61	25.27	56.00	-30.73	QP
0.77	-3.38	19.61	16.23	46.00	-29.77	Average
2.04	-0.74	19.66	18.92	56.00	-37.08	QP
2.04	-7.44	19.66	12.22	46.00	-33.78	Average
2.43	-1.80	19.66	17.86	56.00	-38.14	QP
2.43	-9.97	19.66	9.69	46.00	-36.31	Average
4.62	-6.68	19.68	13.00	56.00	-43.00	QP
4.62	-13.55	19.68	6.13	46.00	-39.87	Average

Note:Correct Factor (dB)=LISN Factor (dB) + Cable Loss (dB)
Final level (dBuV)=Reading level (dBuV) + Correct Factor (dB)

Neutral:



Freq	Reading level	Correct Factor	Final level	Limit level	Over limit	Remark
MHz	dBuV	dB	dBuV	level	dBuV	
0.15	12.79	19.60	32.39	65.78	-33.39	QP
0.15	-2.76	19.60	16.84	55.78	-38.94	Average
0.23	7.72	19.60	27.32	62.44	-35.12	QP
0.23	-3.79	19.60	15.81	52.44	-36.63	Average
0.77	6.84	19.61	26.45	56.00	-29.55	QP
0.77	-2.16	19.61	17.45	46.00	-28.55	Average
1.30	-2.07	19.63	17.56	56.00	-38.44	QP
1.30	-8.39	19.63	11.24	46.00	-34.76	Average
1.90	-4.53	19.66	15.13	56.00	-40.87	QP
1.90	-10.17	19.66	9.49	46.00	-36.51	Average
4.18	-7.48	19.68	12.20	56.00	-43.80	QP
4.18	-13.37	19.68	6.31	46.00	-39.69	Average

Note:Correct Factor (dB)=LISN Factor (dB) + Cable Loss (dB)
Final level (dBuV)=Reading level (dBuV) + Correct Factor (dB)

Notes:
1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission

7.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2020 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2020 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2020 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.6 Spurious Emission in Non-restricted & restricted Bands

7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2020 and KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2020
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Note: For Duty cycle ⩾ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ⩾ 1 / T

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP/PK/AV	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	30m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



	For radiated emissions from 30MHz to1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details

Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Remark:
Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ **Below 1GHz**

Pre-scan all test modes, found worst case at 2440MHz, and so only show the test result of it.

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
31.399	32.72	12.86	1.26	33.40	13.44	40.00	-26.56	QP
49.533	27.68	13.25	1.47	33.40	9.00	40.00	-31.00	QP
141.826	30.36	13.27	2.33	33.20	12.76	43.50	-30.74	QP
364.260	25.95	14.57	3.92	32.82	11.62	46.00	-34.38	QP
647.386	25.21	19.70	5.38	32.32	17.97	46.00	-28.03	QP
965.542	23.85	23.21	6.58	30.99	22.65	54.00	-31.35	QP

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
30.424	36.59	12.84	1.25	33.40	17.28	40.00	-22.72	QP
52.208	28.81	12.98	1.50	33.39	9.90	40.00	-30.10	QP
96.099	33.70	9.32	1.98	33.31	11.69	43.50	-31.81	QP
167.824	34.37	12.92	2.47	33.15	16.61	43.50	-26.89	QP
396.242	25.48	15.33	4.08	32.79	12.10	46.00	-33.90	QP
818.834	25.23	21.52	6.21	31.87	21.09	46.00	-24.91	QP

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

- **Above 1GHz**
- **Unwanted Emissions in Non-restricted Frequency Bands**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	49.76	32.22	5.56	38.02	49.52	74.00	-24.48	Peak
7206.000	36.52	36.41	7.17	37.96	42.14	74.00	-31.86	Peak
9608.000	38.71	38.20	9.07	39.18	46.80	74.00	-27.20	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4804.000	47.18	32.22	5.56	38.02	46.94	74.00	-27.06	Peak
7206.000	36.51	36.41	7.17	37.96	42.13	74.00	-31.87	Peak
9608.000	38.89	38.20	9.07	39.18	46.98	74.00	-27.02	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Middle	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4884.000	48.70	32.57	5.67	37.97	48.97	74.00	-25.03	Peak
7326.000	36.61	36.65	7.27	38.06	42.47	74.00	-31.53	Peak
9768.000	38.19	38.30	9.18	39.23	46.44	74.00	-27.56	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Middle	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4884.000	39.94	32.57	5.67	37.97	40.21	74.00	-33.79	Peak
7326.000	38.75	36.65	7.27	38.06	44.61	74.00	-29.39	Peak
9768.000	37.23	38.30	9.18	39.23	45.48	74.00	-28.52	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	48.58	32.74	5.77	37.92	49.17	74.00	-24.83	Peak
7440.000	37.44	36.68	7.33	38.15	43.30	74.00	-30.70	Peak
9920.000	38.67	38.40	9.24	39.28	47.03	74.00	-26.97	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	41.61	32.74	5.77	37.92	42.20	74.00	-31.80	Peak
7440.000	37.09	36.68	7.33	38.15	42.95	74.00	-31.05	Peak
9920.000	38.18	38.40	9.24	39.28	46.54	74.00	-27.46	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Notes:
1. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ **Unwanted Emissions in Restricted Frequency Bands**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	34.68	28.05	4.09	38.86	27.96	54.00	-26.04	Average
2310.000	45.49	28.05	4.09	38.86	38.77	74.00	-35.23	Peak
2377.868	49.05	27.14	4.11	38.88	41.42	54.00	-12.58	Average
2377.868	56.70	27.14	4.11	38.88	49.07	74.00	-24.93	Peak
2390.000	35.19	27.03	4.11	38.88	27.45	54.00	-26.55	Average
2390.000	46.33	27.03	4.11	38.88	38.59	74.00	-35.41	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	34.27	28.05	4.09	38.86	27.55	54.00	-26.45	Average
2310.000	45.93	28.05	4.09	38.86	39.21	74.00	-34.79	Peak
2390.000	35.35	27.03	4.11	38.88	27.61	54.00	-26.39	Average
2390.000	45.05	27.03	4.11	38.88	37.31	74.00	-36.69	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	36.57	26.78	4.13	38.90	28.58	54.00	-25.42	Average
2483.500	46.14	26.78	4.13	38.90	38.15	74.00	-35.85	Peak
2500.000	36.42	26.48	4.14	38.90	28.14	54.00	-25.86	Average
2500.000	45.93	26.48	4.14	38.90	37.65	74.00	-36.35	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	34.24	28.22	4.13	38.90	27.69	54.00	-26.31	Average
2483.500	45.55	28.22	4.13	38.90	39.00	74.00	-35.00	Peak
2500.000	35.08	28.63	4.14	38.90	28.95	54.00	-25.05	Average
2500.000	45.79	28.63	4.14	38.90	39.66	74.00	-34.34	Peak

Remarks:
Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Notes:
1. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------