

TEST REPORT

Reference No...... : WTX26X04113218W004
FCC ID..... : 2BVI9-MLWK1
Applicant..... : Mallow
Address..... : 229 rue Saint Honore, Paris 75001, France
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Mallow Kids Speaker
Model No...... : MLWK1
Standards..... : FCC Part 15.247
Date of Receipt sample..... : 2026-04-24
Date of Test..... : 2026-05-06 to 2026-08-24
Date of Issue..... : 2026-09-02
Test Report Form No...... : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,

Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 EUT SETUP AND TEST MODE	7
1.6 MEASUREMENT UNCERTAINTY	8
1.7 TEST EQUIPMENT LIST AND DETAILS	9
2. SUMMARY OF TEST RESULTS	13
3. ANTENNA REQUIREMENT	14
3.1 STANDARD APPLICABLE	14
3.2 EVALUATION INFORMATION	14
4. POWER SPECTRAL DENSITY	15
4.1 STANDARD APPLICABLE	15
4.2 TEST SETUP BLOCK DIAGRAM	15
4.3 TEST PROCEDURE	15
4.4 SUMMARY OF TEST RESULTS/PLOTS	15
5. DTS BANDWIDTH	16
5.1 STANDARD APPLICABLE	16
5.2 TEST SETUP BLOCK DIAGRAM	16
5.3 TEST PROCEDURE	16
5.4 SUMMARY OF TEST RESULTS/PLOTS	16
6. RF OUTPUT POWER	17
6.1 STANDARD APPLICABLE	17
6.2 TEST SETUP BLOCK DIAGRAM	17
6.3 TEST PROCEDURE	17
6.4 SUMMARY OF TEST RESULTS/PLOTS	17
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	18
7.1 STANDARD APPLICABLE	18
7.2 TEST PROCEDURE	18
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	20
7.4 SUMMARY OF TEST RESULTS/PLOTS	20
8. OUT OF BAND EMISSIONS	43
8.1 STANDARD APPLICABLE	43
8.2 TEST PROCEDURE	43
8.3 SUMMARY OF TEST RESULTS/PLOTS	44
9. CONDUCTED EMISSIONS	53
9.1 TEST PROCEDURE	53
9.2 BASIC TEST SETUP BLOCK DIAGRAM	53
9.3 TEST RECEIVER SETUP	53
9.4 SUMMARY OF TEST RESULTS/PLOTS	53
APPENDIX SUMMARY	56
APPENDIX A: DTS BANDWIDTH	57
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	60
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	67
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	72
APPENDIX E: REFERENCE LEVEL MEASUREMENT	77
APPENDIX F: BAND EDGE MEASUREMENTS	82
APPENDIX G: CONDUCTED SPURIOUS EMISSION	86
APPENDIX H: DUTY CYCLE	95

APPENDIX PHOTOGRAPHS 100

Report version

Version No.	Date of issue	Description
Rev.00	2026-09-02	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Mallow Kids Speaker
Trade Name:	Mallow
Model No.:	MLWK1
Adding Model(s):	/
Rated Voltage:	Battery:DC3.7V Type-C:DC5V
Battery Capacity:	2500mAh
Power Adapter:	/
<i>Note: The sample information is provided by the customer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V5.2 (LE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	Metal Antenna: 1Mbps: 6.87dBm (Conducted) 2Mbps: 7.01dBm (Conducted) PCB Antenna: 1Mbps: 7.18dBm (Conducted) 2Mbps: 7.33dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Metal Antenna & PCB Antenna
Antenna Gain:	Metal Antenna: -3.19dBi PCB Antenna: -0.24dBi
<i>Note: 1: The Antenna Gain is provided by the customer and can affect the validity of results. 2: The data provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz
Note: The prototype does not support MIMO modes, During work, only one antenna can be used for transmission		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	0.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Network cable	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	Xiaomi	MDY-11-EX	/
Router	TP-LINK	MR550	/
Phone	iphone	iphone 15	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.57\text{dB}$
Occupied Bandwidth	Conducted	$\pm 0.015\text{MHz}$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emission 1#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Conducted Emission 2#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: $\pm 5.36\text{dB}$
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.28\text{dB}$
		@1GHz to 6GHz: $\pm 5.56\text{dB}$
		@6GHz to 18GHz: $\pm 5.72\text{dB}$
		@18GHz to 40GHz: $\pm 6.12\text{dB}$

1.7 Test Equipment List and Details

Internal No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1002	Communication Tester	Rohde & Schwarz	CMW500	1201.0002 k50-14865 0-FB	2026-03-25	2027-03-24
WTXE1005A 1005	MXA Signal Analyzer	Agilent	N9020A	US471401 02	2026-03-25	2027-03-24
WTXE1084A 1001	MXA Signal Analyzer	KEYSIGHT	N9020A	MY543205 48	2026-02-06	2027-02-05
WTXE1005A 1006	Spectrum Analyzer	Rohde & Schwarz	FSP40	1164.4391 K38Ser. 100368	2026-04-29	2027-04-28
WTXW1105A 1010	MXA signal Analyzer	KEYSIGHT	N9020A	MY512856 78	2026-02-06	2027-02-05
WTXE1105A 1008	RF Control Unit	Tonscend	JS0806-2	/	2026-02-06	2027-02-05
WTXW1105A 1136	RF ATTENUATOR	FEIYANG	N-JK	/	2026-02-06	2027-02-05
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2026-02-23	2027-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2026-02-05	2027-02-04
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2026-02-05	2027-02-04
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2026-03-11	2029-03-10
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2026-02-05	2027-02-04
WTXE1001A	EMI Test	Rohde &	ESPI	101611	2026-02-05	2027-02-04

1001	Receiver	Schwarz				
WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2026-02-05	2027-02-04
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2026-02-05	2027-02-04
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2026-02-23	2027-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2026-02-05	2027-02-04
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2026-02-05	2027-02-04
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2026-02-23	2027-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2026-02-05	2027-02-04
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2026-02-05	2027-02-04
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
WTXE1104A	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22

1034-2						
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2026-02-23	2027-02-22
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2026-02-05	2027-02-04
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2026-02-05	2027-02-04
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2026-02-10	2027-02-09
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2026-02-05	2027-02-04
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2026-02-23	2027-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2026-02-05	2027-02-04
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2026-02-05	2027-02-04
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2026-02-23	2027-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2026-02-05	2027-02-04
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2026-02-05	2027-02-04
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2026-02-23	2027-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software/EZ-EMC (Radiated Emission A)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission B)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission C)	Farad	RA-03A1-2	1.1.4.2
EMI Test Software/EZ-EMC (Conducted Emission Room 1#)	Farad	3A1*CE-RE	1.1.4.3
EMI Test Software/EZ-EMC (Conducted Emission Room 2#)	Farad	3A1*CE-RE	1.1.4.3
RF Test System	Tonscend	JS1120-3	V3.6.21

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has a PCB antenna and Metal antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.10.2, the test method of power spectral density as below:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3kHz) and repeat.

4.4 Summary of Test Results/Plots


Please refer to Appendix D

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2020 Subclause 11.8.1, the test method of DTS Bandwidth as below:

Option 1:

The steps for the first option are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB downamplitude” value, then it shall be as close as possible to this value.

Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in ANSI C63.10-2020 Subclause 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB

5.4 Summary of Test Results/Plots


Please refer to Appendix A

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2020 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq 3 \times$ RBW.
- Set span $\geq 3 \times$ RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz
RBW=10kHz,
VBW =30kHz
Sweep time= Auto
Trace = max hold

Frequency :30MHz-1GHz
RBW=120kHz,
VBW=300kHz
Sweep time= Auto
Trace = max hold

Frequency :Above 1GHz
RBW=1MHz,
VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto
Trace = max hold

Detector function = peak

Detector function = peak, QP

Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


7.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Reference No.: WTX26X04113218W004

- Spurious Emissions 9kHz to 30MHz
- LE 1Mbps(worst case)
- Metal Antenna


Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	0.0099	57.53	-7.20	50.33	127.67	-77.34	-	-	peak
2	0.0352	51.29	-7.46	43.83	116.66	-72.83	-	-	peak
3	0.0889	47.35	-7.80	39.55	108.62	-69.07	-	-	peak
4	0.6271	59.54	-8.03	51.51	71.66	-20.15	-	-	peak
5	10.6763	39.76	-7.81	31.95	69.50	-37.55	-	-	peak
6	20.5944	38.81	-7.53	31.28	69.50	-38.22	-	-	peak

➤ PCB Antenna


Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	0.0114	55.57	-7.23	48.34	126.45	-78.11	-	-	peak
2	0.0338	51.29	-7.44	43.85	117.01	-73.16	-	-	peak
3	0.0769	48.62	-7.80	40.82	109.88	-69.06	-	-	peak
4	0.6271	58.46	-8.03	50.43	71.66	-21.23	-	-	peak
5	10.9050	38.00	-7.83	30.17	69.50	-39.33	-	-	peak
6	20.5944	37.31	-7.53	29.78	69.50	-39.72	-	-	peak


- Spurious Emissions Below 1GHz
- LE 1Mbps(worst case)
- Metal Antenna

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.9305	28.98	-8.55	20.43	40.00	-19.57	-	-	peak
2	78.5644	35.18	-12.04	23.14	40.00	-16.86	-	-	peak
3	148.9173	35.82	-8.54	27.28	43.50	-16.22	-	-	peak
4	261.2729	36.82	-9.64	27.18	46.00	-18.82	-	-	peak
5	455.1887	34.37	-4.56	29.81	46.00	-16.19	-	-	peak
6	781.9605	30.25	1.53	31.78	46.00	-14.22	-	-	peak


Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1824	31.38	-8.94	22.44	40.00	-17.56	-	-	peak
2	78.0143	34.39	-11.93	22.46	40.00	-17.54	-	-	peak
3	137.8398	32.80	-9.05	23.75	43.50	-19.75	-	-	peak
4	230.2295	31.75	-11.09	20.66	46.00	-25.34	-	-	peak
5	505.7890	37.59	-3.38	34.21	46.00	-11.79	-	-	peak
6	899.9576	32.00	2.66	34.66	46.00	-11.34	-	-	peak


➤ PCB Antenna

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.4086	30.00	-8.27	21.73	40.00	-18.27	-	-	peak
2	78.0143	35.31	-11.93	23.38	40.00	-16.62	-	-	peak
3	148.9173	33.90	-8.54	25.36	43.50	-18.14	-	-	peak
4	318.0875	39.19	-7.79	31.40	46.00	-14.60	-	-	peak
5	478.1394	34.83	-4.17	30.66	46.00	-15.34	-	-	peak
6	945.3336	32.09	3.54	35.63	46.00	-10.37	-	-	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.1824	31.37	-8.94	22.43	40.00	-17.57	-	-	peak
2	74.2696	32.42	-11.20	21.22	40.00	-18.78	-	-	peak
3	146.8391	33.34	-8.65	24.69	43.50	-18.81	-	-	peak
4	272.5245	30.75	-9.11	21.64	46.00	-24.36	-	-	peak
5	458.3987	37.79	-4.51	33.28	46.00	-12.72	-	-	peak
6	925.6131	31.08	3.16	34.24	46.00	-11.76	-	-	peak

- Spurious Emissions Above 1GHz
- LE 1Mbps(worst case)


Metal Antenna

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4804.000	52.79	-12.21	40.58	74.00	-33.42	-	-	peak
2	7206.000	51.41	-5.88	45.53	74.00	-28.47	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4804.000	52.61	-12.21	40.40	74.00	-33.60	-	-	peak
2	7206.000	51.05	-5.88	45.17	74.00	-28.83	-	-	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4880.000	52.43	-11.92	40.51	74.00	-33.49	-	-	peak
2	7320.000	50.25	-5.12	45.13	74.00	-28.87	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4880.000	53.06	-11.92	41.14	74.00	-32.86	-	-	peak
2	7320.000	51.11	-5.12	45.99	74.00	-28.01	-	-	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4960.000	53.01	-12.80	40.21	74.00	-33.79	-	-	peak
2	7440.000	50.85	-6.05	44.80	74.00	-29.20	-	-	peak


Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4960.000	52.17	-12.80	39.37	74.00	-34.63	-	-	peak
2	7440.000	50.80	-6.05	44.75	74.00	-29.25	-	-	peak


PCB Antenna

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4804.000	53.34	-12.21	41.13	74.00	-32.87	-	-	peak
2	7206.000	52.03	-5.88	46.15	74.00	-27.85	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4804.000	51.67	-12.21	39.46	74.00	-34.54	-	-	peak
2	7206.000	50.50	-5.88	44.62	74.00	-29.38	-	-	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4880.000	51.02	-11.92	39.10	74.00	-34.90	-	-	peak
2	7320.000	49.60	-5.12	44.48	74.00	-29.52	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4880.000	51.15	-11.92	39.23	74.00	-34.77	-	-	peak
2	7320.000	49.66	-5.12	44.54	74.00	-29.46	-	-	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4960.000	51.31	-12.80	38.51	74.00	-35.49	-	-	peak
2	7440.000	50.81	-6.05	44.76	74.00	-29.24	-	-	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4960.000	52.17	-12.80	39.37	74.00	-34.63	-	-	peak
2	7440.000	50.88	-6.05	44.83	74.00	-29.17	-	-	peak

Reference No.: WTX26X04113218W004

- Spurious Emission From Above 18GHz
- Metal Antenna:


Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency	Reading	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(dBuV/m)	(dB)	
1	25752	46.79	74.00	-27.21	peak

Reference No.: WTX26X04113218W004

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	25760	45.55	74.00	-28.45	peak

Reference No.: WTX26X04113218W004

- Spurious Emission From Above 18GHz
- PCB Antenna:

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	25712	45.98	74.00	-28.02	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	25600	45.30	74.00	-28.70	peak

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Conducted Spurious Emission Please refer to Appendix G

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2020 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

RBW as a function of frequency

Frequency	RBW
9kHz to 150kHz	200Hz to 300Hz
0.15MHz to 30MHz	9kHz to 10kHz
30MHz to 1000MHz	100kHz to 120kHz
>1000MHz	1MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots

- Radiated test
- LE 1Mbps


Metal Antenna

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.93	-18.90	25.03	54.00	-28.97	Average Detector
	2310.000	56.04	-18.90	37.14	74.00	-36.86	Peak Detector
2	2390.000	45.95	-18.82	27.13	54.00	-26.87	Average Detector
	2390.000	57.49	-18.82	38.67	74.00	-35.33	Peak Detector
3	2401.827	111.33	-18.85	92.48	/	/	Average Detector
	2401.623	112.23	-18.85	93.38	/	/	Peak Detector


Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.740	113.59	-18.63	94.96	/	/	Average Detector
	2479.940	114.65	-18.63	96.02	/	/	Peak Detector
2	2483.500	64.38	-18.65	45.73	54.00	-8.27	Average Detector
	2483.500	71.89	-18.65	53.24	74.00	-20.76	Peak Detector
3	2500.000	50.68	-18.75	31.93	54.00	-22.07	Average Detector
	2500.000	62.90	-18.75	44.15	74.00	-29.85	Peak Detector


PCB Antenna

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.00	-18.90	25.10	54.00	-28.90	Average Detector
	2310.000	56.72	-18.90	37.82	74.00	-36.18	Peak Detector
2	2390.000	45.68	-18.82	26.86	54.00	-27.14	Average Detector
	2390.000	58.00	-18.82	39.18	74.00	-34.82	Peak Detector
3	2402.031	111.38	-18.84	92.54	/	/	Average Detector
	2401.827	112.17	-18.85	93.32	/	/	Peak Detector


Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.790	113.92	-18.63	95.29	/	/	Average Detector
	2479.990	114.64	-18.63	96.01	/	/	Peak Detector
2	2483.500	64.39	-18.65	45.74	54.00	-8.26	Average Detector
	2483.500	72.16	-18.65	53.51	74.00	-20.49	Peak Detector
3	2500.000	50.72	-18.75	31.97	54.00	-22.03	Average Detector
	2500.000	62.99	-18.75	44.24	74.00	-29.76	Peak Detector


➤ LE 2Mbps
Metal Antenna

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.16	-18.90	25.26	54.00	-28.74	Average Detector
	2310.000	56.45	-18.90	37.55	74.00	-36.45	Peak Detector
2	2390.000	45.76	-18.82	26.94	54.00	-27.06	Average Detector
	2390.000	57.79	-18.82	38.97	74.00	-35.03	Peak Detector
3	2403.867	110.44	-18.83	91.61	/	/	Average Detector
	2403.867	112.34	-18.83	93.51	/	/	Peak Detector


Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2477.843	112.78	-18.62	94.16	/	/	Average Detector
	2477.893	114.45	-18.62	95.83	/	/	Peak Detector
2	2483.500	53.96	-18.65	35.31	54.00	-18.69	Average Detector
	2483.500	65.34	-18.65	46.69	74.00	-27.31	Peak Detector
3	2500.000	51.34	-18.75	32.59	54.00	-21.41	Average Detector
	2500.000	60.00	-18.75	41.25	74.00	-32.75	Peak Detector


PCB Antenna

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.88	-18.90	24.98	54.00	-29.02	Average Detector
	2310.000	56.75	-18.90	37.85	74.00	-36.15	Peak Detector
2	2390.000	51.17	-18.82	32.35	54.00	-21.65	Average Detector
	2390.000	56.58	-18.82	37.76	74.00	-36.24	Peak Detector
3	2403.867	110.21	-18.83	91.38	/	/	Average Detector
	2403.867	112.27	-18.83	93.44	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2477.843	113.11	-18.62	94.49	/	/	Average Detector
	2477.893	114.63	-18.62	96.01	/	/	Peak Detector
2	2483.500	54.34	-18.65	35.69	54.00	-18.31	Average Detector
	2483.500	64.97	-18.65	46.32	74.00	-27.68	Peak Detector
3	2500.000	49.79	-18.75	31.04	54.00	-22.96	Average Detector
	2500.000	61.41	-18.75	42.66	74.00	-31.34	Peak Detector

➤ Conducted test
Please refer to Appendix E&F


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	14.84	9.63	24.47	53.20	-28.73	AVG
2	0.2220	24.54	9.63	34.17	62.74	-28.57	QP
3	0.7900	24.34	9.75	34.09	56.00	-21.91	QP
4	0.8059	12.06	9.75	21.81	46.00	-24.19	AVG
5	1.1700	23.92	9.69	33.61	56.00	-22.39	QP
6	1.3260	13.06	9.63	22.69	46.00	-23.31	AVG
7	1.8620	23.16	9.42	32.58	56.00	-23.42	QP
8	1.8620	9.38	9.42	18.80	46.00	-27.20	AVG
9	4.0860	18.67	9.47	28.14	56.00	-27.86	QP
10	4.0980	5.16	9.47	14.63	46.00	-31.37	AVG
11*	13.5500	40.88	9.60	50.48	60.00	-9.52	QP
12	13.5500	8.75	9.60	18.35	50.00	-31.65	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1900	25.27	9.59	34.86	64.03	-29.17	QP
2	0.2140	13.84	9.63	23.47	53.04	-29.57	AVG
3	0.3020	13.23	9.63	22.86	50.19	-27.33	AVG
4	0.3339	22.03	9.63	31.66	59.35	-27.69	QP
5	0.7900	12.52	9.75	22.27	46.00	-23.73	AVG
6	0.8100	24.52	9.75	34.27	56.00	-21.73	QP
7	1.8540	9.23	9.42	18.65	46.00	-27.35	AVG
8	1.8740	23.03	9.41	32.44	56.00	-23.56	QP
9	5.4380	18.34	9.61	27.95	60.00	-32.05	QP
10	5.4620	3.80	9.62	13.42	50.00	-36.58	AVG
11*	13.5940	35.44	9.59	45.03	60.00	-14.97	QP
12	13.5940	6.86	9.59	16.45	50.00	-33.55	AVG

APPENDIX SUMMARY

Project No.	WTX26X04113218W004	Test Engineer	BAldi zhong
Start date	2026/6/20	Finish date	2026/8/24
Temperature	22.6℃	Humidity	57%
RF specifications	Bluetooth-LE		

APPENDIX	Description of Test Item	Result
A	DTS Bandwidth	Compliant
B	Occupied Channel Bandwidth	Compliant
C	Maximum conducted output power	Compliant
D	Maximum power spectral density	Compliant
E	Reference level measurement	Compliant
F	Band edge measurements	Compliant
G	Conducted Spurious Emission	Compliant
H	Duty Cycle	Compliant

Appendix A: DTS Bandwidth**Test Result****PCB Antenna:**

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
LE_1M	Ant1	2402	0.712	2401.596	2402.308	0.5	PASS
LE_1M	Ant1	2440	0.672	2439.644	2440.316	0.5	PASS
LE_1M	Ant1	2480	0.696	2479.620	2480.316	0.5	PASS
LE_2M	Ant1	2404	1.148	2403.360	2404.508	0.5	PASS
LE_2M	Ant1	2440	1.068	2439.436	2440.504	0.5	PASS
LE_2M	Ant1	2478	1.076	2477.452	2478.528	0.5	PASS

Metal Antenna:

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
LE_1M	Ant1	2402	0.656	2401.628	2402.284	0.5	PASS
LE_1M	Ant1	2440	0.668	2439.636	2440.304	0.5	PASS
LE_1M	Ant1	2480	0.668	2479.620	2480.288	0.5	PASS
LE_2M	Ant1	2404	1.500	2403.220	2404.720	0.5	PASS
LE_2M	Ant1	2440	1.140	2439.380	2440.520	0.5	PASS
LE_2M	Ant1	2478	1.292	2477.292	2478.584	0.5	PASS

Test Graphs

PCB Antenna:



LE_1M-Ant1-2402-PASS



LE_1M-Ant1-2440-PASS



LE_1M-Ant1-2480-PASS



LE_2M-Ant1-2404-PASS



LE_2M-Ant1-2440-PASS



LE_2M-Ant1-2478-PASS

Appendix B: Occupied Channel Bandwidth**Test Result****PCB Antenna:**


TestMode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
LE_1M	Ant1	2402	1.0230	2401.4602	2402.4832	---	---
LE_1M	Ant1	2440	1.0454	2439.4449	2440.4903	---	---
LE_1M	Ant1	2480	1.0323	2479.4551	2480.4874	---	---
LE_2M	Ant1	2404	2.0834	2402.9296	2405.0130	---	---
LE_2M	Ant1	2440	2.0499	2438.9422	2440.9921	---	---
LE_2M	Ant1	2478	2.0937	2476.9237	2479.0174	---	---

Metal Antenna:


TestMode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
LE_1M	Ant1	2402	1.0186	2401.4635	2402.4821	---	---
LE_1M	Ant1	2440	1.0489	2439.4416	2440.4905	---	---
LE_1M	Ant1	2480	1.0056	2479.4590	2480.4646	---	---
LE_2M	Ant1	2404	2.0883	2402.9220	2405.0103	---	---
LE_2M	Ant1	2440	2.0645	2438.9468	2441.0113	---	---
LE_2M	Ant1	2478	2.0881	2476.9447	2479.0328	---	---

Test Graphs


PCB Antenna:



LE_1M-Ant1-2402



LE_1M-Ant1-2440



LE_1M-Ant1-2480



LE_2M-Ant1-2404



LE_2M-Ant1-2440



LE_2M-Ant1-2478

Metal Antenna:



LE_1M-Ant1-2402-PASS



LE_1M-Ant1-2440-PASS



LE_1M-Ant1-2480-PASS



LE_2M-Ant1-2404-PASS



LE_2M-Ant1-2440-PASS



LE_2M-Ant1-2478-PASS