

FCC Test Report

Report No. : 1811C60462916201

Applicant : Oriental Megawill Trading Limited

Address : NO.7 ON 11TH FLOOR HO KING COMMERCIAL
CENTRE NOS.2-16 FA YUEN STREET,
MONG KOK, HONG KONG

Product Name : PORTABLE GENERATOR

Report Date : 2026-09-17



Guangdong Anbotek Testing Co., Ltd.

Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Modes	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
1.9. Disclaimer	9
2. Summary of Test Results	10
3. Conducted Emission Test	11
3.1. Test Standard and Limit	11
3.2. Test Setup	11
3.3. Test Procedure	11
3.4. Test Data	11
4. Radiation Spurious Emission Test	14
4.1. Test Standard and Limit	14
4.2. Test Setup	14
4.3. Test Procedure	15
4.4. Test Data	15
5. 20dB Occupy Bandwidth Test	20
5.1. Test Standard and Limit	20
5.2. Test Setup	20
5.3. Test Procedure	20
5.4. Test Data	20
6. Antenna Requirement	22
6.1. Test Standard and Requirement	22
6.2. Antenna Connected Construction	22
APPENDIX I -- TEST SETUP PHOTOGRAPH	23
APPENDIX II -- EXTERNAL PHOTOGRAPH	23
APPENDIX III -- INTERNAL PHOTOGRAPH	23

TEST REPORT

Applicant : Oriental Megawill Trading Limited
Manufacturer : Huizhou Intelligent Energy Co., Ltd.
Product Name : PORTABLE GENERATOR
Model No. : EB300, T300
Trade Mark : EBL, GRECELL
Battery Capacity: 11.1V, 26Ah, 288.6Wh
PV/DC Input: 12V-26V $\Rightarrow$ 5A Max , 55W Max
DC5521 Output*2: 12V $\Rightarrow$ 5A, 60W Max
Car Outlet Output: 12V $\Rightarrow$ 10A, 120W Max
Rating(s) : (DC5521 Output*2+Car Outlet Output: Total 120W)
USB 3.0 Output*3: 5V $\Rightarrow$ 2.5A, 9V $\Rightarrow$ 2A, 12V $\Rightarrow$ 1.5A, Total 54W Max
Type-C Output: 5V $\Rightarrow$ 3A, 9V $\Rightarrow$ 3A, 12V $\Rightarrow$ 3A 15V $\Rightarrow$ 3A, 20V $\Rightarrow$ 3A, 60W Max
AC Output: Pure Sine Wave, 120V~60Hz, 330W Max
Wireless Charger: 5V $\Rightarrow$ 1A, 5W Max
AC+DC Output: Total 300W

Test Standard(s) : **FCC Part15 Subpart C**
Test Method(s) : **ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024**
ANSI C63.30-2021

The device described above is tested by Guangdong Anbotek Testing Co., Ltd to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Guangdong Anbotek Testing Co., Ltd is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Guangdong Anbotek Testing Co., Ltd.

Date of Receipt 2026-08-26

Date of Test 2026-08-26 to 2026-09-08

Prepared By

Cecilia Chen

(Cecilia Chen)

Approved & Authorized Signer

Jules Guo

(Jules Guo)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2026-09-17

1. General Information

1.1. Client Information

Applicant	:	Oriental Megawill Trading Limited
Address	:	NO.7 ON 11TH FLOOR HO KING COMMERCIAL CENTRE NOS.2-16 FA YUEN STREET, MONG KOK, HONG KONG
Manufacturer	:	Huizhou Intelligent Energy Co., Ltd.
Address	:	Floors 8-9, Unit 1 & Unit 2, E2-1 Factory Building, Zone E2, Qunyi Intelligent Manufacturing Industrial Park, No. 1 Xingyuan South Road, China-Korea (Huizhou) Industrial Park Pilot Zone, Zhongkai High-Tech District, Huizhou
Factory	:	Huizhou Intelligent Energy Co., Ltd.
Address	:	Floors 8-9, Unit 1 & Unit 2, E2-1 Factory Building, Zone E2, Qunyi Intelligent Manufacturing Industrial Park, No. 1 Xingyuan South Road, China-Korea (Huizhou) Industrial Park Pilot Zone, Zhongkai High-Tech District, Huizhou

1.2. Description of Device (EUT)

Product Name	:	PORTABLE GENERATOR
Model No.	:	EB300, T300
Trade Mark	:	EBL,GRECELL
Test Power Supply	:	AC 120V 60Hz ; DC 26V ; DC 22.2V
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Model: A653-1504000D (Input:100-240VAC,50/60Hz,1.5A;Output:15V/4A,60W)
RF Specification		
Operation Frequency	:	113-205kHz
Modulation Type	:	ASK
Antenna Type	:	Inductive loop coil Antenna
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.3) All samples are the same except the model number, so we prepare "EB300" for test only.		

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
Wireless charging load	Shenzhen Ouju Technology Co., Ltd.	CD2577	/


1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Modes	Descriptions
TM1	Adapter+WPT Mode (10W 1% Load)
TM2	Adapter+WPT Mode (10W 50% Load)
TM3	Adapter+WPT Mode (10W 99% Load)
TM4	Standby Mode

1.5. Description Of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
1.	MXG RF Vector Signal Generator	Agilent	N5182A	2026-01-20	1 Year
2.	Spectrum analyzer	Agilent	N9020A	2026-04-13	1 Year
3.	Spectrum analyzer	Rohde & Schwarz	FSV40-N	2026-01-20	1 Year
4.	Electric and Magnetic Field Analyzer	Narda	EHP-200A	2026-01-22	1 Year
5.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	2025-08-05	2 Year
6.	Loop Antenna(9K-30M)	Schwarzbeck	FMZB1519B	2026-04-17	1 Year
7.	Pre-amplifier	EMtrace	RP01A	2026-06-15	1 Year
8.	EMI Test Receiver	Rohde & Schwarz	ESPI7	2026-06-15	1 Year
9.	EMI Test Receiver	Rohde & Schwarz	ESCI3	2026-06-15	1 Year
10.	Slicer	EMtrace	PL00903	2026-06-15	1 Year
11.	Three-phase AC/DC artificial power network	EMtrace	PWL-50-3400	2026-07-22	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
HZ_Conducted emissions (AMN 150kHz~30MHz)	3.00dB
HZ_Occupied Bandwidth	370Hz
HZ_Radiated emissions (9KHz~30MHz)	9KHz~150KHz:3.04 dB; 150KHz~30MHz:3.02 dB
HZ_Radiated emissions (30MHz~1000MHz)	Horizontal: 5.48 dB; Vertical: 5.48 dB
The measurement uncertainty and decision risk evaluated according to ABST/WI-EMC-F-001. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Test Location

Guangdong Anbotek Testing Co., Ltd.

Building C, No. 76, Huifeng 4th Road, Zhongkai High-tech Zone, Huizhou, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission Test	PASS
15.205/15.209	Spurious Emission	PASS
15.215(c)	20dB Occupy Bandwidth	PASS

Note: N/A" denotes test is not applicable in this Test Report


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.
Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: TM3
Test Specification: AC 120V/60Hz
Comment: Live Line
Temp.(°C)/Hum.(%RH): 26°C/40%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	48.97	11.22	60.19	66.00	-5.81	QP	
2	0.1905	28.00	11.31	39.31	54.01	-14.70	AVG	
3	0.2580	40.76	11.39	52.15	61.50	-9.35	QP	
4	0.6270	11.16	11.42	22.58	46.00	-23.42	AVG	
5	0.9103	23.03	11.35	34.38	56.00	-21.62	QP	
6	1.4640	8.53	11.36	19.89	46.00	-26.11	AVG	
7	2.9895	11.03	11.36	22.39	46.00	-23.61	AVG	
8	3.6015	27.29	11.17	38.46	56.00	-17.54	QP	
9	8.7765	27.85	10.51	38.36	60.00	-21.64	QP	
10	8.8393	18.56	10.50	29.06	50.00	-20.94	AVG	
11	19.7520	33.13	10.36	43.49	60.00	-16.51	QP	
12	19.7520	32.59	10.36	42.95	50.00	-7.05	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: TM3
Test Specification: AC 120V/60Hz
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 26°C/40%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1544	48.91	11.20	60.11	65.76	-5.65	QP	
2	0.1949	25.74	11.32	37.06	53.83	-16.77	AVG	
3	0.2535	21.74	11.37	33.11	51.64	-18.53	AVG	
4	0.2670	38.01	11.38	49.39	61.21	-11.82	QP	
5	0.4200	31.19	11.37	42.56	57.45	-14.89	QP	
6	0.6270	12.54	11.42	23.96	46.00	-22.04	AVG	
7	2.9264	13.29	11.34	24.63	46.00	-21.37	AVG	
8	3.8083	28.72	11.13	39.85	56.00	-16.15	QP	
9	8.7765	27.33	10.51	37.84	60.00	-22.16	QP	
10	8.8392	18.91	10.50	29.41	50.00	-20.59	AVG	
11	19.9680	32.12	10.37	42.49	60.00	-17.51	QP	
12	19.9680	31.05	10.37	41.42	50.00	-8.58	AVG	

4. Radiation Spurious Emission Test

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data


PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.


Test Results (Between 9KHz – 150KHz)

Test Mode: TM3
Distance: 3m
Power Source: AC 120V/60Hz
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 24°C/50%RH
Fundamental



Test Results (Between 0.15MHz – 30MHz)

Test Mode: TM3
Distance: 3m
Power Source: AC 120V/60Hz
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 24°C/50%RH




Remark:


1. According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.
2. Only record the worst data in the report.

Test Results (Between 30MHz –1000 MHz)

Test Mode: TM3
Distance: 3m
Power Source: AC 120V/60Hz
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 24°C/50%RH



Test Mode: TM3
Distance: 3m
Power Source: AC 120V/60Hz
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 24°C/50%RH




5. 20dB Occupy Bandwidth Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.215(c)
Test Limit	Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.2. Test Setup




5.3. Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1%-5%OBW, VBW≥3*RBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.4. Test Data

Temperature:	25.8 °C	Humidity:	53 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Freq. (MHz)	Bandwidth (kHz)	Results
0.14684	0.780	PASS



Date: 8.SEP.2026 15:44:04

Note: When required, the occupied bandwidth shall be measured using the procedure specified by the regulatory authority or purchasing agency, e.g., in ANSI C63.10 [B1]. However, in case of continuous wave WPT systems, it is acceptable to use an RBW that is above the 1% to 5% range usually prescribed for OBW measurement. See also 10.4.2c) and 10.4.2d).

6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----