

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BVIG-CSAP07006

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time $ E ^2, H ^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time $ E ^2, H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW/ cm2)	Result
2.4G WIFI	16±1	17	50.1187	0.8299 (-0.81dBi)	0.0083	1	Pass
BLE	2±1	3	1.9953	0.8299 (-0.81dBi)	0.0003	1	Pass
5.8GWIFI	16±1	17	50.1187	0.9661 (-0.15dBi)	0.0096	1	Pass
BAND 2	22±1	23	199.526 2	0.9120 (-0.4dBi)	0.0362	1	Pass
BAND 4	23±1	24	251.188 6	0.6714 (-1.73dBi)	0.0336	1	Pass
BAND 5	23±1	24	251.188 6	0.8531 (-0.69dBi)	0.0427	0.5	Pass
BAND 12	23±1	24	251.188 6	1.0740 (0.31dBi)	0.0537	0.5	Pass
BAND 13	22±1	23	199.526 2	0.7709 (-1.13dBi)	0.03062	0.5	Pass

BT+WIFI+4G supported simultaneous transmission:

BLE+2.4GWIFI+4G: $\sum \text{MPE Ratio} = 0.0003/1 + 0.0083/1 + 0.0537/0.5 = 0.116 \leq 1$,

BLE+5GWIFI+4G: $\sum \text{MPE Ratio} = 0.0003/1 + 0.0096/1 + 0.0537/0.5 = 0.1173 \leq 1$,

So passed.