



Shenzhen Most Technology Service Co., Ltd.
No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan,
Shenzhen, Guangdong, China.

TEST REPORT

FCC Rules Part 15.247

Report Reference No......: **MTEB26040213-R**

FCC ID.....: **2BVLD-C201T**

Compiled by

(position+printed name+signature)..: File administrators
Ekaterina Zhang

Ekaterina Zhang

Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng

Sunny Deng

Approved by

(position+printed name+signature)..: Manager Yvette Zhou

Yvette Zhou

Date of issue.....: Apr.22,2026

Representative Laboratory Name.: **Shenzhen Most Technology Service Co., Ltd.**

Address.....: East A, 1/F., New Aolin Factory Buiding, Langshan Erlu, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Applicant's name.....: **Xiamen Lanxu Intelligent Technology Co., Ltd.**

Address.....: Room 101, No. 65 Hongxi South Road, Torch(Xiang'an) Industrial Zone. Xiamen, Fujian, China

Test specification/ Standard.....: **FCC Rules Part 15.247**

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Automatic Cleaning Robot

Trade Mark: N/A

Model/Type reference.....: SLW-C201T

Listed Models: SLW-XXXXX,LIT-C-T4M-P1-N,LIT-X-XXX-XX-X

Modulation Type.....: GFSK

Operation Frequency.....: 920.3 – 924.8 MHz

Hardware Version.....: V2.0

Software Version.....: V1.33

Rating.....: DC 24V

Result.....: PASS

TEST REPORT

Equipment under Test : Automatic Cleaning Robot

Model /Type : SLW-C201T

Listed Models : SLW-XXXXX,LIT-C-T4M-P1-N,LIT-X-XXX-XX-X

Remark : The differences among them are as follows: the series models only vary in model designation and color; all other specifications are identical.

Applicant : Xiamen Lanxu Intelligent Technology Co., Ltd.

Address : Room 101, No. 65 Hongxi South Road, Torch(Xiang'an) Industrial Zone. Xiamen, Fujian, China

Manufacturer : Xiamen Lanxu Intelligent Technology Co., Ltd.

Address : Room 101, No. 65 Hongxi South Road, Torch(Xiang'an) Industrial Zone. Xiamen, Fujian, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. REVISION HISTORY	4
2. TEST STANDARDS	5
3. SUMMARY	6
3.1. General Remarks	6
3.2. Product Description	6
3.3. Equipment Under Test	6
3.4. Short description of the Equipment under Test (EUT)	6
3.5. EUT operation mode	7
3.6. Block Diagram of Test Setup	7
3.7. Test Item (Equipment Under Test) Description*	7
3.8. Auxiliary Equipment (AE) Description	7
3.9. Antenna Information*	7
3.10. EUT configuration	8
3.11. Modifications	8
4. TEST ENVIRONMENT	9
4.1. Address of the test laboratory	9
4.2. Environmental conditions	9
4.3. Test Description	10
4.4. Statement of the measurement uncertainty	10
4.5. Equipments Used during the Test	11
5. TEST CONDITIONS AND RESULTS	12
5.1. AC Power Conducted Emission	12
5.2. Radiated Emission	13
5.3. Maximum Peak Output Power	20
5.4. Power Spectral Density	21
5.5. 6dB Bandwidth and 99% Bandwidth	22
5.6. Band Edge Compliance of RF Emission	24
5.7. Spurious RF Conducted Emission	26
5.8. Antenna Requirement	27
6. TEST SETUP PHOTOS OF THE EUT	28
7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	29
.....End of Report.....	29

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2026.04.22	Initial Issue	Ekaterina Zhang

2. TEST STANDARDS

The tests were performed according to following standards:

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2020](#) : American National Standard for Testing Unlicensed Wireless Devices

3. SUMMARY

3.1. General Remarks

Date of receipt of test sample	:	2026.04.08
Testing commenced on	:	2026.04.09
Testing concluded on	:	2026.04.21

3.2. Product Description

Product Name:	Automatic Cleaning Robot
Model/Type reference:	SLW-C201T
Power Supply:	DC 24V
Testing sample ID:	MTYP12608
LORA :	
Modulation:	GFSK
Operation frequency:	920.3-924.8 MHz
Antenna type:	GLASS-ANTENNA
Antenna gain:	8.69dBi

3.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 24V

3.4. Short description of the Equipment under Test (EUT)


This is a Automatic Cleaning Robot For more details, refer to the user's manual of the EUT.

3.5. EUT operation mode


The system was configured in testing mode(Duty Cycle 100%), which was provided by manufacturer. For 500kbps mode, 10 channels are provided for testing:

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	920.3	6	922.8
2	920.8	7	923.3
3	921.3	8	923.8
4	921.8	9	924.3
5	922.3	10	924.8

EUT was tested with channel 1, 6 and 10.



3.6. Block Diagram of Test Setup



3.7. Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A	/	/	/	/	/
EUT B	/	/	/	/	/

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8. Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1	/	/	/	/
AE 2	/	/	/	/

3.9. Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	GLASS-ANTENNA	2.4–2.5 GHz	---	8.69dBi
Antenna 2	/	/	/	/	/

*: declared by the applicant.

3.10. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

☐	ADAPTER	M/N:	
☐		Manufacturer:	

3.11. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.
The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2. Environmental conditions

Radiated Emission:

Temperature:	25.5°C
Humidity:	57.5%
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	25.5°C
Humidity:	57.5%
Atmospheric pressure:	950-1050mbar

4.3. Test Description

FCC and IC Requirements		
FCC Part 15.207	AC Power Conducted Emission	N/A
FCC Part 15.247 (a)(2)	6dB Bandwidth & 99% Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247 (e)	Power Spectral Density	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	100 kHz Bandwidth of Frequency Band Edge	PASS

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)
6dB Bandwidth & 99% Bandwidth	/	5%	(1)
Maximum Conducted Output Power	/	0.80dB	(1)
Spurious RF Conducted Emission	/	1.6dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5. Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.
1.	L.I.S.N.	R&S	ENV216	100093	/	2026/02/28
2	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2026/02/28
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2026/02/28
4	Receiver	R&S	ESPI	101202	V3.0-10-2	2026/02/28
5	Spectrum analyzer	Agilent	9020A	MT-E306	A14.16	2026/02/28
6	Bilong Antenna	Sunol Sciences	JB3	A121206	/	2025/11/22
7	Horn antenna	HF Antenna	HF Antenna	MT-E158	/	2025/03/16
8	Loop antenna	Beijing Daze	ZN30900B	/	/	2026/02/28
9	Horn antenna	R&S	OBH100400	26999002	/	2025/03/16
10	Wireless Communication Test Set	R&S	CMW500	/	CMW-BASE-3.7.21	2026/02/28
11	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2026/02/28
12	High gain antenna	Schwarzbeck	LB-180400KF	MT-E389	/	2026/02/28
13	Preamplifier	Schwarzbeck	BBV 9743	MT-E390	/	2026/02/28
14	Pre-amplifier	EMCI	EMC051845S E	MT-E391	/	2026/02/28
15	Pre-amplifier	Agilent	83051A	MT-E392	/	2026/02/28
16	High pass filter unit	Tonscend	JS0806-F	MT-E393	/	2026/02/28
17	RF Cable(below1GHz)	Times	9kHz-1GHz	MT-E394	/	2026/02/28
18	RF Cable(above 1GHz)	Times	1-40G	MT-E395	/	2026/02/28
19	RF Cable (9KHz-40GHz)	Tonscend	170660	N/A	/	2026/02/28
20	Power meter	R&S	NRVS	100444	/	2026/02/28

Note: 1. The Cal.Interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
- 4 The EUT received DC 5V power, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For unintentional device, according to RSS Gen 8.8 and § 15.207(a) Line Conducted Emission Limits is as following:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


TEST RESULTS

N/A


5.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission

Unwanted emissions that fall into restricted bands shall comply with the limits specified in RSS-Gen; and Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. For below 1GHz testing recorded worst at GFSK middle channel.
2. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.


For 30MHz-1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	52.3911	24.88	8.22	33.10	40.00	-6.90	QP	200	360	P	
2	73.8756	16.41	9.61	26.02	40.00	-13.98	QP	200	360	P	
3	119.0180	14.76	15.69	30.45	43.50	-13.05	QP	200	360	P	
4	195.8220	19.67	15.07	34.74	43.50	-8.76	QP	200	360	P	
5	220.6170	16.71	14.62	31.33	46.00	-14.67	QP	200	360	P	
6	303.5437	9.93	15.57	25.50	46.00	-20.50	QP	200	360	P	

*:Maximum data x:Over limit !:over margin

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.0000	12.49	20.90	33.39	40.00	-6.61	QP	100	110	P	
2 *	52.3911	26.87	8.22	35.09	40.00	-4.91	QP	100	360	P	
3	117.7724	15.45	15.55	31.00	43.50	-12.50	QP	100	250	P	
4	197.2000	15.29	15.12	30.41	43.50	-13.09	QP	100	360	P	
5	223.7333	12.28	14.54	26.82	46.00	-19.18	QP	100	360	P	
6	267.5452	11.57	14.40	25.97	46.00	-20.03	QP	100	360	P	

*:Maximum data x:Over limit !:over margin

Above 1GHz

920.3MHz							
Frequency	Antenna	Reading	Factor	Emission Level	Limits	Over	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
1840.6	H	53.26	-4.28	48.98	74	-25.02	PK
1840.6	H	37.72	-4.28	33.44	54	-20.56	AV
1840.6	V	56.10	-4.28	51.82	74	-22.18	PK
1840.6	V	39.39	-4.28	35.11	54	-18.89	AV
2760.9	H	51.68	1.13	52.81	74	-21.19	PK
2760.9	H	38.56	1.13	39.69	54	-14.31	AV
2760.9	V	51.86	1.13	52.99	74	-21.01	PK
2760.9	V	36.67	1.13	37.8	54	-16.2	AV

922.8MHz							
Frequency	Antenna	Reading	Factor	Emission Level	Limits	Over	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
1845.6	H	51.73	-4.14	47.59	74	-26.41	PK
1845.6	H	36.94	-4.14	32.8	54	-21.2	AV
1845.6	V	53.41	-4.14	49.27	74	-24.73	PK
1845.6	V	37.82	-4.14	33.68	54	-20.32	AV
2768.4	H	48.65	0.56	49.21	74	-24.79	PK
2768.4	H	35.68	0.56	36.24	54	-17.76	AV
2768.4	V	48.68	0.56	49.24	74	-24.76	PK
2768.4	V	35.64	0.56	36.2	54	-17.8	AV

924.8MHz							
Frequency	Antenna	Reading	Factor	Emission Level	Limits	Over	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
1840.6	H	52.44	-4.03	48.41	74	-25.59	PK
1840.6	H	36.25	-4.03	32.22	54	-21.78	AV
1840.6	V	54.08	-4.03	50.05	74	-23.95	PK
1840.6	V	36.99	-4.03	32.96	54	-21.04	AV
2774.4	H	49.63	1.68	51.31	74	-22.69	PK
2774.4	H	36.33	1.68	38.01	54	-15.99	AV
2774.4	V	48.91	1.68	50.59	74	-23.41	PK
2774.4	V	35.37	1.68	37.05	54	-16.95	AV

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

5.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE


According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2. The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS

Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)
500kbps	Low	920.3	6.225	≤ 30
	Middle	922.8	6.239	
	High	924.8	6.251	



5.4. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE


1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 3 kHz.
3. Set the VBW = 10 KHz.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be ≤ 8 dBm.

LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS

Mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
500kbps	Low	920.3	4.918	≤ 8
	Middle	922.8	5.110	
	High	924.8	4.581	



5.5. 6dB Bandwidth and 99% Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 V03 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 43 KHz RBW and 150 KHz VBW record the 99% bandwidth.


LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS

Mode	Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)
500kbps	Low	920.3	609.9	≥ 500
	Middle	922.8	622.3	
	High	924.8	612.8	






5.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was placed on a turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT was 3 meter:
6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

TEST RESULTS**Results of Band Edges Test (Radiated)**

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
901.825	25.95	46	20.05	H	1.6
920.069	94.76	--	--	H	2.1
901.825	23.99	46	22.01	V	1.6
920.135	90.41	--	--	V	2.1
924.585	95.13	--	--	H	2.3
928.020	40.15	46	5.85	H	2.3
924.585	91.86	--	--	V	2.3
928.020	35.2	46	10.8	V	2.3

Results of Band Edges Test (Conducted)

5.7. Spurious RF Conducted Emission

TEST CONFIGURATION




TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST RESULTS



5.8. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance



The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The directional gains of antenna used for transmitting is 8.69dBi, and the antenna is an GLASS-ANTENNA to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6. Test Setup Photos of the EUT



7. External and Internal Photos of the EUT

See related photo report.

.....End of Report.....