

MPE Evaluation

Applicant: Guangzhou Petovate Ventures Technology Co.,Ltd.

FCC ID: 2BVNB-LITO-A1

Model: WY-TX15W-V2

MPE Evaluation

RF Exposure Compliance Requirement

Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06 and FCC 1.1310 Radio frequency radiation exposure limits for General Population/Uncontrolled Exposure.

Limit For Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	< 6
3.0-30	1824/f	4.89/f	*(900/f ²)	< 6
30-300	61.4	0.163	1.0	< 6
300-1500	/	/	f/300	< 6
1500-100,000	/	/	5	< 6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	< 30
1.34-30	824/f	2.19/f	*(180/f ²)	< 30
30-300	27.5	0.073	0.2	< 30
300-1500	/	/	f/1500	< 30
1500-100,000	/	/	1.0	< 30
Note: f = frequency in MHz. * = Plane-wave equivalent power density.				

EUT RF Exposure

For MPP 360KHz

The Max Output Power is -22.03 dBm

$$R=20\text{cm}$$

$$P_d = PG/(4\pi R^2) = 0.00001 \text{ mW/cm}^2 < 1 (\text{limits}) \text{ mW/cm}^2$$

For MPP 134KHz

The Max Output Power is -15.51 dBm

$$R=20\text{cm}$$

$$P_d = PG/(4\pi R^2) = 0.00001 \text{ mW/cm}^2 < 1 (\text{limits}) \text{ mW/cm}^2$$

--END--