

FCC RF Exposure Evaluation

Product Name : Smart Glasses

Mode: WAI3

FCC ID : 2BVNZ-WAI3

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

FCC Exposure Evaluation

Mode	Max Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. Result	limit
BR/EDR	-1.91	0.644	2402	5	0.200	3.0
BLE	-3.39	0.458	2402	5	0.142	3.0
2.4WIFI	5.81	3.81	2412	5	1.183	3.0

BT ANT

ANT Gain= 2.49dBi

WiFi ANT

ANT Gain= 2.48dBi

Result: Compliant

So a SAR test is not required