

RF Test Report

For

Applicant name: INDIESEMIC PRIVATE LIMITED
Address: A-1101 ,B-1101, The First, B/H Keshavbaug Party Plot, Vastrapur, Ahmedabad, Ahmedabad, Gujarat, 380015
EUT name: ISC-SX1262-B Module
Brand name: Indiesemic
Model number: ISC-SX1262-B
Series model number: N/A
FCC ID: 2BVP2ISC-SX1262-B

Issued By

Company name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

Report number: BTF260617R01301
Test standards: 47 CFR Part 15.247
Test conclusion: Pass

Date of sample receipt: 2026-06-17
Test date: 2026-06-17 to 2026-07-31
Date of issue: 2026-08-19

Prepared by: Sean.He
Sean.He / Project engineer

Approved by: 
Ryan.CJ / EMC Manager

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2026-08-19	Original
Note: <i>Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1 Introduction	4
1.1 Laboratory Location	4
1.2 Laboratory Facility	4
1.3 Announcement	4
2 Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Technical Information	6
2.6 Channel List	6
3 Summary of Test Results	7
3.1 Test Standards	7
3.2 Uncertainty of Test	7
3.3 Summary of Test Result	7
3.4 Additions to, deviations, or exclusions from the method	8
4 Test Configuration	8
4.1 Test Equipment List	8
4.2 Test Auxiliary Equipment	9
4.3 Test Modes	9
4.4 Test software	9
5 Evaluation Results (Evaluation)	10
5.1 Antenna requirement	10
5.1.1 Conclusion	10
6 Radio Spectrum Matter Test Results (RF)	11
6.1 Conducted Emission at AC power line	11
6.1.1 Test Data	12
6.2 20dB Bandwidth	14
6.2.1 Test Data	15
6.3 Maximum Conducted Output Power	16
6.3.1 Test Data	16
6.4 Channel Separation	17
6.4.1 Test Data	17
6.5 Number of Hopping Frequencies	18
6.5.1 Test Data	19
6.6 Dwell Time	20
6.6.1 Test Data	21
6.7 Emissions in non-restricted frequency bands	22
6.7.1 Test Data	22
6.8 Emissions in frequency bands (below 1GHz)	23
6.8.1 Test Data	25
6.9 Emissions in frequency bands (above 1GHz)	27
6.9.1 Test Data	28
7 Test Setup Photos	30
8 EUT Constructional Details (EUT Photos)	30

1 Introduction

1.1 Laboratory Location

Test location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Phone number:	+86-0755-23146130
Fax number:	+86-0755-23146130

1.2 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1409**
BTF Testing Lab (Shenzhen) Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Registration No. is 695374.
- **CNAS - Registration No.: CNAS L17568**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L17568.
- **A2LA - Registration No.: 6660.01**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.
- **ISED – CAB identifier.: CN0135**
The 3m Semi-anechoic chamber of BTF Testing Lab (Shenzhen) Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 27844.

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.
- (7) All entrusted information in this report is provided by the client and has been confirmed through consultation with the client; The testing items for this report have been discussed and confirmed with the client, and our company is only responsible for the content reflected in the report.

2 Product Information

2.1 Application Information

Company name:	INDIESEMIC PRIVATE LIMITED
Address:	A-1101 ,B-1101, The First, B/H Keshavbaug Party Plot, Vastrapur, Ahmedabad, Ahmedabad, Gujarat, 380015

2.2 Manufacturer Information

Company name:	INDIESEMIC PRIVATE LIMITED
Address:	A-1101 ,B-1101, The First, B/H Keshavbaug Party Plot, Vastrapur, Ahmedabad, Ahmedabad, Gujarat, 380015

2.3 Factory Information

Company name:	VINROX TECHNOLOGIES LLP
Address:	GIDC ESTATE, 336/22, MAKARPURA ROAD MAKARPURA, Gujarat, 390010

2.4 General Description of Equipment under Test (EUT)

EUT name:	ISC-SX1262-B Module
Under test model name:	ISC-SX1262-B
Series model name:	N/A
Description of model name differentiation:	N/A
Hardware version:	V2
Software version:	nRF Connect SDK v3.1.1
Rating:	Input: DC 1.8~3.6 V, 0.118 A

2.5 Technical Information

Operation Frequency:	902.300MHz~914.900MHz
Channel numbers:	64
Modulation technology:	CSS (Chirp Spread Spectrum)
Antenna type:	External Antenna
Antenna gain:	1.7dBi (declare by Applicant)
Maximum Peak Conducted Output Power (dBm)	18.87dBm

2.6 Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	902.3	18	905.7	35	909.1	52	912.5
2	902.5	19	905.9	36	909.3	53	912.7
3	902.7	20	906.1	37	909.5	54	912.9
4	902.9	21	906.3	38	909.7	55	913.1
5	903.1	22	906.5	39	909.9	56	913.3
6	903.3	23	906.7	40	910.1	57	913.5
7	903.5	24	906.9	41	910.3	58	913.7
8	903.7	25	907.1	42	910.5	59	913.9
9	903.9	26	907.3	43	910.7	60	914.1
10	904.1	27	907.5	44	910.9	61	914.3
11	904.3	28	907.7	45	911.1	62	914.5
12	904.5	29	907.9	46	911.3	63	914.7
13	904.7	30	908.1	47	911.5	64	914.9
14	904.9	31	908.3	48	911.7	--	--
15	905.1	32	908.5	49	911.9	--	--
16	905.3	33	908.7	50	912.1	--	--
17	905.5	34	908.9	51	912.3	--	--

Remark: Channel 1, 32 & 64 have been tested.

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10-2020+Cor.1-2023: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

3.2 Uncertainty of Test

Measurement	Value
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.45 dB
Occupied Channel Bandwidth	±5 %
Unwanted Emissions, conducted	±3.0 dB
Supply voltages	±3 %
Time	±5 %
Conducted Emission for LISN (9kHz ~ 150kHz)	±2.97 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.45 dB
Radiated Emission(9kHz~30MHz)	±2.20 dB
Radiated Emission (30MHz ~ 1000MHz)	±4.80 dB
Radiated Emission (1GHz ~ 18GHz)	±4.82 dB

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
20dB Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(1)(i)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(2)	Pass
Channel Separation	47 CFR Part 15.247	47 CFR 15.247(a)(1)	Pass
Number of Hopping Frequencies	47 CFR Part 15.247	47 CFR 15.247(a)(1)(i)	Pass
Dwell Time	47 CFR Part 15.247	47 CFR 15.247(a)(1)(i)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

Remark:

1. Pass: Meet the requirements.
2. N/A: not applicable.

3.4 Additions to, deviations, or exclusions from the method

None

4 Test Configuration

4.1 Test Equipment List

Channel Separation Number of Hopping Frequencies Dwell Time Emissions in non-restricted frequency bands 20dB Bandwidth Maximum Conducted Output Power Power Spectral Density					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Test Software	TST Pass	/	Version: 2.0	/	/
Cell Site Test Set	HP	8921A	US35010158	2025-10-17	2026-10-16
Spectrum Analyzer	Keysight	N9020A	MY50410020	2025-10-17	2026-10-16
ESG Vector Signal Generator	Agilent	E4438C	MY45094854	2025-10-17	2026-10-16
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2025-10-17	2026-10-16
Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	161997	2025-10-17	2026-10-16
Programmable Constant Temperature And Humidity Test Chamber	ZZCKONG	ZZ-K02A	20210928007	2025-10-17	2026-10-16
DC Power Supply	Tongmen	etm-6050c	20211026123	2025-10-17	2026-10-16
RF Control Unit	Techy	TR1029-1	10291	2025-10-17	2026-10-16
RF Sensor Unit	Techy	TR1029-2	10292	2025-10-17	2026-10-16
RF shielding box	Yinuoxin Electronics	50*50*50 cm	050505M	2025-10-21	2026-10-20

Band edge emissions (Radiated) Emissions in frequency bands (below 1GHz) Emissions in frequency bands (above 1GHz)					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Test Software	Frad	EZ EMC	Version: FA-03A2 RE+	/	/
EMI Receiver	Rohde & Schwarz	ESCI7	101032	2025-10-17	2026-10-16
Signal Analyzer	Rohde & Schwarz	FSQ40	100010	2025-10-17	2026-10-16
Log periodic antenna	Schwarzbeck	VULB 9168	01328	2025-10-18	2026-10-17
Preamplifier (9kHz ~ 6GHz)	Schwarzbeck	BBV9744	00246	2026-05-10	2027-05-09
BELOW-Cable	REBES Talent	9K1G	21101576	2025-08-23	2026-08-22
Horn Antenna	Schwarzbeck	BBHA9120D	2597	2025-10-18	2026-10-17
Preamplifier (1GHz ~ 18GHz)	Schwarzbeck	BBV9718D	00008	2025-10-18	2026-10-17
Preamplifier	TSTPASS	LNA10180G45	TS2215007	2026-05-10	2027-05-09
ABOVE-Cable	REBES Talent	1~18G	21101558	2025-08-23	2026-08-22
Horn Antenna	SCHWARZBECK	BBHA9170	1157	2025-10-18	2026-10-17
Low Noise Pre-amplifier	Sket	LNPA_1840G-50	SK2022032902	2025-10-17	2026-10-16
ABOVE-Cable2	REBES Talent	18~40G	21101686	2025-08-23	2026-08-22
ABOVE-Cable1	REBES Talent	18~40G	21101687	2025-08-23	2026-08-22
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00059	2025-06-25	2027-06-24
Band-rejection filter	Microwave	WT.A3678-R10	FIL-915-001	2025-10-18	2026-10-17

4.2 Test Auxiliary Equipment

The EUT has been tested as an independent unit.

4.3 Test Modes

No.	Test Modes
TM1	TX mode(902.3MHz)
TM2	TX mode(908.5MHz)
TM3	TX mode(914.9MHz)

4.4 Test software

Test software:	Version:	Power Class:
SecureCRTPortable.exe	Version 8.7.2	22

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Operating Environment:	
Temperature:	22.5 °C
Humidity:	50.3 %
Atmospheric Pressure:	1010 mbar
Test voltage:	/

5.1.1 Conclusion

The antenna is an External Antenna which permanently attached, and the best case gain of the antenna is 1.7dBi. See product photos for details.

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Method:	ANSI C63.10-2020+Cor.1-2023 section 6.2		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Procedure:	Refer to ANSI C63.10-2020+Cor.1-2023 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		
Test Setup:	Diagram illustrating the test setup for conducted emissions. The setup includes a table with three EUT/AE units and a PSU. Cables connect the EUT/AE units to an AMN (Antenna Measurement Network) and AAN (Antenna Attachment Network), which are connected to a vertical reference ground plane. The distance between the EUT/AE units is 0.1 m. The distance from the EUT/AE units to the AMN/AAN is 0.8 m. The distance from the AMN/AAN to the vertical reference ground plane is 0.4 m. The distance from the EUT/AE units to the vertical reference ground plane is 0.8 m. The distance from the EUT/AE units to other metallic surfaces is ≥ 0.8 m. The AMN and AAN are bonded to a reference ground plane. The diagram is labeled IEC.		
Operating Environment:			
Temperature:	25.5 $^{\circ}$ C		
Humidity:	49.9 %		
Atmospheric Pressure:	1010 mbar		
Test voltage:	AC 120V 60Hz		

6.1.1 Test Data


Remark: The report only reflects the test data of worst mode.

TM2 / Line: Line / Band: 902.300MHz~914.900MHz/ BW: 125kHz / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1770	21.09	10.20	31.29	64.63	-33.34	QP	P	
2	0.2130	4.31	10.12	14.43	53.09	-38.66	AVG	P	
3	0.3165	18.32	10.13	28.45	59.80	-31.35	QP	P	
4	0.3255	0.87	10.13	11.00	49.57	-38.57	AVG	P	
5 *	0.6540	20.26	10.18	30.44	56.00	-25.56	QP	P	
6	0.6674	0.88	10.19	11.07	46.00	-34.93	AVG	P	
7	1.3965	0.22	10.21	10.43	46.00	-35.57	AVG	P	
8	1.7430	14.03	10.26	24.29	56.00	-31.71	QP	P	
9	4.3935	16.38	10.28	26.66	56.00	-29.34	QP	P	
10	4.3935	-1.84	10.28	8.44	46.00	-37.56	AVG	P	
11	5.7570	-1.84	10.34	8.50	50.00	-41.50	AVG	P	
12	5.7975	17.65	10.34	27.99	60.00	-32.01	QP	P	

TM2/ Line: Neutral / 902.300MHz~914.900MHz/ BW: 125kHz / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1770	21.56	10.11	31.67	64.63	-32.96	QP	P	
2	0.2130	4.53	10.12	14.65	53.09	-38.44	AVG	P	
3	0.3209	1.91	10.12	12.03	49.68	-37.65	AVG	P	
4	0.3614	19.87	10.12	29.99	58.70	-28.71	QP	P	
5	0.6630	4.34	10.15	14.49	46.00	-31.51	AVG	P	
6 *	0.6720	22.95	10.15	33.10	56.00	-22.90	QP	P	
7	1.3874	0.66	10.19	10.85	46.00	-35.15	AVG	P	
8	1.6754	15.68	10.20	25.88	56.00	-30.12	QP	P	
9	3.0840	13.04	10.26	23.30	56.00	-32.70	QP	P	
10	3.0840	-1.07	10.26	9.19	46.00	-36.81	AVG	P	
11	4.3800	-1.60	10.31	8.71	46.00	-37.29	AVG	P	
12	4.4565	15.35	10.31	25.66	56.00	-30.34	QP	P	

Note:Margin=Level-Limit=Reading+factor-Limit=Reading+LISN+Cable loss-Limit

6.2 20dB Bandwidth


Test Requirement:	47 CFR 15.247(a)(1)(i)
Test Method:	ANSI C63.10-2020+Cor.1-2023, section 7.8.6, For occupied bandwidth measurements, use the procedure in 6.9.2. Frequency hopping shall be disabled for this test.
Test Limit:	Refer to 47 CFR 15.247(a)(1)(i), for frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
Procedure:	A dBc bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.⁵¹ a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.6.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max-hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to

	this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth. k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
Test Setup:	
Operating Environment:	
Temperature:	25.8 °C
Humidity:	47.1 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 3.3V

6.2.1 Test Data

Please Refer to Appendix-LORA for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(2)
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 7.8.5
Test Limit:	Refer to 47 CFR 15.247(b)(2), For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.
Test Setup:	
Operating Environment:	
Temperature:	25 °C
Humidity:	51.8 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 3.3V

6.3.1 Test Data

Please Refer to Appendix-LORA for Details.


6.4 Channel Separation

Test Requirement:	47 CFR 15.247(a)(1)
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 7.8.2
Test Limit:	Refer to 47 CFR 15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: Wide enough to capture the peaks of two adjacent channels. b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. c) Video (or average) bandwidth (VBW) $\geq$ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A spectral plot of the data shall be included in the test report.
Test Setup:	 The diagram illustrates the test setup. On the left, a rack of instruments includes an E4438C, N5182A, CMW500, N9020A, RF Control Unit and Sensor Unit, SPD, and a DC Power Source. Red and black cables connect these instruments to a green box labeled 'EUT' (Equipment Under Test) which is placed inside a 'Temperature Humidity Chamber'.
Operating Environment:	
Temperature:	25.7 °C
Humidity:	55 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 3.3V

6.4.1 Test Data

Please Refer to Appendix-LORA for Details.

6.5 Number of Hopping Frequencies

Test Requirement:	47 CFR 15.247(a)(1)(i)
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 7.8.3
Test Limit:	Refer to 47 CFR 15.247(a)(1)(i), For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen. b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. c) VBW $\geq$ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow the trace to stabilize. It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A spectral plot of the data shall be included in the test report.
Test Setup:	 The diagram illustrates the test setup. On the left, a rack of test equipment includes an E4438C signal generator, an N5182A network analyzer, a CMW500 software-defined radio, an N9020A spectrum analyzer, an RF Control Unit and Sensor Unit, an SPD (Signal Power Divider), and a DC Power Source. Red and black cables connect these units to an EUT (Equipment Under Test), which is shown as a green box inside a Temperature Humidity Chamber on the right.
Operating Environment:	


Temperature:	24.1 °C
Humidity:	53.4 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 3.3V

6.5.1 Test Data

Please Refer to Appendix-LORA for Details.

6.6 Dwell Time


Test Requirement:	47 CFR 15.247(a)(1)(i)
Test Method:	ANSI C63.10-2020+Cor 1-2023, section 7.8.4
Test Limit:	Refer to 47 CFR 15.247(a)(1)(i), For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
Procedure:	The dwell time per hop on a channel is the time from the start of the first transmission to the end of the last transmission for that hop. If the device has a single transmission per hop then the dwell time is the duration of that transmission. If the device has a multiple transmissions per hop then the dwell time is measured from the start of the first transmission to the end of the last transmission. The time of occupancy is the total time that the device dwells on a channel over an observation period specified in the regulatory requirement. To determine the time of occupancy the spectrum analyzer will be configured to measure both the dwell time per hop and the number of times the device transmits on a specific channel in a given period. The EUT shall have its hopping function enabled. Compliance with the requirements shall be made with the minimum and with the maximum number of channels enabled. If the dwell time per channel does not vary with the number of channels than compliance with the requirements may be based on the minimum number of channels. If the device supports different dwell times per channel (example Bluetooth devices can dwell on a channel for 1, 3 or 5 time slots) then measurements can be limited to the longest dwell time with the minimum number of channels. Use the following spectrum analyzer settings to determine the dwell time per hop: a) Span: Zero span, centered on a hopping channel. b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected transmission time per hop. c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this. d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel. e) Detector function: Peak. f) Trace: Clear-write, single sweep. g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers. To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel

	across the sweep time. The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is $3 / 0.5 \times 10$, or 60 hops. The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.
Test Setup:	 The diagram illustrates the test setup. On the left, a vertical stack of equipment includes a spectrum analyzer (E4438C), a signal generator (N5182A), a microwave power supply (CMW500), a signal generator (N9020A), an RF control unit and sensor unit, a SPD (Signal Power Divider), and a DC power source. On the right, a Temperature Humidity Chamber (THC) contains the Equipment Under Test (EUT). Red and black cables connect the RF control unit and the DC power source to the EUT inside the THC.
Operating Environment:	
Temperature:	22.6 °C
Humidity:	54.7 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 3.3V

6.6.1 Test Data

Please Refer to Appendix-LORA for Details.


6.7 Emissions in non-restricted frequency bands


Test Requirement:	47 CFR 15.247(d)
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 7.8.7
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Setup:	
Operating Environment:	
Temperature:	25.7 °C
Humidity:	54.9 %
Atmospheric Pressure:	1010 mbar
Test voltage:	DC 3.3V

6.7.1 Test Data

Please Refer to Appendix-LORA for Details.

6.8 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4		
Test Setup:			



6.8.1 Test Data

Remark: The report only reflects the test data of worst mode.

(9KHz-30 MHz)


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits (dBuV) + distance extrapolation factor.


(30MHz-1GMHz)

TM2 / Band: 902.300MHz~914.900MHz/ BW: 125kHz / CH: M/ Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	59.0251	28.61	-9.22	19.39	40.00	-20.61	QP	Pass
2	124.3508	28.90	-9.37	19.53	43.50	-23.97	QP	Pass
3	165.7771	28.65	-7.66	20.99	43.50	-22.51	QP	Pass
4	323.3204	28.39	-5.71	22.68	46.00	-23.32	QP	Pass
5	438.6554	28.68	-2.22	26.46	46.00	-19.54	QP	Pass
6 *	811.6872	28.49	6.41	34.90	46.00	-11.10	QP	Pass


TM2 / Band: 902.300MHz~914.900MHz/ BW: 125kHz / CH: M /Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	50.2324	31.88	-9.25	22.63	40.00	-17.37	QP	Pass
2	64.7728	31.22	-11.13	20.09	40.00	-19.91	QP	Pass
3	131.5270	32.98	-8.70	24.28	43.50	-19.22	QP	Pass
4	165.7771	31.65	-7.66	23.99	43.50	-19.51	QP	Pass
5	545.1825	28.56	0.25	28.81	46.00	-17.19	QP	Pass
6 *	842.1296	28.85	6.22	35.07	46.00	-10.93	QP	Pass

Note:Margin=Level-Limit=Reading+factor-Limit=Reading+Antenna factor+ cable loss -amplifier gain-Limit

6.9 Emissions in frequency bands (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Method:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Procedure:	ANSI C63.10-2020+Cor 1-2023 section 6.5.4		
Test Setup:			
Operating Environment:			
Temperature:	24.8 °C		
Humidity:	49 %		
Atmospheric Pressure:	1010 mbar		
Test voltage:	N/A		

6.9.1 Test Data

Remark: The report only reflects the test data of worst mode.

Test Channel: 902.30MHz, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
1804.600	44.79	4.07	48.86	74.00	-25.14	peak	Pass
1804.600	34.69	4.07	38.76	54.00	-15.24	AVG	Pass
2706.900	46.07	7.91	53.97	74.00	-20.03	peak	Pass
2706.900	35.76	7.91	43.66	54.00	-10.34	AVG	Pass
3609.200	43.99	9.93	53.91	74.00	-20.09	peak	Pass
3609.200	33.28	9.93	43.20	54.00	-10.80	AVG	Pass
Test Channel: 902.30MHz, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
1804.600	44.70	4.07	48.77	74.00	-25.23	peak	Pass
1804.600	34.96	4.07	39.03	54.00	-14.97	AVG	Pass
2706.900	46.85	7.91	54.76	74.00	-19.24	peak	Pass
2706.900	36.37	7.91	44.28	54.00	-9.72	AVG	Pass
3609.200	46.35	9.93	56.27	74.00	-17.73	peak	Pass
3609.200	35.85	9.93	45.77	54.00	-8.23	AVG	Pass

Test Channel: 908.50MHz, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
1817.000	44.87	4.07	48.94	74.00	-25.06	peak	Pass
1817.000	34.23	4.07	38.30	54.00	-15.70	AVG	Pass
2725.500	46.63	7.92	54.55	74.00	-19.45	peak	Pass
2725.500	36.52	7.92	44.44	54.00	-9.56	AVG	Pass
3634.000	42.89	9.94	52.83	74.00	-21.17	peak	Pass
3634.000	33.04	9.94	42.97	54.00	-11.03	AVG	Pass
Test Channel: 908.50MHz, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
1817.000	44.70	4.07	48.78	74.00	-25.22	peak	Pass
1817.000	34.84	4.07	38.91	54.00	-15.09	AVG	Pass

2725.500	46.54	7.92	54.46	74.00	-19.54	peak	Pass
2725.500	36.82	7.92	44.74	54.00	-9.26	AVG	Pass
3634.000	47.32	9.94	57.26	74.00	-16.74	peak	Pass
3634.000	37.51	9.94	47.44	54.00	-6.56	AVG	Pass

Test Channel: 914.90MHz, Test Polarization: Vertical							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
1829.800	45.60	4.08	49.67	74.00	-24.33	peak	Pass
1829.800	35.82	4.08	39.90	54.00	-14.10	AVG	Pass
2744.700	46.93	7.94	54.86	74.00	-19.14	peak	Pass
2744.700	37.20	7.94	45.13	54.00	-8.87	AVG	Pass
3659.600	43.40	9.95	53.36	74.00	-20.64	peak	Pass
3659.600	33.01	9.95	42.96	54.00	-11.04	AVG	Pass
Test Channel: 914.90MHz, Test Polarization: Horizontal							
Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Marging (dB)	Detector	Result
1829.800	45.38	4.08	49.46	74.00	-24.54	peak	Pass
1829.800	35.88	4.08	39.95	54.00	-14.05	AVG	Pass
2744.700	45.67	7.94	53.61	74.00	-20.39	peak	Pass
2744.700	35.83	7.94	43.77	54.00	-10.23	AVG	Pass
3659.600	46.59	9.95	56.54	74.00	-17.46	peak	Pass
3659.600	36.36	9.95	46.32	54.00	-7.68	AVG	Pass

Note:Margin=Level-Limit=Reading+factor-Limit
Factor= Antenna factor+ cable loss -amplifier gain

7 Test Setup Photos

Please refer to the Appendix I Test Setup Photos.

8 EUT Constructional Details (EUT Photos)

Please refer to the Appendix II External Photos.



BTF Testing Lab (Shenzhen) Co., Ltd.

Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, Guangdong, China

www.btf-lab.com

-- END OF REPORT --