

RF Exposure Evaluation Report

Applicant: Wuhu Hongjing Electronic Co., Ltd.

Address of Applicant: No. 216, Huashan Road, Economic and Technological Development Zone, Wuhu, Anhui, China

Product Name: HEAD UNIT

Model No.: 8015 AIO BASE (More models are listed in Section 2.2)

Brand Name:



FCC ID: 2BVPG-8015AIOBASE

Test Standards: FCC CFR Title 47 Part 2 (§2.1091)

Date of Sample Receipt: Jul. 13, 2026

Date of Test: Jul. 14 to 26, 2026

Date of Report Issue:

Jul. 27, 2026


Prepared By:

Shenzhen Acote Technology Co., Ltd.

Room 719, Excellence Times Building, No. 27, Xinqiao 3rd Road, Xinqiao Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong Province, China



Winner Zhang / Manager
Approved by



Aron Wu / Senior Engineer
Reviewed by

Report Revision History

Rev.	Issue Date	Description
V00	Jul. 27, 2026	Initial Release



Table of Contents

Cover Page	1
Report Revision History	2
Table of Contents.....	3
1 Laboratory Introduction	4
1.1 Laboratory Location.....	4
1.2 Laboratory Facility	4
1.3 Announcement	4
1.4 Disclaimer.....	4
2 Equipment Under Test Information	5
2.1 Application Information.....	5
2.2 Product Information	5
2.3 EUT Technical Parameters	5
3 Test Information	6
3.1 Test Methodology.....	6
3.2 Additions to, Deviations, or Exclusions from the Method.....	6
3.3 Test Mode	6
3.4 Worst-case	6
4 Technical requirements specification	7
4.1 Limits	7
4.2 Result	8
4.3 Conclusion.....	8

1 Laboratory Introduction

1.1 Laboratory Location

Company Name:	Shenzhen Acote Technology Co., Ltd.
Address of Laboratory:	Room 719, Excellence Times Building, No. 27, Xinqiao 3rd Road, Xinqiao Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong Province, China.
	101, F1, building 15, zhongda 365, Xincheng Road No.9, Songshanhu, Dongguan, Guangdong, China.
Website:	www.acotelabs.com
Email:	Service@acotelabs.com
Tel.:	+86-0755-2788 9963

1.2 Laboratory Facility

Our company's laboratory facilities have received accreditation, certification, or authorization from the following organizations:

- **FCC - Designation No.: CN1450**
Shenzhen Acote Technology Co., Ltd. has been certified by the FCC (Federal Communications Commission) as a testing laboratory. Test Firm Registration Number: **832670**.
- **ISED - CAB Identifier: CN0202**
Shenzhen Acote Technology Co., Ltd. is registered with ISED (Innovation, Science and Economic Development Canada) as a Conformity Assessment Body (CAB) for radio equipment testing.
- **A2LA - Accreditation Number: 7697.01**
Shenzhen Acote Technology Co., Ltd. has been accredited by A2LA (American Association for Laboratory Accreditation) in compliance with the internationally recognized standard ISO/IEC 17025:2017, "General Requirements for the Competence of Testing and Calibration Laboratories."

1.3 Announcement

Shenzhen Acote Technology Co., Ltd. tested the equipment in accordance with the requirements set forth in the test standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by Shenzhen Acote Technology Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Shenzhen Acote Technology Co., Ltd. will constitute fraud and shall nullify the document.

1.4 Disclaimer

For the information or data provided by the client in this report, the relevant results or conclusions of this report are only made for these data or information. The testing laboratory is not responsible for the authenticity and accuracy of these data or information.

2 Equipment Under Test Information

2.1 Application Information

Applicant:	Wuhu Hongjing Electronic Co., Ltd.
Address of Applicant:	No. 216, Huashan Road, Economic and Technological Development Zone, Wuhu, Anhui, China
Manufacturer:	Wuhu Hongjing Electronic Co., Ltd.
Address of Manufacturer:	No. 216, Huashan Road, Economic and Technological Development Zone, Wuhu, Anhui, China
Factory:	Wuhu Hongjing Electronic Co., Ltd.
Address of Factory:	No. 216, Huashan Road, Economic and Technological Development Zone, Wuhu, Anhui, China

2.2 Product Information

Product Name:	HEAD UNIT		
Model No.:	8015 AIO BASE		
Models of Product Family:	8015 AIO DAB		
Description of Model Differentiation:	The two products share identical shell structures and PCBs. The difference lies in whether they support DAB functionality: those that support DAB (type 8015 AIODAB) utilize the corresponding DAB chips and connectors, while those that do not omit them (type 8015 AIO BASE).		
	The difference refer the below table:		
	Function	8015 AIO BASE	8015 AIO DAB
	BT(5.0)	√	√
	Wifi 5G (band 6)	√	√
	FM/AM	√	√
	DAB	×	√
	DAB HSD socket	√	√
	DMS	×	×
	DMS HSD socket	×	×
	Offline navigation (software)	×	×
	Online navigation (software)	×	×
	Memory (RAM)	4G	4G
	GNSS receiver	√	√

2.3 EUT Technical Parameters

Operation Frequency:	BT: 2402MHz ~ 2480MHz BLE: 2402MHz ~ 2480MHz 5G WiFi: ☒ Band 1: 5180MHz ~ 5240MHz ☒ Band 4: 5745MHz ~ 5825MHz
Antenna Type:	Chip Antenna
Antenna Gain:	BT: <u>3.0</u> dBi (declared by applicant) BLE: <u>3.0</u> dBi (declared by applicant) 5G WiFi: ☒ Band 1: <u>3.3</u> dBi (declared by applicant) ☒ Band 4: <u>3.3</u> dBi (declared by applicant)
Power Supply:	DC 6 ~ 18V
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3 Test Information

3.1 Test Methodology

The tests documented in this report were performed in accordance with:

- FCC CFR Title 47 Part 2 (§2.1091)

3.2 Additions to, Deviations, or Exclusions from the Method

None

3.3 Test Mode

TM 1:	Keep the EUT continuously transmitting in BT mode.
TM 2:	Keep the EUT continuously transmitting in BLE mode.
TM 3:	Keep the EUT continuously transmitting in 5G WiFi mode.

3.4 Worst-case

This RF exposure assessment is based on the maximum EIRP derived from worst-case engineering measurements across all modulation types at various data rates.

4 Technical requirements specification

4.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-3.0	614	1.63	*(100)	30
3.0-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100000			1.0	30

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

4.2 Result

Worse case:

Mode	Maximum Tune-up power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm ²)	Limits for General Population/ Uncontrolled Exposure (mW/cm ²)
BT	6.00	3.98	3.00	2.00	20.00	0.002	1.0
BLE	6.00	3.98	3.00	2.00	20.00	0.002	1.0
5G WiFi Band 1	18.00	63.10	3.30	2.14	20.00	0.027	1.0
5G WiFi Band 4	14.00	25.12	3.30	2.14	20.00	0.011	1.0

Simultaneous transmission (Worse mode):

Frequency range (MHz)	Mode	Power Density / Limit	Total Power Density / Limit	Limit	Verdict
1500-100000	Bluetooth	0.002	0.029	1	Pass
	5G WiFi	0.027			

4.3 Conclusion

The device is exempt from the SAR test and satisfies RF exposure evaluation.

----- End of Report -----