

FCC TEST REPORT

FCC ID:2BVQN-PB0621

Applicant Name..... : HUNAN C-SMARTLINK TECHNOLOGY CO.,LTD

Address..... : Building 5-6-7-8, Chengnan Electronic Information Industrial Park, Chenxi Industrial Development Zone, Chenxi County, Huaihua, Hunan Province

Manufacturer Name..... : HUNAN C-SMARTLINK TECHNOLOGY CO.,LTD

Address..... : Building 5-6-7-8, Chengnan Electronic Information Industrial Park, Chenxi Industrial Development Zone, Chenxi County, Huaihua, Hunan Province

Product..... : Power Bank

Model(s)..... : PB0621

Additional Model(s)..... : MOPB0621, SEPB0621, LIPB0621, HSPB0621

Trademark..... : /

Model Difference..... : PB0621 is the test model, while other models are derivative models. These models are the same on the circuit, with only different model names. Therefore, the test data of PB0621 can represent the remaining models.

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : Apr. 9, 2026

Date of Test(s)..... : Apr. 9, 2026 to Apr. 16, 2026

Date of Issue..... : Apr. 16, 2026

Test Requested..... : Select test(s) as requested by the client.

Test Standard(s)..... : FCC CFR Title 47 Part 15 Subpart C

Test procedure..... : ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

In the configuration tested, the EUT complied with the standards specified above.

Prepared by:

Kimi Lu

Kimi Lu/ Engineer

Reviewed by:

Baret Wu

Baret Wu/ Director



Note: The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report shall not be reproduced except in full, without prior written approval of ZHT. This document may be altered or revised by ZHT, personnel only, and shall be noted in the revision of the document.



TABLE OF CONTENTS

1. TEST SUMMARY	3
2. GENERAL INFORMATION	4
3.1 GENERAL DESCRIPTION OF EUT	4
3.2 Test mode	5
3.3 Block Diagram of EUT Configuration	6
3.4 Test Conditions	6
3. TEST FACILITY AND TEST INSTRUMENT USED	7
4.1 Test Facility	7
4.2 Instrument List For All Test Items	7
4.3 Testing software	8
4.4 Measurement Uncertainty	8
4. CONDUCTED EMISSION TEST	9
5.1 CONDUCTED EMISSION MEASUREMENT	9
5.1.1 POWER LINE CONDUCTED EMISSION Limits	9
5.1.2 TEST PROCEDURE	9
5.1.3 DEVIATION FROM TEST STANDARD	9
5.1.4 TEST SETUP	10
5.1.5 EUT OPERATING CONDITIONS	10
5.1.6 Test Result	11
5. RADIATED EMISSION MEASUREMENT	13
6.1 Radiated Emission Limits	13
6.2 Anechoic Chamber Test Setup Diagram	14
6.3 Test Procedure	14
6.4 DEVIATION FROM TEST STANDARD	14
6.5 Test Result	15
6. BANDWIDTH TEST	18
7. ANTENNA REQUIREMENT	21
8. TEST SETUP PHOTO	22
9. EUT CONSTRUCTIONAL DETAILS	22

1. TEST SUMMARY

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT


Product Name:	Power Bank
Test Model No:	PB0621
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	110.1-205kHz, 360KHz
Modulation type:	ASK
Antenna Type:	Inductive loop coil Antenna
Antenna gain:	0dBi
Power supply:	Input: 5V---3A, 9V---3A, 12V---2.5A or DC7.7V for 3.85V*2 Rechargeable Li-ion battery Wireless output: 5W/7.5W/10W/15W/25W(MAX)
Sample Number:	260409117YP001
Remark:The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	

2.2 Test mode


Test Modes:	
Mode 1	AC Mains + WPT + phone charging port-25W(Battery Status:≤1%)
Mode 2	AC Mains + WPT + phone charging port-25W(Battery Status:≤50%)
Mode 3	AC Mains + WPT + phone charging port-25W(Battery Status:≤98%)
Mode 4	AC Mains + WPT + phone charging port-15W(Battery Status:≤1%)
Mode 5	AC Mains + WPT + phone charging port-15W(Battery Status:≤50%)
Mode 6	AC Mains + WPT + phone charging port-15W(Battery Status:≤98%)
Mode 7	AC Mains + WPT + phone charging port-10W(Battery Status:≤1%)
Mode 8	AC Mains + WPT + phone charging port-10W(Battery Status:≤50%)
Mode 9	AC Mains + WPT + phone charging port-10W(Battery Status:≤98%)
Mode 10	AC Mains + WPT + phone charging port-7.5W(Battery Status:≤1%)
Mode 11	AC Mains + WPT + phone charging port-7.5W(Battery Status:≤50%)
Mode 12	AC Mains + WPT + phone charging port-7.5W(Battery Status:≤98%)
Mode 13	AC Mains + WPT + phone charging port-5W(Battery Status:≤1%)
Mode 14	AC Mains + WPT + phone charging port-5W(Battery Status:≤50%)
Mode 15	AC Mains + WPT + phone charging port-5W(Battery Status:≤98%)
Mode 16	WPT + phone charging port-25W(Battery Status:≤1%)
Mode 17	WPT + phone charging port-25W(Battery Status:≤50%)
Mode 18	WPT + phone charging port-25W(Battery Status:≤98%)
Mode 19	WPT + phone charging port-15W(Battery Status:≤1%)
Mode 20	WPT + phone charging port-15W(Battery Status:≤50%)
Mode 21	WPT + phone charging port-15W(Battery Status:≤98%)
Mode 22	WPT + phone charging port-10W(Battery Status:≤1%)
Mode 23	WPT + phone charging port-10W(Battery Status:≤50%)
Mode 24	WPT + phone charging port-10W(Battery Status:≤98%)
Mode 25	WPT + phone charging port-7.5W(Battery Status:≤1%)
Mode 26	WPT + phone charging port-7.5W(Battery Status:≤50%)
Mode 27	WPT + phone charging port-7.5W(Battery Status:≤98%)
Mode 28	WPT + phone charging port-5W(Battery Status:≤1%)
Mode 29	WPT + phone charging port-5W(Battery Status:≤50%)
Mode 30	WPT + phone charging port-5W(Battery Status:≤98%)
Mode 31	Standby
Note: All modes were tested, only the worst-case was recorded in the report. Mode 16 is the worst mode, In the Conducted Emission project Mode 1 is the worst mode	

2.3 Block Diagram of EUT Configuration

Conducted Emission



Radiated Emission



2.4 Test Conditions

Temperature: 25.5℃

Relative Humidity: 54.4

3. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	AC Adapter	Lanto Electronic Ltd.	191106C	/	AE
E-2	Mobile phone	Apple Inc.	iPhone 15	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:	
(1)	The support equipment was authorized by Declaration of Confirmation.
(2)	For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(3)	“YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

**4. TEST FACILITY AND TEST INSTRUMENT USED****4.1 Test Facility**

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. :Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

4.2 Instrument List For All Test Items**Radiation Test equipment**

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	May 6, 2025	May 5, 2026
2	Loop antenna	EMCI	LAP600	272	Sept. 8, 2025	Sept. 7, 2026
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	May 6, 2025	May 5, 2026
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	May 7, 2025	May 6, 2026
5	Bilog Antenna	Schwarzbeck	VULB9162	00498	May 15, 2025	May 14, 2026
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	May 15, 2025	May 14, 2026
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	Oct. 20, 2025	Oct. 19, 2026
8	Amplifier	AEROFLEX	100KHz-40GHz	097	Oct. 20, 2025	Oct. 19, 2026
9	Spectrum Analyzer	R&S	FSV40	101413	Oct. 20, 2025	Oct. 19, 2026
10	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 7, 2025	May 6, 2026
11	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	May 7, 2025	May 6, 2026
12	Single Generator	Agilent	N5182A	MY48180575	May 7, 2025	May 6, 2026
13	Power Sensor	MWRFtest	MW100-RFCB	/	May 7, 2025	May 6, 2026
14	CABLE	EMToni	DA800-NM-NM-11000MM	/	Nov. 25, 2021	Nov. 24, 2026

Conduction Test equipment

Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Receiver	R&S	ESCI	100874	May 6, 2025	May 5, 2026
LISN	R&S	ENV216	102794	May 6, 2025	May 5, 2026
ISN CAT 6	Schwarzbeck	NTFM 8158	00318	May 7, 2025	May 6, 2026
ISN CAT 5	Schwarzbeck	CAT5 8158	00343	May 7, 2025	May 6, 2026
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	00101	May 8, 2025	May 7, 2026
Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	May 8, 2025	May 7, 2026
CABLE	EMToni	G223-NM-BNCM-2000MM	/	May 6, 2025	May 5, 2026

4.3 Testing software

Project	Software name	Edition
Conducted Emission	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission	EZ-EMC	FA-03A2 RE+
RF Test	MTS 8310	2.0.0.0

4.4 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	0.92dB
2	RF conducted power	0.16dB
3	Conducted spurious emissions	0.21dB
4	All radiated emissions (9k-30MHz)	4.68dB
5	All radiated emissions (30-1GHz)	5.1dB
6	All radiated emissions (1-6GHz)	3.9dB
7	All radiated emissions (6GHz-18GHz)	4.3dB
8	All radiated emissions (18-40GHz)	4.65dB
9	Temperature	0.5°C
10	Humidity	2%
11	Occupied Bandwidth	4.96%

Decision Rule

- ☒ Uncertainty is not included
☐ Uncertainty is inclu

5. CONDUCTED EMISSION TEST

5.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

5.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	QP	AVG	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


5.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

5.1.3 DEVIATION FROM TEST STANDARD

No deviation

5.1.4 TEST SETUP




5.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



5.1.6 Test Result

Temperature:	24.6°C	Relative Humidity:	54.7%
Pressure:	1014kPa	Phase :	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.1770	42.40	9.90	52.30	64.63	-12.33	QP	P	
2	0.1770	28.61	9.90	38.51	54.63	-16.12	AVG	P	
3	0.2105	36.28	9.91	46.19	63.19	-17.00	QP	P	
4	0.2105	20.91	9.91	30.82	53.19	-22.37	AVG	P	
5	0.2354	33.60	9.92	43.52	62.26	-18.74	QP	P	
6	0.2354	24.17	9.92	34.09	52.26	-18.17	AVG	P	
7	0.2983	28.09	9.95	38.04	60.29	-22.25	QP	P	
8	0.2983	17.35	9.95	27.30	50.29	-22.99	AVG	P	
9	0.4154	27.35	9.99	37.34	57.54	-20.20	QP	P	
10	0.4154	23.57	9.99	33.56	47.54	-13.98	AVG	P	
11	2.8814	27.54	10.07	37.61	56.00	-18.39	QP	P	
12	2.8814	22.47	10.07	32.54	46.00	-13.46	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



Temperature:	24.6°C	Relative Humidity:	54.7%
Pressure:	1014kPa	Phase :	N
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1590	43.20	9.89	53.09	65.52	-12.43	QP	P	
2 *	0.1590	33.36	9.89	43.25	55.52	-12.27	AVG	P	
3	0.1770	42.19	9.90	52.09	64.63	-12.54	QP	P	
4	0.1770	31.17	9.90	41.07	54.63	-13.56	AVG	P	
5	0.2128	35.82	9.92	45.74	63.10	-17.36	QP	P	
6	0.2128	19.10	9.92	29.02	53.10	-24.08	AVG	P	
7	0.2400	34.84	9.93	44.77	62.10	-17.33	QP	P	
8	0.2400	22.10	9.93	32.03	52.10	-20.07	AVG	P	
9	0.2940	29.57	9.95	39.52	60.41	-20.89	QP	P	
10	0.2940	17.79	9.95	27.74	50.41	-22.67	AVG	P	
11	0.4155	28.16	9.99	38.15	57.54	-19.39	QP	P	
12	0.4155	22.28	9.99	32.27	47.54	-15.27	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

6. RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024				
Test Frequency Range:	9kHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

6.1 Radiated Emission Limits

Limits for frequency below 30MHz


Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz


Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value

6.2 Anechoic Chamber Test Setup Diagram

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024. The specification used was the FCC 15.209 and FCC 15.205 limits.

6.3 Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

6.4 DEVIATION FROM TEST STANDARD

No deviation



6.5 Test Result


Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz

Temperature:	23.6℃	Relative Humidity:	54.2%
Pressure:	1014kPa	Polarization:	coaxial
Test Voltage:	DC 7.7V	Test Modes:	Mode 16



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.3584	66.79	0.84	67.63	96.52	-28.89	peak
2	0.5281	45.48	1.16	46.64	73.15	-26.51	QP
3	0.5964	45.48	1.30	46.78	72.09	-25.31	QP
4	0.7922	44.62	1.69	46.31	69.63	-23.32	QP
5 *	1.1130	42.07	2.34	44.41	66.67	-22.26	QP
6	1.4676	38.91	3.07	41.98	64.27	-22.29	QP

Note:

Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Emission Level = Meter Reading - Factor

Margin = Emission Level- Limit.


The amplitude of emissions which are attenuated by more than 20db below the permissible value has no need to be reported.

.'-Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report




30MHz-1GHz

Temperature:	23.6°C	Relative Humidity:	54.2%
Pressure:	1014 kPa	Polarization:	Horizontal
Test Voltage:	DC 7.7V	Test Modes:	Mode 16





Temperature:	23.6°C	Relative Humidity:	54.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.7V	Test Modes:	Mode 16



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.6796	35.13	-9.29	25.84	40.00	-14.16	QP
2	49.0144	33.89	-8.49	25.40	40.00	-14.60	QP
3	77.0504	42.26	-12.92	29.34	40.00	-10.66	QP
4	81.2116	43.69	-13.06	30.63	40.00	-9.37	QP
5 *	87.1115	44.67	-12.02	32.65	40.00	-7.35	QP
6	199.2855	41.55	-10.04	31.51	43.50	-11.99	QP

Remarks:

- Factor = Antenna Factor + Cable Loss – Preamplifier Factor
- Level = Reading + Factor
- Margin = Emission Level- Limit.
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.



7. BANDWIDTH TEST

1. Set RBW = 10 Hz for 1%-5%OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.


TEST SETUP



Temperature:	25.4 °C	Relative Humidity:	55%
Pressure:	1014kPa		

Frequency (KHz)	20dB bandwidth (KHz)	Result
128	0.025	Pass

110.1KHz to 205KHz Coil ANT




Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 10 Hz to perform the 20dB bandwidth test.

Temperature:	25.4 °C	Relative Humidity:	55%
Pressure:	1014kPa		

Frequency (KHz)	20dB bandwidth (KHz)	Result
358.4	0.055	Pass

360KHz Coil ANT



Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 10 Hz to perform the 20dB bandwidth test.

ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is Coil Antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details	

8. TEST SETUP PHOTO

Reference to the appendix I for details.

9. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

******* END OF REPORT *******