

RF EXPOSURE Test Report

Product: 4K Display Adapter

Trade Mark: N/A

Model Number: WD1902A

FCC ID: 2BVQN-WD1902ATX

Prepared for

HUNAN C-SMARTLINK TECHNOLOGY CO.,LTD

Building 5-6-7-8, Chengnan Electronic Information Industrial Park, Chenxi
Industrial Development Zone, Chenxi County, Huaihua, Hunan Province

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd

Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China

Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110

Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	DESCRIPTION OF EUT	5
1.2	TEST MODE.....	5
1.3	TEST SETUP	6
1.4	ANCILLARY EQUIPMENT	6
2	TEST FACILITIES AND ACCREDITATIONS	7
2.1	TEST LABORATORY	7
2.2	ENVIRONMENTAL CONDITIONS	7
2.3	MEASUREMENT UNCERTAINTY	7
2.4	TEST SOFTWARE	7
3	LIST OF TEST EQUIPMENT	8
4	RF EXPOSURE.....	9
4.1	STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	9
4.1.1.	<i>Limit</i>	9
4.1.2.	<i>Test Result</i>	9

TEST RESULT CERTIFICATION

Applicant's Name..... : HUNAN C-SMARTLINK TECHNOLOGY CO.,LTD
Building 5-6-7-8, Chengnan Electronic Information Industrial
Address : Park, Chenxi Industrial Development Zone, Chenxi County,
Huaihua, Hunan Province
Manufacturer's Name : HUNAN C-SMARTLINK TECHNOLOGY CO.,LTD
Building 5-6-7-8, Chengnan Electronic Information Industrial
Address : Park, Chenxi Industrial Development Zone, Chenxi County,
Huaihua, Hunan Province

Product description

Product name : 4K Display Adapter

Model Number : WD1902A

Standards : FCC CFR 47 PART 1 , 1.1310

Test procedure..... : KDB 447498 D01 General RF Exposure Guidance v06


This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test..... :

Date (s) of performance of tests..... : July 29, 2026~Sept. 07, 2026


Test Result..... : **Pass**

Testing Engineer :




(Z o e S u)

Technical Manager :



(M i n g L i u)

Authorized Signatory :



(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	4K Display Adapter
Model name:	WD1902A
Series Model:	WD1902, WD1902B, MOWD1902, SEWD1902, MOWD1902A, SEWD1902A, MOWD1902B, SEWD1902B
Different of series model:	All the models are the same circuit and module, except the brand and model No..
Operation frequency:	2.4GHz WIFI: IEEE 802.11b/g/n20: 2412-2462MHz 5GHz WIFI: U-NII-1: 5180-5240MHz U-NII-3: 5745-5825MHz
Modulation type:	2.4GHz WIFI: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n(HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM) 5GHz WIFI: 802.11a/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
Bit Rate of transmitter:	2.4GHz WIFI: IEEE 802.11b: 1/2/5.5/11Mbps IEEE 802.11g: 6/9/12/18/24/36/48/54Mbps IEEE 802.11n (20MHz): MCS0-7, up to 72.2Mbps 5GHz WIFI: 802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n(20MHz): MCS0-7, up to 72.2Mbps
Antenna type:	Internal Antenna
Antenna gain:	2.4GHz WIFI: 3.04dBi 5GHz WIFI: 2.22dBi
Max. output power:	2.4GHz WIFI: 16.72dBm 5GHz WIFI: U-NII-1: 16.81dBm U-NII-3: 17.93dBm
Hardware version:	V012
Software version:	V16249053
Battery:	N/A
Power supply:	Input: 5V=2A
Adapter information:	N/A

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	TX

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
/	/	/	/

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
Designation Number:	848916
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
RF Test System	MWRF	MTS 8310	V2.0.0.0

3 List of Test Equipment

RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaioog Signal Generator	Agilent	N5181A	MY47070421	2026-04-27	2027-04-26
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2026-04-27	2027-04-26
3	HB-E043	MXG Anaioog Signal Generator	Agilent	N5182A	US46240335	2026-04-28	2027-04-27
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2026-04-28	2027-04-27
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2026-04-28	2027-04-27
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2026-04-30	2027-04-29

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4 RF Exposure

4.1 Standalone SAR test exclusion considerations

4.1.1. Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm².

If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

4.1.2. Test Result

2.4GHz WIFI:

Operation Frequency: IEEE 802.11b/g/n20: 2412-2462MHz

Power density limited: 1mW/ cm²

5GHz WIFI:

Operation Frequency:

U-NII-1: 5180-5240MHz

U-NII-3: 5745-5825MHz

Antenna Type: Internal Antenna

Antenna gain:

2.4GHz WIFI: 3.04dBi

5GHz WIFI: 2.22dBi

R=20cm

$mW=10^{(dBm/10)}$

Antenna Gain Numeric= $10^{(dBi/10)} = 10^{(3.04/10)} = 2.01$

Antenna Gain Numeric= $10^{(dBi/10)} = 10^{(2.22/10)} = 1.67$

2.4GHz WIFI(Worst):

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)
2437	802.11b	16.72	16±1	17	50.119	3.04	2.01	0.0201	1

5GHz WIFI(Worst):

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5745	802.11n20	17.93	17±1	18	63.096	2.22	1.67	0.0209	1

For the max result: $0.0209 \leq 1g$ SAR, No SAR is required.

***** END OF REPORT *****