

	ShenZhen XinErSheng Technology Co.,Ltd

SPECIFICATION FOR APPROVAL

Customer nane: A5RK-FP

Product name: 2.4G FPC antenna, 1.13mm black wire, L = 120mm, with IPEX connector (4212)

Customer Part Number:

Manufacturers of Material: XESANT12B131342

Deliver quantity: 5PCS

Mark	Check	Examine and approve	Datelanded
Biao	Lisen	Amy	2026.1.14

That Customers:

Acknowledge	Check	Examine and approve	Datelanded

Admit that situation: ☒new product ☐ product shanges

Admit that project: ☐acknowledgement ☐soecimen 5PCS

Admit that conclusion: ☐reception ☐refuse

Company address： Floor 3, Building D, No.96 Lingxia Road, Fuyong Fenghuang
Fourth Industrial Zone, Baoan District, Shenzhen

Phone number: 0755-33881455 Fax NO.: 0755-33233276

Email: liqinghui@xinershengant.com

	ShenZhen XinErSheng Technology Co.,Ltd

Contents




Item	Description
1、	cover
2、	Revised records
3、	Contents
4、	parameter
5、	Drawing
6、	Test equipment
7、	Test report
8、	2D、3DRaditation Pattern
9、	ORT test
10、	Packing

	ShenZhen XinErSheng Technology Co.,Ltd


Main technical parameters of the product

Main technical specifications	
Frequency Range(MHZ)	2400-2500
Impedance(Ω)	50 ± 10
Gain(dBi)	3. 29
ReTurnLoss(dB)	≤ -10
VSWR	≤ 2
Admitted Power	1W
Polarization	Linear Vertical
Connector Type	IPEX
Physical Properties	
Antenna Base	FPC
Operating Temp	-20℃-+60℃
Storage Temp	-20℃-+70℃

Product drawing

Finished product image.																																	
																																	
1. An IPCS/ROSH label needs to be affixed to the outer box label. 2. A IPCS/outer carton label needs to be affixed to the upper right corner of the outer carton side.		Specification: Frequency Rang:2400-2500MHZ Return Loss:-10DB or less VSWR: 2.0 Max Gain:3dbi																															
<table><tr><td>1</td><td>terminal</td><td>copper</td><td>1</td><td></td></tr><tr><td>NO</td><td colspan="2">DESCRIPTION</td><td>QTY</td><td>REMARK</td></tr></table>		1	terminal	copper	1		NO	DESCRIPTION		QTY	REMARK	<table><tr><td>TITLE:</td><td>2.4G FPC antenna, 1.13mm black wire, L = 120mm, with IPEX connector (4312)</td></tr><tr><td>P/N</td><td></td></tr><tr><td>CUSTOMER:</td><td></td></tr><tr><td>DRAW NO:</td><td>XESANT12B131342</td></tr><tr><td colspan="2">DIMENSIONS TOLERANCES UNLESS OTHERWISE NOTED</td></tr><tr><td colspan="2">TOLERANCE</td></tr><tr><td>XXX ±0.05</td><td>XX±1.0</td></tr><tr><td>XX±0.1</td><td></td></tr><tr><td>X±0.2</td><td></td></tr><tr><td>X±0.5</td><td></td></tr></table>		TITLE:	2.4G FPC antenna, 1.13mm black wire, L = 120mm, with IPEX connector (4312)	P/N		CUSTOMER:		DRAW NO:	XESANT12B131342	DIMENSIONS TOLERANCES UNLESS OTHERWISE NOTED		TOLERANCE		XXX ±0.05	XX±1.0	XX±0.1		X±0.2		X±0.5	
1	terminal	copper	1																														
NO	DESCRIPTION		QTY	REMARK																													
TITLE:	2.4G FPC antenna, 1.13mm black wire, L = 120mm, with IPEX connector (4312)																																
P/N																																	
CUSTOMER:																																	
DRAW NO:	XESANT12B131342																																
DIMENSIONS TOLERANCES UNLESS OTHERWISE NOTED																																	
TOLERANCE																																	
XXX ±0.05	XX±1.0																																
XX±0.1																																	
X±0.2																																	
X±0.5																																	
																																	
SHEET:1/1		SCALE:1/1																															
UNIT:MM		REV. A																															
APPROVED		CHECKED																															
DRAWN		DRAWN																															

Test equipment



OTA testing system

Brand: Feitu


Frequency range: 400MHz-8.5GHz

Dimensions of the dark chamber: 4m x 4m x 4m

Number of probes: 24 (23 dual-polarized probes and 1 communication probe)

Functions: Passive and active testing; G network, C network, 2G/3G/4G.

WIFI, BT, and other standard TRP, TIS testing, and so on.



Model: 5071C

Brand: Agilent

Frequency range: 9KHz-8.5GHz

Function: Comprehensive passive testing of antennas, including 2G/3G/4G/BT/WIFI.



Model: 8960

Brand: Agilent

Frequency range: 292MHz-2700GHz

Function: Suitable for active testing of 2G/3G devices.



Model: CMW500


Brand: Rohde & Schwarz

Frequency range: 70KHz-6GHz

Function: Comprehensive active testing of antennas, including 2G/3G/4G/BT/WIFI/NB-Lot.

Network analyzer test report


SWR



OTA test

	signal path	TRP	signal path	TIS
WIFI	1	10.24	1	-64.96
	6	9.6	6	-65.91
	11	7.62	11	-61.7

2D、3DRaditation Pattern



	ShenZhen XinErSheng Technology Co.,Ltd

Reliability testing report

1	SAIT SPRAY TEST	Saltwater spray test: in accordance with the standard GB1266-86. Distilled water: Single distillation PH6.5~7 Spray volume: 1.4me80cm² /h Compressed air pressure: 1Kgf/cm² Relative test angle: 98° Temperature: 45° to 47° Pressure-temperature: 35° Test duration: 48 hours	All characteristic range is 30% of the initial value There are no signs indicating any damage to the electrical performance of the device.
2	HEAT TEST	for 96 hours, after keep in normal condition for 30mim the to test.	
3	HUMIDITY TEST	40+2℃ 90-95%RH for 96hours, after keep in normal condition for 30mim the to test.	
4	COLD TEST	-20+2℃ for 96hours, after keep in normal condition for 30mim the to test.	

	ShenZhen XinErSheng Technology Co.,Ltd

Product packaging specifications

Product name/Specifications

1、 Labeling Requirements

采购单号	*****
物料编码	*****
品名规格	*****
数量/单位	*****
备注	*****

采购单号	*****
物料编码	*****
品名规格	*****
数量/单位	*****
备注	*****

2、 Packing requirements

Homework instructions:

Inner packaging:

Product: 100 pieces per small bag

Exterior packaging:

Quantity determined based on actual quantity/box

Precautions:

- 1. Is it necessary to add dividers or polyethylene foam;
- 2. Adhesion of labels, such as ROHS;