



TEST REPORT

Applicant: Shenzhen Hongshengda Photoelectric Technology Co. , Ltd
Address of Applicant: 3rd Floor, Building 4, No.161, Xingye Road,Fenghuang Community,Fuyong Street,Bao 'an District, Shenzhen, China
Manufacturer: Shenzhen Hongshengda Photoelectric Technology Co. , Ltd
Address of Manufacturer: 3rd Floor, Building 4, No.161, Xingye Road,Fenghuang Community,Fuyong Street,Bao 'an District, Shenzhen, China
Product Name: Portable Touchscreen Smart TV
Model No.: H27BF,HSD01,H27CF,H27FC,H270F,H27UC,H27BF*****,H27FC*****
Trade Mark: N/A
FCC ID: 2BVSY-H27BF
Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
Date of Test: Apr.11, 2026 - Apr.22, 2026
Date of report issued: Apr.23, 2026

Remark:

The results shown in this test report refer only to the sample(s) tested , this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Reviewed by:

Approved by:

Yuan Fan

Project Engineer

Smith Chen

Project Manager

Smith Chen

Authorized Signature



Report Revision History		
Report No.	Description	Issue Date
ET-26041391E03	Original	Apr.23, 2026



Contents

Page

1	TEST SUMMARY	4
1.1	MEASUREMENT UNCERTAINTY	4
2	GENERAL INFORMATION	5
2.1	GENERAL DESCRIPTION OF EUT	5
2.2	TEST MODE	7
2.3	DESCRIPTION OF SUPPORT UNITS	8
2.4	TEST FACILITY	8
2.5	ADDITIONAL INSTRUCTIONS.....	8
3	TEST INSTRUMENTS LIST	9
4	TEST RESULTS AND MEASUREMENT DATA	10
4.1	ANTENNA REQUIREMENT	10
4.2	CONDUCTED EMISSIONS	11
4.3	DUTY CYCLE.....	14
4.4	CONDUCTED OUTPUT POWER.....	18
4.5	BANDWIDTH &99% OCCUPY BANDWIDTH.....	20
4.6	POWER SPECTRAL DENSITY	28
4.7	BAND EDGE.....	36
4.7.1	Conducted test Method	36
4.7.2	Radiated test Method	45
4.8	SPURIOUS EMISSION	56
4.8.1	Radiated Emission Method	56
5	TEST SETUP PHOTO	66
6	EUT CONSTRUCTIONAL DETAILS.....	66

1 Test Summary

Test Item	Section in CFR 47	Result	Test by
Antenna requirement	47CFR part 15.203	Pass	/
AC Power Line Conducted Emission	47CFR part 15.207	Pass	Jason Huang
Conducted Output Power	47CFR part 15.407 (a)(1)/(a)(3)	Pass	Kara Wu
26dB Bandwidth and 99% Occupied Bandwidth	47CFR part 15.407 (a)(12)	Pass	Kara Wu
6dB Bandwidth	47CFR part 15.407 (e)	Pass	Kara Wu
Power Spectral Density	47CFR part 15.407(a)(1)/(a)(3)	Pass	Kara Wu
Band Edge	47CFR part 15.407(b)(1)/(b)(4)	Pass	Kara Wu
Spurious Emission	47CFR part 15.205/15.209 47CFR part 15.407(b)(1)/(b)(4)/(b)(8)	Pass	Jason Huang

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10-2020+COR 1-2023 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
3. Note: Compliance determination rules
 - 1).The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacturer. If measurement uncertainty is taken into account, the applicant/manufacturer will bear all possible risks of non-compliance.
 - 2).The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"

1.1 Measurement Uncertainty

Test Item	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	0.72%	(1)
RF output power, conducted	±0.67 dB	(1)
Power Spectral Density, conducted	±0.51 dB	(1)
Unwanted Emissions, conducted	±0.64 dB	(1)
AC Power Line Conducted Emission	± 3.38 dB	(1)
Radiated emissions 9K-30MHz	±4.26 dB	(1)
Radiated emissions 30M- 1GHz	±4.88 dB	(1)
Radiated emissions 1GHz-18GHz	± 4.16 dB	(1)
Radiated emissions 18GHz-40GHz	±4.14 dB	(1)
Frequency error	Uc=6X10 ⁻⁷	(1)
Duty Cycle	0.03	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

2 General Information

2.1 General Description of EUT

Product Name:	Portable Touchscreen Smart TV
Model No.:	H27BF,HSD01,H27CF,H27FC,H270F,H27UC,H27BF*****,H27FC*****,H***** ("*" consists of the numbers 0-9, the letters A-Z, a-z, symbols or spaces. The differences between various models only lie in the color patterns and sales channels, while all other aspects are the same. This difference does not affect the product's safety and electromagnetic compatibility performance.)
Difference of model(s)	Except for the model name, color, and sales area, all models have the same circuit and RF module
Test Model:	H27BF
Hardware Version:	N/A
Software Version:	N/A
Sample(s) Status:	Engineer sample
Operation Frequency:	☒ 5180-5240MHz for 802.11a/n(HT20)/ac20(VHT20); 5190-5230MHz for 802.11n(HT40)/ac40(VHT40); 5210MHz for 802.11 ac80(VHT80); ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac20(VHT20); 5755-5795 MHz for 802.11n(HT40)/ac40(VHT40); 5775MHz for 802.11 ac80(VHT80);
Channel numbers:	☒ 4 channels for 802.11a/n20(HT20)/ac20(VHT20) in the 5180-5240MHz band; 2 channels for 802.11 n40(HT40)/ac40(VHT40) in the 5190-5230MHz band ; 1 channels for 802.11 ac80(VHT80) in the 5210MHz band ; ☒ 5 channels for 802.11802.11a/n20(HT20)/ac20(VHT20) in the 5745-5825MHz band ; 2 channels for 802.11 n40(HT40)/ac40(VHT40) in the 5755-5795MHz band ; 1 channels for 802.11 ac80(VHT80) in the 5775MHz band
Channel bandwidth:	802.11a/802.11n(HT20)/ 802.11ac(VHT20): 20MHz 802.11n(HT40)/ 802.11ac(VHT40) : 40MHz 802.11ac(VHT80) : 80MHz
Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT/20/40/80):NSS1, MCS0-MCS9
Modulation technology:	Orthogonal Frequency Division Multiplexing (OFDM) with BPSK/QPSK/16QAM/64QAM/256QAM
Antenna Type:	FPC Antenna
Antenna gain:	4.80dBi(Declare by applicant) Note: Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information.
Power supply:	DC 19V From Adapter
Battery:	DC 11.1V 8700mAh
Adapter Model:	Model: FX65C-190342Z INPUT:AC 100-240V 50/60Hz 1.5A Output:DC 11.1V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	38	5190MHz	40	5200MHz	42	5210MHz
44	5220MHz	46	5230MHz	48	5240MHz	/	/
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	153	5765MHz	155	5775MHz
157	5785MHz	159	5795MHz	161	5805MHz	/	/
165	5825MHz	/					

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)		
	802.11 a /n(HT20)/ac(VHT20)	802.11 n(HT40)/ac(VHT40)	802.11ac(VHT80)
Lowest channel	5180	5190	5210
Middle channel	5200	X	
Highest channel	5240		

Test channel	Frequency (MHz)		
	802.11 a /n(HT20)/ac(VHT20)	802.11 n(HT40)/ac(VHT40)	802.11ac(VHT80)
Lowest channel	5745	5755	5775
Middle channel	5785	X	
Highest channel	5825		

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: For battery operated equipment, the EUT was performed using a new DC 11.1V battery.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pretest Mode	Description
Mode 1	802.11a / n 20/ ac 20 CH36/ CH40/ CH 48 802.11a /n 20/ac 20 CH149/ CH157/ CH 165
Mode 2	802.11n 40/ac 40 CH38/ CH 46 802.11n 40/ac 40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155
Mode 4	/
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a / n 20/ ac 20 CH36/ CH40/ CH 48 802.11a /n 20/ac 20 CH149/ CH157/ CH 165
Mode 2	802.11n 40/ac 40 CH38/ CH 46 802.11n 40/ac 40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155
Mode 4	/

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
1	Notebook	DELL	Vostro 3520	/
2	MOUSE	DELL	MS116	/

2.4 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064
IC Company Number:	28440
IC CAB identifier:	CN0132
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

2.5 Additional Instructions

Test Software	ADB Special Serial Port Commands
Power level setup	Default

3 Test Instruments list

Conducted Emission

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI3	102696	2026.3.05	2027.3.04
2	Artificial power network	schwarabeck	NSLK8127	8127483	2026.3.05	2027.3.04
3	Artificial power network	ETS	3186/2NM	1132	2026.3.05	2027.3.04
4	10dB attenuator	HUBER+SUHNER	10dB	/	2026.3.05	2027.3.04
5	Cable 4	HUBER SUNNER	3M	/	2026.3.05	2027.3.04
6	Absorbing Clamp	schwarabeck	MDS21	D69250	2025.3.06	2026.3.05

Radiated Emission & RF Conducted test:

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101032	2026.3.05	2027.3.04
2	Broadband antenna	schwarabeck	VULB9168	1064	2026.3.11	2028.3.10
3	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2026.3.08	2028.3.07
4	Amplifier	EMtrace	RP01A	50117	2026.3.05	2027.3.04
5	Amplifier	Space-Dtronics	EWLAN0118G-P40	19113001	2026.3.05	2027.3.04
6	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2026.3.05	2027.3.04
7	Power detector meter	MWRFtest	MW100-PSB	MW201020JYT	2026.3.05	2027.3.04
8	Signal generator	Agilent	N5182A	MY49060455	2026.3.05	2027.3.04
9	Spectrum analyzer	Rohde&schwarz	FSV-40N	101321	2026.3.05	2027.3.04
10	Amplifier	SKET	LNPA_1840-50	SK2019040302	2026.3.05	2027.3.04
11	Horn antenna	schwarabeck	BBHA 9170	946	2026.3.08	2028.3.07
12	Loop antenna	schwarabeck	FMZB 1519 B	1519	2026.3.08	2028.3.07
13	Cable 6	HUBER SUNNER	0.5M	/	2026.3.05	2027.3.04
14	Cable7	HUBER SUNNER	2.0M	/	2026.3.05	2027.3.04
15	Cable8	HUBER SUNNER	6.0M	/	2026.3.05	2027.3.04
16	Filter	Xin bo	XBLBQ-GTA29	210410-3-2	2026.3.05	2027.3.04
17	Power Sensor	Keysight	U2021XA	MY54111006	2026.3.05	2027.3.04
18	Temp. & Humidity Chamber	Jiecheng Instrument	QA-LP-80	20160705001	2026/3/06	2027/3/05

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4 Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:	47CFR Part 15.203
<i>15.203 requirement:</i> <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
The antenna is FPC Antenna, the best case gain of the antenna is 4.80 dBi, reference to the internal photos for details..	

4.2 Conducted Emissions


Test Requirement:	47CFR Part 15.207					
Test Method:	ANSI C63.10-2020+COR 1-2023 §6.2					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2020+COR 1-2023 on conducted measurement.					
Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	24.8°C	Humid.:	48%	Press.:	1012mbar
Test voltage:	AC 120V 60Hz					
Test results:	Pass					

Remark:

1. Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V 60Hz
2. All mode have been tested, the report only shows the worst mode (802.11a 5240MHz)


Measurement Result

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1635	45.76	9.97	55.73	65.28	-9.55	QP
2	0.1635	27.48	9.97	37.45	55.28	-17.83	AVG
3	0.2444	39.35	9.98	49.33	61.95	-12.62	QP
4	0.2444	19.42	9.98	29.40	51.95	-22.55	AVG
5	0.4515	34.09	10.06	44.15	56.85	-12.70	QP
6	0.4515	21.11	10.06	31.17	46.85	-15.68	AVG
7	0.5635	32.10	10.08	42.18	56.00	-13.82	QP
8	0.5635	23.18	10.08	33.26	46.00	-12.74	AVG
9	5.5815	29.94	10.04	39.98	60.00	-20.02	QP
10	5.5815	19.72	10.04	29.76	50.00	-20.24	AVG
11	16.0395	36.39	9.99	46.38	60.00	-13.62	QP
12	16.0395	28.20	9.99	38.19	50.00	-11.81	AVG

Neutral:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	44.21	9.97	54.18	66.00	-11.82	QP
2	0.1500	25.72	9.97	35.69	56.00	-20.31	AVG
3	0.1922	40.69	9.97	50.66	63.94	-13.28	QP
4	0.1922	24.27	9.97	34.24	53.94	-19.70	AVG
5	0.5459	32.54	10.08	42.62	56.00	-13.38	QP
6	0.5459	23.76	10.08	33.84	46.00	-12.16	AVG
7	0.8204	27.65	10.09	37.74	56.00	-18.26	QP
8	0.8204	19.90	10.09	29.99	46.00	-16.01	AVG
9	5.4508	24.59	10.03	34.62	60.00	-25.38	QP
10	5.4508	11.99	10.03	22.02	50.00	-27.98	AVG
11	18.5100	34.30	9.95	44.25	60.00	-15.75	QP
12	18.5100	24.51	9.95	34.46	50.00	-15.54	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Duty cycle

Test Method :	ANSI C63.10-2020+COR 1-2023§11.6	
Limit:	/	
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve, is connected to an E.U.T (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a table labeled 'Non-Conducted Table'. This table is supported by two vertical legs that rest on a thick grey bar at the bottom labeled 'Ground Reference Plane'.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 24.8°C	Humid.: 48%RH
Test voltage:	DC 11.1V	
Test results:	Pass	

Measurement Result

5180-5240MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	100	0
TX 802.11n20 Mode	100	0
TX 802.11ac20 Mode	100	0
TX 802.11n40 Mode	100	0
TX 802.11a40 Mode	100	0
TX 802.11ac80 Mode	100	0


5745-5825 MHz

Mode	Duty cycle (%)	Correction Factor (dB)
TX 802.11a Mode	100	0
TX 802.11n20 Mode	100	0
TX 802.11ac20 Mode	100	0
TX 802.11n40 Mode	100	0
TX 802.11a40 Mode	100	0
TX 802.11ac80 Mode	100	0


Test plot

5180-5240MHz


(802.11a) plot




(802.11 n20) plot




(802.11ac20) plot




(802.11 n40) plot



(802.11ac40) plot




(802.11ac80) plot




5745-5825 MHz


(802.11a) plot



(802.11 n20) plot




(802.11ac20) plot




(802.11 n40) plot




(802.11ac40) plot



(802.11ac80) plot



4.4 Conducted Output Power

Test Requirement:	47CFR Part 15.407 (a)(1)/(a)(3)	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 ANSI C63.10-2020+COR 1-2023 § 12.4	
Limit:	5150-5250MHz : 250mW 5725~5850MHz : 1W	
Test setup:	 The diagram illustrates the test setup. A Power Sensor is connected via red lines to an E.U.T. (Equipment Under Test) and a PC. The E.U.T. is placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.3°C	Humid.: 60%RH
Test voltage:	DC 11.1V	
Test results:	Pass	

Measurement Result


5180-5240MHz

Test Channel	Frequency	Correction Factor	Maximum output power	Total Power	LIMIT	Result
	(MHz)	(dB)	(dBm)	(dBm)	dBm	
TX 802.11a Mode						
CH36	5180	0	14.34	14.34	24	Pass
CH40	5200	0	14.17	14.17	24	Pass
CH48	5240	0	14.36	14.36	24	Pass
TX 802.11 n20 Mode						
CH36	5180	0	14.05	14.05	24	Pass
CH40	5200	0	14.32	14.32	24	Pass
CH48	5240	0	14.24	14.24	24	Pass
TX 802.11 ac20 Mode						
CH36	5180	0	14.14	14.14	24	Pass
CH40	5200	0	14.91	14.91	24	Pass
CH48	5240	0	14.09	14.09	24	Pass
TX 802.11 n40 Mode						
CH38	5190	0	13.20	13.20	24	Pass
CH46	5230	0	13.19	13.19	24	Pass
TX 802.11 ac40 Mode						
CH38	5190	0	13.25	13.25	24	Pass
CH46	5230	0	13.60	13.60	24	Pass
TX 802.11 ac80 Mode						
CH42	5210	0	12.76	12.76	24	Pass

5745-5825 MHz

Test Channel	Frequency	Correction Factor	Maximum output power	Total Power	LIMIT	Result
	(MHz)	(dB)	(dBm)	(dBm)	dBm	
TX 802.11a Mode						
CH149	5745	0	14.58	14.58	30	Pass
CH157	5785	0	14.62	14.62	30	Pass
CH165	5825	0	14.43	14.43	30	Pass
TX 802.11 n20 Mode						
CH149	5745	0	14.58	14.58	30	Pass
CH157	5785	0	14.58	14.58	30	Pass
CH165	5825	0	14.60	14.60	30	Pass
TX 802.11 ac20 Mode						
CH149	5745	0	14.46	14.46	30	Pass
CH157	5785	0	14.57	14.57	30	Pass
CH165	5825	0	14.62	14.62	30	Pass
TX 802.11 n40 Mode						
CH151	5755	0	13.41	13.41	30	Pass
CH159	5795	0	13.27	13.27	30	Pass
TX 802.11 ac40 Mode						
CH151	5755	0	13.34	13.34	30	Pass
CH159	5795	0	13.26	13.26	30	Pass
TX 802.11 ac80 Mode						
CH155	5775	0	12.08	12.08	30	Pass

4.5 Bandwidth &99% Occupy Bandwidth

Test Requirement:	47CFR Part 15.407(a)(12)&15.407(e),	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, ANSI C63.10-2020+COR 1-2023§12.5	
Limit:	Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.	
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.3°C	Humid.: 60%RH
Test voltage:	DC 11.1V	
Test results:	Pass	


Measurement Result

5180-5240MHz


Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)
NVNT	a	5180	Ant1	19.446
NVNT	a	5200	Ant1	19.511
NVNT	a	5240	Ant1	19.394
NVNT	n20	5180	Ant1	19.671
NVNT	n20	5200	Ant1	20.068
NVNT	n20	5240	Ant1	19.856
NVNT	n40	5190	Ant1	40.289
NVNT	n40	5230	Ant1	40.015
NVNT	ac20	5180	Ant1	19.88
NVNT	ac20	5200	Ant1	19.814
NVNT	ac20	5240	Ant1	19.825
NVNT	ac40	5190	Ant1	40.17
NVNT	ac40	5230	Ant1	40.223
NVNT	ac80	5210	Ant1	79.65

(802.11a) plot on channel 36


(802.11 n20) plot on channel 36




(802.11a) plot on channel 40





(802.11 n20) plot on channel 40



(802.11a) plot on channel 48




(802.11 n20) plot on channel 48




Test plot


(802.11ac20) plot on channel 36




(802.11 n40) plot on channel 38




(802.11ac20) plot on channel 40



(802.11 n40) plot on channel 46




(802.11ac20) plot on channel 48




Test plot


(802.11ac40) plot on channel 38



(802.11ac80) plot on channel 42



(802.11ac40) plot on channel 46




5745-5825MHz

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	a	5745	Ant1	16.059	0.5	Pass
NVNT	a	5785	Ant1	16.052	0.5	Pass
NVNT	a	5825	Ant1	16.039	0.5	Pass
NVNT	n20	5745	Ant1	17.093	0.5	Pass
NVNT	n20	5785	Ant1	16.659	0.5	Pass
NVNT	n20	5825	Ant1	16.506	0.5	Pass
NVNT	n40	5755	Ant1	35.865	0.5	Pass
NVNT	n40	5795	Ant1	35.139	0.5	Pass
NVNT	ac20	5745	Ant1	16.88	0.5	Pass
NVNT	ac20	5785	Ant1	16.297	0.5	Pass
NVNT	ac20	5825	Ant1	16.904	0.5	Pass
NVNT	ac40	5755	Ant1	35.796	0.5	Pass
NVNT	ac40	5795	Ant1	35.238	0.5	Pass
NVNT	ac80	5775	Ant1	76.457	0.5	Pass


Remark: “---”is not applicable

Test plot


(802.11a) plot on channel 149




(802.11 n20) plot on channel 149




(802.11a) plot on channel 157




(802.11 n20) plot on channel 157



(802.11a) plot on channel 165




(802.11 n20) plot on channel 165




Test plot


(802.11ac20) plot on channel 149




(802.11 n40) plot on channel 151




(802.11ac20) plot on channel 157



(802.11 n40) plot on channel 159




(802.11ac20) plot on channel 165




Test plot


(802.11 ac40) plot on channel 151




(802.11 ac80) plot on channel 155



(802.11 ac40) plot on channel 159



4.6 Power Spectral Density


Test Requirement:	47CFR Part 15.407(a)(1)/ (a)(3)	
Test Method:	KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, ANSI C63.10-2020+COR 1-2023§12.6	
Limit:	Frequency band (MHz)	Limit
	5150-5250	≤17dBm/1MHz for master device
		≤11dBm/1MHz for client device
	5250-5350	≤11dBm/1MHz for client device
	5470-5725	≤11dBm/1MHz for client device
	5725-5850	≤30dBm/500kHz
Test setup:		
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.3°C	Humid.: 60%RH
Test voltage:	DC 11.1V	
Test results:	Pass	

Measurement Result


5180-5240MHz

Mode	Frequency	Measured Power Density (dBm/MHz)	Correction Factor (dB)	Total Measured Power Density (dBm/MHz)	Limit (dBm/MHz)
802.11 a	5180 MHz	0.544	0	0.544	11
	5200 MHz	0.418	0	0.418	11
	5240 MHz	0.543	0	0.543	11
802.11 n20	5180 MHz	0.092	0	0.092	11
	5200 MHz	0.546	0	0.546	11
	5240 MHz	0.262	0	0.262	11
802.11 ac20	5180 MHz	0.327	0	0.327	11
	5200 MHz	1.113	0	1.113	11
	5240 MHz	0.196	0	0.196	11
802.11 n40	5190 MHz	-3.768	0	-3.768	11
	5230 MHz	-3.594	0	-3.594	11
802.11 ac40	5190 MHz	-4.004	0	-4.004	11
	5230 MHz	-3.313	0	-3.313	11
802.11 ac80	5210 MHz	-8.822	0	-8.822	11


(802.11a) PSD plot on channel 36




(802.11n20) PSD plot on channel 36




(802.11a) PSD plot on channel 40




(802.11n20) PSD plot on channel 40




(802.11a) PSD plot on channel 48



(802.11n20) PSD plot on channel 48




(802.11ac20) PSD plot on channel 36




(802.11n40) PSD plot on channel 38




(802.11ac20) PSD plot on channel 40




(802.11n40) PSD plot on channel 46



(802.11ac20) PSD plot on channel 48




(802.11ac40) PSD plot on channel 38



(802.11ac80) PSD plot on channel 42



(802.11ac40) PSD plot on channel 46




Mode	Frequency	Measured Power Density (dBm/510KHz)	Measured Power Density (dBm/500KHz)	Correction Factor (dB)	Total Measured Power Density (dBm/500KHz)	Limit (dBm/500kHz)
802.11 a	5745 MHz	-1.891	-1.977	0	-1.977	30
	5785 MHz	-1.967	-2.053	0	-2.053	30
	5825 MHz	-2.237	-2.323	0	-2.323	30
802.11 n20	5745 MHz	-2.328	-2.414	0	-2.414	30
	5785 MHz	-1.993	-2.079	0	-2.079	30
	5825 MHz	-1.997	-2.083	0	-2.083	30
802.11ac20	5745 MHz	-2.546	-2.632	0	-2.632	30
	5785 MHz	-2.139	-2.225	0	-2.225	30
	5825 MHz	-2.082	-2.168	0	-2.168	30
802.11 n40	5755 MHz	-6.433	-6.519	0	-6.519	30
	5795 MHz	-6.669	-6.755	0	-6.755	30
802.11ac40	5755 MHz	-6.599	-6.685	0	-6.685	30
	5795 MHz	-6.899	-6.985	0	-6.985	30
802.11ac80	5775 MHz	-12.406	-12.492	0	-12.492	30


Note:

1. Correction Factor (dB)= duty cycle factor
2. RBW Factor (dB) = $10 \cdot \log(500/510) = -0.086$
3. Measured PSD (dBm/500kHz) = Measured PSD (dBm/510kHz) + RBW Factor (dB)
4. Total Measured Power Density (dBm/500KHz) = Measured PSD (dBm/500kHz) + Correction Factor (dB)


(802.11a) PSD plot on channel 149




(802.11n20) PSD plot on channel 149




(802.11a) PSD plot on channel 157



(802.11n20) PSD plot on channel 157



(802.11a) PSD plot on channel 165



(802.11n20) PSD plot on channel 165

